Key Fob Model: CS-102

FCC PART 15, SUBPART B and C; FCC 15.231; and RSS-210 & RSS GEN TEST REPORT

for

KEY FOB

Model: CS-102

Prepared for

ECOLINK INTELLIGENT TECHNOLOGY, INC. 2055 CORTE DEL NOGAL CARLSBAD, CALIFORNIA 92011

Prepared by:___

KYLE FUJIMOTO

Approved by: James Ross

JAMES ROSS

COMPATIBLE ELECTRONICS INC. 114 OLINDA DRIVE BREA, CALIFORNIA 92823 (714) 579-0500

DATE: SEPTEMBER 21, 2020

	REPORT	APPENDICES			TOTAL		
	BODY	\boldsymbol{A}	В	C	D	E	
PAGES	21	2	2	2	10	26	63

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

Section	/ Title	PAGE
GENERA.	AL REPORT SUMMARY	4
SUMMA.	RY OF TEST RESULTS	5
1. PU	TRPOSE	6
1.1	Decision Rule & Risk	6
2. AI	OMINISTRATIVE DATA	7
2.1	Location of Testing	7
2.2	Traceability Statement	7
2.3	Cognizant Personnel	7
2.4	Date Test Sample was Received	7
2.5	Disposition of the Test Sample	7
2.6	Abbreviations and Acronyms	7
3. AF	PPLICABLE DOCUMENTS	8
4. DH	ESCRIPTION OF TEST CONFIGURATION	9
4.1	Description of Test Configuration – Emissions	9
4.1.1	Cable Construction and Termination	9
5. LI	STS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1	EUT and Accessory List	10
5.2	Emissions Test Equipment	11
6. TE	ST SITE DESCRIPTION	12
6.1	Test Facility Description	12
6.2	EUT Mounting, Bonding and Grounding	12
6.3	Measurement Uncertainty	12
7. TE	EST PROCEDURES	13
7.1	RF Emissions	13
7.1.1	Conducted Emissions Test	13
7.1.2	Radiated Emissions Test	14
7.1.3	RF Emissions Test Results	16
7.1.4	Sample Calculations	17
7.1.5	Duty Cycle Calculation	18
7.1.6	99 % Bandwidth	19
7.1.7	-20 dB Bandwidth	19
7.1.8	Transmission Time	20
8. CO	ONCLUSIONS	21

LIST OF APPENDICES

APPENDIX	TITLE		
A	Laboratory Accreditations and Recognitions		
В	Modifications to the EUT		
С	Models Covered Under This Report		
D	Diagrams, Charts, and Photos		
	Test Setup Diagrams		
	Antenna and Effective Gain Factors		
	Radiated Emissions Photos		
Е	Data Sheets		

LIST OF FIGURES

FIGURE	TITLE
1	
1	Layout of the Semi-Anechoic Test Chamber

LIST OF TABLES

TABLE	TITLE		
1	Radiated Emission Results		

Key Fob Model: CS-102

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used by the client to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the United States government.

Device Tested: Key Fob

Model: CS-102 S/N: N/A

Product Description: The equipment under test is a battery powered Key Fob manufactured by Ecolink Intelligent

Technology. The transmit frequency is 345 MHz. The clock frequencies are 4 MHz and

10.78125 MHz. Dimensions: 6.0 cm (L) x 3.0 cm (W) x 1.0 cm (H).

Modifications: The EUT was not modified to meet the specifications.

Customer: Ecolink Intelligent Technology, Inc.

> 2055 Corte Del Nogal Carlsbad, California 92011

Test Dates: September 24 and 25, 2020

Test Specifications covered by accreditation:

Test Specifications: Emissions requirements

CFR Title 47, Part 15, Subpart B;

CFR Title 47, Part 15, Subpart C, sections 15.205, 15.209, and 15.231; RSS-210 and

RSS-Gen



Test Procedures: ANSI C63.4 and ANSI C63.10

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Spurious Radiated RF Emissions, 9 kHz – 3.45 GHz (Transmitter and Digital portion)	Complies with the Class B limits of CFR Title 47, Part 15 Subpart B; the limits of CFR Title 47, Part 15 Subpart C, sections 15.205, 15.209, and 15.231; and the limits of RSS-210 and RSS-Gen Highest reading in relation to spec limit 53.74 dBuV/m (AVG) @ 2760 MHz (*U = 3.95 dB)
2	-20 dB Bandwidth	Complies with limits of CFR Title 47, Part 15 Subpart C, section 15.231 (c); and the limits of RSS-210
3	Transmission Time	Complies with limits of CFR Title 47, Part 15 Subpart C, section 15.231 (a)(1) and (a)(2); and the limits of RSS-210

^{*}U = Expanded Uncertainty with a coverage factor of k=2

Key Fob Model: CS-102

PURPOSE 1.

This document is a qualification test report based on the emissions tests performed on the Key Fob, Model: CS-102. The emissions measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the Class B specification limits defined by CFR Title 47, Part 15 Subpart B section, 15.109; the specification limits defined by CFR Title 47, Part 15 Subpart C sections 15.205, 15.209 and 15.231; and the specifications limits defined by RSS-210 and RSS-Gen.

1.1 **Decision Rule & Risk**

If a measured value exceeds a specification limit it implies non-compliance. If the value is below a specification limit it implies compliance. Measurement uncertainty of the laboratory is reported with all measurement results but generally not taken into consideration unless a standard, rule or law requires it to be considered.

Qualification test reports are only produced for products that are in compliance with the test requirements, therefore results are always in conformity. Otherwise, an engineering report or just the data is provided to the customer.

When performing a measurement and making a statement of conformity, in or out-of-specification to manufacturer's specifications or Pass/Fail against a requirement, there are two possible outcomes:

- The result is reported as conforming with the specification
- The result is reported as not conforming with the specification

The decision rule is defined below.

When the test result is found to be below the limit but within our measurement uncertainty of the limit, it is our policy that the final acceptance decision is left to the customer, after discussing the implications and potential risks of the decision.

When the test result is found to be exactly on the specification, it is our policy, in the case of unwanted emissions measurements to consider the result non-compliant, however, the final decision is left to the customer, after discussing the implications and potential risks of the decision.

When the test result is found to be over the specification limit under any condition, it is our policy to consider the result non-compliant.

In terms of uncertainty of measurement, the laboratory is a calibrated and tightly controlled environment and generally exceptionally stable, the measurement uncertainties are evaluated without the considering of the test sample. When it comes to the test sample however, as most testing is performed on a single sample rather than a sample population, and that sample is often a preproduction representation of the final product, that test sample represents a significantly higher source of measurement uncertainty. We advise our customers of this and that when in doubt (small test to limit margins), they may wish to perform statistical sampling on a population to gain a higher confidence in the results. All lab reported results are that of a single sample in any event.

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

Key Fob

2. ADMINISTRATIVE DATA

2.1 Location of Testing

The emissions tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Ecolink Intelligent Technology, Inc.

David Shepard

Engineer

Jay Stone

Director of Engineering

Compatible Electronics Inc.

Kyle Fujimoto James Ross Test Engineer Test Engineer

2.4 Date Test Sample was Received

The test sample was received prior to the date of this report.

2.5 Disposition of the Test Sample

The test sample has not been returned to Ecolink Intelligent Technology, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

EMI Electromagnetic Interference

EUT Equipment Under Test

P/N Part Number S/N Serial Number

FCC Federal Communications Commission

DoC Declaration of Conformity

N/A
Not Applicable
Tx
Transmit
Rx
Receive
Inc.
Incorporated
RF
Radio Frequency
BLE
Bluetooth Low Energy
CFR
Code of Federal Regulations

N/A Not Applicable DC Direct Current

Key Fob Model: CS-102

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this emission Test Report.

SPEC	TITLE	
CFR Title 47, Part 15 Subpart C	FCC Rules – Radio frequency devices (including digital devices) – Intentional Radiators	
CFR Title 47, Part 15 Subpart B	FCC Rules – Radio frequency devices (including digital devices) –Unintentional Radiators	
RSS-210 Issue 10: 2019	License-exempt Radio Apparatus: Category I Equipment	
RSS-Gen Issue 5: 2019 + Amendment 1	General Requirements for Compliance of Radio Apparatus	
ANSI C63.4: 2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	
ANSI C63.10: 2013	American National Standard of procedure for compliance testing of unlicensed wireless devices	

Key Fob Model: CS-102

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration – Emissions

The Key Fob, Model: CS-102 (EUT) was tested as a stand-alone unit, and is internal battery powered. The EUT was transmtting at 345 MHz on a continuous basis.

The EUT was tested for emissions while in the X, Y and Z axis. The X orientation is when the EUT is parallel to the ground. The Y orientation is when the EUT is perpendicular to the ground mounted vertically. The Z orientation is when the EUT is perpendicular to the ground mounted horizontally.

The EUT was tested with a new battery.

The final radiated emissions data for the EUT was taken in the configuration described above. Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

The EUT contained no external cables.

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

Key Fob

Model: CS-102

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT

5.1 EUT and Accessory List

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
KEY FOB (EUT)	ECOLINK INTELLIGENT TECHNOLOGY, INC.	CS-102	N/A	XQC-CS102 IC: 9863B-CS102

5.2 **Emissions Test Equipment**

EQUIPMENT TYPE	MANU- FACTURER	MODEL NUMBER	SERIAL NUMBER	CALIBRATION DATE	CAL. CYCLE
	RADIATED EMISSIONS TEST EQUIPMENT				
TDK TestLab	TDK RF Solutions, Inc.	9.22	700145	N/A	N/A
EMI Receiver, 20 Hz – 40GHz	Rohde & Schwarz	ESIB40	100172	July 15, 2020	1 Year
Loop Antenna	Com-Power	AL-130R	121090	February 5, 2019	2 Year
CombiLog Antenna	Com-Power	AC-220	061093	June 5, 2019	2 Year
Horn Antenna	Com-Power	AH-118	10050113	February 4, 2020	2 Year
Preamplifier	Com-Power	PA-118	181653	February 5, 2020	1 Year
System Controller	Sunol Sciences Corporation	SC110V	112213-1	N/A	N/A
Turntable	Sunol Sciences Corporation	2011VS	N/A	N/A	N/A
Antenna-Mast	Sunol Sciences Corporation	TWR95-4	112213-3	N/A	N/A
Computer	Hewlett Packard	p6716f	MXX1030PX0	N/A	N/A
LCD Monitor	Hewlett Packard	52031a	3CQ046N3MG	N/A	N/A

Key Fob Model: CS-102

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 of this report for emissions test location.

6.2 EUT Mounting, Bonding and Grounding

For frequencies 1 GHz and below: The EUT was mounted on a 0.6 by 1.2 meter non-conductive table 0.8 meters above the ground plane.

For frequencies above 1 GHz: The EUT was mounted on a 0.6 by 1.2 meter non-conductive table 1.5 meters above the ground plane.

The EUT was not grounded.

6.3 Measurement Uncertainty

Compatible Electronics' U_{lab} value is less than U_{cispr} , thus based on this – compliance is deemed to occur if no measured disturbance exceeds the disturbance limit

$$u_{\mathsf{c}}(y) = \sqrt{\sum_{i} c_{i}^{2} \ u^{2}(x_{i})}$$

Measurement			$U_{lab} = 2 uc (y)$
Conducted disturbance (mains port)	(150 kHz - 30 MHz)	3.4 dB	2.73 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(30 MHz – 1 000 MHz)	6.3 dB	3.27 dB (Vertical) 3.19 dB (Horizontal)
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(1 GHz - 6 GHz)	5.2 dB	3.95 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(6 GHz – 18 GHz)	5.5 dB	3.95 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(18 GHz – 26.5 GHz)	N/A	4.69 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(26.5 GHz – 40 GHz)	N/A	4.55 dB

Report Number: B00924D1 Page 13 of 21

Key Fob

TEST PROCEDURES 7.

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 **RF Emissions**

7.1.1 **Conducted Emissions Test**

The EMI Receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. A 10 dB attenuator was used for the protection of the EMI Receiver input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the EMI Receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63:4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by computer software. The final qualification data is located in Appendix E.

Test Results:

This test was not performed because the EUT operates on battery power only and cannot be connected to the AC public mains.

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

Key Fob

Model: CS-102

7.1.2 Radiated Emissions Test

The EMI Receiver was used as the measuring meter. An internal preamplifier was used to increase the sensitivity of the instrument during emissions tests up to 1000 MHz, and an external preamplifier was used to increase the sensitivity of the instrument during emissions tests above 1 GHz. The EMI Receiver was initially used with the Analyzer mode feature activated. In this mode, the EMI receiver can then record the actual frequency to be measured. This final reading is then taken accurately in the EMI Receiver mode, which takes into account the cable loss, amplifier gain and antenna factors, so that a true reading is compared to the true limit. The effective measurement bandwidth used for the radiated emissions test was according to the frequency measured.

The frequencies below 1 GHz, except for the fundamental frequency and the 2nd harmonic of the fundamental frequency, were quasi-peaked using the quasi-peak detector of the EMI Receiver.

The harmonic frequencies above 1 GHz, the fundamental frequency, and the 2nd harmonic were averaged using the duty cycle correction calculation.

All other frequencies above 1 GHz were averaged using the average detector of the EMI Receiver.

The EMI test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna to ensure accurate results.

The EUT was tested at a 3-meter test distance. The six highest emissions are listed in Table 1.

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report Key Fob

Radiated Emissions Test (Continued)

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Loop Antenna
150 kHz to 30 MHz	9 kHz	Loop Antenna
30 MHz to 1 GHz	120 kHz	CombiLog Antenna
1 GHz to 3.45 GHz	1 MHz	Horn Antenna

Test Results:

The EUT complies with the **Class B** limits of CFR Title 47, Part 15, Subpart B; the limits of CFR Title 47, Part 15, Subpart C sections 15.205, 15.209 and 15.231; and the limits of RSS-210 and RSS-Gen for radiated emissions.



7.1.3 **RF Emissions Test Results**

Table 1 RADIATED EMISSION RESULTS

> Key Fob Model: CS-102

Frequency (MHz)	EMI Reading (dBuV/m)	Specification Limit (dBuV/m)	Delta (Cor. Reading – Spec. Limit) (dB)
2760 (H) (Z-Axis)	53.74 (AVG)	53.97	-0.23
2760 (H) (X-Axis)	53.39 (AVG)	53.97	-0.58
2760 (V) (Y-Axis)	52.37 (AVG)	53.97	-1.60
1380 (H) (Y-Axis)	51.55 (AVG)	53.97	-2.42
1380 (V) (Z-Axis)	51.16 (AVG)	53.97	-2.81
1380 (H) (X-Axis)	50.16 (AVG)	53.97	-3.81

Notes:

- The complete emissions data is given in Appendix E of this report.
- (V) Vertical Polarization
- **Horizontal Polarization** (H)
- (AVG) Average Reading

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

TIBLE

Key Fob

Model: CS-102

7.1.4 Sample Calculations

A correction factor for the antenna, cable and a distance factor (if any) must be applied to the meter reading before a true field strength reading can be obtained. This Corrected Meter Reading is then compared to the specification limit in order to determine compliance with the limits.

Conversion to logarithmic terms: Specification limit ($\mu V/m$) log x 20 = Specification Limit in dBuV/m

To correct for distance when measuring at a distance other than the specification

For measurements below 30 MHz: (Specification distance / test distance) log x 40 = distance factor

For measurements above 30 MHz: (Specification distance / test distance) $\log x = 20 = 100$

Note: When using an Active Antenna, the Antenna factor shall be subtracted due to the combination of the internal amplification and antenna loss.

Corrected Meter Reading = meter reading + F - A + C

where: F = antenna factor

A= amplifier gain

C = cable loss

The correction factors for the antenna and the amplifier gain are attached in Appendix D of this report. The data sheets are attached in Appendix E.

The distance factor D is 0 when the test is performed at the required specification distance.

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report Key Fob

Model: CS-102

7.1.5 Duty Cycle Calculation

The fundamental and harmonics were measured at a 3-meter test distance. The EMI Receiver was used to obtain the final test data. The final qualification data sheets are located in Appendix E.

Where

$$\delta(dB) = 20 \log \left[\sum (nt_1 + mt_2 + ... + \xi t_x) / T \right]$$

n is the number of pulses of duration t1 m is the number of pulses of duration t2 ξ is the number of pulses of duration tx

T is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

Duty Cycle Correction Factor = -18.50 dB

Time of One Small Pulse = 150.300601 us

Time of One Large Pulse = 290.581162 us

Number of Small Pulses = 50

Number of Large Pulses = 15

Total On Time = 11873.74748 us = 11.87374748 ms

The time between pulses is greater than 100 ms

Duty Cycle = 11.87374748 ms / 100 ms = 11.87374748%

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

TIBLE

Key Fob

Model: CS-102

7.1.6 99% Bandwidth

The 99% bandwidth was measured using an EMI Receiver.

The following steps were performed for measuring the 99% bandwidth per RSS-GEN, Issue 5, clause 6.7:

- 1. Set RBW to 1 % to 5 % of the actual occupied bandwidth.
- 2. Set VBW to greater than 3 times the RBW.
- 3. Set the EMI Receiver to the occupied bandwidth Function set at 99%
- 4. Set the peak detector to max hold.
- 5. Set the sweep time to auto
- 6. Allow the trace to stabilize.

Please note that this was only used to determine the emission bandwidth and that there are no limits or pass/fail criteria for this test. Please see the data sheets located in Appendix E.

7.1.7 -20 dB Bandwidth

The -20 dB bandwidth was measured using an EMI Receiver.

The following steps were performed for measuring the -20 dB bandwidth:

- 1. Set RBW to at least 1% of the maximum occupied bandwidth allowed.
- 2. Set VBW to greater than 3 times the RBW.
- 3. Set the peak detector to max hold.
- 4. Set the sweep time to auto
- 5. Allow the trace to stabilize.
- 6. Set the markers to -20 dB of the peak fundamental emission

Test Results:

The EUT complies with limits of CFR Title 47, Part 15, Subpart C section 15.231 (c); and the limits of RSS-210.

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

TIBLE

Key Fob

Model: CS-102

7.1.8 Transmission Time

The transmission time was measured using an EMI Receiver.

The following steps were performed for measuring transmission time:

- 1. Set RBW = 120 kHz.
- 2. Set VBW = 500 kHz
- 3. Span = 0 Hz
- 4. Set the sweep time to 10 seconds
- 5. Push a button on the EUT, which automatically activated the transmitter.
- 6. Allow the trace to stabilize.
- 7. Set the 1st marker to start of the transmission
- 8. Set the 2nd marker for 5 seconds after the start of the transmission
- 9. Verify the transmission does not go beyond the 2nd marker.

Test Results:

The EUT complies with limits of CFR Title 47, Part 15, Subpart C section 15.231 (a)(1) and (a)(2); and the limits of RSS-210.

Report Number: B00924D1 Page 21 of 21

Key Fob

Model: CS-102

8. **CONCLUSIONS**

The Key Fob, Model: CS-102 (EUT), as tested, meets all of the specification limits defined in RSS-210, RSS-Gen, the Class B specification limits defined in CFR Title 47, Part 15, Subpart B; and the specification limits defined in CFR Title 47, Part, 15, Subpart C, sections 15.205, 15.209 and 15.231.

APPENDIX A

LABORATORY ACCREDITATIONS AND RECOGNITIONS



LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025.

For the most up-to-date version of our scopes and certificates please visit http://celectronics.com/quality/scope/

Model: CS-102

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."

Innovation, Science and Economic Development Canada Lab Code 2154A

APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC Subpart B, FCC 15.231, RSS-210, and RSS-Gen specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.



APPENDIX C

MODELS COVERED UNDER THIS REPORT

MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Key Fob Model: CS-102 S/N: N/A


There are no additional models or part numbers covered under this report.



APPENDIX D

DIAGRAMS, CHARTS, AND PHOTOS

FIGURE 1: LAYOUT OF THE SEMI -ANECHOIC TEST CHAMBER



COM-POWER AL-130R LOOP ANTENNA

S/N: 121090

CALIBRATION DATE: FEBRUARY 5, 2019

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
	16.1	` ′
0.009 0.01	15.6	-35.4 -35.9
0.02	14.8	-36.7
0.03	15.6	-35.9
0.04	15.1	-36.4
0.05	14.4	-37.0
0.06	14.6	-36.9
0.07	14.4	-37.1
0.08	14.3	-37.1
0.09	14.5	-36.9
0.10	14.1	-37.3
0.20	14.1	-37.3
0.30	14.0	-37.4
0.40	14.0	-37.4
0.50	14.2	-37.2
0.60	14.2	-37.2
0.70	14.2	-37.2
0.80	14.2	-37.3
0.90	14.3	-37.2
1.00	14.5	-37.0
2.00	14.5	-36.9
3.00	14.5	-36.9
4.00	14.7	-36.8
5.00	14.6	-36.9
6.00	14.6	-36.9
7.00	14.6	-36.9
8.00	14.6	-36.9
9.00	14.6	-36.9
10.00	14.8	-36.6
11.00	14.9	-36.6
12.00	14.8	-36.6
13.00	14.8	-36.7
14.00	14.6	-36.8
15.00	14.5	-36.9
16.00	14.5	-37.0
17.00	14.6	-36.9
18.00	14.7	-36.7
19.00	14.8	-36.6
20.00	14.9	-36.6
21.00	14.6	-36.8
22.00	14.2	-37.2
23.00	13.7	-37.7
24.00	13.3	-38.2
25.00	13.0	-38.5
26.00	12.9	-38.6
27.00	13.0	-38.5
28.00	13.1	-38.4
29.00	13.1	-38.4
30.00	12.9	-38.5

COM-POWER AC-220

COMBILOG ANTENNA

S/N: 61093

CALIBRATION DATE: JUNE 5, 2019

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	22.10	200	15.30
35	20.90	250	16.80
40	20.10	300	19.00
45	19.40	350	19.60
50	18.40	400	21.70
60	15.10	450	21.60
70	12.00	500	22.20
80	11.60	550	22.70
90	13.50	600	24.20
100	14.70	650	24.40
120	15.90	700	24.50
125	15.90	750	25.40
140	14.80	800	26.30
150	15.50	850	26.70
160	19.80	900	27.50
175	15.20	950	27.80
180	14.90	1000	27.90



COM POWER AH-118

HORN ANTENNA

S/N: 10050113

CALIBRATION DATE: FEBRUARY 4, 2020

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	24.343	10.0	38.826
1.5	25.419	10.5	39.102
2.0	28.838	11.0	38.259
2.5	28.971	11.5	39.920
3.0	29.919	12.0	40.149
3.5	30.674	12.5	40.576
4.0	31.670	13.0	40.264
4.5	32.437	13.5	40.364
5.0	33.414	14.0	40.424
5.5	34.003	14.5	41.677
6.0	34.799	15.0	43.010
6.5	35.381	15.5	39.799
7.0	37.024	16.0	40.187
7.5	37.403	16.5	40.155
8.0	37.445	17.0	40.507
8.5	37.390	17.5	41.963
9.0	38.076	18.0	43.196
9.5	38.809		




PREAMPLIFIER

S/N: 181653

CALIBRATION DATE: FEBRUARY 5, 2020

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	40.10	6.0	40.60
1.1	40.10	6.5	39.50
1.2	40.00	7.0	39.40
1.3	39.70	7.5	39.30
1.4	39.60	8.0	39.20
1.5	39.90	8.5	40.50
1.6	40.00	9.0	39.60
1.7	39.70	9.5	39.50
1.8	39.50	10.0	38.80
1.9	39.60	11.0	38.70
2.0	39.90	12.0	42.20
2.5	40.10	13.0	40.00
3.0	40.80	14.0	40.30
3.5	40.60	15.0	40.20
4.0	40.50	16.0	41.00
4.5	41.60	17.0	39.70
5.0	39.20	18.0	40.90
5.5	40.00		





FRONT VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.


KEY FOB

MODEL: CS-102

FCC SUBPART B AND C; RSS-210 AND RSS-GEN - RADIATED EMISSIONS - BELOW 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS





REAR VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.


KEY FOB

MODEL: CS-102

FCC SUBPART B AND C; RSS-210 AND RSS-GEN - RADIATED EMISSIONS - BELOW 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS





FRONT VIEW


ECOLINK INTELLIGENT TECHNOLOGY, INC.

KEY FOB

MODEL: CS-102

FCC SUBPART B AND C; RSS-210 AND RSS-GEN - RADIATED EMISSIONS - ABOVE 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS



REAR VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.

KEY FOB

MODEL: CS-102

FCC SUBPART B AND C; RSS-210 AND RSS-GEN - RADIATED EMISSIONS - ABOVE 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONs

APPENDIX E

DATA SHEETS

RADIATED EMISSIONS

DATA SHEETS



Title: Pre-Scan - FCC Class B File: 1 - LF - Pre-Scan - Key Fob - X-Axis - FCC Class B - 09-25-2020.set Operator: Kyle Fujimoto EUT Type: Key Fob EUT Condition: The EUT is continuously transmitting at 345 MHz Company: Ecolink Intelligent Technology, Inc. M/N: CS-102


9/25/2020 6:11:57 AM Sequence: Preliminary Scan

S/N: N/A X-Axis (Worst Case)

(PEAK) EMI (V)

Note: The Frequency at 345 MHz is from the intentional radiator and is subject to the limits of FCC 15.231 instead.

FCC Class B







FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report
COMPATIBLE
Key Fob
ELECTRONICS
Model: CS-102

Title: Radiated Final - FCC Class B File: 1 - LF - Final Scan - Key Fob - X-Axis - FCC Class B - 09-25-2020.set Operator: Kyle Fujimoto EUT Type: Key Fob EUT Condition: The EUT is continuously transmitting at 345 MHz Company: Ecolink Intelligent Technology, Inc. M/N: CS-102 S/N: N/A X-Axis (Worst Case)

9/25/2020 6:36:51 AM Sequence: Final Measurements

FCC Class B

Freq	Pol	(PEAK) EMI	(QP) EMI	(PEAK) Margin	(QP) Margin	Limit	Transducer	Cable	Ttbl Agl	Twr Ht
(MHz)		(dBµV/m)	(dBµV/m)	(dB)	(dB)	(dBµV/m)	(dB)	(dB)	(deg)	(cm)
332.10	Н	25.88	16.95	-20.12	-29.05	46.00	19.20	1.37	287.25	258.26
332.60	Н	28.71	20.76	-17.29	-25.24	46.00	19.20	1.37	306.25	127.58
333.50	Н	26.26	17.29	-19.74	-28.71	46.00	19.20	1.38	24.25	400.00
334.50	Н	21.67	21.16	-24.33	-24.84	46.00	19.20	1.38	346.00	144.17
335.00	Н	36.51	26.28	-9.49	-19.72	46.00	19.20	1.38	100.25	111.34
335.40	Н	29.85	19.77	-16.15	-26.23	46.00	19.20	1.38	347.00	323.40
399.90	H	24.65	19.10	-21.35	-26.90	46.00	21.70	1.53	221.25	241.97



FUNDAMENTAL AND HARMONICS

DATA SHEETS



FCC 15.231

Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Key Fob Lab: D

Model: CS-102 Tested By: Kyle Fujimoto

Fundamental

_					Peak /	Table	Ant.	
Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	QP / Avg	Angle (deg)	Height (cm)	Comments
345.00	68.81	\/	97.26	-28.45	Peak	230.00	100.00	X-Axis
345.00	50.31	V	77.26	-26.95	Avg	230.00	100.00	Vertical Polarization
345.00	84.37	V	97.26	-12.89	Peak	291.25	210.20	Y-Axis
345.00	65.87	V	77.26	-11.39	Avg	291.25	210.20	Vertical Polarization
						7		
345.00	84.82	V	97.26	-12.44	Peak	267.75	178.08	Z-Axis
345.00	66.32	V	77.26	-10.94	Avg	267.75	178.08	Vertical Polarization
345.00	88.45	Η	97.26	-8.81	Peak	359.00	100.00	X-Axis
345.00	69.95	Н	77.26	-7.31	Avg	359.00	100.00	Horizontal Polarization
345.00	80.25	Н	97.26	-17.01	Peak	181.00	214.02	Y-Axis
345.00	61.75	Н	77.26	-15.51	Avg	181.00	214.02	Horizontal Polarization
345.00	82.65	Н	97.26	-14.61	Peak	158.00	104.71	Z-Axis
345.00	64.15	Н	77.26	-13.11	Avg	158.00	104.71	Horizontal Polarization





Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Lab: D Key Fob

Model: CS-102 Tested By: Kyle Fujimoto

Harmonics

Transmit Mode - X-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	33.87	\ \ \	77.26	-43.39	Peak	131.50	158.08	Comments
690.00	15.37	V	57.26	-43.39 -41.89		131.50	158.08	
090.00	15.57	V	57.20	-41.09	Avg	131.50	130.00	
1035.00	45.53	V	73.97	-28.44	Peak	288.00	248.43	
1035.00	27.03	V	53.97	-26.94	Avg	288.00	248.43	
4000.00	00.00	\ /	70.07	40.44	Deal	000.50	000.00	
1380.00	63.83	V	73.97	-10.14	Peak	228.50	238.26	
1380.00	45.33	V	53.97	-8.64	Avg	228.50	238.26	
1725.00	50.30	V	77.26	-26.96	Peak	216.50	222.26	
1725.00	31.80	V	57.26	-25.46	Avg	216.50	222.26	
			N.		2 / /	region or the second		
2070.00	57.80	V	77.26	-19.46	Peak	271.50	225.97	
2070.00	39.30	V	57.26	-17.96	Avg	271.50	225.97	
2415.00	48.40	V	77.26	-28.86	Peak	210.00	249.67	
2415.00	29.90	V	57.26	-27.36	Avg	210.00	249.67	
2760.00	61.36	V	73.97	-12.61	Peak	112.75	145.91	
2760.00	42.86	V	53.97	-11.11	Avg	112.75	145.91	
					J			
3105.00	57.85	V	77.26	-19.41	Peak	188.25	189.37	
3105.00	39.35	V	57.26	-17.91	Avg	188.25	189.37	
0.450.00	00.00	\ /	77.00	44.00	Deal	440.05	000.4.4	
3450.00	63.26	V	77.26	-14.00	Peak	119.25	238.14	
3450.00	44.76	V	57.26	-12.50	Avg	119.25	238.14	





Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Lab: D Key Fob

Model: CS-102 Tested By: Kyle Fujimoto

Harmonics

Transmit Mode - Y-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	38.42	V	77.26	-38.84	Peak	303.25	163.46	
690.00	19.92	V	57.26	-37.34	Avg	303.25	163.46	
1035.00	55.96	V	73.97	-18.01	Peak	250.50	249.91	
1035.00	37.46	V	53.97	-16.51	Avg	250.50	249.91	
1380.00	66.98	V	73.97	-6.99	Peak	55.00	197.79	
1380.00	48.48	V	53.97	-5.49	Avg	55.00	197.79	
1725.00	68.08	V	77.26	-9.18	Peak	100.75	206.50	
1725.00	49.58	V	57.26	-7.68	Avg	100.75	206.50	
2070.00	66.67	V	77.26	-10.59	Peak	225.00	202.08	
2070.00	48.17	V	57.26	-9.09	Avg	225.00	202.08	
2415.00	61.97	V	77.26	-15.29	Peak	293.75	110.14	
2415.00	43.47	V	57.26	-13.79	Avg	293.75	110.14	
2760.00	70.87	V	73.97	-3.10	Peak	104.75	163.58	
2760.00	52.37	V	53.97	-1.60	Avg	104.75	163.58	
3105.00	69.25	V	77.26	-8.01	Peak	118.75	154.98	
3105.00	50.75	V	57.26	-6.51	Avg	118.75	154.98	
3450.00	65.27	V	77.26	-11.99	Peak	286.50	173.61	
3450.00	46.77	V	57.26	-10.49	Avg	286.50	173.61	





Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Lab: D Key Fob

Model: CS-102 Tested By: Kyle Fujimoto

Harmonics

Transmit Mode - Z-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	35.94	V	77.26	-41.32	Peak	301.75	195.58	
690.00	17.44	V	57.26	-39.82	Avg	301.75	195.58	
1035.00	57.38	V	73.97	-16.59	Peak	229.25	209.19	
1035.00	38.88	V	53.97	-15.09	Avg	229.25	209.19	
1380.00	69.66	V	73.97	-4.31	Peak	156.75	216.00	
1380.00	51.16	V	53.97	-2.81	Avg	156.75	216.00	
1725.00	58.27	V	77.26	-18.99	Peak	166.75	157.67	
1725.00	39.77	V	57.26	-17.49	Avg	166.75	157.67	
2070.00	66.81	V	77.26	-10.45	Peak	169.75	137.07	
2070.00	48.31	V	57.26	-8.95	Avg	169.75	137.07	
2415.00	58.54	V	77.26	-18.72	Peak	173.00	138.50	
2415.00	40.04	V	57.26	-17.22	Avg	173.00	138.50	
2760.00	60.62	V	73.97	-13.35	Peak	85.75	183.82	
2760.00	42.12	V	53.97	-11.85	Avg	85.38	183.82	
3105.00	67.70	V	77.26	-9.56	Peak	260.25	117.43	
3105.00	49.20	V	57.26	-8.06	Avg	260.25	117.43	
3450.00	68.83	V	77.26	-8.43	Peak	10.75	221.73	
3450.00	50.33	V	57.26	-6.93	Avg	10.75	221.73	





Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Lab: D Key Fob

Model: CS-102 Tested By: Kyle Fujimoto

Harmonics

Transmit Mode - X-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	38.31	Н	77.26	-38.95	Peak	96.00	101.49	
690.00	19.81	Н	57.26	-37.45	Avg	96.00	101.49	
1035.00	57.52	Н	73.97	-16.45	Peak	216.50	141.19	
1035.00	39.02	Н	53.97	-14.95	Avg	216.50	141.19	
1380.00	68.66	Н	73.97	-5.31	Peak	303.75	127.16	
1380.00	50.16	Н	53.97	-3.81	Avg	303.75	127.16	
1725.00	57.80	Н	77.26	-19.46	Peak	44.75	174.44	
1725.00	39.30	Н	57.26	-17.96	Avg	44.75	174.44	
2070.00	66.56	Н	77.26	-10.70	Peak	56.00	188.29	
2070.00	48.06	Н	57.26	-9.20	Avg	56.00	188.29	
2415.00	61.91	Н	77.26	-15.35	Peak	78.25	126.32	
2415.00	43.41	Н	57.26	-13.85	Avg	78.25	126.32	
2760.00	71.89	Н	73.97	-2.08	Peak	262.50	137.25	
2760.00	53.39	Н	53.97	-0.58	Avg	262.50	137.25	
3105.00	70.37	Н	77.26	-6.89	Peak	242.75	143.76	
3105.00	51.87	Н	57.26	-5.39	Avg	242.75	143.76	
3450.00	70.52	Н	77.26	-6.74	Peak	342.75	128.59	
3450.00	52.02	Н	57.26	-5.24	Avg	342.75	128.59	





Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Lab: D Key Fob

Model: CS-102 Tested By: Kyle Fujimoto

Harmonics

Transmit Mode - Y-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	35.23	Н	77.26	-42.03	Peak	202.25	151.04	
690.00	16.73	Н	57.26	-40.53	Avg	202.25	151.04	
1035.00	53.18	Н	73.97	-20.79	Peak	158.50	236.95	
1035.00	34.68	Н	53.97	-19.29	Avg	158.50	236.95	
1380.00	70.05	Н	73.97	-3.92	Peak	336.75	160.23	
1380.00	51.55	Н	53.97	-2.42	Avg	336.75	160.23	
1725.00	59.06	Н	77.26	-18.20	Peak	156.25	185.49	
1725.00	40.56	Н	57.26	-16.70	Avg	156.25	185.49	
2070.00	66.02	Н	77.26	-11.24	Peak	173.00	142.92	
2070.00	47.52	Н	57.26	-9.74	Avg	173.00	142.92	
2415.00	58.97	Н	77.26	-18.29	Peak	152.25	175.88	
2415.00	40.47	Н	57.26	-16.79	Avg	152.25	175.88	
2760.00	59.35	Н	73.97	-14.62	Peak	204.50	149.31	
2760.00	40.85	Н	53.97	-13.12	Avg	204.50	149.31	
3105.00	62.21	Н	77.26	-15.05	Peak	155.00	101.67	
3105.00	43.71	Н	57.26	-13.55	Avg	155.00	101.67	
3450.00	65.87	Н	77.26	-11.39	Peak	153.00	102.20	
3450.00	47.37	Н	57.26	-9.89	Avg	153.00	102.20	





Ecolink Intelligent Technology, Inc. Date: 09/24/2020

Lab: D Key Fob

Model: CS-102 Tested By: Kyle Fujimoto

Harmonics

Transmit Mode - Z-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	37.97	Н	77.26	-39.29	Peak	182.25	133.31	
690.00	19.47	Н	57.26	-37.79	Avg	182.25	133.31	
1035.00	48.40	Н	73.97	-25.57	Peak	184.75	106.14	
1035.00	29.90	Н	53.97	-24.07	Avg	184.75	106.14	
1380.00	59.65	Н	73.97	-14.32	Peak	144.00	217.43	
1380.00	41.15	Н	53.97	-12.82	Avg	144.00	217.43	
1725.00	49.91	Н	77.26	-27.35	Peak	315.75	202.38	
1725.00	31.41	Н	57.26	-25.85	Avg	315.75	202.38	
2070.00	65.64	Н	77.26	-11.62	Peak	357.50	193.97	
2070.00	47.14	Н	57.26	-10.12	Avg	357.50	193.97	
2415.00	63.19	Н	77.26	-14.07	Peak	0.00	149.79	
2415.00	44.69	Н	57.26	-12.57	Avg	0.00	149.79	
2760.00	72.24	Н	73.97	-1.73	Peak	168.00	187.64	
2760.00	53.74	Н	53.97	-0.23	Avg	168.00	187.64	
3105.00	68.17	Н	77.26	-9.09	Peak	161.50	160.00	
3105.00	49.67	Н	57.26	-7.59	Avg	161.50	160.00	
3450.00	65.46	Н	77.26	-11.80	Peak	179.25	214.92	
3450.00	46.96	Н	57.26	-10.30	Avg	179.25	214.92	

FCC Class B and FCC 15.231

Ecolink Intelligent Technology, Inc. Date: 09/24/2020


Key Fob Lab: D

Model: CS-102 Tested By: Kyle Fujimoto

Non Harmonic Emissions from the Tx and Digital Portion - 9 kHz to 30 MHz Non Harmonic Emissions from the Tx and Digital Portion - 1 GHz To 3.45 GHz


Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
								No Emissions Detected
								from 9 kHz to 30 MHz
								for the digital portion
								of the EUT
								No Emissions Detected
						439		from 1 GHz to 3.45 GHz
			1					for the digital portion
								of the EUT
					7.44			
								from 9 kHz to 30 MHz
								for the Non-Harmonic Emissions
								of the Transmitter for the EUT
								No Emissions Detected
								from 1 GHz to 3.45 GHz
								for the Non-Harmonic Emissions
								of the Transmitter for the EUT
								Investigated in the X-Axis,
								Y-Axis, and Z-Axis

99 % BANDWIDTH DATA SHEET



99 Percent Bandwidth Plot


-20 dB BANDWIDTH PLOT DATA SHEET



-20 dB Bandwidth Plot

TRANSMISSION TIME DATA SHEET






24.SEP.2020 09:53:13 Date:

Transmission time 681.362725 ms

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report COMPATIBLE

Key Fob

Model: CS-102




24.SEP.2020 09:53:33 Date:

The transmission shuts off within 5 seconds of being activated

DUTY CYCLE

DATA SHEETS






24.SEP.2020 08:47:28 Date:

Center 345 MHz

The pulse train only appears once every 100 ms

100 ms/




24.SEP.2020 08:54:42 Date:

Center 345 MHz


The pulse train only appears once every 100 ms – 200 ms scale

20 ms/



24.SEP.2020 09:13:10 Date:

Time of Small Pulse = 150.300601 us



Time of Large Pulse = 290.581162 us


24.SEP.2020

Date:

09:12:15

FCC Part 15 Subpart B and FCC Section 15.231; RSS-210 & RSS-GEN Test Report

Key Fob Model: CS-102



Date: 24.SEP.2020 09:18:57

Number of Small Pulses = 50 = (50*150.300601 us) = 7515.03005 usNumber of Large Pulses = 15 = (15*290.581162 us) = 4358.71743 us

Total On Time = 11873.74748 us = 11.87374748 ms

Duty Cycle = 11.87374748 ms / 100 ms = 11.87374748%

The peak to average ratio is -18.50 dB