

RF TEST REPORT

FCC ID:2AUTE-IF4

Test Report No.....: RF240615019-01-004

Product(s) Name.....: Thermal Transfer Barcode Printer

Model(s).....: iF4, iF4 Plus, iH4, iH400, FT400, FT430, XT400, XT430, SF400, SF430, NF400, NT430, EF400, EF430, JF400, JF430, Y40, Y43, SF401, SF603, NF400, J400, J403, Y401, Y403, iF400, iF430, X400, X430, D400, D430, T400, T430, iF888, FT888, F8, F400, F430, JT400, ST400

Trade Mark.....: iDPRT

Applicant.....: Xiamen Hanin Co., Ltd.

Address.....: Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen

Receipt Date.....: 2024.07.22

Test Date.....: 2024.09.08~2024.09.14

Issued Date.....: 2024.09.20

Standards.....: 47 CFR FCC Part 15, Subpart C(Section 15.247); ANSI C63.10:2013

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Jason Huang	Tim Zhang	Misue Su	
<i>Jason Huang</i>	<i>Tim Zhang</i>	<i>Misue Su</i>	

Table of Contents

History of this test report.....	4
1. General Information	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Factory.....	5
1.4 Basic Description of Equipment Under Test.....	5
1.5 Transmit Operating Mode.....	6
2. Summary of Test Results	7
2.1 Summary of Test Items	7
2.2 Application of Standard	7
2.3 Test Instruments.....	8
2.4 Test Mode.....	9
2.5 Test Condition	10
2.6 Duty Cycle of Test SignalX.....	10
2.7 Measurement Uncertainty	13
2.8 Test Location	13
2.9 Description of Support Units.....	13
3. Test Procedure And Results	14
3.1 AC Power Line Conducted Emission.....	14
3.1.1 Limit	14
3.1.2 Test Procedure	14
3.1.3 Test Setup	14
3.1.4 Test Result	15
3.2 Radiated Emission and Band Edge.....	17
3.2.1 Limit	17
3.2.2 Test Procedure	17
3.2.3 Test Setup	18
3.2.4 Test Result	20

3.3	Spurious Emission at Antenna Port.....	37
3.3.1	Limit	37
3.3.2	Test Procedure	37
3.3.3	Test Setup	38
3.3.4	The Result	39
3.4	6dB Bandwidth	56
3.4.1	Limit	56
3.4.2	Test Procedure	56
3.4.3	Test Setup	56
3.4.4	Test Result	57
3.5	Maximum conducted output power.....	69
3.5.1	Limit.....	69
3.5.2	Test Procedure	69
3.5.3	Test Setup	69
3.5.4	Table of Parameters of Text Software Setting.....	70
3.5.5	The Result	71
3.6	Power Spectral Density	72
3.6.1	Limit.....	72
3.6.2	Test Procedure	72
3.6.3	Test Setup	72
3.6.4	The Result	73

History of this test report

Original Report Issue Date: 2024.09.20

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. General Information

1.1 Applicant

Xiamen Hanin Co., Ltd.

Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen

1.2 Manufacturer

Xiamen Hanin Co., Ltd.

Room 305A, Angye Building, Pioneering Park, Torch High-tech, Zone, Xiamen

1.3 Factory

Xiamen Hanin Co., Ltd.

No.96, Rongyuan Road, Tong'an District, Xiamen, China 361100

1.4 Basic Description of Equipment Under Test

Product No.	POC240615019-S006	
Equipment Name	Thermal Transfer Barcode Printer	
Test Model	iF4	
Model Number	iF4, iF4 Plus, iH4, iH400, FT400, FT430, XT400, XT430, SF400, SF430, NF400, NT430, EF400, EF430, JF400, JF430, Y40, Y43, SF401, SF603, NF400, J400, J403, Y401, Y403, iF400, iF430, X400, X430, D400, D430, T400, T430, iF888, FT888, F8, F400, F430, JT400, ST400	
Model difference	Only the model name is different.	
Trade Mark	iDPRT	
Power Supply	DC 24V from adapter	
Adapter information	Model: GM53-240200-D Input: 100-240V~50/60Hz 2.0A Output: 24V $\overline{=}$ 2.0A, 48.0W	
Operate temperature	-20℃-60℃	
EUT Stage	○ Product Unit	● Final-Sample
Operating Band and Conducted Output Power (Max power)	2400MHz ~ 2483.5MHz	● IEEE 802.11n20:22.03dBm(0.16W)
Product Type	IEEE 802.11b: WLAN IEEE 802.11g: WLAN IEEE 802.11n: WLAN	
Nominal Bandwidth	20MHz	
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: OFDM	
Data Rate (Mbps)	IEEE 802.11b mode : 1/2/5.5/11 IEEE 802.11g mode : 6/9/12/18/24/36/48/54 IEEE 802.11n mode : up to 72.2	
Antenna gain	Ant1:2.72 dBi	
Antenna type	PIFA Anatnna	

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400MHz ~ 2483.5 MHz	01	2412MHz	07	2442MHz
	02	2417MHz	08	2447MHz
	03	2422MHz	09	2452MHz
	04	2427MHz	10	2457MHz
	05	2432MHz	11	2462MHz
	06	2437MHz	/	/

1.5 Transmit Operating Mode

Transmit Operating Mode		Transmit Multiple Antennas					
☒	Operating mode 1 (single antenna)	☒	1TX				
☐	Operating mode 2 (multiple antenna, no beam forming)	☐	2TX	☐	3TX	☐	4TX
☐	Operating mode 3 (multiple antenna, with beam forming)	☐	2TX	☐	3TX	☐	4TX

2. Summary of Test Results

2.1 Summary of Test Items

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Test item	FCC Clause	Results	Remarks
AC Power Conducted Emission	15.207	Pass	Meet the requirement of the limit
Radiated Emission and Band Edge Measurement	15.205/15.209 /15.247(d)	Pass	Meet the requirement of the limit
Spurious Emission at Antenna Port	15.247(d)	Pass	Meet the requirement of the limit
6dB Bandwidth	15.247(a)(2)	Pass	Meet the requirement of the limit
Maximum Conducted Power	15.247(b)	Pass	Meet the requirement of the limit
Power Spectral Density	15.247(e)	Pass	Meet the requirement of the limit
Antenna Requirements	15.203	Compliance	Note
Note: The EUT has two PIFA antenna arrangement which was permanently attached.			

2.2 Application of Standard

47 CFR FCC Part 15, Subpart C (Section 15.247)

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10:2013

2.3 Test Instruments

No.	Name of Equipment	Manufacturer	Model Number	Serial Number	Inventory No.	Last Calibration	Due Calibration
Radiated Emission							
1	Test receiver	Rohde&Schwarz	ESU	100184	JLE011	2024/4/24	2025/4/23
2	Log periodic antenna	Schwarzbeck	VULB 9168	1151	JLE012	2024/4/20	2025/4/19
3	Low frequency amplifier	/	LNA 0920N	2014	JLE023	2024/4/24	2025/4/23
4	High frequency amplifier	Schwarzbeck	BBV 9718	284	JLE024	2024/4/24	2025/4/23
5	Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1273	JLE028	2024/4/20	2025/4/19
6	Temp&Humidity Recorder	Meideshi	JR900	/	JLE021	2024/4/24	2025/4/23
7	Horn Antenna	SCHWARZBECK	BBHA 9170	9170#685	JLE029	2024/7/15	2025/7/14
8	Loop Antenna	SCHWARZBECK	FMZB1519B	00029	JLE030	2024/7/15	2025/7/14
9	Broadband preamplifier	Schwarzbeck	BBV9721	9721-019	JLE025	2024/4/24	2025/4/23
10	SAC	SAEMC	9*6*6	/	/	2022/5/4	2025/5/3
11	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
Conducted Emission							
1	LISN	Rohde&Schwarz	ENV216	100075	JLE002	2024/4/24	2025/4/23
2	ISN	Schwarzbeck	CATE 5 8158	#171	JLE003	2024/4/24	2025/4/23
3	ISN	Schwarzbeck	CAT 3 8158	00187	JLE032	2024/3/31	2025/3/30
4	Test receiver	Rohde&Schwarz	ESCI	100718	JLE010	2024/4/24	2025/4/23
5	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	JLE047	2024/4/24	2025/4/23
6	Temp&Humidity Recorder	Meideshi	JR900	/	JLE020	2024/4/24	2025/4/23
7	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				

RF Conducted Emissions							
1	MXA Signal Analyzer	Keysight	N9021B	MY60080169	JLE050	2024/4/20	2025/4/19
2	RF Control Unit	dsusoft	JS0806-2	21G8060449	JLE053	2024/4/20	2025/4/19
3	power supply unit	dsusoft	JS0806-4 ADC	N/A	JLE055	2024/4/20	2025/4/19
4	VXG Signal Generator	Keysight	M9384B	MY61270787	JLE051	2024/4/20	2025/4/19
5	EXG Analog Signal Generator	Keysight	N5173B	MY59101282	JLE052	2024/4/20	2025/4/19
6	Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	1201.0002K5 0-116064-Dt	JLE054	2024/4/20	2025/4/19
7	Test software	dsusoft	JS1120-3 Ver.3.2.22.0				

2.4 Test Mode

Test Items	Mode	Data Rate	Channel
AC Power Conducted Emission	802.11n(20MHz)	MCS0	11
Radiated Emission and Band Edge Measurement	802.11b	1Mbps	01/06/11
	802.11g	6Mbps	01/06/11
	802.11n(20MHz)	MCS0	01/06/11
Spurious Emission at Antenna Port	802.11b	1Mbps	01/06/11
	802.11g	6Mbps	01/06/11
	802.11n(20MHz)	MCS0	01/06/11
6dB Bandwidth	802.11b	1Mbps	01/06/11
	802.11g	6Mbps	01/06/11
	802.11n(20MHz)	MCS0	01/06/11
Maximum Conducted Power	802.11b	1Mbps	01/06/11
	802.11g	6Mbps	01/06/11
	802.11n(20MHz)	MCS0	01/06/11
Power Spectral Density	802.11b	1Mbps	01/06/11
	802.11g	6Mbps	01/06/11
	802.11n(20MHz)	MCS0	01/06/11

Note: For AC Power Conducted Emission and Radiated Emission below 1GHz, only worst case was recorded.

2.5 Test Condition

Applicable to	Environmental conditions	Input Power	Tested by
AC Power Conducted Emission	24.2°C, 51% RH	AC 120V/60Hz	Freedom Zhuo
Radiated Emission and Band Edge Measurement	23.8°C, 56% RH	AC 120V/60Hz	Freedom Zhuo
Spurious Emission at Antenna Port	23.4°C, 52% RH	AC 120V/60Hz	Albert Fan
6dB Bandwidth	23.4°C, 52% RH	AC 120V/60Hz	Albert Fan
Maximum Conducted Power	23.4°C, 52% RH	AC 120V/60Hz	Albert Fan
Power Spectral Density	23.4°C, 52% RH	AC 120V/60Hz	Albert Fan

Note: Adapter supply voltage AC 120V/60Hz.

The applicant declare the operating environment of EUT as below:

Normal conditions: AC 120 V, 0~45°C


2.6 Duty Cycle of Test SignalX

If duty cycle is $\geq 98\%$, duty factor is not required.


If duty cycle is $< 98\%$, duty factor shall be considered.

All the duty factor of other test mode have been considered.


TestMode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Factor
11B	Ant1	2412	12.41	12.54	98.96	0.05
11G	Ant1	2412	2.07	2.20	94.09	0.26
11N20SISO	Ant1	2412	1.92	2.05	93.66	0.28



NTNV-11B-Ant1-2412



NTNV-11G-Ant1-2412



NTNV-11N20SISO-Ant1-2412

2.7 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 102\text{kHz}$
Power Spectral Density	$\pm 0.743\text{dB}$
Conducted Spurious Emission	$\pm 1.328\text{dB}$
RF power conducted	$\pm 0.377\text{dB}$
Conducted emission(9kHz~30MHz) AC main	$\pm 2.68\text{dB}$
Radiated emission(9kHz~30MHz)	$\pm 2.74\text{dB}$
Radiated emission (30MHz~1GHz)	$\pm 4.22\text{dB}$
Radiated emission (1GHz~18GHz)	$\pm 5.06\text{dB}$
Radiated emission (18GHz~40GHz)	$\pm 4.98\text{dB}$

2.8 Test Location

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier	CN0145
A2LA Certificate Number	6823.01
Telephone:	0755-26024411

2.9 Description of Support Units

No.	Equipment	Model	Manufacturer	Series No
1	/	/	/	/

3. Test Procedure And Results

3.1 AC Power Line Conducted Emission

3.1.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3.1.2 Test Procedure

Test Method	
☒ Conducted Measurement	☐ Radiated Measurement
Test Channels	
☐ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme

Note: ● : Test ○ : No Test

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

3.1.3 Test Setup




3.1.4 Test Result

Note:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Measurement = Reading + Correct Factor.
3. Over = Measurement – Limit

We only recorded the data of the worst mode. Please see the following:


150kHz~30MHz	Worst Case Operating Mode: 11n20 Channel 11
--------------	---



150kHz~30MHz

Worst Case Operating Mode: 11n20 Channel 11

Neutral



3.2 Radiated Emission and Band Edge

3.2.1 Limit

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Distance Meters(m)	Field Strength Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 – 0.49	300	2400/F(kHz)	-
0.490 – 1.705	30	24000/F(kHz)	-
1.705 – 30	30	30	-
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V}/\text{m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.2.2 Test Procedure

Test Method	
☐ Conducted Measurement	☒ Radiated Measurement
Test Channels	
☒ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme

Note: ☒ : Test ☐ : No Test


- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of

the antenna are set to make the measurement.


- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e) The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f) The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g) All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h) All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i) For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.2.3 Test Setup


(A) Radiated Emission Test Set-Up Frequency Below 30 MHz



(B) Radiated Emission Test Set-Up Frequency 30 MHz-1000 MHz



(C) Radiated Emission Test Set-Up Frequency Above 1 GHz



3.2.4 Test Result

1) Radiated emission: 9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

2) Radiated emission: 30MHz-1G

Note:


1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit

We only recorded the data of the worst mode. Please see the following:


Below 1G (30MHz~1GHz)

Worst Case Operating Mode: 11n20 Channel 11

VERTICAL



HORIZONTAL





3) Radiated emission: Above 1G

Note:

1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit


Above 1G (1GHz~18GHz)	Test mode:11B	Test Channel:1
-----------------------	---------------	----------------

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4824.000	56.53	-4.18	52.35	74.00	-21.65	peak		
2 *		4824.000	54.20	-4.18	50.02	54.00	-3.98	AVG		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	47.78	-1.78	46.00	74.00	-28.00	peak		
2 *		2390.000	48.93	-1.54	47.39	74.00	-26.61	peak		

Above 1G (1GHz~18GHz)


Test mode:11B

Test Channel:6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11B

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4944.000	61.44	-5.07	56.37	74.00	-17.63			peak
2 *		4944.000	57.56	-5.07	52.49	54.00	-1.51			AVG


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1 *		2483.500	47.14	-0.90	46.24	74.00	-27.76			peak
2		2500.000	44.18	-0.74	43.44	74.00	-30.56			peak


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4944.000	61.25	-5.07	56.18	74.00	-17.82	peak		
2 *		4944.000	58.05	-5.07	52.98	54.00	-1.02	AVG		

Radiated Emission





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1 *		2483.500	47.21	-0.90	46.31	74.00	-27.69	peak		
2		2500.000	45.21	-0.74	44.47	74.00	-29.53	peak		

Above 1G (1GHz~18GHz)

Test mode:11G


Test Channel:1

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4824.000	65.42	-4.18	61.24	74.00	-12.76	peak		
2 *		4824.000	54.52	-4.18	50.34	54.00	-3.66	AVG		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	37.17	8.22	45.39	74.00	-28.61	peak		
2		2390.000	50.25	8.46	58.71	74.00	-15.29	peak		
3 *		2390.000	38.77	8.46	47.23	54.00	-6.77	AVG		

Above 1G (1GHz~18GHz)


Test mode:11G

Test Channel:6

VERTICAL



HORIZONTAL





Above 1G (1GHz~18GHz)

Test mode: 11G


Test Channel:11

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4944.000	64.85	-5.07	59.78	74.00	-14.22	peak		
2 *		4944.000	51.91	-5.07	46.84	54.00	-7.16	AVG		

Radiated Emission





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2483.500	54.69	9.10	63.79	74.00	-10.21	peak		
2 *		2483.500	43.67	9.10	52.77	54.00	-1.23	AVG		
3		2500.000	43.22	9.26	52.48	74.00	-21.52	peak		

Above 1G (1GHz~18GHz)

Test mode: 11N20


Test Channel:1

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4824.000	62.06	-4.18	57.88	74.00	-16.12	peak		
2 *		4824.000	51.30	-4.18	47.12	54.00	-6.88	AVG		

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	34.05	8.22	42.27	74.00	-31.73	peak		
2		2390.000	47.89	8.46	56.35	74.00	-17.65	peak		
3 *		2390.000	37.82	8.46	46.28	54.00	-7.72	AVG		

Above 1G (1GHz~18GHz)


Test mode:11N20

Test Channel:6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11N20

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4944.000	63.07	-5.07	58.00	74.00	-16.00			peak
2 *		4944.000	50.18	-5.07	45.11	54.00	-8.89			AVG


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1 *		2483.500	43.92	9.10	53.02	74.00	-20.98			peak
2		2500.000	34.43	9.26	43.69	74.00	-30.31			peak


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4944.000	64.20	-5.07	59.13	74.00	-14.87	peak		
2 *		4944.000	52.70	-5.07	47.63	54.00	-6.37	AVG		

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	54.62	9.10	63.72	74.00	-10.28	peak		
2 *		2483.500	43.79	9.10	52.89	54.00	-1.11	AVG		
3		2500.000	40.05	9.26	49.31	74.00	-24.69	peak		

The high frequency, which started from 18GHz to 25GHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

3.3 Spurious Emission at Antenna Port

3.3.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

3.3.2 Test Procedure


Test Method	
☒ Conducted Measurement	☐ Radiated Measurement
Test Channels	
☒ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme
Note: ☒ : Test ☐ : No Test	

a) The EUT was directly connected to the tonscond test system and antenna output port as show in the block diagram below.

b) Spectrum Setting as below:

Centre Frequency	The centre frequency of the channel under test
Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.3.3 Test Setup




3.3.4 The Result


Conducted Spurious Emission



11B-Ant1-2412-0~Reference-PASS




11B-Ant1-2412-30~1000-PASS



11B-Ant1-2412-1000~26500-PASS



11B-Ant1-2437-0~Reference-PASS




11B-Ant1-2437-30~1000-PASS



11B-Ant1-2437-1000~26500-PASS



11B-Ant1-2462-0~Reference-PASS




11B-Ant1-2462-30~1000-PASS



11B-Ant1-2462-1000~26500-PASS



11G-Ant1-2412-0~Reference-PASS




11G-Ant1-2412-30~1000-PASS



11G-Ant1-2412-1000~26500-PASS



11G-Ant1-2437-0~Reference-PASS



11G-Ant1-2437-30~1000-PASS