

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
BT EDR	2402MHz	6.06	4.04	5.7	0.00299	1.0	PASS
BLE	2402MHz	4.75	2.99	5.7	0.00221	1.0	
2.4G WIFI	2437MHz ANT 1	10.69	11.72	7.3	0.01252	1.0	
	2412MHz MIMO	12.34	17.14	10.41	0.03747	1.0	
5.2G WIFI	5180MHz ANT 1	12.26	16.83	5.9	0.01302	1.0	
	5190MHz MIMO	8.49	7.06	9.48	0.01246	1.0	
5.3G WIFI	5290MHz ANT 1	12.41	17.42	5.9	0.01348	1.0	
	5270MHz MIMO	8.56	7.18	9.37	0.01235	1.0	
5.6G WIFI	5580MHz ANT 2	11.12	12.94	7.1	0.01321	1.0	
	5670MHz MIMO	7.89	6.15	10.31	0.01314	1.0	
5.8G WIFI	5755MHz ANT 2	10.83	12.11	7.4	0.01325	1.0	
	5795MHz MIMO	6.95	4.95	10.98	0.01235	1.0	

Remark: Directional gain= $10\log [(10^{\text{ANT1}/20}+10^{\text{ANT2}/20})^2/2]$ dBi

BT and WIFI Simultaneous Transmission:

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

BT EDR + 2.4G WIFI +5.3G WIFI =(0.00299/1)+(0.03747/1) +(0.01348/1)=0.05394<1

The max power density is less than MPE exempt limit, so it is compliance.