

## RF Exposure evaluation

### According to 447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison.

$$\text{eirp} = p_t \times g_t = (E \times d)^2 / 30$$

where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m, ---  $10^{((\text{dBuV/m})/20)}/10^6$ ,

$d$  = measurement distance in meters (m)--- 3m.

$$\text{So } p_t = (E \times d)^2 / (30 \times g_t)$$

### Worse case is as below:

Field strength = 91.77 dBuV/m @3m

Ant gain -0.26 dBi; so Ant numeric gain=0.94

$$\text{So } p_t = \{ [10^{(91.77/20)} / 10^6 \times 3]^2 / (30 \times 0.94) \} \times 1000 \text{mW} = 0.48 \text{mW}$$

$$\text{So } (0.48 \text{mW} / 5 \text{mm}) \times \sqrt{2.480 \text{GHz}} = 0.15 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required.