



RF TEST REPORT

Applicant Xiaomi Communications Co., Ltd.
FCC ID 2AFZZ119SG
Product Mobile Phone
Brand Redmi
Model 21121119SG
Report No. R2109A0819-R1V1
Issue Date November 15, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2020)/ FCC CFR 47 Part 22H (2020)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	5
1.1. Notes of the Test Report	5
1.2. Test facility	5
1.3. Testing Location	5
2. General Description of Equipment under Test	6
2.1. Applicant and Manufacturer Information	6
2.2. General Information	6
3. Applied Standards	8
4. Test Configuration	9
5. Test Case Results	11
5.1. RF Power Output and Effective Radiated Power	11
5.2. Occupied Bandwidth	16
5.3. Band Edge Compliance	27
5.4. Peak-to-Average Power Ratio (PAPR)	38
5.5. Frequency Stability	41
5.6. Spurious Emissions at Antenna Terminals	45
5.7. Radiates Spurious Emission	50
6. Main Test Instruments	59
ANNEX A: The EUT Appearance	60
ANNEX B: Test Setup Photos	61



Version	Revision description	Issue Date
Rev.0	Initial issue of report.	November 8, 2021
Rev.1	Update Extreme Temperature	November 15, 2021
Note: This revised report (Report No. R2109A0819-R1V1) supersedes and replaces the previously issued report (Report No. R2109A0819-R1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Radiated Power	2.1046 22.913(a)(5)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 / 22.917(a)	PASS
4	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS

Date of Testing: October 15, 2021~ October 21, 2021

Date of Sample Received: September 30, 2021

Note: PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Xiaomi Communications Co., Ltd.
Applicant address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer	Xiaomi Communications Co., Ltd.
Manufacturer address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

2.2. General Information

EUT Description			
Model	21121119SG		
IMEI	IMEI 1: 860406050010980 IMEI 2: 860406050010998		
Hardware Version	P2		
Software Version	MIUI12.5		
Antenna Type	PIFA Antenna		
Antenna Gain	Low Antenna	Upper Antenna	
	-2.4 dBi	-6.7 dBi	
Test Mode(s)	GSM 850; WCDMA Band V; LTE Band 5;		
Test Modulation	(GSM/GPRS)GMSK, (EGPRS) GMSK/ 8PSK; (WCDMA) BPSK, QPSK,16QAM; (LTE) QPSK, 16QAM, 64QAM;		
GPRS Multislot Class	12		
EGPRS Multislot Class	12		
HSDPA UE Category	24		
HSUPA UE Category	7		
LTE Category	7		
Maximum E.R.P.	GSM 850:	28.13 dBm	
	WCDMA Band V:	9.84 dBm	
	LTE Band 5:	20.22 dBm	
Rated Power Supply Voltage	3.87V		
Operating Voltage	Minimum:3.60V Maximum: 4.45V		
Operating Temperature	Lowest: -10°C Highest: +60°C		
Extreme Temperature	Lowest: -30°C Highest: +60°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894



	LTE Band 5	824 ~ 849	869 ~ 894
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR 47 Part 22H (2020)

FCC CFR47 Part 2 (2020)

Reference standard:

ANSI C63.26 (2015)

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, horizontal polarization for GSM/WCDMA; X axis, horizontal polarization for LTE, Upper Antenna; Z axis, vertical polarization for LTE, Low Antenna) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in GSM/WCDMA/LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test items	Modes/Modulation	
	GSM 850	WCDMA Band V
RF Power Output and Effective Radiated power	GSM GPRS EGPRS	RMC/ AMR HSDPA/HSUPA DC-HSDPA/HSPA+
Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Spurious Emissions at Antenna Terminals	GSM	RMC
Radiates Spurious Emission	GSM	RMC

Test modes are chosen as the worst case configuration below for LTE Band 5.

Test items	Bandwidth (MHz)				Modulation		RB			Test Channel		
	1.4	3	5	10	QPSK	16QAM/ 64QAM	1	50%	100%	L	M	H
RF power output and Effective Radiated power	O	O	O	O	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	-	-	O	O	O	O



Band Edge Compliance	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	O	-	-	-	O	-
Spurious Emissions at Antenna Terminals	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	-	O	O	O	-	O	-	-	-	O	-
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.											

5. Test Case Results

5.1. RF Power Output and Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$EIRP \text{ (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$

where:dBd refers to gain relative to an ideal dipole.

$EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB)}$.

Test Setup



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 22.913(a)(5) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W}$ (38.45 dBm)
-------	--------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4 \text{ dB}$ for RF power output, $k = 2$, $U = 1.19 \text{ dB}$ for ERP.



Test Results

GSM 850		Maximum Output Power (dBm)			ERP (dBm) (Low Antenna)			ERP (dBm) (Upper Antenna)		
		Channel 128	Channel 190	Channel 251	Channel 128	Channel 190	Channel 251	Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)	824.2 (MHz)	836.6 (MHz)	848.8 (MHz)	824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GSM	CS	32.68	32.67	32.66	28.13	28.12	28.11	23.83	23.82	23.81
GPRS /EGPRS (GMSK)	1TXslot	32.67	32.67	32.65	28.12	28.12	28.10	23.82	23.82	23.80
	2TXslots	31.95	31.95	31.93	27.40	27.40	27.38	23.10	23.10	23.08
	3TXslots	30.21	30.22	30.20	25.66	25.67	25.65	21.36	21.37	21.35
	4TXslots	29.10	29.09	29.08	24.55	24.54	24.53	20.25	20.24	20.23
EGPRS (8PSK)	1TXslot	26.23	26.22	26.15	21.68	21.67	21.60	17.38	17.37	17.30
	2TXslots	24.44	24.19	24.20	19.89	19.64	19.65	15.59	15.34	15.35
	3TXslots	21.74	21.93	21.80	17.19	17.38	17.25	12.89	13.08	12.95
	4TXslots	20.55	20.71	20.99	16.00	16.16	16.44	11.70	11.86	12.14

WCDMA Band V		Maximum Output Power (dBm)			ERP (dBm) (Low Antenna)			ERP (dBm) (Upper Antenna)		
		Channel 4132	Channel 4183	Channel 4233	Channel 4132	Channel 4183	Channel 4233	Channel 4132	Channel 4183	Channel 4233
		826.4 (MHz)	836.6 (MHz)	846.6 (MHz)	826.4 (MHz)	836.6 (MHz)	846.6 (MHz)	826.4 (MHz)	836.6 (MHz)	846.6 (MHz)
RMC		24.26	24.25	24.25	19.71	19.70	19.70	15.41	15.40	15.40
AMR		24.10	24.39	24.37	19.55	19.84	19.82	15.25	15.54	15.52
HSDPA	Sub - Test 1	23.18	23.11	23.31	18.63	18.56	18.76	14.33	14.26	14.46
	Sub - Test 2	23.34	23.29	23.37	18.79	18.74	18.82	14.49	14.44	14.52
	Sub - Test 3	22.62	22.87	22.87	18.07	18.32	18.32	13.77	14.02	14.02
	Sub - Test 4	22.82	22.85	22.85	18.27	18.30	18.30	13.97	14.00	14.00
HSUPA	Sub - Test 1	22.16	22.17	22.33	17.61	17.62	17.78	13.31	13.32	13.48
	Sub - Test 2	21.82	21.79	21.67	17.27	17.24	17.12	12.97	12.94	12.82
	Sub - Test 3	22.82	22.89	22.77	18.27	18.34	18.22	13.97	14.04	13.92
	Sub - Test 4	21.24	21.27	21.29	16.69	16.72	16.74	12.39	12.42	12.44
	Sub - Test 5	22.82	22.83	22.81	18.27	18.28	18.26	13.97	13.98	13.96
DC-HSDPA	Sub - Test 1	23.34	23.29	23.41	18.79	18.74	18.86	14.49	14.44	14.56
	Sub - Test 2	23.18	23.25	23.29	18.63	18.70	18.74	14.33	14.40	14.44
	Sub - Test 3	22.88	22.89	22.79	18.33	18.34	18.24	14.03	14.04	13.94
	Sub - Test 4	22.78	22.65	22.65	18.23	18.10	18.10	13.93	13.80	13.80
HSPA+	16QAM	21.68	21.59	21.89	17.13	17.04	17.34	12.83	12.74	13.04



LTE Band 5				Maximum Output Power(dBm)			ERP (dBm) (Low Antenna)			ERP (dBm) (Upper Antenna)		
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				20407 /824.7	20525 /836.5	20643 /848.3	20407 /824.7	20525 /836.5	20643 /848.3	20407 /824.7	20525 /836.5	20643 /848.3
1.4MHz	QPSK	1	0	24.54	24.61	24.52	19.99	20.06	19.97	15.69	15.76	15.67
		1	2	24.77	24.61	24.62	20.22	20.06	20.07	15.92	15.76	15.77
		1	5	24.51	24.47	24.63	19.96	19.92	20.08	15.66	15.62	15.78
		3	0	24.52	24.56	24.55	19.97	20.01	20.00	15.67	15.71	15.70
		3	2	24.53	24.62	24.61	19.98	20.07	20.06	15.68	15.77	15.76
		3	3	24.51	24.57	24.59	19.96	20.02	20.04	15.66	15.72	15.74
		6	0	23.52	23.69	23.58	18.97	19.14	19.03	14.67	14.84	14.73
	16QAM	1	0	23.78	23.65	23.66	19.23	19.10	19.11	14.93	14.80	14.81
		1	2	23.76	23.69	23.72	19.21	19.14	19.17	14.91	14.84	14.87
		1	5	24.00	23.68	23.96	19.45	19.13	19.41	15.15	14.83	15.11
		3	0	23.61	23.54	23.58	19.06	18.99	19.03	14.76	14.69	14.73
		3	2	23.59	23.50	23.54	19.04	18.95	18.99	14.74	14.65	14.69
		3	3	23.52	23.65	23.47	18.97	19.10	18.92	14.67	14.80	14.62
		6	0	22.74	22.70	22.73	18.19	18.15	18.18	13.89	13.85	13.88
	64QAM	1	0	22.76	22.66	22.74	18.21	18.11	18.19	13.91	13.81	13.89
		1	2	22.79	22.72	22.77	18.24	18.17	18.22	13.94	13.87	13.92
		1	5	22.82	22.74	22.81	18.27	18.19	18.26	13.97	13.89	13.96
		3	0	22.72	22.56	22.73	18.17	18.01	18.18	13.87	13.71	13.88
		3	2	22.76	22.64	22.73	18.21	18.09	18.18	13.91	13.79	13.88
		3	3	22.61	22.49	22.56	18.06	17.94	18.01	13.76	13.64	13.71
		6	0	21.71	21.61	21.70	17.16	17.06	17.15	12.86	12.76	12.85
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				20415 /825.5	20525 /836.5	20635 /847.5	20415 /825.5	20525 /836.5	20635 /847.5	20415 /825.5	20525 /836.5	20635 /847.5
3MHz	QPSK	1	0	24.56	24.65	24.55	20.01	20.10	20.00	15.71	15.80	15.70
		1	7	24.75	24.64	24.66	20.20	20.09	20.11	15.90	15.79	15.81
		1	14	24.54	24.52	24.67	19.99	19.97	20.12	15.69	15.67	15.82
		8	0	23.62	23.68	23.68	19.07	19.13	19.13	14.77	14.83	14.83
		8	4	23.65	23.72	23.73	19.10	19.17	19.18	14.80	14.87	14.88
		8	7	23.61	23.68	23.69	19.06	19.13	19.14	14.76	14.83	14.84
		15	0	23.52	23.73	23.61	18.97	19.18	19.06	14.67	14.88	14.76
	16QAM	1	0	23.81	23.67	23.69	19.26	19.12	19.14	14.96	14.82	14.84



		1	7	23.79	23.69	23.76	19.24	19.14	19.21	14.94	14.84	14.91
		1	14	23.88	23.72	23.99	19.33	19.17	19.44	15.03	14.87	15.14
		8	0	22.72	22.67	22.70	18.17	18.12	18.15	13.87	13.82	13.85
		8	4	22.70	22.63	22.66	18.15	18.08	18.11	13.85	13.78	13.81
		8	7	22.62	22.77	22.60	18.07	18.22	18.05	13.77	13.92	13.75
		15	0	22.77	22.74	22.76	18.22	18.19	18.21	13.92	13.89	13.91
	64QAM	1	0	22.79	22.68	22.77	18.24	18.13	18.22	13.94	13.83	13.92
		1	7	22.82	22.72	22.79	18.27	18.17	18.24	13.97	13.87	13.94
		1	14	22.84	22.73	22.84	18.29	18.18	18.29	13.99	13.88	13.99
		8	0	21.83	21.69	21.85	17.28	17.14	17.30	12.98	12.84	13.00
		8	4	21.87	21.77	21.85	17.32	17.22	17.30	13.02	12.92	13.00
		8	7	21.71	21.61	21.69	17.16	17.06	17.14	12.86	12.76	12.84
		15	0	21.74	21.65	21.73	17.19	17.10	17.18	12.89	12.80	12.88
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				20425 /826.5	20525 /836.5	20625 /846.5	20425 /826.5	20525 /836.5	20625 /846.5	20425 /826.5	20525 /836.5	20625 /846.5
5MHz	QPSK	1	0	24.53	24.63	24.51	19.98	20.08	19.96	15.68	15.78	15.66
		1	13	24.73	24.60	24.63	20.18	20.05	20.08	15.88	15.75	15.78
		1	24	24.51	24.47	24.63	19.96	19.92	20.08	15.66	15.62	15.78
		12	0	23.59	23.63	23.64	19.04	19.08	19.09	14.74	14.78	14.79
		12	6	23.63	23.68	23.68	19.08	19.13	19.13	14.78	14.83	14.83
		12	13	23.59	23.66	23.65	19.04	19.11	19.10	14.74	14.81	14.80
		25	0	23.52	23.72	23.59	18.97	19.17	19.04	14.67	14.87	14.74
	16QAM	1	0	23.78	23.63	23.66	19.23	19.08	19.11	14.93	14.78	14.81
		1	13	23.76	23.67	23.73	19.21	19.12	19.18	14.91	14.82	14.88
		1	24	23.99	23.70	23.95	19.44	19.15	19.40	15.14	14.85	15.10
		12	0	22.70	22.63	22.67	18.15	18.08	18.12	13.85	13.78	13.82
		12	6	22.67	22.58	22.62	18.12	18.03	18.07	13.82	13.73	13.77
		12	13	22.59	22.72	22.56	18.04	18.17	18.01	13.74	13.87	13.71
		25	0	22.75	22.70	22.71	18.20	18.15	18.16	13.90	13.85	13.86
	64QAM	1	0	22.76	22.68	22.74	18.21	18.13	18.19	13.91	13.83	13.89
		1	13	22.79	22.74	22.76	18.24	18.19	18.21	13.94	13.89	13.91
		1	24	22.85	22.71	22.80	18.30	18.16	18.25	14.00	13.86	13.95
		12	0	21.81	21.65	21.86	17.26	17.10	17.31	12.96	12.80	13.01
		12	6	21.84	21.72	21.81	17.29	17.17	17.26	12.99	12.87	12.96
		12	13	21.68	21.56	21.65	17.13	17.01	17.10	12.83	12.71	12.80
		25	0	21.72	21.61	21.68	17.17	17.06	17.13	12.87	12.76	12.83



BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				20450 /829	20525 /836.5	20600 /844	20450 /829	20525 /836.5	20600 /844	20450 /829	20525 /836.5	20600 /844
10MHz	QPSK	1	0	24.51	24.56	24.49	19.96	20.01	19.94	15.66	15.71	15.64
		1	25	24.73	24.60	24.62	20.18	20.05	20.07	15.88	15.75	15.77
		1	49	24.48	24.45	24.59	19.93	19.90	20.04	15.63	15.60	15.74
		25	0	23.57	23.59	23.61	19.02	19.04	19.06	14.72	14.74	14.76
		25	13	23.61	23.64	23.65	19.06	19.09	19.10	14.76	14.79	14.80
		25	25	23.55	23.62	23.62	19.00	19.07	19.07	14.70	14.77	14.77
		50	0	23.51	23.65	23.54	18.96	19.10	18.99	14.66	14.80	14.69
	16QAM	1	0	23.58	23.60	23.61	19.03	19.05	19.06	14.73	14.75	14.76
		1	25	23.73	23.66	23.70	19.18	19.11	19.15	14.88	14.81	14.85
		1	49	23.97	23.65	23.93	19.42	19.10	19.38	15.12	14.80	15.08
		25	0	22.67	22.62	22.65	18.12	18.07	18.10	13.82	13.77	13.80
		25	13	22.63	22.55	22.58	18.08	18.00	18.03	13.78	13.70	13.73
		25	25	22.57	22.68	22.53	18.02	18.13	17.98	13.72	13.83	13.68
		50	0	22.73	22.66	22.68	18.18	18.11	18.13	13.88	13.81	13.83
	64QAM	1	0	22.71	22.61	22.69	18.16	18.06	18.14	13.86	13.76	13.84
		1	25	22.76	22.69	22.73	18.21	18.14	18.18	13.91	13.84	13.88
		1	49	22.79	22.66	22.78	18.24	18.11	18.23	13.94	13.81	13.93
		25	0	21.78	21.64	21.80	17.23	17.09	17.25	12.93	12.79	12.95
		25	13	21.80	21.69	21.77	17.25	17.14	17.22	12.95	12.84	12.92
		25	25	21.66	21.52	21.62	17.11	16.97	17.07	12.81	12.67	12.77
		50	0	21.70	21.57	21.65	17.15	17.02	17.10	12.85	12.72	12.80

5.2. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to $\geq 1\%EBW$, VBW is set to 3x RBW.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Result

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GMSK)	128	824.2	0.248	0.310
	190	836.6	0.247	0.318
	251	848.8	0.246	0.314
GPRS 850 (GMSK)	128	824.2	0.253	0.321
	190	836.6	0.244	0.310
	251	848.8	0.249	0.317
EGPRS 850 (8PSK)	128	824.2	0.248	0.316
	190	836.6	0.267	0.310
	251	848.8	0.247	0.309
WCDMA Band V (RMC)	4132	826.4	4.166	4.699
	4183	836.6	4.156	4.695
	4233	846.6	4.155	4.686

LTE Band 5						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	20407	824.7	1.098	1.276
			20525	836.5	1.089	1.279
			20643	848.3	1.090	1.291
		3	20415	825.5	2.694	2.929
			20525	836.5	2.693	2.926
			20635	847.5	2.687	2.909
		5	20425	826.5	4.502	4.915
			20525	836.5	4.502	4.907
			20625	846.5	4.496	4.935
		10	20450	829	8.981	9.753
			20525	836.5	8.995	9.638
			20600	844	8.987	9.648
	16QAM	1.4	20407	824.7	1.096	1.282
			20525	836.5	1.098	1.286
			20643	848.3	1.092	1.275



		3	20415	825.5	2.692	2.939
			20525	836.5	2.683	2.913
			20635	847.5	2.694	2.915
		5	20425	826.5	4.503	4.933
			20525	836.5	4.506	4.917
			20625	846.5	4.506	4.933
		10	20450	829	8.988	9.686
			20525	836.5	8.976	9.712
			20600	844	8.981	9.743
	64QAM	1.4	20407	824.7	1.097	1.288
			20525	836.5	1.097	1.300
			20643	848.3	1.087	1.286
		3	20415	825.5	2.680	2.931
			20525	836.5	2.688	2.926
			20635	847.5	2.687	2.940
		5	20425	826.5	4.499	4.938
			20525	836.5	4.526	4.927
			20625	846.5	4.508	4.902
		10	20450	829	8.971	9.657
			20525	836.5	8.989	9.636
			20600	844	8.981	9.773



GSM 850 CH-Low



GSM 850 GPRS CH-Low



GSM 850 CH-Middle



GSM 850 GPRS CH-Middle



GSM 850 CH-High



GSM 850 GPRS CH-High





GSM 850 EGPRS CH-Low




WCDMA Band V CH-Low



GSM 850 EGPRS CH-Middle



WCDMA Band V CH-Middle




GSM 850 EGPRS CH-High




WCDMA Band V CH-High




LTE Band 5 QPSK 1.4MHz CH-Low




LTE Band 5 QPSK 3MHz CH-Low




LTE Band 5 QPSK 1.4MHz CH-Middle




LTE Band 5 QPSK 3MHz CH-Middle




LTE Band 5 QPSK 1.4MHz CH-High




LTE Band 5 QPSK 3MHz CH-High




LTE Band 5 QPSK 5MHz CH-Low




LTE Band 5 QPSK 10MHz CH-Low




LTE Band 5 QPSK 5MHz CH-Middle




LTE Band 5 QPSK 10MHz CH-Middle



LTE Band 5 QPSK 5MHz CH-High




LTE Band 5 QPSK 10MHz CH-High







LTE Band 5 16QAM 1.4MHz CH-Low




LTE Band 5 16QAM 3MHz CH-Low




LTE Band 5 16QAM 1.4MHz CH-Middle




LTE Band 5 16QAM 3MHz CH-Middle



LTE Band 5 16QAM 1.4MHz CH-High




LTE Band 5 16QAM 3MHz CH-High







LTE Band 5 16QAM 5MHz CH-Low




LTE Band 5 16QAM 10MHz CH-Low




LTE Band 5 16QAM 5MHz CH-Middle




LTE Band 5 16QAM 10MHz CH-Middle



LTE Band 5 16QAM 5MHz CH-High




LTE Band 5 16QAM 10MHz CH-High







LTE Band 5 64QAM 1.4MHz CH-Low




LTE Band 5 64QAM 3MHz CH-Low




LTE Band 5 64QAM 1.4MHz CH-Middle




LTE Band 5 64QAM 3MHz CH-Middle




LTE Band 5 64QAM 1.4MHz CH-High




LTE Band 5 64QAM 3MHz CH-High




LTE Band 5 64QAM 5MHz CH-Low




LTE Band 5 64QAM 10MHz CH-Low




LTE Band 5 64QAM 5MHz CH-Middle




LTE Band 5 64QAM 10MHz CH-Middle



LTE Band 5 64QAM 5MHz CH-High



LTE Band 5 64QAM 10MHz CH-High



5.3. Band Edge Compliance

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to $\geq 1\%EBW$, VBW is set to 3x RBW.

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684dB$.




Test Result:


GSM 850 CH-Low




GSM 850 CH-High




GSM 850 GPRS CH-Low




GSM 850 GPRS CH-High



GSM 850 EGPRS CH-Low



GSM 850 EGPRS CH-High






WCDMA Band V CH-Low




WCDMA Band V CH-High




LTE Band 5 QPSK 1.4MHz CH-Low 1RB



LTE Band 5 QPSK 1.4MHz CH-High 1RB




LTE Band 5 QPSK 1.4MHz CH-Low 100%RB




LTE Band 5 QPSK 1.4MHz CH-High 100%RB




LTE Band 5 QPSK 3MHz CH-Low 1RB




LTE Band 5 QPSK 3MHz CH-High 1RB




LTE Band 5 QPSK 3MHz CH-Low 100%RB




LTE Band 5 QPSK 3MHz CH-High 100%RB




LTE Band 5 QPSK 5MHz CH-Low 1RB




LTE Band 5 QPSK 5MHz CH-High 1RB




LTE Band 5 QPSK 5MHz CH-Low 100%RB




LTE Band 5 QPSK 5MHz CH-High 100%RB




LTE Band 5 QPSK 10MHz CH-Low 1RB




LTE Band 5 QPSK 10MHz CH-High 1RB




LTE Band 5 QPSK 10MHz CH-Low 100%RB




LTE Band 5 QPSK 10MHz CH-High 100%RB




LTE Band 5 16QAM 1.4MHz CH-Low 1RB



LTE Band 5 16QAM 1.4MHz CH-High 1RB




LTE Band 5 16QAM 1.4MHz CH-Low 100%RB




LTE Band 5 16QAM 1.4MHz CH-High 100%RB




LTE Band 5 16QAM 3MHz CH-Low 1RB




LTE Band 5 16QAM 3MHz CH-High 1RB




LTE Band 5 16QAM 3MHz CH-Low 100%RB




LTE Band 5 16QAM 3MHz CH-High 100%RB




LTE Band 5 16QAM 5MHz CH-Low 1RB




LTE Band 5 16QAM 5MHz CH-High 1RB




LTE Band 5 16QAM 5MHz CH-Low 100%RB




LTE Band 5 16QAM 5MHz CH-High 100%RB




LTE Band 5 16QAM 10MHz CH-Low 1RB




LTE Band 5 16QAM 10MHz CH-High 1RB




LTE Band 5 16QAM 10MHz CH-Low 100%RB




LTE Band 5 16QAM 10MHz CH-High 100%RB




LTE Band 5 64QAM 1.4MHz CH-Low 1RB



LTE Band 5 64QAM 1.4MHz CH-High 1RB




LTE Band 5 64QAM 1.4MHz CH-Low 100%RB




LTE Band 5 64QAM 1.4MHz CH-High 100%RB




LTE Band 5 64QAM 3MHz CH-Low 1RB




LTE Band 5 64QAM 3MHz CH-High 1RB




LTE Band 5 64QAM 3MHz CH-Low 100%RB




LTE Band 5 64QAM 3MHz CH-High 100%RB




LTE Band 5 64QAM 5MHz CH-Low 1RB




LTE Band 5 64QAM 5MHz CH-High 1RB




LTE Band 5 64QAM 5MHz CH-Low 100%RB




LTE Band 5 64QAM 5MHz CH-High 100%RB




LTE Band 5 64QAM 10MHz CH-Low 1RB




LTE Band 5 64QAM 10MHz CH-High 1RB



LTE Band 5 64QAM 10MHz CH-Low 100%RB



LTE Band 5 64QAM 10MHz CH-High 100%RB



5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GMSK)	128	824.2	32.49	29.86	2.63	≤13	PASS
	190	836.6	32.47	29.84	2.63	≤13	PASS
	251	848.8	32.48	29.85	2.63	≤13	PASS
GPRS 850 (GMSK)	128	824.2	32.53	29.91	2.62	≤13	PASS
	190	836.6	32.54	29.91	2.63	≤13	PASS
	251	848.8	32.53	29.91	2.62	≤13	PASS
EGPRS 850 (8PSK)	128	824.2	29.06	23.05	6.01	≤13	PASS
	190	836.6	28.97	22.91	6.06	≤13	PASS
	251	848.8	28.85	22.78	6.07	≤13	PASS
WCDMA Band V (RMC)	4132	826.4	27.06	24.13	2.93	≤13	PASS
	4183	836.6	27.03	24.14	2.89	≤13	PASS
	4233	846.6	27.05	24.12	2.93	≤13	PASS

LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	28.53	23.36	5.17	≤13	PASS
		20525	836.5	28.29	23.30	4.99	≤13	PASS
		20643	848.3	28.17	23.30	4.87	≤13	PASS
	3	20415	825.5	28.49	23.30	5.19	≤13	PASS
		20525	836.5	28.34	23.27	5.07	≤13	PASS
		20635	847.5	28.29	23.26	5.03	≤13	PASS
	5	20425	826.5	28.59	23.32	5.27	≤13	PASS
		20525	836.5	28.40	23.29	5.11	≤13	PASS
		20625	846.5	28.49	23.27	5.22	≤13	PASS
	10	20450	829	28.57	23.36	5.21	≤13	PASS
		20525	836.5	28.50	23.35	5.15	≤13	PASS
		20600	844	28.50	23.33	5.17	≤13	PASS
16QAM	1.4	20407	824.7	28.33	22.38	5.95	≤13	PASS
		20525	836.5	28.08	22.31	5.77	≤13	PASS
		20643	848.3	28.05	22.26	5.79	≤13	PASS
	3	20415	825.5	28.42	22.39	6.03	≤13	PASS
		20525	836.5	28.22	22.30	5.92	≤13	PASS



	5	20635	847.5	28.20	22.29	5.91	≤13	PASS
		20425	826.5	28.37	22.41	5.96	≤13	PASS
		20525	836.5	28.23	22.30	5.93	≤13	PASS
		20625	846.5	28.30	22.29	6.01	≤13	PASS
	10	20450	829	28.38	22.40	5.98	≤13	PASS
		20525	836.5	28.25	22.31	5.94	≤13	PASS
		20600	844	28.36	22.32	6.04	≤13	PASS
64QAM	1.4	20407	824.7	27.89	21.91	5.98	≤13	PASS
		20525	836.5	27.63	21.83	5.80	≤13	PASS
		20643	848.3	27.72	21.93	5.79	≤13	PASS
	3	20415	825.5	27.96	21.89	6.07	≤13	PASS
		20525	836.5	27.76	21.81	5.95	≤13	PASS
		20635	847.5	27.80	21.83	5.97	≤13	PASS
	5	20425	826.5	27.97	21.92	6.05	≤13	PASS
		20525	836.5	27.76	21.84	5.92	≤13	PASS
		20625	846.5	27.82	21.81	6.01	≤13	PASS
	10	20450	829	27.94	21.94	6.00	≤13	PASS
		20525	836.5	27.81	21.85	5.96	≤13	PASS
		20600	844	27.91	21.84	6.07	≤13	PASS

5.5. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +60°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.


(3) Repeat the above measurements at 10°C increments from -30°C to +60°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.60V and 4.45V, with a nominal voltage of 3.87V.

Test setup



Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	-----------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

Test Result

	Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
	Temperature	Voltage	GMSK	8PSK	GMSK	8PSK	
GSM850	Normal (25℃)	Normal	11.55	3.74	0.01380	0.00447	PASS
	Extreme (60℃)		14.73	10.78	0.01761	0.01288	PASS
	Extreme (50℃)		3.95	7.08	0.00472	0.00847	PASS
	Extreme (40℃)		4.03	6.17	0.00481	0.00738	PASS
	Extreme (30℃)		4.77	7.42	0.00571	0.00887	PASS
	Extreme (20℃)		12.29	6.03	0.01469	0.00721	PASS
	Extreme (10℃)		9.51	7.27	0.01136	0.00870	PASS
	Extreme (0℃)		16.18	5.74	0.01934	0.00686	PASS
	Extreme (-10℃)		8.91	1.56	0.01065	0.00186	PASS
	Extreme (-20℃)		14.88	3.58	0.01779	0.00428	PASS
	Extreme (-30℃)		10.91	9.88	0.01304	0.01181	PASS
	25℃	LV	7.47	10.59	0.00892	0.01266	PASS
		HV	2.50	1.56	0.00299	0.00187	PASS

	Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
	Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
WCDMA B5	Normal (25℃)	Normal	16.78	9.63	0.02006	0.01151	PASS
	Extreme (60℃)		11.95	10.10	0.01428	0.01207	PASS
	Extreme (50℃)		10.48	15.95	0.01253	0.01906	PASS
	Extreme (40℃)		3.60	4.69	0.00430	0.00561	PASS
	Extreme (30℃)		12.66	15.05	0.01513	0.01799	PASS
	Extreme (20℃)		3.83	10.88	0.00458	0.01301	PASS
	Extreme (10℃)		5.97	17.94	0.00713	0.02144	PASS
	Extreme (0℃)		7.31	12.56	0.00874	0.01501	PASS
	Extreme (-10℃)		1.46	3.62	0.00175	0.00433	PASS
	Extreme (-20℃)		6.37	10.69	0.00761	0.01278	PASS
	Extreme (-30℃)		17.50	1.48	0.02092	0.00177	PASS
	25℃	LV	1.36	1.96	0.00163	0.00234	PASS
		HV	8.93	3.03	0.01067	0.00362	PASS



LTE Band5								
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	8.61	4.78	13.80	0.01029	0.00572	0.01649	PASS
Extreme (60℃)		6.37	14.44	14.85	0.00762	0.01726	0.01776	PASS
Extreme (50℃)		10.54	12.67	3.39	0.01260	0.01514	0.00405	PASS
Extreme (40℃)		3.01	9.97	16.57	0.00359	0.01192	0.01981	PASS
Extreme (30℃)		4.75	17.98	1.30	0.00568	0.02150	0.00156	PASS
Extreme (20℃)		7.33	7.94	15.91	0.00876	0.00949	0.01901	PASS
Extreme (10℃)		8.59	16.83	9.94	0.01027	0.02012	0.01188	PASS
Extreme (0℃)		16.70	8.52	16.68	0.01997	0.01018	0.01994	PASS
Extreme (-10℃)		8.48	17.84	6.05	0.01014	0.02132	0.00723	PASS
Extreme (-20℃)		14.90	14.46	4.10	0.01781	0.01729	0.00490	PASS
Extreme (-30℃)		17.61	9.58	16.53	0.02105	0.01146	0.01976	PASS
25℃	LV	9.77	3.09	4.36	0.01168	0.00369	0.00521	PASS
	HV	13.36	9.15	1.77	0.01598	0.01094	0.00211	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	13.31	14.97	13.15	0.01591	0.01790	0.01572	PASS
Extreme (60℃)		17.34	13.31	5.39	0.02073	0.01592	0.00644	PASS
Extreme (50℃)		3.49	10.58	13.50	0.00417	0.01265	0.01614	PASS
Extreme (40℃)		1.64	5.85	13.67	0.00196	0.00700	0.01634	PASS
Extreme (30℃)		11.25	11.67	12.38	0.01344	0.01395	0.01480	PASS
Extreme (20℃)		15.81	15.50	12.93	0.01890	0.01853	0.01546	PASS
Extreme (10℃)		14.52	6.48	5.86	0.01736	0.00774	0.00701	PASS
Extreme (0℃)		15.72	17.66	12.21	0.01880	0.02111	0.01460	PASS
Extreme (-10℃)		2.28	13.11	12.24	0.00272	0.01567	0.01464	PASS
Extreme (-20℃)		5.64	8.47	9.82	0.00674	0.01012	0.01173	PASS
Extreme (-30℃)		12.47	13.01	7.51	0.01491	0.01556	0.00897	PASS
25℃	LV	3.12	15.33	16.76	0.00373	0.01832	0.02004	PASS
	HV	11.15	9.81	8.13	0.01332	0.01173	0.00972	PASS



Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	17.06	5.40	10.47	0.02039	0.00645	0.01252	PASS
Extreme (60℃)		3.35	5.79	11.77	0.00400	0.00693	0.01408	PASS
Extreme (50℃)		9.67	14.38	15.69	0.01157	0.01719	0.01875	PASS
Extreme (40℃)		17.17	10.66	10.52	0.02053	0.01274	0.01258	PASS
Extreme (30℃)		5.14	16.23	9.91	0.00615	0.01940	0.01185	PASS
Extreme (20℃)		10.58	9.29	15.92	0.01265	0.01111	0.01903	PASS
Extreme (10℃)		14.55	6.77	5.55	0.01740	0.00809	0.00664	PASS
Extreme (0℃)		8.11	1.05	2.41	0.00970	0.00126	0.00288	PASS
Extreme (-10℃)		12.25	9.63	2.09	0.01464	0.01151	0.00250	PASS
Extreme (-20℃)		12.14	6.48	7.09	0.01451	0.00774	0.00848	PASS
Extreme (-30℃)		11.13	17.55	5.86	0.01331	0.02098	0.00701	PASS
25℃	LV	16.72	3.28	16.83	0.01999	0.00392	0.02012	PASS
	HV	13.52	11.25	8.28	0.01617	0.01345	0.00990	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	6.88	5.84	16.65	0.00823	0.00698	0.01990	PASS
Extreme (60℃)		9.83	9.70	9.76	0.01175	0.01159	0.01167	PASS
Extreme (50℃)		10.69	13.50	12.32	0.01278	0.01614	0.01472	PASS
Extreme (40℃)		16.64	16.55	16.52	0.01989	0.01979	0.01975	PASS
Extreme (30℃)		16.13	6.33	1.20	0.01928	0.00757	0.00143	PASS
Extreme (20℃)		13.28	13.25	1.61	0.01588	0.01584	0.00192	PASS
Extreme (10℃)		7.12	8.49	12.21	0.00852	0.01014	0.01460	PASS
Extreme (0℃)		7.55	3.39	14.38	0.00903	0.00406	0.01719	PASS
Extreme (-10℃)		8.59	5.12	5.40	0.01027	0.00612	0.00645	PASS
Extreme (-20℃)		9.99	4.16	16.32	0.01195	0.00497	0.01951	PASS
Extreme (-30℃)		13.48	3.84	1.02	0.01612	0.00459	0.00122	PASS
25℃	LV	2.55	10.80	6.16	0.00305	0.01291	0.00736	PASS
	HV	16.43	13.55	12.24	0.01965	0.01619	0.01463	PASS

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),


RBW is set to 10 kHz (0.15 MHz~ 30 MHz)

RBW is set to 100 kHz (30MHz~1000 MHz)

RBW is set to 1000 kHz (above 1000MHz)

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-18GHz	1.407 dB




Test Result


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.


GSM 850 CH-Low 9kHz ~ 20GHz




GPRS 850 CH-Low 9kHz ~ 20GHz




GSM 850 CH-Middle 9kHz ~ 20GHz




GPRS 850 CH-Middle 9kHz ~ 20GHz



GSM 850 CH-High 9kHz ~ 20GHz




GPRS 850 CH-High 9kHz ~ 20GHz






EGPRS 850 CH-Low 9kHz ~ 20GHz




10:54:16 13.10.2021

WCDMA BAND V CH-Low 9kHz ~ 20GHz




11:04:40 13.10.2021

EGPRS 850 CH-Middle 9kHz ~ 20GHz




10:53:39 13.10.2021

WCDMA BAND V CH-Middle 9kHz ~ 20GHz




11:03:56 13.10.2021

EGPRS 850 CH-High 9kHz ~ 20GHz




10:52:46 13.10.2021

WCDMA BAND V CH-High 9kHz ~ 20GHz




11:05:05 13.10.2021


LTE Band 5 1.4MHz CH-Low 9kHz~10GHz




LTE Band 5 3MHz CH-Low 9kHz~10GHz




LTE Band 5 1.4MHz CH-Middle 9kHz~10GHz




LTE Band 5 3MHz CH-Middle 9kHz~10GHz




LTE Band 5 1.4MHz CH-High 9kHz~10GHz




LTE Band 5 3MHz CH-High 9kHz~10GHz




LTE Band 5 5MHz CH-Low 9kHz~10GHz




LTE Band 5 10MHz CH-Low 9kHz~10GHz




LTE Band 5 5MHz CH-Middle 9kHz~10GHz




LTE Band 5 10MHz CH-Middle 9kHz~10GHz



LTE Band 5 5MHz CH-High 9kHz~10GHz



LTE Band 5 10MHz CH-High 9kHz~10GHz



5.7. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100kHz, VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$


The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB)

and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15dB$.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

**Test Result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

Low Antenna**GSM 850 CH-Middle**

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1672.75	-57.48	1.70	8.70	Horizontal	-52.63	-13.00	39.63	135
3	2509.85	-50.04	2.30	12.00	Horizontal	-42.49	-13.00	29.49	0
4	3346.40	-64.76	2.70	12.70	Horizontal	-56.91	-13.00	43.91	180
5	4183.00	-62.36	3.00	12.50	Horizontal	-55.01	-13.00	42.01	225
6	5019.60	-61.08	3.40	12.50	Horizontal	-54.13	-13.00	41.13	0
7	5856.20	-61.88	3.40	12.80	Horizontal	-54.63	-13.00	41.63	90
8	6692.80	-57.35	4.10	11.50	Horizontal	-52.10	-13.00	39.10	0
9	7529.40	-55.41	4.20	12.20	Horizontal	-49.56	-13.00	36.56	135
10	8366.00	-55.50	4.30	12.50	Horizontal	-49.45	-13.00	36.45	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1671.20	-57.87	1.70	8.70	Horizontal	-53.02	-13.00	40.02	45
3	2510.40	-64.43	2.30	12.00	Horizontal	-56.88	-13.00	43.88	225
4	3346.40	-64.08	2.70	12.70	Horizontal	-56.23	-13.00	43.23	315
5	4183.00	-63.67	3.00	12.50	Horizontal	-56.32	-13.00	43.32	0
6	5019.60	-61.55	3.40	12.50	Horizontal	-54.60	-13.00	41.60	45
7	5856.20	-61.76	3.40	12.80	Horizontal	-54.51	-13.00	41.51	90
8	6692.80	-57.88	4.10	11.50	Horizontal	-52.63	-13.00	39.63	225
9	7529.40	-55.49	4.20	12.20	Horizontal	-49.64	-13.00	36.64	270
10	8366.00	-55.72	4.30	12.50	Horizontal	-49.67	-13.00	36.67	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1671.95	-57.05	1.70	8.70	Vertical	-52.20	-13.00	39.20	180
3	2508.40	-54.89	2.30	12.00	Vertical	-47.34	-13.00	34.34	0
4	3346.00	-55.17	2.70	12.70	Vertical	-47.32	-13.00	34.32	45
5	4182.50	-64.37	3.00	12.50	Vertical	-57.02	-13.00	44.02	0
6	5019.00	-61.86	3.40	12.50	Vertical	-54.91	-13.00	41.91	225
7	5855.50	-62.42	3.40	12.80	Vertical	-55.17	-13.00	42.17	135
8	6692.00	-58.05	4.10	11.50	Vertical	-52.80	-13.00	39.80	45
9	7528.50	-56.04	4.20	12.20	Vertical	-50.19	-13.00	37.19	135
10	8365.00	-55.57	4.30	12.50	Vertical	-49.52	-13.00	36.52	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Vertical position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.50	-55.83	1.70	8.70	Vertical	-50.98	-13.00	37.98	180
3	2503.00	-53.00	2.30	12.00	Vertical	-45.45	-13.00	32.45	225
4	3337.40	-55.70	2.70	12.70	Vertical	-47.85	-13.00	34.85	225
5	4170.00	-63.95	3.00	12.50	Vertical	-56.60	-13.00	43.60	90
6	5004.00	-62.30	3.40	12.50	Vertical	-55.35	-13.00	42.35	135
7	5838.00	-62.10	3.40	12.80	Vertical	-54.85	-13.00	41.85	135
8	6672.00	-57.98	4.10	11.50	Vertical	-52.73	-13.00	39.73	135
9	7506.00	-56.27	4.20	12.20	Vertical	-50.42	-13.00	37.42	45
10	8340.00	-55.42	4.30	12.50	Vertical	-49.37	-13.00	36.37	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Vertical position.

LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.15	-53.67	1.70	8.70	Vertical	-48.82	-13.00	35.82	90
3	2496.25	-55.57	2.30	12.00	Vertical	-48.02	-13.00	35.02	0
4	3326.00	-57.69	2.70	12.70	Vertical	-49.84	-13.00	36.84	45
5	4157.00	-64.39	3.00	12.50	Vertical	-57.04	-13.00	44.04	0
6	4989.00	-62.49	3.40	12.50	Vertical	-55.54	-13.00	42.54	135
7	5820.50	-62.23	3.40	12.80	Vertical	-54.98	-13.00	41.98	0
8	6652.00	-57.26	4.10	11.50	Vertical	-52.01	-13.00	39.01	135
9	7483.50	-54.95	4.20	12.20	Vertical	-49.10	-13.00	36.10	135
10	8315.00	-55.58	4.30	12.50	Vertical	-49.53	-13.00	36.53	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

**Upper Antenna****GSM 850 CH-Middle**

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.10	-59.31	1.70	8.70	Horizontal	-54.46	-13.00	41.46	0
3	2509.85	-51.99	2.30	12.00	Horizontal	-44.44	-13.00	31.44	0
4	3346.40	-67.27	2.70	12.70	Horizontal	-59.42	-13.00	46.42	0
5	4183.00	-62.86	3.00	12.50	Horizontal	-55.51	-13.00	42.51	135
6	5019.60	-63.08	3.40	12.50	Horizontal	-56.13	-13.00	43.13	315
7	5856.20	-63.45	3.40	12.80	Horizontal	-56.20	-13.00	43.20	45
8	6692.80	-58.67	4.10	11.50	Horizontal	-53.42	-13.00	40.42	225
9	7529.40	-55.90	4.20	12.20	Horizontal	-50.05	-13.00	37.05	90
10	8366.00	-55.29	4.30	12.50	Horizontal	-49.24	-13.00	36.24	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1671.20	-59.03	1.70	8.70	Horizontal	-54.18	-13.00	41.18	45
3	2510.40	-66.87	2.30	12.00	Horizontal	-59.32	-13.00	46.32	225
4	3346.40	-63.88	2.70	12.70	Horizontal	-56.03	-13.00	43.03	315
5	4183.00	-65.98	3.00	12.50	Horizontal	-58.63	-13.00	45.63	0
6	5019.60	-63.80	3.40	12.50	Horizontal	-56.85	-13.00	43.85	45
7	5856.20	-62.65	3.40	12.80	Horizontal	-55.40	-13.00	42.40	90
8	6692.80	-59.51	4.10	11.50	Horizontal	-54.26	-13.00	41.26	225
9	7529.40	-56.23	4.20	12.20	Horizontal	-50.38	-13.00	37.38	270
10	8366.00	-56.31	4.30	12.50	Horizontal	-50.26	-13.00	37.26	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1672.00	-61.36	1.70	8.70	Horizontal	-56.51	-13.00	43.51	45
3	2508.05	-66.44	2.30	12.00	Horizontal	-58.89	-13.00	45.89	180
4	3346.00	-53.53	2.70	12.70	Horizontal	-45.68	-13.00	32.68	225
5	4182.50	-65.48	3.00	12.50	Horizontal	-58.13	-13.00	45.13	0
6	5019.00	-63.42	3.40	12.50	Horizontal	-56.47	-13.00	43.47	90
7	5855.50	-62.98	3.40	12.80	Horizontal	-55.73	-13.00	42.73	180
8	6692.00	-58.26	4.10	11.50	Horizontal	-53.01	-13.00	40.01	225
9	7528.50	-56.74	4.20	12.20	Horizontal	-50.89	-13.00	37.89	315
10	8365.00	-56.05	4.30	12.50	Horizontal	-50.00	-13.00	37.00	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.45	-62.59	1.70	8.70	Horizontal	-57.74	-13.00	44.74	270
3	2503.05	-66.58	2.30	12.00	Horizontal	-59.03	-13.00	46.03	315
4	3337.40	-54.29	2.70	12.70	Horizontal	-46.44	-13.00	33.44	315
5	4170.00	-64.89	3.00	12.50	Horizontal	-57.54	-13.00	44.54	225
6	5004.00	-61.69	3.40	12.50	Horizontal	-54.74	-13.00	41.74	0
7	5838.00	-62.32	3.40	12.80	Horizontal	-55.07	-13.00	42.07	90
8	6672.00	-58.01	4.10	11.50	Horizontal	-52.76	-13.00	39.76	180
9	7506.00	-55.25	4.20	12.20	Horizontal	-49.40	-13.00	36.40	270
10	8340.00	-54.03	4.30	12.50	Horizontal	-47.98	-13.00	34.98	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.05	-59.40	1.70	8.70	Horizontal	-54.55	-13.00	41.55	45
3	2496.20	-60.10	2.30	12.00	Horizontal	-52.55	-13.00	39.55	90
4	3326.00	-49.99	2.70	12.70	Horizontal	-42.14	-13.00	29.14	90
5	4157.00	-63.49	3.00	12.50	Horizontal	-56.14	-13.00	43.14	90
6	4989.00	-62.47	3.40	12.50	Horizontal	-55.52	-13.00	42.52	225
7	5820.50	-62.01	3.40	12.80	Horizontal	-54.76	-13.00	41.76	180
8	6652.00	-56.60	4.10	11.50	Horizontal	-51.35	-13.00	38.35	45
9	7483.50	-56.29	4.20	12.20	Horizontal	-50.44	-13.00	37.44	90
10	8315.00	-54.31	4.30	12.50	Horizontal	-48.26	-13.00	35.26	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2021-05-15	2022-05-14
Climate Chamber	Weiss	VT4002	58226119450010	2021-05-15	2022-05-14
Spectrum Analyzer	Key sight	N9020	MY52330084	2021-05-15	2022-05-14
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2021-05-15	2022-05-14
Signal Analyzer	R&S	FSV3030	101411	2020-12-13	2021-12-12
Signal Analyzer	R&S	FSV30	100815	2020-12-13	2021-12-12
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	01111	2019-9-12	2022-09-11
Horn Antenna	Schwarzbeck	BBHA 9120D	1594	2020-12-17	2021-12-16

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.