

1900 MHz Body Liquid System Validation (Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Forward Power = 20.24 dBm, 12/8/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 1900 MHz

Probe: ET3DV2 - SN3019; ConvF(4.60,4.60,4.60); Crest factor: 1.0; Body Liquid 1900 MHz: $\sigma = 1.50 \text{ mho/m}$, $\epsilon_r = 53.4$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 2.63 mW/g, SAR (10g): 1.18 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: -0.00 dB



1900 MHz Head Liquid System Validation (Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Forward Power = 20.04 dBm, 12/8/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 1900 MHz

Probe: ET3DV2 - SN3019; ConvF(4.70,4.70,4.70); Crest factor: 1.0; Head Liquid 1900 MHz: $\sigma = 1.41 \text{ mho/m}$, $\epsilon_r = 39.2$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 3.90 mW/g, SAR (10g): 1.72 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: -0.02 dB



APPENDIX E - EUT SCANS

HTC, Model #: PM10C (835 MHz GPRS + BT activate, Bottom touching flat phantom with accessory (headset, pouch, and memory card), Middle Channel, Ambient Temp = 23 Deg C, Liquid, Temp = 22 Deg C, Middle Channel, 12/18/2004)


SAM Phantom; Flat Section; Position: (90°, 90°); Frequency: 837 MHz

Probe: ES3DV2 - SN3019; ConvF(6.10,6.10,6.10); Crest factor: 8.0; 835 MHz Body : $\sigma = 0.93 \text{ mho/m}$, $\epsilon_r = 55.4$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7; SAR (1g): 0.613 mW/g, SAR (10g): 0.425 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 13.0, Dz = 10.0

Powerdrift: -0.02 dB



Plot #1

HTC, Model #: PM10C (835 MHz GSM + BT activate, Bottom touching to flat phantom with accessory (headset and pouch), Middle Channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Middle Channel, 12/18/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 837 MHz

Probe: ES3DV2 - SN3019; ConvF(6.10,6.10,6.10); Crest factor: 8.0; 835 MHz Body : $\sigma = 0.93 \text{ mho/m}$ $\epsilon_r = 55.4$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.717 mW/g, SAR (10g): 0.478 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 13.0, Dz = 10.0

Powerdrift: -0.03 dB



Plot #2

HTC, Model #: PM10C (835 MHz GSM + BT activate, Bottom touching to flat phantom with accessory (headset, pouch, and memory card), Middle Channel, Ambient Temp = 23 Deg C, Liquid, Temp = 22 Deg C, Middle Channel, 12/18/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 837 MHz

Probe: ES3DV2 - SN3019; ConvF(6.10,6.10,6.10); Crest factor: 8.0; 835 MHz Body : $\sigma = 0.93 \text{ mho/m}$ $\epsilon_r = 55.4$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.740 mW/g, SAR (10g): 0.496 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 13.0, Dz = 10.0

Powerdrift: -0.00 dB



Plot #3

HTC, Model #: PM10C (Left Head, Cheek with BT activate, Middle Channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Middle Channel, 12/18/2004)


SAM Phantom; Left Hand Section; Position: (90°,60°); Frequency: 837 MHz

Probe: ET3DV6 - SN1064; ConvF(6.45,6.45,6.45); Crest factor: 8.0; (Head) 835 MHz: $\sigma = 0.88 \text{ mho/m}$, $\epsilon_r = 41.7$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.337 mW/g, SAR (10g): 0.203 mW/g, (Worst-case extrapolation)

Coarse: Dx = 11.0, Dy = 11.0, Dz = 10.0

Powerdrift: 0.01 dB



Plot #4

HTC, Model #: PM10C (Left Head, Tilted with BT activate, Middle Channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Middle Channel, 12/18/2004)


SAM Phantom; Left Hand Section; Position: (90°,60°); Frequency: 837 MHz

Probe: ET3DV6 - SN1604; ConvF(6.45,6.45,6.45); Crest factor: 8.0; (Head) 835MHZ: $\sigma = 0.88 \text{ mho/m}$, $\epsilon_r = 41.7$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.284 mW/g, SAR (10g): 0.167 mW/g, (Worst-case extrapolation)

Coarse: Dx = 11.0, Dy = 11.0, Dz = 10.0

Powerdrift: 0.00 dB



Plot #5

HTC, Model: PM10C (Right Head, Cheek with BT activate, Middle Channel, Ambient Temp
= 23 Deg C, Liquid Temp = 22 Deg C, 12/18/2004)


SAM Phantom; Righ Hand Section; Position: (90°, 120°); Frequency: 837 MHz

Probe: ET3DV6 - SN1604; ConvF(6.45,6.45,6.45); Crest factor: 8.0; (Head) 835 MHz: $\sigma = 0.88 \text{ mho/m}$, $\epsilon_r = 41.7$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.307 mW/g, SAR (10g): 0.197 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: -0.02 dB



Plot #6

HTC, Model: PM10C (Right Head, Tilted with BT activate, Middle Channel, Ambient Temp
= 23 Deg C, Liquid Temp = 22 Deg C, 12/18/2004)


SAM Phantom; Righ Hand Section; Position: (90°, 120°); Frequency: 837 MHz

Probe: ET3DV6 - SN1604; ConvF(6.45,6.45,6.45); Crest factor: 8.0; (Head) 835 MHz: $\sigma = 0.88 \text{ mho/m}$, $\epsilon_r = 41.7$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.283 mW/g, SAR (10g): 0.213 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: -0.02 dB



Plot #7

HTC, Model #: PM10C (GSM 1900 MHz + BT activate, Body Worn, Bottom touching flat phantom with accessory (headset and pouch), Mid Channel, Ambient Temp = 23 C, Liquid Temp = 22 C, 12/8/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 1880 MHz

Probe: ET3DV2 - SN3019; ConvF(4.60,4.60,4.60); Crest factor: 1.0; Body Liquid 1900 MHz: $\sigma = 1.50 \text{ mho/m}$, $\epsilon_r = 53.4$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.279 mW/g, SAR (10g): 0.146 mW/g, (Worst-case extrapolation)

Coarse: Dx = 13.0, Dy = 13.0, Dz = 10.0

Powerdrift: 0.01 dB



Plot #8

HTC, Model #: PM10C (GSM 1900 MHz + BT activate, Body Worn, Bottom touching flat phantom with accessory (headset, pouch and memory card), Mid Channel, Ambient Temp = 23 C, Liquid Temp = 22 C, 12/8/2004)


SAM Phantom; Flat Section; Position: (90°, 90°); Frequency: 1880 MHz

Probe: ET3DV2 - SN3019; ConvF(4.60,4.60,4.60); Crest factor: 1.0; Body Liquid 1900 MHz: $\sigma = 1.50 \text{ mho/m}$, $\epsilon_r = 53.4$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.296 mW/g, SAR (10g): 0.156 mW/g, (Worst-case extrapolation)

Coarse: Dx = 13.0, Dy = 13.0, Dz = 10.0

Powerdrift: -0.02 dB



Plot #9

HTC, Model #: PM10C (GPRS 1900 MHz + BT activate, Body Worn, Bottom touching flat phantom with accessory (headset and pouch), Mid Channel, Ambient Temp = 23 C, Liquid Temp = 22 C, 12/8/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 1880 MHz

Probe: ET3DV2 - SN3019; ConvF(4.60,4.60,4.60); Crest factor: 1.0; Body Liquid 1900 MHz: $\sigma = 1.50 \text{ mho/m}$, $\epsilon_r = 53.4$, $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.270 mW/g, SAR (10g): 0.129 mW/g, (Worst-case extrapolation)

Coarse: Dx = 13.0, Dy = 13.0, Dz = 10.0

Powerdrift: 0.02 dB



Plot #10

HTC, Model: PM10C (Left Head, Cheek with BT activate, Middle Channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, 12/8/2004)


SAM Phantom; Left Hand Section; Position: (90°, 60°); Frequency: 1880 MHz

Probe: ET3DV6 - SN1604; ConvF(5.23, 5.23, 5.23); Crest factor: 8.0; (Head) 1900 MHz: $\sigma = 1.41 \text{ mho/m}$, $\epsilon_r = 39.2$, $\rho = 1.31 \text{ g/cm}^3$

Cube 5x5x7; SAR (1g): 0.399 mW/g, SAR (10g): 0.217 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.01 dB



Plot #11

HTC, Model: PM10C (Left Head, Tilted with BT activate, Middle Channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, 12/8/2004)


SAM Phantom; Left Hand Section; Position: (90°,60°); Frequency: 1880 MHz

Probe: ET3DV6 - SN1604; ConvF(5.23,5.23,5.23); Crest factor: 8.0; (Head) 1900 MHz: $\sigma = 1.41 \text{ mho/m}$, $\epsilon_r = 39.2$, $\rho = 1.31 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.532 mW/g, SAR (10g): 0.293 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.03 dB



Plot #12

HTC, Model: PM10C (Right Head, Cheek with BT activate, Middle Channel, Ambient Temp
= 23 Deg C, Liquid Temp = 22 Deg C, 12/8/2004)


SAM Phantom; Right Hand Section; Position: (90°, 300°); Frequency: 1880 MHz

Probe: ET3DV6 - SN1604; ConvF(5.23, 5.23, 5.23); Crest factor: 8.0; (Head) 1900 MHz: $\sigma = 1.41 \text{ mho/m}$, $\epsilon_r = 39.2$, $\rho = 1.31 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.308 mW/g, SAR (10g): 0.173 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: -0.01 dB



Plot #13

HTC, Model: PM10C (Right Head, Tilted with BT activate, Middle Channel, Ambient Temp
= 23 Deg C, Liquid Temp = 22 Deg C, 12/8/2004)


SAM Phantom; Righ Hand Section; Position: (90°,300°); Frequency: 1880 MHz

Probe: ET3DV6 - SN1604; ConvF(5.23,5.23,5.23); Crest factor: 8.0; (Head) 1900 MHz: $\sigma = 1.41 \text{ mho/m}$, $\epsilon_r = 39.2$, $\rho = 1.31 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.403 mW/g, SAR (10g): 0.229 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: 0.02 dB



Plot #14

APPENDIX F – CONDUCTED OUTPUT POWER MEASUREMENT

Provision Applicable

According to FCC §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts. According to FCC § 24.232(b), EIRP peak power for mobile/portable stations are limited to 2 watts.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Test equipment

Hewlett Packard HP8564E Spectrum Analyzer, Calibration Due Date: 2005-08-01.

Hewlett Packard HP 7470A Plotter, Calibration not required.

A.H. Systems SAS200 Horn Antenna, Calibration Due Date: 2005-05-31

Com-Power AB-100 Dipole Antenna, Calibration Due Date: 2005-09-05

Test Results



GSM:



Frequency (MHz)	Output Power in dBm	Output Power in W	Limit (W)
836.60	33	1.995	7
1880.00	29.50	0.891	2

GPRS:

Frequency (MHz)	Output Power in dBm	Output Power in W	Limit (W)
836.60	33	1.995	7
1880.00	29.50	0.891	2

Please refer to the following plots.





APPENDIX G – Z-AXIS PLOT


HTC, Model #: PM10C (850 MHz GSM + BT activate, 1.5 cm separation to flat phantom with accessory (headset, pouch, and memory card), Middle Channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Middle Channel, 12/18/2004)

SAM Phantom; Section; Position: ; Frequency: 837 MHz

Probe: ES3DV2 - SN3019; ConvF(6.10,6.10,6.10); Crest factor: 8.0; 835 MHz Body : $\sigma = 0.93 \text{ mho/m}$, $\epsilon_r = 55.4$, $\rho = 1.00 \text{ g/cm}^3$

: , 0

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 2.0




HTC, Model #: PM10C (GSM 1900 MHz + BT activate, Body Worn, Bottom touching flat phantom with accessory (headset and pouch), Mid Channel, Ambient Temp = 23 C, Liquid Temp = 22 C, 12/8/2004)

SAM Phantom; Section; Position: ; Frequency: 1880 MHz

Probe: ET3DV2 - SN3019; ConvF(4.60,4.60,4.60); Crest factor: 1.0; Body Liquid 1900 MHz: $\sigma = 1.50 \text{ mho/m}$, $\epsilon_r = 53.4$ $\rho = 1.00 \text{ g/cm}^3$

: , 0

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 2.0




APPENDIX H – EUT TEST POSITION PHOTOS

Bottom Touching 1cm Flat Phantom with Accessory



Left Head Cheek



Left Head Tilted



Right Tilted



Right Head, Cheek



APPENDIX I – EUT & ACCESSORIES PHOTOS

Chassis – Top View



Chassis – Back View




Chassis – Port View**Chassis – Cover off View**



Chassis – Battery off View**Chassis – Battery View**


Chassis – Open View




Main Board – Component with Shielding View



Main Board – Component without Shielding View**Main Board – Solder with Shielding View**


Main Board – Solder without Shielding View**LCD Display View 1**

LCD Display View 2**Antenna View**

Adapter View



Data Cable View



Pouch View



APPENDIX J - INFORMATIVE REFERENCES

- [1] Federal Communications Commission, "Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, "Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, "Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105-113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, "Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645-652, May 1997.
- [5] CENELEC, "Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, "Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15-17, 1997, pp. 120-24.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, "E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23-25 June, 1996, pp. 172-175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, "The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865-1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, "The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, "The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, "Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10.