




RADIO TEST REPORT

Test Report No. : 13924099S-A-R2

Applicant : CASIO COMPUTER CO., LTD.
Type of EUT : Watch
Model Number of EUT : MTG-B3000
(Bluetooth Module: CW5672 is contained.)
FCC ID : BBQS30W
Test regulation : FCC Part 15 Subpart C: 2021
Test Result : Complied (Refer to SECTION 3)

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
6. This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. The all test items in this test report are conducted by UL Japan, Inc. Shonan EMC Lab.
8. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.
9. The information provided from the customer for this report is identified in SECTION 1.
10. This report is a revised version of 13924099S-A-R1. 13924099S-A-R1 is replaced with this report.

Date of test: October 5 and 7, 2021

Representative test engineer: 
Akihiro Oda
Engineer

Approved by: 
Akio Hayashi
Manager



CERTIFICATE 1266.03

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
☒ There is no testing item of "Non-accreditation".

UL Japan, Inc.
Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone : +81 463 50 6400
Facsimile : +81 463 50 6401

REVISION HISTORY

Original Test Report No.: 13924099S-A

Revision	Test report No.	Date	Page revised	Contents
- (Original)	13924099S-A	November 16, 2021	-	-
1	13924099S-A-R1	January 18, 2022	23	Changed the description from “(Plot data, Worst case)” to “(Plot data, Worst case mode for Maximum Peak Output Power)”.
2	13924099S-A-R2	March 4, 2022	5	Changed the description from “Normal: DC 3.0 V” to “Typical: DC 3.0 V” in Rating of CW5672 (Module).
			6	Added “RSS-Gen 6.7” to Test Procedure of “6dB Bandwidth”. Changed the description from “wireless transmitter” to “RF part”.
			9	Corrected from “MTG-3000” to “MTG-B3000”.
			27	Corrected frequency in table.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	MCS	Modulation and Coding Scheme
AC	Alternating Current	MRA	Mutual Recognition Arrangement
AFH	Adaptive Frequency Hopping	N/A	Not Applicable
AM	Amplitude Modulation	NIST	National Institute of Standards and Technology
Amp, AMP	Amplifier	NS	No signal detect.
ANSI	American National Standards Institute	NSA	Normalized Site Attenuation
Ant, ANT	Antenna	NVLAP	National Voluntary Laboratory Accreditation Program
AP	Access Point	OBW	Occupied Band Width
ASK	Amplitude Shift Keying	OFDM	Orthogonal Frequency Division Multiplexing
Atten., ATT	Attenuator	P/M	Power meter
AV	Average	PCB	Printed Circuit Board
BPSK	Binary Phase-Shift Keying	PER	Packet Error Rate
BR	Bluetooth Basic Rate	PHY	Physical Layer
BT	Bluetooth	PK	Peak
BT LE	Bluetooth Low Energy	PN	Pseudo random Noise
BW	BandWidth	PRBS	Pseudo-Random Bit Sequence
Cal Int	Calibration Interval	PSD	Power Spectral Density
CCK	Complementary Code Keying	QAM	Quadrature Amplitude Modulation
Ch., CH	Channel	QP	Quasi-Peak
CISPR	Comite International Special des Perturbations Radioelectriques	QPSK	Quadri-Phase Shift Keying
CW	Continuous Wave	RBW	Resolution Band Width
DBPSK	Differential BPSK	RDS	Radio Data System
DC	Direct Current	RE	Radio Equipment
D-factor	Distance factor	RF	Radio Frequency
DFS	Dynamic Frequency Selection	RMS	Root Mean Square
DQPSK	Differential QPSK	RSS	Radio Standards Specifications
DSSS	Direct Sequence Spread Spectrum	Rx	Receiving
EDR	Enhanced Data Rate	SA, S/A	Spectrum Analyzer
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	SG	Signal Generator
EMC	ElectroMagnetic Compatibility	SVSWR	Site-Voltage Standing Wave Ratio
EMI	ElectroMagnetic Interference	TR	Test Receiver
EN	European Norm	Tx	Transmitting
ERP, e.r.p.	Effective Radiated Power	VBW	Video BandWidth
EU	European Union	Vert.	Vertical
EUT	Equipment Under Test	WLAN	Wireless LAN
Fac.	Factor		
FCC	Federal Communications Commission		
FHSS	Frequency Hopping Spread Spectrum		
FM	Frequency Modulation		
Freq.	Frequency		
FSK	Frequency Shift Keying		
GFSK	Gaussian Frequency-Shift Keying		
GNSS	Global Navigation Satellite System		
GPS	Global Positioning System		
Hori.	Horizontal		
ICES	Interference-Causing Equipment Standard		
IEC	International Electrotechnical Commission		
IEEE	Institute of Electrical and Electronics Engineers		
IF	Intermediate Frequency		
ILAC	International Laboratory Accreditation Conference		
ISED	Innovation, Science and Economic Development Canada		
ISO	International Organization for Standardization		
JAB	Japan Accreditation Board		
LAN	Local Area Network		
LIMS	Laboratory Information Management System		

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

CONTENTS	PAGE
SECTION 1: Customer information.....	5
SECTION 2: Equipment under test (EUT).....	5
SECTION 3: Test specification, procedures & results.....	6
SECTION 4: Operation of EUT during testing.....	9
SECTION 5: Radiated Spurious Emission	10
SECTION 6: Antenna Terminal Conducted Tests.....	12
APPENDIX 1: Test data	13
99 % Occupied Bandwidth and 6 dB Bandwidth.....	13
Maximum Peak Output Power.....	15
Average Output Power.....	16
Radiated Spurious Emission	18
Conducted Spurious Emission	24
Power Density	27
APPENDIX 2: Test instruments	29
APPENDIX 3: Photographs of test setup	31
Radiated Spurious Emission	31
Worst Case Position	32
Antenna Terminal Conducted Tests.....	33

SECTION 1: Customer information

Company Name	:	CASIO COMPUTER CO., LTD.
Address	:	2-1, Sakaecho 3 chome, Hamura-shi, Tokyo 205-8555 Japan
Telephone Number	:	+81-42-579-7282
Contact Person	:	Shuji Yamashita

The information provided from the customer is as follows;

- Applicant, Type of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer information
- SECTION 2: Equipment under test (EUT) other than the Receipt Date
- SECTION 4: Operation of EUT during testing

* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Type	:	Watch
Model Number	:	MTG-B3000
Serial Number	:	Refer to SECTION 4.2
Receipt Date	:	September 13, 2021
Condition	:	Production prototype
		(Not for Sale: This sample is equivalent to mass-produced items.)
Modification	:	No Modification by the test lab.

2.2 Product Description

Model: MTG-B3000 (referred to as the EUT in this report) is a Watch.

* MTG-B3000 has an alternative name as R040.

General specification

Rating	:	MTG-B3000 (Watch): Typical: DC 2.5 V, Min.: DC 1.9 V, Max.: DC 2.7 V CW5672 (Module): Typical: DC 3.0 V, Min.: DC 1.9 V, Max.: DC 3.3 V
Clock frequency (ies) in the system	:	32 MHz, 32.768 kHz

Radio Specification

Bluetooth Low Energy

Equipment Type	:	Transceiver
Frequency of Operation	:	2402 MHz – 2480 MHz
Type of Modulation	:	GFSK
Antenna Type	:	Chip antenna
Antenna Gain	:	2.5 dBi

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C
FCC Part 15 final revised on May 3, 2021 and effective July 2, 2021

Title : FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz,
and 5725-5850 MHz

* Also the EUT complies with FCC Part 15 Subpart B.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	N/A	N/A	*1)
6dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.7	FCC: Section 15.247(a)(2) ISED: RSS-247 5.2(a)	See data.	Complied a)	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section 15.247(b)(3) ISED: RSS-247 5.4(d)		Complied b)	Conducted
Power Density	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(e) ISED: RSS-247 5.2(b)		Complied c)	Conducted
Spurious Emission Restricted Band Edges	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section 15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	8.9 dB 2483.500 MHz, AV, Hori. Tx BT LE 2480 MHz	Complied d), e)	Conducted (below 30 MHz)/ Radiated (above 30 MHz) *2)

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

*1) The test is not applicable since the EUT does not have AC mains.

*2) Radiated test was selected over 30 MHz based on section 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 8.5 and 8.6.

a) Refer to APPENDIX 1 (data of 6 dB Bandwidth and 99 % Occupied Bandwidth)

b) Refer to APPENDIX 1 (data of Maximum Peak Output Power)

c) Refer to APPENDIX 1 (data of Power Density)

d) Refer to APPENDIX 1 (data of Conducted Spurious Emission)

e) Refer to APPENDIX 1 (data of Radiated Spurious Emission)

Symbols:

Complied The data of this test item has enough margin, more than the measurement uncertainty.

Complied# The data of this test item meets the limits unless the measurement uncertainty is taken into consideration.

* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.

FCC Part 15.31 (e)

The EUT provides stable voltage constantly to RF part regardless of input voltage.

Instead of a new battery, DC power supply was used for the test. That does not affect the test result, therefore the EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the requirement.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	- a)	Conducted
a) Refer to APPENDIX 1 (data of 6 dB Bandwidth and 99 % Occupied Bandwidth)					

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

There is no applicable rule of uncertainty in this applied standard. Therefore, the results are derived depending on whether or not laboratory uncertainty is applied.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Shonan EMC Lab.

Item	Frequency range	Uncertainty (+/-)			
		No. 1 SAC / SR	No. 2 SAC / SR	No. 3 SAC / SR	No. 4,5,6,8 SR
Conducted emission (AC Mains) LISN	150 kHz-30 MHz	2.6 dB	2.6 dB	2.7 dB	2.7 dB
Radiated emission (Measurement distance: 3 m)	9 kHz-30 MHz	2.9 dB	2.9 dB	2.9 dB	-
	30 MHz-200 MHz	4.6 dB	4.6 dB	4.6 dB	-
	200 MHz-1 GHz	6.0 dB	6.0 dB	6.0 dB	-
	1 GHz-6 GHz	4.8 dB	4.8 dB	4.8 dB	-
	6 GHz-18 GHz	5.4 dB	5.4 dB	5.4 dB	-
	18 GHz-40 GHz	5.6 dB	5.6 dB	5.7 dB	-
Radiated emission (Measurement distance: 1 m)	1 GHz-18 GHz	5.7 dB	5.7 dB	5.7 dB	-
	18 GHz-40 GHz	5.9 dB	5.9 dB	5.9 dB	-

SAC=Semi-Anechoic Chamber

SR= Shielded Room is applied besides radiated emission

Antenna terminal test	Uncertainty (+/-)
Power Measurement above 1 GHz (Average Detector)_SPM-06	1.2 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-06	2.0 dB
Power Measurement above 1 GHz (Average Detector)_SPM-07	1.2 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-07	1.3 dB
Power Measurement above 1 GHz (Average Detector)_SPM-13	1.3 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-13	1.3 dB
Spurious emission (Conducted) below 1GHz	0.93 dB
Spurious emission (Conducted) 1 GHz-3 GHz	0.92 dB
Spurious emission (Conducted) 3 GHz-18 GHz	2.3 dB
Spurious emission (Conducted) 18 GHz-26.5 GHz	2.3 dB
Spurious emission (Conducted) 26.5 GHz-40 GHz	2.3 dB
Bandwidth Measurement	0.012 %
Duty cycle and Time Measurement	0.27 %
Temperature_SCH-01	0.93 deg.C.
Humidity_SCH-01	4.1 %
Temperature_SCH-02	2.0 deg.C.
Humidity_SCH-02	6.6 %
Voltage	0.97 %

3.5 Test Location

UL Japan, Inc. Shonan EMC Lab.
1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN
Telephone: +81 463 50 6400, Facsimile: +81 463 50 6401
A2LA Certificate Number: 1266.03
(FCC test firm registration number: 626366, ISED lab company number: 2973D / CAB identifier: JP0001)

Test site	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
No.1 Semi-anechoic chamber	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10 m
No.2 Semi-anechoic chamber	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10 m
No.3 Semi-anechoic chamber	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5 m
No.4 Semi-anechoic chamber	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
No.1 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.2 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.3 Shielded room	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
No.4 Shielded room	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
No.5 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.6 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.8 Shielded room	-	3.45 x 5.5 x 2.4	3.45 x 5.5	-
No.1 Measurement room	-	2.55 x 4.1 x 2.5	-	-

3.6 Test data, Test instruments, and Test set up


Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)

Mode	Frequency	Remarks*
Bluetooth Low Energy (BT LE)	2402 MHz, 2440 MHz, 2480 MHz	PRBS9
*Power of the EUT was set by the software as follows; Power settings: BT LE 1 M-PHY: Fixed Software: BLE RF Test Version 9.9 (Date: September 13, 2021, Storage location: EUT memory) *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.		

4.2 Configuration and peripherals



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Watch	MTG-B3000	26 *1) 08 *2)	CASIO COMPUTER	EUT
B	Power Supply (DC)	PW16-5ADP	19100034	TEXIO	*1)
		PAN35-10A	DE001677	KIKUSUI	*2)

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC	0.1 + 1.5 *1) 0.1 + 1.9 *2)	Unshielded	Unshielded	*3)
2	Signal	0.1	Unshielded	Unshielded	*4)
3	AC	2.0	Unshielded	Unshielded	-

*1) Used for Antenna Terminal conducted test

*2) Used for Radiated Emission test

*3) Cable for test operation

*4) Cable for system reset during the development, not used for the product

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 5: Radiated Spurious Emission

Test Procedure

It was measured based on "8.5 and 8.6 of KDB 558074 D01 15.247 Meas Guidance v05r02".

[For below 1 GHz]

EUT was placed on a platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The table is made of expanded polystyrol and expanded polypropylene and the table top is covered with polycarbonate. That has very low permittivity.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.


20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9(ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV *1)	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	11.12.2.5.2 RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (Linear voltage) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz

*1) Average Power Measurement was performed based on ANSI C63.10-2013.

Figure 2: Test Setup


Below 1 GHz



x : Center of turn table

Test Distance: 3 m

1 GHz - 10 GHz




r : Radius of an outer periphery of EUT
x : Center of turn table

Distance Factor: $20 \times \log (3.97 \text{ m} / 3.0 \text{ m}) = 2.43 \text{ dB}$
* Test Distance: $(3 + \text{SVSWR Volume} / 2) - r = 3.97 \text{ m}$

SVSWR Volume : 2.0 m
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)
r = 0.03 m

10 GHz – 26.5 GHz



x : Center of turn table

Distance Factor: $20 \times \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.54 \text{ dB}$
*Test Distance: 1 m

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Antenna polarization	Frequency	Spurious				
		Below 1 GHz	1 GHz – 2.8 GHz	2.8 GHz – 10 GHz	10 GHz - 18 GHz	18 GHz - 26 GHz
Horizontal		X	X	Y	X	X
Vertical		X	X	Y	X	X

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30 MHz - 26.5 GHz
Test data : APPENDIX
Test result : Pass

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone : +81 463 50 6400
Facsimile : +81 463 50 6401

SECTION 6: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
6dB Bandwidth	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/Average *2)	-	Power Meter (Sensor: 160 MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3 kHz	9.1 kHz	Auto	Peak	Max Hold	Spectrum Analyzer *3)
Conducted Spurious Emission *4), *5)	9kHz to 150kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150kHz to 30MHz	10 kHz	30 kHz				

*1) Peak hold was applied as Worst-case measurement.

*2) Reference data

*3) Section 11.10.2 Method PKPSD (peak PSD) of "ANSI C63.10-2013".

*4) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.

*5) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

The test results and limit are rounded off to two decimals place, so some differences might be observed.
The equipment and cables were not used for factor 0 dB of the data sheets.

Test data : APPENDIX
Test result : Pass


APPENDIX 1: Test data

99 % Occupied Bandwidth and 6 dB Bandwidth

Report No. 13924099S-A-R2
Test place Shonan EMC Lab. No.6 Shielded Room
Date October 5, 2021
Temperature / Humidity 22 deg. C / 41 % RH
Engineer Akihiro Oda
Mode Tx BT LE

Mode	Frequency [MHz]	99 % Occupied Bandwidth [kHz]	6 dB Bandwidth [MHz]	Limit for 6 dB Bandwidth [MHz]
BT LE	2402	1054.8	0.726	> 0.5000
	2440	1061.5	0.725	> 0.5000
	2480	1061.3	0.716	> 0.5000

99 % Occupied Bandwidth and 6 dB Bandwidth



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Peak Output Power

Report No. 13924099S-A-R2
Test place Shonan EMC Lab. No.6 Shielded Room
Date October 5, 2021
Temperature / Humidity 22 deg. C / 41 % RH
Engineer Akihiro Oda
Mode Tx BT LE

Freq.	Reading	Cable Loss	Atten. Loss	Conducted Power					Antenna Gain	e.i.r.p. for RSS-247					
				Result		Limit		Margin		Result		Limit		Margin	
				[dBm]	[mW]	[dBm]	[mW]			[dB]	[dBm]	[mW]	[dBm]		[mW]
[MHz]	[dBm]	[dB]	[dB]						[dBi]						
2402	-11.44	1.15	9.94	-0.35	0.92	30.00	1000	30.35	2.50	2.15	1.64	36.02	4000	33.87	
2440	-11.44	1.16	9.94	-0.34	0.92	30.00	1000	30.34	2.50	2.16	1.64	36.02	4000	33.86	
2480	-11.47	1.16	9.94	-0.37	0.92	30.00	1000	30.37	2.50	2.13	1.63	36.02	4000	33.89	

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

*The equipment and cables were not used for factor 0 dB of the data sheets.

Average Output Power
(Reference data for RF Exposure)

Report No. 13924099S-A-R2
Test place Shonan EMC Lab. No.6 Shielded Room
Date October 5, 2021
Temperature / Humidity 22 deg. C / 41 % RH
Engineer Akihiro Oda
Mode Tx BT LE

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
				[dBm]	[mW]		[dBm]	[mW]
2402	-13.80	1.15	9.94	-2.71	0.54	1.62	-1.09	0.78
2440	-13.79	1.16	9.94	-2.69	0.54	1.62	-1.07	0.78
2480	-13.81	1.16	9.94	-2.71	0.54	1.62	-1.09	0.78

Sample Calculation:


Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

Result (Burst power average) = Time average + Duty factor

*The equipment and cables were not used for factor 0 dB of the data sheets.

Burst rate confirmation

Report No. 13924099S-A-R2
 Test place Shonan EMC Lab. No.6 Shielded
 Date October 5, 2021
 Temperature 22 deg. C / 41 % RH
 / Humidity
 Engineer Akihiro Oda
 Mode Tx BT LE



* Since the burst rate is not different between the channels, the data has been obtained on the representative channel.

Radiated Spurious Emission

Report No. 13924099S-A-R2
Test place Shonan EMC Lab.
Semi Anechoic Chamber No.3
Date October 7, 2021 October 5, 2021
Temperature / Humidity 24 deg. C / 51 % RH 24 deg. C / 50 % RH
Engineer Yasumasa Owaki Yasumasa Owaki
(30 MHz - 1 GHz) (1 GHz - 26.5 GHz)
Mode Tx BT LE 2402 MHz

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	192.000	QP	21.70	16.37	7.82	32.06	0.00	13.83	43.5	29.6	100	0	-
Hori.	320.000	QP	21.90	14.25	8.68	31.96	0.00	12.87	46.0	33.1	100	0	-
Hori.	544.000	QP	21.60	17.76	9.68	31.96	0.00	17.08	46.0	28.9	100	0	-
Hori.	736.000	QP	21.80	20.20	10.40	31.77	0.00	20.63	46.0	25.3	100	0	-
Hori.	960.000	QP	20.90	22.13	11.15	30.51	0.00	23.67	46.0	22.3	100	0	-
Hori.	2390.000	PK	48.34	28.33	14.42	41.62	2.43	51.90	73.9	22.0	141	198	-
Hori.	4804.000	PK	49.46	31.77	7.02	42.89	2.43	47.79	73.9	26.1	336	355	-
Hori.	7206.000	PK	49.27	37.37	8.49	43.39	2.43	54.17	73.9	19.7	150	0	-
Hori.	7206.000	AV	39.59	37.37	8.49	43.39	2.43	44.49	53.9	9.4	150	0	Floor noise
Vert.	32.000	QP	22.40	18.15	6.49	32.18	0.00	14.86	40.0	25.1	100	0	-
Vert.	160.000	QP	23.60	15.20	7.86	32.08	0.00	14.58	43.5	28.9	100	0	-
Vert.	480.000	QP	21.50	17.44	9.41	31.92	0.00	16.43	46.0	29.5	100	0	-
Vert.	640.000	QP	21.70	19.23	10.03	31.92	0.00	19.04	46.0	26.9	100	0	-
Vert.	800.000	QP	21.70	20.74	10.61	31.55	0.00	21.50	46.0	24.5	100	0	-
Vert.	2390.000	PK	47.82	28.33	14.42	41.62	2.43	51.38	73.9	22.5	115	10	-
Vert.	4804.000	PK	50.27	31.77	7.02	42.89	2.43	48.60	73.9	25.3	100	37	-
Vert.	7206.000	PK	49.42	37.37	8.49	43.39	2.43	54.32	73.9	19.5	150	0	-
Vert.	7206.000	AV	39.39	37.37	8.49	43.39	2.43	44.29	53.9	9.6	150	0	Floor noise

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log (3.97 m / 3.0 m) = 2.43 dB

10 GHz - 40 GHz : 20log (1.0 m / 3.0 m) = -9.54 dB

Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2390.000	AV	37.81	28.33	14.42	41.62	3.24	2.43	44.61	53.9	9.2	*1)
Hori.	4804.000	AV	40.62	31.77	7.02	42.89	3.24	2.43	42.19	53.9	11.7	-
Vert.	2390.000	AV	37.81	28.33	14.42	41.62	3.24	2.43	44.61	53.9	9.2	*1)
Vert.	4804.000	AV	41.58	31.77	7.02	42.89	3.24	2.43	43.15	53.9	10.7	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log (3.97 m / 3.0 m) = 2.43 dB

10 GHz - 40 GHz : 20log (1.0 m / 3.0 m) = -9.54 dB

Duty factor refer to "Burst rate confirmation" sheet.

*1) Not out of band emission (Leakage Power)

20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2402.000	PK	71.20	28.31	14.44	41.63	2.43	74.75	-	-	Carrier
Hori.	2400.000	PK	40.14	28.31	14.44	41.63	2.43	43.69	54.7	11.0	-
Vert.	2402.000	PK	70.49	28.31	14.44	41.63	2.43	74.04	-	-	Carrier
Vert.	2400.000	PK	39.24	28.31	14.44	41.63	2.43	42.79	54.0	11.2	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log (3.97 m / 3.0 m) = 2.43 dB

10 GHz - 40 GHz : 20log (1.0 m / 3.0 m) = -9.54 dB

UL Japan, Inc.

Shonan EMC Lab.



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission (Reference Plot for band-edge)

Report No.	13924099S-A-R2
Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.3
Date	October 5, 2021
Temperature / Humidity	24 deg. C / 50 % RH
Engineer	Yasumasa Owaki (1 GHz – 10 GHz)
Mode	Tx BT LE 2402 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Report No.	13924099S-A-R2	
Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	October 7, 2021	October 5, 2021
Temperature / Humidity	24 deg. C / 51 % RH	24 deg. C / 50 % RH
Engineer	Yasumasa Owaki	Yasumasa Owaki
	(30 MHz - 1 GHz)	(1 GHz - 26.5 GHz)
Mode	Tx BT LE 2440 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	192.000	QP	21.70	16.37	7.82	32.06	0.00	13.83	43.5	29.6	100	0	-
Hori.	320.000	QP	21.80	14.25	8.68	31.96	0.00	12.77	46.0	33.2	100	0	-
Hori.	544.000	QP	21.60	17.76	9.68	31.96	0.00	17.08	46.0	28.9	100	0	-
Hori.	736.000	QP	21.80	20.20	10.40	31.77	0.00	20.63	46.0	25.3	100	0	-
Hori.	960.000	QP	20.90	22.13	11.15	30.51	0.00	23.67	46.0	22.3	100	0	-
Hori.	4880.000	PK	50.22	31.87	7.08	42.89	2.43	48.71	73.9	25.1	110	39	-
Hori.	7320.000	PK	48.21	37.53	8.57	43.52	2.43	53.22	73.9	20.6	150	0	-
Hori.	7320.000	AV	38.85	37.53	8.57	43.52	2.43	43.86	53.9	10.0	150	0	Floor noise
Vert.	32.000	QP	22.40	18.15	6.49	32.18	0.00	14.86	40.0	25.1	100	0	-
Vert.	160.000	QP	24.00	15.20	7.86	32.08	0.00	14.98	43.5	28.5	100	0	-
Vert.	480.000	QP	21.50	17.44	9.41	31.92	0.00	16.43	46.0	29.5	100	0	-
Vert.	640.000	QP	21.70	19.23	10.03	31.92	0.00	19.04	46.0	26.9	100	0	-
Vert.	800.000	QP	21.70	20.74	10.61	31.55	0.00	21.50	46.0	24.5	100	0	-
Vert.	4880.000	PK	50.47	31.87	7.08	42.89	2.43	48.96	73.9	24.9	107	49	-
Vert.	7320.000	PK	48.06	37.53	8.57	43.52	2.43	53.07	73.9	20.8	150	0	-
Vert.	7320.000	AV	38.57	37.53	8.57	43.52	2.43	43.58	53.9	10.3	150	0	Floor noise

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log(3.97 m / 3.0 m) = 2.43 dB

10 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.54 dB

Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	4880.000	AV	40.88	31.87	7.08	42.89	3.24	2.43	42.61	53.9	11.2	-
Vert.	4880.000	AV	41.81	31.87	7.08	42.89	3.24	2.43	43.54	53.9	10.3	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log(3.97 m / 3.0 m) = 2.43 dB

10 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.54 dB

Duty factor refer to "Burst rate confirmation" sheet.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission

Report No.	13924099S-A-R2	
Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	October 7, 2021	October 5, 2021
Temperature / Humidity	24 deg. C / 51 % RH	24 deg. C / 50 % RH
Engineer	Yasumasa Owaki	Yasumasa Owaki
	(30 MHz - 1 GHz)	(1 GHz - 26.5 GHz)
Mode	Tx BT LE 2480 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	192.000	QP	21.70	16.37	7.82	32.06	0.00	13.83	43.5	29.6	100	0	-
Hori.	320.000	QP	21.90	14.25	8.68	31.96	0.00	12.87	46.0	33.1	100	0	-
Hori.	544.000	QP	21.50	17.76	9.68	31.96	0.00	16.98	46.0	29.0	100	0	-
Hori.	736.000	QP	21.80	20.20	10.40	31.77	0.00	20.63	46.0	25.3	100	0	-
Hori.	960.000	QP	20.80	22.13	11.15	30.51	0.00	23.57	46.0	22.4	100	0	-
Hori.	2483.500	PK	47.87	28.24	14.52	41.65	2.43	51.41	73.9	22.4	144	350	-
Hori.	4960.000	PK	49.93	32.14	7.14	42.89	2.43	48.75	73.9	25.1	108	36	-
Hori.	7440.000	PK	48.97	37.62	8.64	43.65	2.43	54.01	73.9	19.8	150	0	-
Hori.	7440.000	AV	38.57	37.62	8.64	43.65	2.43	43.61	53.9	10.2	150	0	Floor noise
Vert.	32.000	QP	22.30	18.15	6.49	32.18	0.00	14.76	40.0	25.2	100	0	-
Vert.	160.000	QP	23.90	15.20	7.86	32.08	0.00	14.88	43.5	28.6	100	0	-
Vert.	480.000	QP	21.50	17.44	9.41	31.92	0.00	16.43	46.0	29.5	100	0	-
Vert.	640.000	QP	21.70	19.23	10.03	31.92	0.00	19.04	46.0	26.9	100	0	-
Vert.	800.000	QP	21.60	20.74	10.61	31.55	0.00	21.40	46.0	24.6	100	0	-
Vert.	2483.500	PK	48.12	28.24	14.52	41.65	2.43	51.66	73.9	22.2	112	323	-
Vert.	4960.000	PK	49.67	32.14	7.14	42.89	2.43	48.49	73.9	25.4	152	39	-
Vert.	7440.000	PK	48.08	37.62	8.64	43.65	2.43	53.12	73.9	20.7	150	0	-
Vert.	7440.000	AV	38.50	37.62	8.64	43.65	2.43	43.54	53.9	10.3	150	0	Floor noise

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.43\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2483.500	AV	38.18	28.24	14.52	41.65	3.24	2.43	44.96	53.9	8.9	*1)
Hori.	4960.000	AV	40.95	32.14	7.14	42.89	3.24	2.43	43.01	53.9	10.8	-
Vert.	2483.500	AV	38.10	28.24	14.52	41.65	3.24	2.43	44.88	53.9	9.0	*1)
Vert.	4960.000	AV	41.28	32.14	7.14	42.89	3.24	2.43	43.34	53.9	10.5	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.43\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Duty factor refer to "Burst rate confirmation" sheet.

*1) Not out of band emission (Leakage Power)

UL Japan, Inc.

Shonan EMC Lab.



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission (Reference Plot for band-edge)

Report No.	13924099S-A-R2
Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.3
Date	October 5, 2021
Temperature / Humidity	24 deg. C / 50 % RH
Engineer	Yasumasa Owaki (1 GHz – 10 GHz)
Mode	Tx BT LE 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge was shown in tabular data.

UL Japan, Inc.

Shonan EMC Lab.


1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission
(Plot data, Worst case mode for Maximum Peak Output Power)


Report No.	13924099S-A-R2	
Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	October 7, 2021	October 5, 2021
Temperature / Humidity	24 deg. C / 51 % RH	24 deg. C / 50 % RH
Engineer	Yasumasa Owaki	Yasumasa Owaki
	(30 MHz - 1 GHz)	(1 GHz - 26.5 GHz)
Mode	Tx BT LE 2440 MHz	



*These plots data contains sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Report No.	13924099S-A-R2
Test place	Shonan EMC Lab. No.6 Shielded Room
Date	October 5, 2021
Temperature / Humidity	22 deg. C / 41 % RH
Engineer	Akihiro Oda
Mode	Tx BT LE 2402 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
13.35	-97.58	0.01	9.87	2.50	1	-85.20	300	6.0	-23.9	45.0	68.9	-
274.00	-89.75	0.01	9.87	2.50	1	-77.37	300	6.0	-16.1	18.8	34.9	-


$E [dBuV/m] = EIRP [dBm] - 20 \log (Distance [m]) + Ground\ bounce [dB] + 104.8 [dBuV/m]$

$EIRP[dBm] = Reading [dBm] + Cable\ loss [dB] + Attenuator\ Loss [dB] + Antenna\ gain [dBi] + 10 * \log (N)$

N: Number of output

Conducted Spurious Emission

Report No.	13924099S-A-R2
Test place	Shonan EMC Lab. No.6 Shielded Room
Date	October 5, 2021
Temperature / Humidity	22 deg. C / 41 % RH
Engineer	Akihiro Oda
Mode	Tx BT LE 2440 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
9.12	-97.16	0.01	9.87	2.50	1	-84.78	300	6.0	-23.5	48.4	71.9	-
424.00	-89.96	0.01	9.88	2.50	1	-77.57	300	6.0	-16.3	15.0	31.3	-


$E [dBuV/m] = EIRP [dBm] - 20 \log (Distance [m]) + Ground\ bounce [dB] + 104.8 [dBuV/m]$

$EIRP[dBm] = Reading [dBm] + Cable\ loss [dB] + Attenuator\ Loss [dB] + Antenna\ gain [dBi] + 10 * \log (N)$

N: Number of output

Conducted Spurious Emission

Report No.	13924099S-A-R2
Test place	Shonan EMC Lab. No.6 Shielded Room
Date	October 5, 2021
Temperature / Humidity	22 deg. C / 41 % RH
Engineer	Akihiro Oda
Mode	Tx BT LE 2480 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
14.64	-98.80	0.01	9.87	2.50	1	-86.42	300	6.0	-25.2	44.2	69.4	-
921.00	-90.47	0.01	9.88	2.50	1	-78.08	30	6.0	3.2	28.3	25.1	-

$E [dBuV/m] = EIRP [dBm] - 20 \log (Distance [m]) + Ground\ bounce [dB] + 104.8 [dBuV/m]$

$EIRP[dBm] = Reading [dBm] + Cable\ loss [dB] + Attenuator\ Loss [dB] + Antenna\ gain [dBi] + 10 * \log (N)$

N: Number of output

Power Density

Report No. 13924099S-A-R2
Test place Shonan EMC Lab. No.6 Shielded Room
Date October 5, 2021
Temperature / Humidity 22 deg. C / 41 % RH
Engineer Akihiro Oda
Mode Tx BT LE


Freq.	Reading	Cable Loss	Atten. Loss	Result	Limit	Margin
[MHz]	[dBm / 3 kHz]	[dB]	[dB]	[dBm / 3 kHz]	[dBm / 3 kHz]	[dB]
2402	-25.72	1.15	9.94	-14.63	8.00	22.63
2440	-26.22	1.16	9.94	-15.12	8.00	23.12
2480	-25.55	1.16	9.94	-14.45	8.00	22.45

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

*The equipment and cables were not used for factor 0 dB of the data sheets.

Power Density



APPENDIX 2: Test instruments

Test equipment (1/2)

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	COTS-SEMI-5	170932	EMI Software	TSJ (Techno Science Japan)	TEPTO-DV3(RE,CE,ME,PE)	-	-	-
RE	KJM-02	146432	Measure	TAJIMA	GL19-55	-	-	-
RE	SAEC-03(NSA)	145565	Semi-Anechoic Chamber	TDK	SAEC-03(NSA)	3	2021/04/27	12
RE	SAEC-03(SVSWR)	145566	Semi-Anechoic Chamber	TDK	SAEC-03(SVSWR)	3	2021/05/21	12
RE	SAF-03	145126	Pre Amplifier	SONOMA	310N	290213	2021/02/10	12
RE	SAF-06	145005	Pre Amplifier	Toyo Corporation	TPA0118-36	1440491	2021/02/08	12
RE	SAF-09	145008	Pre Amplifier	Toyo Corporation	HAP18-26W	18	2021/09/03	12
RE	SAT10-05	145136	Attenuator	Keysight Technologies Inc	8493C-010	74864	2020/10/05	12
RE	SAT6-13	167094	Attenuator	JFW	50HF-006N	-	2021/02/10	12
RE	SBA-03	145023	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	BBA9106	91032666	2021/05/15	12
RE	SCC-C1/C2/C3/C4/C5/C10/SRSE-03	145171	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/TOYO	BD2W/12DSFA/141PE/141PE/141PE/141PE/NS4906	/0901-271(RF Selector)	2021/04/12	12
RE	SCC-G40	166491	Coaxial Cable	Junkosha	MWX221-01000NFSNMS/B	1612S005	2021/01/19	12
RE	SCC-G43	156380	Coaxial Cable	Huber+Suhner	SUCOFLEX_104_E	SN MY 13406/4E	2021/05/17	12
RE	SCC-G45	168301	Coaxial Cable	Huber+Suhner	SUCOFLEX 102 E	800137/2EA	2021/03/01	12
RE	SCC-G58	183047	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	800287/4A	2021/05/17	12
RE	SCC-G70	200010	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	575618/4	2021/07/06	12
RE	SFL-02	145301	Highpass Filter	MICRO-TRONICS	HPM50111	51	2020/10/05	12
RE	SHA-03	145501	Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	9120D-739	2021/06/14	12
RE	SHA-05	145513	Horn Antenna	ETS-Lindgren	3160-09	00094867	2021/06/14	12
RE	SHA-10	194685	Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA 9120 C	711	2021/03/03	12
RE	SLA-07	145529	Logperiodic Antenna	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	196	2021/05/15	12
RE	SOS-23	191840	Humidity Indicator	CUSTOM. Inc	CTH-201	-	2021/08/02	12
RE	SSA-02	145800	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY48250106	2021/04/13	12
RE	STR-08	150463	Test Receiver	Rohde & Schwarz	ESW44	101581	2020/12/02	12
RE	STS-03	146210	Digital Hitester	HIOKI CORPORATION	3805-50	80997823	2021/09/14	12

Test equipment (2/2)

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	KTS-06	145110	Digital Tester	SANWA	PC500	7019240	2021/04/26	12
AT	SAT10-21	204925	Attenuator	Weinschel Corp.	54A-10	-	2021/02/09	12
AT	SCC-G65	196942	Coaxial Cable	Huber+Suhner	SUCOFLEX 102	803416/2	2021/03/01	12
AT	SOS-05	146293	Humidity Indicator	A&D Company	AD-5681	4062518	2021/08/02	12
AT	SPM-13	169910	Power Meter	Keysight Technologies Inc	8990B	MY51000448	2021/01/25	12
AT	SPSS-06	169911	Power sensor	Keysight Technologies Inc	N1923A	MY57270004	2021/01/25	12
AT	SRENT-15	160899	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46185516	2021/01/26	12

***Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.**

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

**Test item: RE: Radiated Emission test
AT: Antenna Terminal Conducted test**