



# TEST REPORT

No. 2014SAR0031

*For*

Client : Fibocom Wireless Inc.

Production : WCDMA/GSM(GPRS) Dual-band  
wireless module

Model Name : H350,H350R

FCC ID: ZMOH35F

Hardware Version: V1.0.2

Software Version: H350\_V3H.00.03

Issued date: 2014-04-04



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

**Test Laboratory:**

ECIT Shanghai, East China Institute of Telecommunications

Add: 7F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: [welcome@ecit.org.cn](mailto:welcome@ecit.org.cn)

**Revision Version**

Report Number	Revision	Date	Memo
2014SAR0031	00	2014-04-04	Initial creation of test report

## CONTENTS

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE .....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>4.1. APPLICABLE STANDARDS .....</b>	<b>7</b>
<b>4.2. TEST LIMITS .....</b>	<b>7</b>
<b>5. TEST RESULTS .....</b>	<b>8</b>
<b>5.1. CONDUCTED RF POWER OUTPUT .....</b>	<b>8</b>
<b>5.2. CALCULATION INFORMATION .....</b>	<b>10</b>
<b>5.3. RESULT OF GSM835 .....</b>	<b>11</b>
<b>5.4. RESULT OF GSM1900 .....</b>	<b>11</b>
<b>5.5. RESULT OF WCDMA BAND II .....</b>	<b>12</b>
<b>5.6. RESULT OF WCDMA BAND V .....</b>	<b>12</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301
FCC Registration NO.:	489729

### 1.2. Testing Environment

Normal Temperature:	15-35°C
Relative Humidity:	20-75%
Ambient noise & Reflection:	< 0.012 W/kg

### 1.3. Project Data

Project Leader:	Gong Yujuan
Testing Start Date:	2014-04-03
Testing End Date:	2014-04-04

### 1.4. Signature

**Hu Jiajing**

(Prepared this test report)

**Yu Naiping**

(Reviewed this test report)

  
**Zheng Zhongbin**  
Director of the laboratory  
(Approved this test report)  


## **2. Client Information**

### **2.1. Applicant Information**

Company Name: Fibocom Wireless Inc.  
Address /Post: 5/F, Block A, Shekou Technology Building II, 1057 Nanhai Blvd,  
Nanshan, Shenzhen, China  
Country: China  
Telephone: 075526733555  
Postal Code: 518067  
Contact: Wang Xuejuan

### **2.2. Manufacturer Information**

Company Name: Fibocom Wireless Inc.  
Address /Post: 5/F, Block A, Shekou Technology Building II, 1057 Nanhai Blvd,  
Nanshan, Shenzhen, China  
Country: China  
Telephone: 075526733555  
Postal Code: 518067  
Contact: Wang Xuejuan

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description	WCDMA/GSM(GPRS) Dual-band wireless module
Model name	H350,H350R
GSM Frequency Band	GSM835/GSM1900
WCDMA Frequency Band	WCDMA band II/WCDMA band V
Antenna Type	External Antenna
FCC ID:	ZMOH35F

**Note:** Photographs of EUT are shown in ANNEX A of this test report.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version:
N01	IMEI:N/A	V1.0.2	H350_V3H.00.03

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Cable	N/A	N/A	N/A
AE2	N/A	N/A	N/A	N/A

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Reference Documents

### 4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

The limits standard is based on the Council Recommendation 1999/519/EC.

FCC CFR 47, Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS, Oct 1,2011

Section 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, Oct 1,2011

### 4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Limits for Occupational / Controlled Exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm <sup>2</sup> ]	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S [minutes]
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1824/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	--	--	F/300	6
1500 - 100000	--	--	5	6

Limits for General Population / Uncontrolled Exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm <sup>2</sup> ]	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S [minutes]
0.3 – 1.34	614	1.63	(100)*	30
1.34 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	--	--	F/1500	30
1500 - 100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

For the DUT, the limits for General Population / Uncontrolled Exposure are applicable.

## 5. Test Results

### 5.1. Conducted RF Power Output

**Table 5.1: The Conducted Power For GPRS 4TS 835MHz and 1900MHz**

GPRS 4TS 835MHz	Conducted Power (dBm)		
	Channel 128 (824.2MHz)	Channel 190 (836.6MHz)	Channel 251 (848.8MHz)
	30.31	30.18	30.27
GPRS 4TS 1900MHz	Conducted Power (dBm)		
	Channel 512 (1850.2MHz)	Channel 661 (1880MHz)	Channel 810 (1909.8MHz)
	27.64	27.49	27.53

**Table 5.2: Tolerance Power For GPRS 4TS 835MHz and 1900MHz**

GPRS 4TS 835MHz	Conducted Power (dBm)		
	Channel 128 (824.2MHz)	Channel 190 (836.6MHz)	Channel 251 (848.8MHz)
	29.5~31.5	29.5~31.5	29.5~31.5
GPRS 4TS 1900MHz	Conducted Power (dBm)		
	Channel 512 (1850.2MHz)	Channel 661 (1880MHz)	Channel 810 (1909.8MHz)
	26.5~28.5	26.5~28.5	26.5~28.5



**Table 5.1: The Conducted Power For WCDMA**

<b>WCDMA Band II</b>	<b>Conducted Power (dBm)</b>		
	<b>Channel 9262 (1852.4MHz)</b>	<b>Channel 9400 (1880MHz)</b>	<b>Channel 9538 (1907.6MHz)</b>
	<b>21.52</b>	<b>21.5</b>	<b>21.23</b>
<b>WCDMA Band V</b>	<b>Conducted Power (dBm)</b>		
	<b>Channel 4132 (826.4MHz)</b>	<b>Channel 4182 (836.4MHz)</b>	<b>Channel 4233 (846.6MHz)</b>
	<b>22.81</b>	<b>22.61</b>	<b>22.91</b>

**Table 5.2: Tolerance Power For WCDMA**

<b>WCDMA Band II</b>	<b>Conducted Power (dBm)</b>		
	<b>Channel 9262 (1852.4MHz)</b>	<b>Channel 9400 (1880MHz)</b>	<b>Channel 9538 (1907.6MHz)</b>
	<b>21.5~23.5</b>	<b>21.5~23.5</b>	<b>21.5~23.5</b>
<b>WCDMA Band V</b>	<b>Conducted Power (dBm)</b>		
	<b>Channel 4132 (826.4MHz)</b>	<b>Channel 4182 (836.4MHz)</b>	<b>Channel 4233 (846.6MHz)</b>
	<b>21.5~23.5</b>	<b>21.5~23.5</b>	<b>21.5~23.5</b>

**5.2. Calculation Information**

From the antenna specifications provided by the applicant, the antenna gain is 2.5 dBi in GSM and WCDMA.

So for conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

### 5.3. Result of GSM835

**Test Results:** MPE Limit Calculation: the EUT's operating frequencies @ 824.2 – 848.8 MHz; as per the original test report the highest power is GSM835, Low channel 128. The maximum tune up procedure power is 31.5 dBm . The maximum gain is 2.5 dBi. The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{EIRP}=31.5+2.5=34.0 \text{ dBm}=2511.89 \text{ mW}$$

$$\text{Power Density}=\text{EIRP} \times \text{Duty Cycle} / (4 \pi R^2)=2511.89 \times (4/8) / (4 \pi \times 20^2)=0.250 \text{ mW/cm}^2$$

Where Duty Cycle is 4/8 and R is 20cm.

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 824.2/1500 = 0.549 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

### 5.4. Result of GSM1900

**Test Results:** MPE Limit Calculation: the EUT's operating frequencies @ 1850.2 – 1909.8 MHz; as per the original test report the highest power is GSM1900, Low channel 512. The maximum tune up procedure power is 28.5 dBm . The maximum gain is 2.5 dBi. The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{EIRP}=28.5+2.5=31.0 \text{ dBm}=1258.93 \text{ mW}$$

$$\text{Power Density}=\text{EIRP} \times \text{Duty Cycle} / (4 \pi R^2)=1258.93 \times (4/8) / (4 \pi \times 20^2)=0.125 \text{ mW/cm}^2$$

Where Duty Cycle is 4/8 and R is 20cm.

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 1 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

### 5.5. Result of WCDMA band II

**Test Results:** MPE Limit Calculation: the EUT's operating frequencies @ 1852.4-1907.6 MHz; as per the original test report the highest power is WCDMA band II, Low channel 9262. The maximum tune up procedure power is 23.5 dBm . The maximum gain is 2.5 dBi. The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{EIRP}=23.5+2.5=26.0 \text{ dBm}=398.11 \text{ mW}$$

$$\text{Power Density}=\text{EIRP} \times \text{Duty Cycle} / (4 \pi R^2)=398.11 \times 1 / (4 \pi \times 20^2)=0.079 \text{ mW/cm}^2$$

Where Duty Cycle is 1 and R is 20cm.

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 1 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

### 5.6. Result of WCDMA band V

**Test Results:** MPE Limit Calculation: the EUT's operating frequencies @ 826.4-846.6 MHz; as per the original test report the highest power is WCDMA band V, High channel 4233. The maximum tune up procedure power is 23.5 dBm . The maximum gain is 2.5 dBi. The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{EIRP}=23.5+2.5=26.0 \text{ dBm}=398.11 \text{ mW}$$

$$\text{Power Density}=\text{EIRP} \times \text{Duty Cycle} / (4 \pi R^2)=398.11 \times 1 / (4 \pi \times 20^2)=0.079 \text{ mW/cm}^2$$

Where Duty Cycle is 1 and R is 20cm.

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 826.4 / 1500 = 0.551 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

**Note:  $\pi=3.1416$**

So the product is under the MPE limits. All is pass.

\*\*\*\*\***End The Report**\*\*\*\*\*