

**SUMMARY OF TEST RESULTS
IN ACCORD WITH FCC RULES PART 15 AND C63.4-1992**

| | |
|---|---|
| Equipment Model: | ACP00743 |
| Transmitter Tested to C63.4-1992 Section: | FCC Rules 15.231 |
| Field Strength at a distance of 3 meters: | 6100 μ V/Mtr (- 3.5 dB below limit) @ 390 MHz |
| Peak to Average Ratio: | 11 dB - Worst Case Duty Cycle |
| Test Conditions: | Radiated (Sections 11 & 13) |
| Transmitter: | |
| Transmitter Frequency: | 390 MHz Nominal (Factory Tuned Only) |
| Bandwidth (20 dB down) | < 0.010% of Center Freq. |
| Frequency Tolerance: | N/A (Nominal +/- 0.125 MHz) |
| Frequency Stability: | N/A (Nominal +/- 0.125 MHz) |
| Transmitter Spurious at 3 meters: (Worst Harmonic) | 790 μ V/Mtr (- 1.3 dB below limit) |
| Frequency: | 1950 MHz |
| Momentary Operation (Yes/No) | Yes |
| Holdover time after manual release: | 0 seconds |
| Duration of transmission after activation: | 45 seconds on any single manual activation |

Attestation: ~


The radio apparatus identified in the application has been subject to all the applicable test conditions specified in FCC Rules Part 15 and all of the requirements of the Standard have been met.

Regulatory Compliance Engineer

John W. Kuivinen, P.E.



Date:



LINEAR CORPORATION
FCC ID: EF4 ACP00743