

## DECLARATION OF COMPLIANCE SAR RF EXPOSURE EVALUATION

### Test Lab

**CELLTECH LABS INC.**  
Testing and Engineering Services  
1955 Moss Court  
Kelowna, B.C.  
Canada V1Y 9L3  
Phone: 250-448-7047  
Fax: 250-448-7046  
e-mail: info@celltechlabs.com  
web site: www.celltechlabs.com

### Applicant Information

**VERTEX STANDARD CO., LTD.**  
4-8-8, Nakameguro, Meguro-Ku  
Tokyo 153-8644  
Japan

|                                     |                                                                                                 |
|-------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Rule Part(s):</b>                | FCC 47 CFR §2.1093; IC RSS-102 Issue 1 (Provisional)                                            |
| <b>Test Procedure(s):</b>           | FCC OET Bulletin 65, Supplement C (01-01)                                                       |
| <b>Device Classification:</b>       | Licensed Non-Broadcast Transmitter Held to Face (TNF)                                           |
| <b>Device Type:</b>                 | Portable UHF PTT Radio Transceiver                                                              |
| <b>FCC ID:</b>                      | K6610524420                                                                                     |
| <b>Model(s):</b>                    | VX-537-4-5                                                                                      |
| <b>Modulation:</b>                  | FM (UHF)                                                                                        |
| <b>TX Frequency Range:</b>          | 450.00 - 490.00 MHz                                                                             |
| <b>Max. RF Output Power Tested:</b> | 36.88 dBm Conducted (450 MHz)<br>36.90 dBm Conducted (470 MHz)<br>36.72 dBm Conducted (490 MHz) |
| <b>Antenna Type(s):</b>             | Whip 450-470 MHz (P/N: ATU-5D)<br>Whip 470-512 MHz (P/N: ATU-5F)                                |
| <b>Battery Type(s):</b>             | NiCd 7.2 V, 1700 mAh (P/N: FNB-29AIS)                                                           |
| <b>Body-Worn Accessories:</b>       | Belt-Clip, Speaker-Microphone (MH-50)                                                           |
| <b>Max. SAR Measured:</b>           | Face-held: 2.58 W/kg (50% Duty Cycle)<br>Body-worn: 7.10 W/kg (50% Duty Cycle)                  |

Celltech Labs Inc. declares under its sole responsibility that this wireless portable device has demonstrated compliance with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 and Health Canada's Safety Code 6. The device was tested in accordance with the measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) and Industry Canada RSS-102 Issue 1 (Provisional) for the Occupational / Controlled Exposure environment. All measurements were performed in accordance with the SAR system manufacturer recommendations.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.



**Russell W. Pipe**  
Senior Compliance Technologist  
Celltech Labs Inc.



| <b>TABLE OF CONTENTS</b> |                                                               |              |
|--------------------------|---------------------------------------------------------------|--------------|
| <b>1.0</b>               | <b>INTRODUCTION.....</b>                                      | <b>3</b>     |
| <b>2.0</b>               | <b>DESCRIPTION OF DUT.....</b>                                | <b>3</b>     |
| <b>3.0</b>               | <b>SAR MEASUREMENT SYSTEM.....</b>                            | <b>4</b>     |
| <b>4.0</b>               | <b>MEASUREMENT SUMMARY.....</b>                               | <b>5</b>     |
| <b>5.0</b>               | <b>DETAILS OF SAR EVALUATION.....</b>                         | <b>6</b>     |
| <b>6.0</b>               | <b>EVALUATION PROCEDURES.....</b>                             | <b>6</b>     |
| <b>7.0</b>               | <b>SYSTEM PERFORMANCE CHECK.....</b>                          | <b>7</b>     |
| <b>8.0</b>               | <b>SIMULATED EQUIVALENT TISSUES.....</b>                      | <b>8</b>     |
| <b>9.0</b>               | <b>SAR SAFETY LIMITS.....</b>                                 | <b>8</b>     |
| <b>10.0</b>              | <b>ROBOT SYSTEM SPECIFICATIONS.....</b>                       | <b>9</b>     |
| <b>11.0</b>              | <b>PROBE SPECIFICATION.....</b>                               | <b>10</b>    |
| <b>12.0</b>              | <b>PLANAR PHANTOM.....</b>                                    | <b>10</b>    |
| <b>13.0</b>              | <b>VALIDATION PHANTOM.....</b>                                | <b>10</b>    |
| <b>14.0</b>              | <b>DEVICE HOLDER.....</b>                                     | <b>10</b>    |
| <b>15.0</b>              | <b>TEST EQUIPMENT LIST.....</b>                               | <b>11</b>    |
| <b>16.0</b>              | <b>MEASUREMENT UNCERTAINTIES.....</b>                         | <b>12-13</b> |
| <b>17.0</b>              | <b>REFERENCES.....</b>                                        | <b>14</b>    |
|                          | <b>APPENDIX A - SAR MEASUREMENT DATA.....</b>                 | <b>15</b>    |
|                          | <b>APPENDIX B - SYSTEM PERFORMANCE CHECK DATA.....</b>        | <b>16</b>    |
|                          | <b>APPENDIX C - SYSTEM VALIDATION PROCEDURES.....</b>         | <b>17</b>    |
|                          | <b>APPENDIX D - PROBE CALIBRATION.....</b>                    | <b>18</b>    |
|                          | <b>APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS.....</b> | <b>19</b>    |
|                          | <b>APPENDIX F - SAR TEST SETUP &amp; DUT PHOTOGRAPHS.....</b> | <b>20</b>    |

## 1.0 INTRODUCTION

This measurement report demonstrates compliance of the Vertex Standard Co., Ltd. Model: VX-537-4-5 Portable UHF PTT Radio Transceiver FCC ID: K6610524420 with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]), and Health Canada's Safety Code 6 (see reference [2]) for the Occupational / Controlled Exposure environment. The measurement procedures described in FCC OET Bulletin 65, Supplement C (Edition 01-01) (see reference [3]) and IC RSS-102 Issue 1 (Provisional) (see reference [4]), were employed. A description of the product, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

## 2.0 DESCRIPTION OF DEVICE UNDER TEST (DUT)


|                                     |                                           |                 |                            |
|-------------------------------------|-------------------------------------------|-----------------|----------------------------|
| <b>FCC Rule Part(s)</b>             | 47 CFR §2.1093                            |                 |                            |
| <b>IC Rule Part(s)</b>              | RSS-102 Issue 1 (Provisional)             |                 |                            |
| <b>Test Procedure(s)</b>            | FCC OET Bulletin 65, Supplement C (01-01) |                 |                            |
| <b>Device Type</b>                  | Portable UHF PTT Radio Transceiver        |                 |                            |
| <b>FCC ID</b>                       | K6610524420                               |                 |                            |
| <b>Model(s)</b>                     | VX-537-4-5                                |                 |                            |
| <b>Serial No.</b>                   | 3M000002 (Identical Prototype)            |                 |                            |
| <b>Modulation</b>                   | FM (UHF)                                  |                 |                            |
| <b>Tx Frequency Range</b>           | 450 - 490 MHz                             |                 |                            |
| <b>Max. RF Output Power Tested</b>  | 450 MHz                                   | 36.88 dBm       | Conducted                  |
|                                     | 470 MHz                                   | 36.90 dBm       | Conducted                  |
|                                     | 490 MHz                                   | 36.72 dBm       | Conducted                  |
| <b>Antenna Type(s)</b>              | Whip                                      | 450-470 MHz     | Length: 175 mm P/N ATU-5D  |
|                                     | Whip                                      | 470-512 MHz     | Length: 157 mm P/N: ATU-5F |
| <b>Battery Type(s)</b>              | NiCd                                      | 7.2 V, 1700 mAh | P/N: FNB-29AIS             |
| <b>Body-Worn Accessories Tested</b> | Belt-Clip                                 |                 |                            |
|                                     | Speaker-Microphone (P/N: MH-50)           |                 |                            |

### 3.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for brain and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



DASY4 SAR Measurement System with validation phantom



DASY4 SAR Measurement System with Plexiglas planar phantom

## 4.0 MEASUREMENT SUMMARY

### SAR EVALUATION RESULTS

| SAR EVALUATION RESULTS                                                                                                                      |             |               |           |                                    |             |                             |                  |                                   |                                            |                     |      |                             |                   |      |
|---------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------------|-----------|------------------------------------|-------------|-----------------------------|------------------|-----------------------------------|--------------------------------------------|---------------------|------|-----------------------------|-------------------|------|
| Test Type                                                                                                                                   | Freq. (MHz) | Chan.         | Test Mode | Measured Conducted RF Output Power |             |                             | Antenna Part No. | Accessory Type                    | Separation Distance to Planar Phantom (cm) | Measured SAR (W/kg) |      | Max. Cond. Power Drift (dB) | Scaled SAR (W/kg) |      |
|                                                                                                                                             |             |               |           | Before (dBm)                       | After (dBm) | Drift (dB)                  |                  |                                   |                                            | Duty Cycle          |      |                             | Duty Cycle        |      |
|                                                                                                                                             |             |               |           |                                    |             |                             |                  |                                   |                                            | 100%                | 50%  |                             | 100%              | 50%  |
| Face                                                                                                                                        | 470         | Mid           | CW        | 36.84                              | 36.00       | -0.84                       | ATU-5D           | -                                 | 2.5                                        | 2.88                | 1.44 | -0.87                       | 3.52              | 1.76 |
| Face                                                                                                                                        | 470         | Mid           | CW        | 36.87                              | 35.96       | -0.91                       | ATU-5F           | -                                 | 2.5                                        | 4.17                | 2.09 | -0.92                       | 5.15              | 2.58 |
| Body                                                                                                                                        | 470         | Mid           | CW        | 36.90                              | 36.11       | -0.79                       | ATU-5D           | Belt-Clip Speaker-Mic             | 1.0                                        | 8.22                | 4.11 | -0.87                       | 10.0              | 5.00 |
| Body                                                                                                                                        | 450         | Low           | CW        | 36.88                              | 36.01       | -0.87                       | ATU-5D           | Belt-Clip Speaker-Mic             | 1.0                                        | 9.44                | 4.72 | -0.87                       | 11.5              | 5.75 |
| Body                                                                                                                                        | 470         | Mid           | CW        | 36.81                              | 36.02       | -0.79                       | ATU-5F           | Belt-Clip Speaker-Mic             | 1.0                                        | 11.5                | 5.75 | -0.92                       | 14.2              | 7.10 |
| Body                                                                                                                                        | 490         | High          | CW        | 36.72                              | 35.80       | -0.92                       | ATU-5F           | Belt-Clip Speaker-Mic             | 1.0                                        | 9.24                | 4.62 | -0.92                       | 11.4              | 5.70 |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak - Controlled Exposure / Occupational<br>BRAIN / BODY: 8.0 W/kg (averaged over 1 gram) |             |               |           |                                    |             |                             |                  |                                   |                                            |                     |      |                             |                   |      |
| Dielectric Constant $\epsilon_r$                                                                                                            |             | Brain 450 MHz |           | Body 450 MHz                       |             | Atmospheric Pressure        |                  | 98.1 kPa                          |                                            |                     |      |                             |                   |      |
|                                                                                                                                             |             | IEEE Target   | Measured  | IEEE Target                        | Measured    | Relative Humidity           |                  | 32%                               |                                            |                     |      |                             |                   |      |
|                                                                                                                                             |             | 43.5 (+/-5%)  | 44.4      | 56.7 (+/-5%)                       | 57.2        | Ambient Temperature         |                  | Brain: 24.7 °C                    |                                            | Body: 25.5 °C       |      |                             |                   |      |
| Conductivity $\sigma$ (mho/m)                                                                                                               |             | Brain 450 MHz |           | Body 450 MHz                       |             | Fluid Temperature           |                  | Brain: 23.0 °C      Body: 22.2 °C |                                            |                     |      |                             |                   |      |
|                                                                                                                                             |             | IEEE Target   | Measured  | IEEE Target                        | Measured    | Fluid Depth                 |                  | $\geq 15$ cm                      |                                            |                     |      |                             |                   |      |
|                                                                                                                                             |             | 0.87 (+/-5%)  | 0.89      | 0.94 (+/-5%)                       | 0.93        | $\rho$ (Kg/m <sup>3</sup> ) |                  | 1000                              |                                            |                     |      |                             |                   |      |

Note(s):

1. Antenna P/N: ATU-5D = 450-740 MHz  
Antenna P/N: ATU-5F = 470-512 MHz
2. The measurement results were obtained with the DUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.
3. If the SAR measurements performed at the mid channel were ≥ 3dB below the SAR limit, SAR evaluation for the low and high channels was optional (per FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [3])).
4. The conducted power levels measured after the SAR evaluations were > 5% from the measured start power. The maximum conducted power drift measured for each antenna type was subsequently added to the corresponding measured SAR levels to show scaled SAR results as listed in the above table.
5. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluation. The temperatures listed were consistent for all measurement periods.
6. The dielectric parameters of the simulated tissue mixtures were measured prior to the evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer (see Appendix E for printout of measured fluid dielectric parameters).



## 5.0 DETAILS OF SAR EVALUATION

The Vertex Standard Co., Ltd. Model: VX-537-4-5 Portable UHF PTT Radio Transceiver FCC ID: K6610524420 was found to be compliant for localized Specific Absorption Rate (Occupational / Controlled Exposure) based on the test provisions and conditions described below. The detailed test setup photographs are shown in Appendix F.

1. The DUT was evaluated in a face-held configuration with the front of the radio placed parallel to the outer surface of the planar phantom. A 2.5 cm separation distance was maintained between the front side of the DUT and the outer surface of the planar phantom for the duration of the tests.
2. The DUT was evaluated in a body-worn configuration with the back of the radio placed parallel to the outer surface of the planar phantom. The attached belt-clip was touching the planar phantom and provided a 1.0 cm separation distance between the back of the DUT and the outer surface of the planar phantom. The DUT was tested for body-worn SAR with the speaker-microphone accessory connected.
3. The conducted power levels were measured before and after each test according to the procedures described in FCC 47 CFR §2.1046. The conducted power levels measured after the SAR evaluations were > 5% from the measured start power. The maximum conducted power drift measured for each antenna type was subsequently added to the corresponding measured SAR levels to show scaled SAR results as shown in the test data table (page 5).
4. The DUT was tested in unmodulated continuous transmit operation (Continuous Wave mode at 100% duty cycle) with the transmit key constantly depressed. For a push-to-talk device the 50% duty cycle compensation reported assumes a transmit/receive cycle of equal time base.
5. The DUT was tested with a fully charged NiCd battery.
6. The SAR evaluations were performed using a Plexiglas planar phantom.
7. A stack of low-density, low-loss dielectric foamed polystyrene was used in place of the device holder.

## 6.0 EVALUATION PROCEDURES

- a. (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.  
(ii) For body-worn and face-held devices a planar phantom was used.
- b. The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.

An area scan was determined as follows:

- c. Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- d. A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.

A 1g and 10g spatial peak SAR was determined as follows:

- e. Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix D). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
- f. Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).

## 7.0 SYSTEM PERFORMANCE CHECK

Prior to the SAR evaluation a system check was performed using a planar phantom with a 450MHz dipole (see Appendix C for system validation procedure). The dielectric parameters of the simulated tissue fluid were measured prior to the system performance check using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer (see Appendix E for printout of measured fluid dielectric parameters). A forward power of 250mW was applied to the dipole and the system was verified to a tolerance of  $\pm 10\%$  (see Appendix B for system performance check test plots).

| SYSTEM PERFORMANCE CHECK |                      |                     |              |                                  |          |                               |          |                             |                 |                  |                  |            |                     |
|--------------------------|----------------------|---------------------|--------------|----------------------------------|----------|-------------------------------|----------|-----------------------------|-----------------|------------------|------------------|------------|---------------------|
| Test Date                | 450MHz Equiv. Tissue | SAR 1g (W/kg)       |              | Dielectric Constant $\epsilon_r$ |          | Conductivity $\sigma$ (mho/m) |          | $\rho$ (Kg/m <sup>3</sup> ) | Amb. Temp. (°C) | Fluid Temp. (°C) | Fluid Depth (cm) | Humid. (%) | Barom. Press. (kPa) |
|                          |                      | IEEE Target         | Measured     | IEEE Target                      | Measured | IEEE Target                   | Measured |                             |                 |                  |                  |            |                     |
| 01/12/04                 | Brain                | 1.23 ( $\pm 10\%$ ) | 1.34 (+8.9%) | 43.5 $\pm 5\%$                   | 44.4     | 0.87 $\pm 5\%$                | 0.89     | 1000                        | 24.7            | 23.0             | $\geq 15$        | 32         | 98.1                |

Note(s):

1. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the system performance check. The temperatures listed in the table above were consistent for all measurement periods.





Figure 1. System Performance Check Setup Diagram



450MHz Dipole Setup

## 8.0 SIMULATED EQUIVALENT TISSUES

The 450MHz brain and body simulated tissue mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The fluid was prepared and measured for dielectric parameters (permittivity and conductivity) according to standardized procedures.

| SIMULATED TISSUE MIXTURES |                                                 |                                 |
|---------------------------|-------------------------------------------------|---------------------------------|
| INGREDIENT                | 450MHz Brain<br>(System Check & DUT Evaluation) | 450MHz Body<br>(DUT Evaluation) |
| Water                     | 38.56 %                                         | 52.00 %                         |
| Sugar                     | 56.32 %                                         | 45.65 %                         |
| Salt                      | 3.95 %                                          | 1.75 %                          |
| HEC                       | 0.98 %                                          | 0.50 %                          |
| Bactericide               | 0.19 %                                          | 0.10 %                          |

## 9.0 SAR SAFETY LIMITS

| EXPOSURE LIMITS                                                 | SAR (W/kg)                                                     |                                                        |
|-----------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------|
|                                                                 | (General Population /<br>Uncontrolled Exposure<br>Environment) | (Occupational /<br>Controlled Exposure<br>Environment) |
| Spatial Average<br>(averaged over the whole body)               | 0.08                                                           | 0.4                                                    |
| Spatial Peak<br>(averaged over any 1g of tissue)                | 1.60                                                           | 8.0                                                    |
| Spatial Peak<br>(hands/wrists/feet/ankles<br>averaged over 10g) | 4.0                                                            | 20.0                                                   |

### Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.



## 10.0 ROBOT SYSTEM SPECIFICATIONS

### Specifications

**POSITIONER:** Stäubli Unimation Corp. Robot Model: RX60L  
**Repeatability:** 0.02 mm  
**No. of axis:** 6

### Data Acquisition Electronic (DAE) System

#### Cell Controller

**Processor:** AMD Athlon XP 2400+  
**Clock Speed:** 2.0 GHz  
**Operating System:** Windows XP Professional

#### Data Converter

**Features:** Signal Amplifier, multiplexer, A/D converter, and control logic  
**Software:** DASY4 software  
**Connecting Lines:** Optical downlink for data and status info.  
 Optical uplink for commands and clock

### DASY4 Measurement Server

**Function:** Real-time data evaluation for field measurements and surface detection  
**Hardware:** PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM  
**Connections:** COM1, COM2, DAE, Robot, Ethernet, Service Interface

### E-Field Probe

**Model:** ET3DV6  
**Serial No.:** 1387  
**Construction:** Triangular core fiber optic detection system  
**Frequency:** 10 MHz to 6 GHz  
**Linearity:**  $\pm 0.2$  dB (30 MHz to 3 GHz)

### Phantom(s)

#### Evaluation Phantom

**Type:** Planar Phantom  
**Shell Material:** Plexiglas  
**Bottom Thickness:** 2.0 mm  $\pm$  0.1 mm  
**Outer Dimensions:** 75.0 cm (L) x 22.5 cm (W) x 20.5 cm (H); Back Plane: 25.7 cm (H)

#### Validation Phantom ( $\leq 450$ MHz)

**Type:** Planar Phantom  
**Shell Material:** Plexiglas  
**Bottom Thickness:** 6.2 mm  $\pm$  0.1 mm  
**Outer Dimensions:** 86.0 cm (L) x 39.5 cm (W) x 21.8 cm (H)

## 11.0 PROBE SPECIFICATION (ET3DV6)

|                    |                                                                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction:      | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g. glycol) |
| Calibration:       | In air from 10 MHz to 2.5 GHz<br>In brain simulating tissue at frequencies of 900 MHz and 1.8 GHz (accuracy $\pm 8\%$ )                                      |
| Frequency:         | 10 MHz to $> 6$ GHz; Linearity: $\pm 0.2$ dB<br>(30 MHz to 3 GHz)                                                                                            |
| Directivity:       | $\pm 0.2$ dB in brain tissue (rotation around probe axis)<br>$\pm 0.4$ dB in brain tissue (rotation normal to probe axis)                                    |
| Dynamic Range:     | 5 $\mu$ W/g to $> 100$ mW/g; Linearity: $\pm 0.2$ dB                                                                                                         |
| Surface Detection: | $\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces                                                                         |
| Dimensions:        | Overall length: 330 mm<br>Tip length: 16 mm<br>Body diameter: 12 mm<br>Tip diameter: 6.8 mm<br>Distance from probe tip to dipole centers: 2.7 mm             |
| Application:       | General dosimetry up to 3 GHz<br>Compliance tests of mobile phone                                                                                            |



ET3DV6 E-Field Probe

## 12.0 PLANAR PHANTOM

The planar phantom is constructed of Plexiglas material with a 2.0 mm shell thickness for face-held and body-worn SAR evaluations of handheld radio transceivers. The planar phantom is mounted on the side of the DASY4 system table.



Plexiglas Planar Phantom

## 13.0 VALIDATION PLANAR PHANTOM

The validation planar phantom is constructed of Plexiglas material with a 6.0 mm shell thickness for system validations at 450MHz and below. The validation planar phantom is mounted in the table of the DASY4 system.



Validation Planar Phantom

## 14.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of  $65^\circ$ . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.



Device Holder

## 15.0 TEST EQUIPMENT LIST

| TEST EQUIPMENT                           | SERIAL NO. | CALIBRATION DATE |
|------------------------------------------|------------|------------------|
| Schmid & Partner DASY4 System            | -          | -                |
| DASY4 Measurement Server                 | 1078       | N/A              |
| -Robot                                   | 599396-01  | N/A              |
| -ET3DV6 E-Field Probe                    | 1387       | Feb 2003         |
| -300MHz Validation Dipole                | 135        | Oct 2003         |
| -450MHz Validation Dipole                | 136        | Nov 2003         |
| -900MHz Validation Dipole                | 054        | June 2003        |
| -1800MHz Validation Dipole               | 247        | June 2003        |
| -2450MHz Validation Dipole               | 150        | Sept 2003        |
| -Planar Phantom                          | 161        | N/A              |
| -Validation Planar Phantom               | 137        | N/A              |
| HP 85070C Dielectric Probe Kit           | N/A        | N/A              |
| Gigatronics 8651A Power Meter            | 8650137    | April 2003       |
| Gigatronics 8652A Power Meter            | 1835267    | April 2003       |
| Power Sensor 80701A                      | 1833542    | Feb 2003         |
| Power Sensor 80701A                      | 1833699    | April 2003       |
| HP E4408B Spectrum Analyzer              | US39240170 | Dec 2003         |
| HP 8594E Spectrum Analyzer               | 3543A02721 | April 2003       |
| HP 8753E Network Analyzer                | US38433013 | May 2003         |
| HP 8648D Signal Generator                | 3847A00611 | May 2003         |
| Amplifier Research 5S1G4 Power Amplifier | 26235      | N/A              |

## 16.0 MEASUREMENT UNCERTAINTIES

| UNCERTAINTY BUDGET FOR DEVICE EVALUATION |                         |                          |         |             |                                 |                    |
|------------------------------------------|-------------------------|--------------------------|---------|-------------|---------------------------------|--------------------|
| Error Description                        | Uncertainty Value<br>±% | Probability Distribution | Divisor | $C_i$<br>1g | Standard Uncertainty<br>±% (1g) | $V_i$ or $V_{eff}$ |
| <b>Measurement System</b>                |                         |                          |         |             |                                 |                    |
| Probe calibration                        | ± 4.8                   | Normal                   | 1       | 1           | ± 4.8                           | ∞                  |
| Axial isotropy of the probe              | ± 4.7                   | Rectangular              | √3      | (1- $C_p$ ) | ± 1.9                           | ∞                  |
| Spherical isotropy of the probe          | ± 9.6                   | Rectangular              | √3      | ( $C_p$ )   | ± 3.9                           | ∞                  |
| Spatial resolution                       | ± 0.0                   | Rectangular              | √3      | 1           | ± 0.0                           | ∞                  |
| Boundary effects                         | ± 5.5                   | Rectangular              | √3      | 1           | ± 3.2                           | ∞                  |
| Probe linearity                          | ± 4.7                   | Rectangular              | √3      | 1           | ± 2.7                           | ∞                  |
| Detection limit                          | ± 1.0                   | Rectangular              | √3      | 1           | ± 0.6                           | ∞                  |
| Readout electronics                      | ± 1.0                   | Normal                   | 1       | 1           | ± 1.0                           | ∞                  |
| Response time                            | ± 0.8                   | Rectangular              | √3      | 1           | ± 0.5                           | ∞                  |
| Integration time                         | ± 1.4                   | Rectangular              | √3      | 1           | ± 0.8                           | ∞                  |
| RF ambient conditions                    | ± 3.0                   | Rectangular              | √3      | 1           | ± 1.7                           | ∞                  |
| Mech. constraints of robot               | ± 0.4                   | Rectangular              | √3      | 1           | ± 0.2                           | ∞                  |
| Probe positioning                        | ± 2.9                   | Rectangular              | √3      | 1           | ± 1.7                           | ∞                  |
| Extrapolation & integration              | ± 3.9                   | Rectangular              | √3      | 1           | ± 2.3                           | ∞                  |
| <b>Test Sample Related</b>               |                         |                          |         |             |                                 |                    |
| Device positioning                       | ± 6.0                   | Normal                   | √3      | 1           | ± 6.7                           | 12                 |
| Device holder uncertainty                | ± 5.0                   | Normal                   | √3      | 1           | ± 5.9                           | 8                  |
| Power drift                              | ± 5.0                   | Rectangular              | √3      |             | ± 2.9                           | ∞                  |
| <b>Phantom and Setup</b>                 |                         |                          |         |             |                                 |                    |
| Phantom uncertainty                      | ± 4.0                   | Rectangular              | √3      | 1           | ± 2.3                           | ∞                  |
| Liquid conductivity (target)             | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| Liquid conductivity (measured)           | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| Liquid permittivity (target)             | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| Liquid permittivity (measured)           | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| <b>Combined Standard Uncertainty</b>     |                         |                          |         |             |                                 |                    |
|                                          |                         |                          |         |             | ± 13.3                          |                    |
| <b>Expanded Uncertainty (k=2)</b>        |                         |                          |         |             |                                 |                    |
|                                          |                         |                          |         |             | ± 26.6                          |                    |

Measurement Uncertainty Table in accordance with IEEE Standard 1528-200X (Draft - see reference [5])

## MEASUREMENT UNCERTAINTIES (Cont.)

| UNCERTAINTY BUDGET FOR SYSTEM VALIDATION |                         |                          |         |             |                                 |                    |
|------------------------------------------|-------------------------|--------------------------|---------|-------------|---------------------------------|--------------------|
| Error Description                        | Uncertainty Value<br>±% | Probability Distribution | Divisor | $C_i$<br>1g | Standard Uncertainty<br>±% (1g) | $V_i$ or $V_{eff}$ |
| <b>Measurement System</b>                |                         |                          |         |             |                                 |                    |
| Probe calibration                        | ± 4.8                   | Normal                   | 1       | 1           | ± 4.8                           | ∞                  |
| Axial isotropy of the probe              | ± 4.7                   | Rectangular              | √3      | (1- $C_p$ ) | ± 1.9                           | ∞                  |
| Spherical isotropy of the probe          | ± 9.6                   | Rectangular              | √3      | ( $C_p$ )   | ± 3.9                           | ∞                  |
| Spatial resolution                       | ± 0.0                   | Rectangular              | √3      | 1           | ± 0.0                           | ∞                  |
| Boundary effects                         | ± 5.5                   | Rectangular              | √3      | 1           | ± 3.2                           | ∞                  |
| Probe linearity                          | ± 4.7                   | Rectangular              | √3      | 1           | ± 2.7                           | ∞                  |
| Detection limit                          | ± 1.0                   | Rectangular              | √3      | 1           | ± 0.6                           | ∞                  |
| Readout electronics                      | ± 1.0                   | Normal                   | 1       | 1           | ± 1.0                           | ∞                  |
| Response time                            | ± 0.8                   | Rectangular              | √3      | 1           | ± 0.5                           | ∞                  |
| Integration time                         | ± 1.4                   | Rectangular              | √3      | 1           | ± 0.8                           | ∞                  |
| RF ambient conditions                    | ± 3.0                   | Rectangular              | √3      | 1           | ± 1.7                           | ∞                  |
| Mech. constraints of robot               | ± 0.4                   | Rectangular              | √3      | 1           | ± 0.2                           | ∞                  |
| Probe positioning                        | ± 2.9                   | Rectangular              | √3      | 1           | ± 1.7                           | ∞                  |
| Extrapolation & integration              | ± 3.9                   | Rectangular              | √3      | 1           | ± 2.3                           | ∞                  |
| <b>Dipole</b>                            |                         |                          |         |             |                                 |                    |
| Dipole Axis to Liquid Distance           | ± 2.0                   | Rectangular              | √3      | 1           | ± 1.2                           | ∞                  |
| Input Power                              | ± 4.7                   | Rectangular              | √3      | 1           | ± 2.7                           | ∞                  |
| <b>Phantom and Setup</b>                 |                         |                          |         |             |                                 |                    |
| Phantom uncertainty                      | ± 4.0                   | Rectangular              | √3      | 1           | ± 2.3                           | ∞                  |
| Liquid conductivity (target)             | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| Liquid conductivity (measured)           | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| Liquid permittivity (target)             | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| Liquid permittivity (measured)           | ± 5.0                   | Rectangular              | √3      | 0.6         | ± 1.7                           | ∞                  |
| <b>Combined Standard Uncertainty</b>     |                         |                          |         |             |                                 |                    |
|                                          |                         |                          |         |             | ± 9.9                           |                    |
| <b>Expanded Uncertainty (k=2)</b>        |                         |                          |         |             |                                 |                    |
|                                          |                         |                          |         |             | ± 19.8                          |                    |

Measurement Uncertainty Table in accordance with IEEE Standard 1528-200X (Draft - see reference [5])

## 17.0 REFERENCES

- [1] Federal Communications Commission, "Radiofrequency radiation exposure evaluation: portable devices", Rule Part 47 CFR §2.1093: 1999.
- [2] Health Canada, "Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz", Safety Code 6.
- [3] Federal Communications Commission, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [4] Industry Canada, "Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields", Radio Standards Specification RSS-102 Issue 1 (Provisional): September 1999.
- [5] IEEE Standards Coordinating Committee 34, Std 1528-200X, "DRAFT Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques".



## APPENDIX A - SAR MEASUREMENT DATA

Dated Tested: 01/12/04

DUT: Vertex Standard Model: VX-537-4-5; Type: Portable UHF PTT Radio Transceiver; Serial: 3M000002

Ambient Temp: 24.7 °C; Fluid Temp: 23.0 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Communication System: FM UHF

Frequency: 470 MHz; Duty Cycle: 1:1

7.2V NiCd Battery Pack (P/N: FNB-29AIS)

RF Output Power: 36.84 dBm (Conducted)

Medium: HSL450 ( $\sigma = 0.89$  mho/m;  $\epsilon_r = 44.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 19/12/2003
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

**Face-Held - Whip Antenna (P/N: ATU-5D) - 2.5 cm Separation Distance - Mid Ch/Area Scan (8x23x1):**

Measurement grid: dx=15mm, dy=15mm


**Face-Held - Whip Antenna (P/N: ATU-5D) - 2.5 cm Separation Distance - Mid Ch/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 4.58 W/kg

**SAR(1 g) = 2.88 mW/g; SAR(10 g) = 2.06 mW/g**

Reference Value = 52.3 V/m



Dated Tested: 01/12/04

DUT: Vertex Standard Model: VX-537-4-5; Type: Portable UHF PTT Radio Transceiver; Serial: 3M000002

Ambient Temp: 24.7 °C; Fluid Temp: 23.0 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Communication System: FM UHF

Frequency: 470 MHz; Duty Cycle: 1:1

7.2V NiCd Battery Pack (P/N: FNB-29AIS)

RF Output Power: 36.87 dBm (Conducted)

Medium: HSL450 ( $\sigma = 0.89$  mho/m;  $\epsilon_r = 44.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 26/02/2003

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 19/12/2003

- Phantom: Planar; Type: Plexiglas; Serial: 161

- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

**Face-Held - Whip Antenna (P/N: ATU-5F) - 2.5 cm Separation Distance - Mid Ch/Area Scan (8x22x1):**

Measurement grid: dx=15mm, dy=15mm


**Face-Held - Whip Antenna (P/N: ATU-5F) - 2.5 cm Separation Distance - Mid Ch/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 6.77 W/kg

**SAR(1 g) = 4.17 mW/g; SAR(10 g) = 2.97 mW/g**

Reference Value = 73.4 V/m





Dated Tested: 01/12/04

DUT: Vertex Standard Model: VX-537-4-5; Type: Portable UHF PTT Radio Transceiver; Serial: 3M000002

Ambient Temp: 25.5 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Body-worn Accessories: Belt-Clip, Speaker-Microphone (P/N: MH-50)

Communication System: FM UHF

Frequency: 470 MHz; Duty Cycle: 1:1

7.2V NiCd Battery Pack (P/N: FNB-29AIS)

RF Output Power: 36.90 dBm (Conducted)

Medium: M450 Medium ( $\sigma = 0.93$  mho/m;  $\epsilon_r = 57.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.7, 7.7, 7.7); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 19/12/2003
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

**Body-Worn - Whip Antenna (P/N: ATU-5D) - 1.0 cm Belt-Clip Separation Distance - Mid Ch/Area Scan (8x23x1):**

Measurement grid: dx=15mm, dy=15mm


**Body-Worn - Whip Antenna (P/N: ATU-5D) - 1.0 cm Belt-Clip Separation Distance - Mid Ch/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 13.3 W/kg

**SAR(1 g) = 8.22 mW/g; SAR(10 g) = 5.73 mW/g**

Reference Value = 74.4 V/m



Dated Tested: 01/12/04

DUT: Vertex Standard Model: VX-537-4-5; Type: Portable UHF PTT Radio Transceiver; Serial: 3M000002

Ambient Temp: 25.5 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Body-worn Accessories: Belt-Clip, Speaker-Microphone (MH-50)

Communication System: FM UHF

Frequency: 450 MHz; Duty Cycle: 1:1

7.2V NiCd Battery Pack (P/N: FNB-29AIS)

RF Output Power: 36.88 dBm (Conducted)

Medium: M450 Medium ( $\sigma = 0.93$  mho/m;  $\epsilon_r = 57.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.7, 7.7, 7.7); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 19/12/2003
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

**Body-Worn - Whip Antenna (P/N: ATU-5D) - 1.0 cm Belt-Clip Separation Distance - Low Ch/Area Scan (8x23x1):**

Measurement grid: dx=15mm, dy=15mm


**Body-Worn - Whip Antenna (P/N: ATU-5D) - 1.0 cm Belt-Clip Separation Distance - Low Ch/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 15.7 W/kg

**SAR(1 g) = 9.44 mW/g; SAR(10 g) = 6.48 mW/g**

Reference Value = 81.6 V/m



Dated Tested: 01/12/04

DUT: Vertex Standard Model: VX-537-4-5; Type: Portable UHF PTT Radio Transceiver; Serial: 3M000002

Ambient Temp: 25.5 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Body-worn Accessories: Belt-Clip, Speaker-Microphone (MH-50)

Communication System: FM UHF

Frequency: 470 MHz; Duty Cycle: 1:1

7.2V NiCd Battery Pack (P/N: FNB-29AIS)

RF Output Power: 36.81 dBm (Conducted)

Medium: M450 Medium ( $\sigma = 0.93$  mho/m;  $\epsilon_r = 57.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.7, 7.7, 7.7); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 19/12/2003
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

**Body-Worn - Whip Antenna (P/N: ATU-5F) - 1.0 cm Belt-Clip Separation Distance - Mid Ch/Area Scan (8x22x1):**

Measurement grid: dx=15mm, dy=15mm


**Body-Worn - Whip Antenna (P/N: ATU-5F) - 1.0 cm Belt-Clip Separation Distance - Mid Ch/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Peak SAR (extrapolated) = 18.7 W/kg

**SAR(1 g) = 11.5 mW/g; SAR(10 g) = 8.03 mW/g**

Reference Value = 97.5 V/m







Dated Tested: 01/12/04

DUT: Vertex Standard Model: VX-537-4-5; Type: Portable UHF PTT Radio Transceiver; Serial: 3M000002

Ambient Temp: 25.5 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Body-worn Accessories: Belt-Clip, Speaker-Microphone (MH-50)

Communication System: FM UHF

Frequency: 490 MHz; Duty Cycle: 1:1

7.2V NiCd Battery Pack (P/N: FNB-29AIS)

RF Output Power: 36.72 dBm (Conducted)

Medium: M450 Medium ( $\sigma = 0.93$  mho/m;  $\epsilon_r = 57.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.7, 7.7, 7.7); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 19/12/2003
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

**Body-Worn - Whip Antenna (P/N: ATU-5F) - 1.0 cm Belt-Clip Separation Distance - High Ch/Area Scan (8x22x1):**

Measurement grid: dx=15mm, dy=15mm


**Body-Worn - Whip Antenna (P/N: ATU-5F) - 1.0 cm Belt-Clip Separation Distance - High Ch/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 14.9 W/kg

**SAR(1 g) = 9.24 mW/g; SAR(10 g) = 6.4 mW/g**

Reference Value = 90.9 V/m



## APPENDIX B - SYSTEM PERFORMANCE CHECK DATA

Dated Tested: 01/12/04

DUT: Dipole 450 MHz; Model: D450V2; Type: System Performance Check; Serial: 136

Ambient Temp: 24.7 °C; Fluid Temp: 23.0 °C; Barometric Pressure: 98.1 kPa; Humidity: 32%

Communication System: CW  
Forward Conducted Power: 250mW  
Frequency: 450 MHz; Duty Cycle: 1:1  
Medium: HSL450 ( $\sigma = 0.89 \text{ mho/m}$ ;  $\epsilon_r = 44.4$ ;  $\rho = 1000 \text{ kg/m}^3$ )

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 19/12/2003
- Phantom: Validation Planar; Type: Plexiglas; Serial: 137
- Measurement SW: DASY4, V4.2 Build 12; Postprocessing SW: SEMCAD, V1.8 Build 93

#### 450 System Performance Check/Area Scan (6x11x1):

Measurement grid: dx=15mm, dy=15mm

#### 450 MHz System Performance Check/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm


Peak SAR (extrapolated) = 2.41 W/kg

**SAR(1 g) = 1.34 mW/g; SAR(10 g) = 0.850 mW/g**

Reference Value = 39.7 V/m

Power Drift = 0.0 dB





## APPENDIX C - SYSTEM VALIDATION

## 450MHz SYSTEM VALIDATION DIPOLE

Type:

**450MHz Validation Dipole**

Serial Number:

**136**

Place of Calibration:

**Celltech Labs Inc.**

Date of Calibration:

**November 4, 2003**

**Celltech Labs Inc. hereby certifies that this device has been calibrated on the date indicated above.**

Calibrated by:

*Spencer Watson*


Approved by:

*Russell W. Pope*

## 1. Dipole Construction & Electrical Characteristics


The validation dipole was constructed in accordance with the IEEE Std “Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”. The electrical properties were measured using an HP 8753E Network Analyzer. The network analyzer was calibrated to the validation dipole N-type connector feed point using an HP85032E Type N calibration kit. The dipole was placed parallel to a planar phantom at a separation distance of 15.0mm from the simulating fluid using a loss-less dielectric spacer. The measured input impedance is:

|                                |                                                                    |
|--------------------------------|--------------------------------------------------------------------|
| Feed point impedance at 450MHz | $\text{Re}\{Z\} = 49.982\Omega$<br>$\text{Im}\{Z\} = 7.2324\Omega$ |
| Return Loss at 450MHz          | -22.597dB                                                          |






CH1 S11 1 U FS 1: 49.982  $\Omega$  7.2324  $\Omega$  2.5579 nH 4 Nov 2003 12:04:21 450.000 000 MHz



4 Nov 2003 12:06:24  
[CH1] S11 LOG 10 dB/REF 0 dB 1:-22.597 dB 450.000 000 MHz



## 2. Validation Dipole Dimensions

| Frequency (MHz) | L (mm) | h (mm) | d (mm) |
|-----------------|--------|--------|--------|
| 300             | 420.0  | 250.0  | 6.2    |
| 450             | 288.0  | 167.0  | 6.2    |
| 835             | 161.0  | 89.8   | 3.6    |
| 900             | 149.0  | 83.3   | 3.6    |
| 1450            | 89.1   | 51.7   | 3.6    |
| 1800            | 72.0   | 41.7   | 3.6    |
| 1900            | 68.0   | 39.5   | 3.6    |
| 2000            | 64.5   | 37.5   | 3.6    |
| 2450            | 51.8   | 30.6   | 3.6    |
| 3000            | 41.5   | 25.0   | 3.6    |


## 3. Validation Phantom

The validation phantom was constructed using relatively low-loss tangent Plexiglas material. The inner dimensions of the phantom are as follows:

Length: 83.5 cm  
Width: 36.9 cm  
Height: 21.8 cm

The bottom section of the validation phantom is constructed of  $6.2 \pm 0.1$ mm Plexiglas.

#### 4. Dimensions of Plexiglas Planar Phantom



## 5. 450MHz System Validation Setup



**450MHz System Validation Setup**



## 6. Measurement Conditions

The planar phantom was filled with brain simulating tissue having the following parameters at 450MHz:

Relative Permittivity: 43.7  
 Conductivity: 0.88 mho/m  
 Fluid Temperature: 22.0 °C  
 Fluid Depth:  $\geq 15.0$  cm

Environmental Conditions:


Ambient Temperature: 22.1 °C  
 Humidity: 49 %  
 Barometric Pressure: 102.8 kPa

The 450MHz simulated brain tissue mixture consists of the following ingredients:

| Ingredient                                   | Percentage by weight                       |
|----------------------------------------------|--------------------------------------------|
| Water                                        | 38.56%                                     |
| Sugar                                        | 56.32%                                     |
| Salt                                         | 3.95%                                      |
| HEC                                          | 0.98%                                      |
| Dowicil 75                                   | 0.19%                                      |
| 450MHz Target Dielectric Parameters at 22 °C | $\epsilon_r = 43.5$<br>$\sigma = 0.87$ S/m |

## 7. SAR Measurement

The SAR measurement was performed with the E-field probe in mechanical detection mode only. The setup and determination of the forward power into the dipole was performed using the following procedures.



First the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power should be 20dB below the forward power.



## 8. Validation Dipole SAR Test Results

Ten SAR measurements were performed in order to achieve repeatability and to establish an average target value.

| Validation Measurement | SAR @ 0.25W<br>Input averaged<br>over 1g | SAR @ 1W<br>Input averaged<br>over 1g | SAR @ 0.25W<br>Input averaged<br>over 10g | SAR @ 1W<br>Input averaged<br>over 10g | Peak SAR @<br>0.25W Input |
|------------------------|------------------------------------------|---------------------------------------|-------------------------------------------|----------------------------------------|---------------------------|
| Test 1                 | 1.29                                     | 5.16                                  | 0.810                                     | 3.24                                   | 2.28                      |
| Test 2                 | 1.31                                     | 5.24                                  | 0.827                                     | 3.31                                   | 2.31                      |
| Test 3                 | 1.30                                     | 5.20                                  | 0.823                                     | 3.29                                   | 2.29                      |
| Test 4                 | 1.30                                     | 5.20                                  | 0.822                                     | 3.29                                   | 2.29                      |
| Test 5                 | 1.29                                     | 5.16                                  | 0.819                                     | 3.28                                   | 2.28                      |
| Test 6                 | 1.30                                     | 5.20                                  | 0.826                                     | 3.30                                   | 2.28                      |
| Test 7                 | 1.31                                     | 5.24                                  | 0.826                                     | 3.30                                   | 2.30                      |
| Test 8                 | 1.31                                     | 5.24                                  | 0.829                                     | 3.32                                   | 2.30                      |
| Test 9                 | 1.30                                     | 5.20                                  | 0.822                                     | 3.29                                   | 2.28                      |
| Test 10                | 1.31                                     | 5.24                                  | 0.822                                     | 3.29                                   | 2.33                      |
| Average Value          | 1.30                                     | 5.21                                  | 0.823                                     | 3.29                                   | 2.29                      |

The results have been normalized to 1W (forward power) into the dipole.

IEEE Target over 1cm<sup>3</sup> (1g) of tissue: 1.23 mW/g (+/- 10%)

Averaged over 1cm (1g) of tissue: 5.21 mW/g

Averaged over 10cm (10g) of tissue: 3.29 mW/g

Test Date: 11/04/03

DUT: Dipole 450MHz; Model: D450V2; Type: System Performance Check; Serial: 136

Ambient Temp: 22.1°C; Fluid Temp: 22.0°C; Barometric Pressure: 102.8 kPa; Humidity: 49%

Communication System: CW

Forward Conducted Power: 250 mW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450 ( $\sigma = 0.88$  mho/m,  $\epsilon_r = 43.7$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 26/02/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 19/05/2003
- Phantom: Validation Planar; Type: Plexiglas; Serial: 137
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 116

**450 MHz Validation/Area Scan (6x11x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 39 V/m

Power Drift = -0.08 dB

Maximum value of SAR = 1.3 mW/g


**450 MHz Validation/Zoom Scan 8 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Peak SAR (extrapolated) = 2.28 W/kg

**SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.822 mW/g**

Reference Value = 39 V/m

Power Drift = 0.08 dB





# 450MHz System Validation

## Measured Fluid Dielectric Parameters (Brain)

November 04, 2003

| Frequency      | e'      | e''     |
|----------------|---------|---------|
| 350.000000 MHz | 46.2660 | 40.8224 |
| 360.000000 MHz | 45.9937 | 40.0986 |
| 370.000000 MHz | 45.7556 | 39.4543 |
| 380.000000 MHz | 45.5625 | 38.7387 |
| 390.000000 MHz | 45.2820 | 38.1140 |
| 400.000000 MHz | 45.0146 | 37.4981 |
| 410.000000 MHz | 44.7508 | 36.9734 |
| 420.000000 MHz | 44.5046 | 36.4917 |
| 430.000000 MHz | 44.2494 | 35.9460 |
| 440.000000 MHz | 43.9621 | 35.5647 |
| 450.000000 MHz | 43.7384 | 35.2106 |
| 460.000000 MHz | 43.5513 | 34.7930 |
| 470.000000 MHz | 43.2846 | 34.3970 |
| 480.000000 MHz | 43.0654 | 33.9576 |
| 490.000000 MHz | 42.8566 | 33.6391 |
| 500.000000 MHz | 42.6744 | 33.2270 |
| 510.000000 MHz | 42.5036 | 32.8459 |
| 520.000000 MHz | 42.3492 | 32.5261 |
| 530.000000 MHz | 42.1783 | 32.1727 |
| 540.000000 MHz | 41.9985 | 31.7385 |
| 550.000000 MHz | 41.8097 | 31.4862 |

## APPENDIX D - PROBE CALIBRATION

Client

Celltech Labs

## CALIBRATION CERTIFICATE

Object(s)

ET3DV6 - SN: 1387

Calibration procedure(s)

QA CAL-01.v2  
Calibration procedure for dosimetric E-field probes

Calibration date:

February 26, 2003

Condition of the calibrated item

In Tolerance (according to the specific calibration document)

This calibration statement documents traceability of M&TE used in the calibration procedures and conformity of the procedures with the ISO/IEC 17025 international standard.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

| Model Type                        | ID #         | Cal Date                         | Scheduled Calibration  |
|-----------------------------------|--------------|----------------------------------|------------------------|
| RF generator HP 8684C             | US3642U01700 | 4-Aug-99 (in house check Aug-02) | In house check: Aug-05 |
| Power sensor E4412A               | MY41495277   | 8-Mar-02                         | Mar-03                 |
| Power sensor HP 8481A             | MY41092180   | 18-Sep-02                        | Sep-03                 |
| Power meter EPM E4419B            | GB41293874   | 13-Sep-02                        | Sep-03                 |
| Network Analyzer HP 8753E         | US38432426   | 3-May-00                         | In house check: May 03 |
| Fluke Process Calibrator Type 702 | SN: 6295803  | 3-Sep-01                         | Sep-03                 |

Calibrated by:

Name

Nico Vetterli

Function

Technician


Signature



Approved by:

Katja Pokovic

Laboratory Director



Date issued: February 26, 2003

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

# Probe ET3DV6

## SN:1387

|                   |                    |
|-------------------|--------------------|
| Manufactured:     | September 21, 1999 |
| Last calibration: | February 22, 2002  |
| Recalibrated:     | February 26, 2003  |

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

## DASY - Parameters of Probe: ET3DV6 SN:1387

### Sensitivity in Free Space

|       |                                                 |
|-------|-------------------------------------------------|
| NormX | <b>1.55</b> $\mu\text{V}/(\text{V}/\text{m})^2$ |
| NormY | <b>1.65</b> $\mu\text{V}/(\text{V}/\text{m})^2$ |
| NormZ | <b>1.64</b> $\mu\text{V}/(\text{V}/\text{m})^2$ |

### Diode Compression

|       |           |    |
|-------|-----------|----|
| DCP X | <b>92</b> | mV |
| DCP Y | <b>92</b> | mV |
| DCP Z | <b>92</b> | mV |

### Sensitivity in Tissue Simulating Liquid

|         |                              |                             |                                       |
|---------|------------------------------|-----------------------------|---------------------------------------|
| Head    | <b>900 MHz</b>               | $\epsilon_r = 41.5 \pm 5\%$ | $\sigma = 0.97 \pm 5\% \text{ mho/m}$ |
| Head    | <b>835 MHz</b>               | $\epsilon_r = 41.5 \pm 5\%$ | $\sigma = 0.90 \pm 5\% \text{ mho/m}$ |
| ConvF X | <b>6.6</b> $\pm 9.5\%$ (k=2) | Boundary effect:            |                                       |
| ConvF Y | <b>6.6</b> $\pm 9.5\%$ (k=2) | Alpha                       | <b>0.37</b>                           |
| ConvF Z | <b>6.6</b> $\pm 9.5\%$ (k=2) | Depth                       | <b>2.61</b>                           |
| Head    | <b>1800 MHz</b>              | $\epsilon_r = 40.0 \pm 5\%$ | $\sigma = 1.40 \pm 5\% \text{ mho/m}$ |
| Head    | <b>1900 MHz</b>              | $\epsilon_r = 40.0 \pm 5\%$ | $\sigma = 1.40 \pm 5\% \text{ mho/m}$ |
| ConvF X | <b>5.2</b> $\pm 9.5\%$ (k=2) | Boundary effect:            |                                       |
| ConvF Y | <b>5.2</b> $\pm 9.5\%$ (k=2) | Alpha                       | <b>0.50</b>                           |
| ConvF Z | <b>5.2</b> $\pm 9.5\%$ (k=2) | Depth                       | <b>2.73</b>                           |


### Boundary Effect

|                       |                              |                                   |             |
|-----------------------|------------------------------|-----------------------------------|-------------|
| Head                  | <b>900 MHz</b>               | Typical SAR gradient: 5 % per mm  |             |
| Probe Tip to Boundary |                              | <b>1 mm</b>                       | <b>2 mm</b> |
| SAR <sub>pe</sub> [%] | Without Correction Algorithm | 10.2                              | 5.9         |
| SAR <sub>pe</sub> [%] | With Correction Algorithm    | 0.4                               | 0.6         |
| Head                  | <b>1800 MHz</b>              | Typical SAR gradient: 10 % per mm |             |
| Probe Tip to Boundary |                              | <b>1 mm</b>                       | <b>2 mm</b> |
| SAR <sub>pe</sub> [%] | Without Correction Algorithm | 14.6                              | 9.8         |
| SAR <sub>pe</sub> [%] | With Correction Algorithm    | 0.2                               | 0.0         |


### Sensor Offset

|                            |                                 |    |
|----------------------------|---------------------------------|----|
| Probe Tip to Sensor Center | <b>2.7</b>                      | mm |
| Optical Surface Detection  | <b>1.4 <math>\pm</math> 0.2</b> | mm |




Receiving Pattern ( $\phi$ ),  $\theta = 0^\circ$ **f = 30 MHz, TEM cell ifi110**


—○— X —●— Y —●— Z —○— Tot

**f = 100 MHz, TEM cell ifi110**


—○— X —●— Y —●— Z —○— Tot

**f = 300 MHz, TEM cell ifi110**


—○— X —●— Y —●— Z —○— Tot

**f = 900 MHz, TEM cell ifi110**

—○— X —●— Y —●— Z —○— Tot




### Isotropy Error ( $\phi$ ), $\theta = 0^\circ$





## Frequency Response of E-Field


( TEM-Cell:ifi110, Waveguide R22)



# Dynamic Range f(SAR<sub>brain</sub>) ( Waveguide R22 )




## Conversion Factor Assessment




|      |          |                              |                                       |
|------|----------|------------------------------|---------------------------------------|
| Head | 900 MHz  | $\epsilon_r = 41.5 \pm 5\%$  | $\sigma = 0.97 \pm 5\% \text{ mho/m}$ |
| Head | 835 MHz  | $\epsilon_r = 41.5 \pm 5\%$  | $\sigma = 0.90 \pm 5\% \text{ mho/m}$ |
|      | ConvF X  | <b>6.6</b> $\pm 9.5\%$ (k=2) | Boundary effect:                      |
|      | ConvF Y  | <b>6.6</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.37</b>                     |
|      | ConvF Z  | <b>6.6</b> $\pm 9.5\%$ (k=2) | Depth <b>2.61</b>                     |
| Head | 1800 MHz | $\epsilon_r = 40.0 \pm 5\%$  | $\sigma = 1.40 \pm 5\% \text{ mho/m}$ |
| Head | 1900 MHz | $\epsilon_r = 40.0 \pm 5\%$  | $\sigma = 1.40 \pm 5\% \text{ mho/m}$ |
|      | ConvF X  | <b>5.2</b> $\pm 9.5\%$ (k=2) | Boundary effect:                      |
|      | ConvF Y  | <b>5.2</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.50</b>                     |
|      | ConvF Z  | <b>5.2</b> $\pm 9.5\%$ (k=2) | Depth <b>2.73</b>                     |

## Conversion Factor Assessment



|      |          |                              |                                       |
|------|----------|------------------------------|---------------------------------------|
| Body | 900 MHz  | $\epsilon_r = 55.0 \pm 5\%$  | $\sigma = 1.05 \pm 5\% \text{ mho/m}$ |
| Body | 835 MHz  | $\epsilon_r = 55.2 \pm 5\%$  | $\sigma = 0.97 \pm 5\% \text{ mho/m}$ |
|      | ConvF X  | <b>6.4</b> $\pm 9.5\%$ (k=2) | Boundary effect:                      |
|      | ConvF Y  | <b>6.4</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.45</b>                     |
|      | ConvF Z  | <b>6.4</b> $\pm 9.5\%$ (k=2) | Depth <b>2.35</b>                     |
| Body | 1800 MHz | $\epsilon_r = 53.3 \pm 5\%$  | $\sigma = 1.52 \pm 5\% \text{ mho/m}$ |
| Body | 1900 MHz | $\epsilon_r = 53.3 \pm 5\%$  | $\sigma = 1.52 \pm 5\% \text{ mho/m}$ |
|      | ConvF X  | <b>4.9</b> $\pm 9.5\%$ (k=2) | Boundary effect:                      |
|      | ConvF Y  | <b>4.9</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.60</b>                     |
|      | ConvF Z  | <b>4.9</b> $\pm 9.5\%$ (k=2) | Depth <b>2.59</b>                     |

## Conversion Factor Assessment



**Head      2450      MHz       $\epsilon_r = 39.2 \pm 5\%$        $\sigma = 1.80 \pm 5\%$  mho/m**

ConvF X      **5.0**  $\pm 8.9\%$  (k=2)

Boundary effect:

ConvF Y      **5.0**  $\pm 8.9\%$  (k=2)

Alpha      **1.04**

ConvF Z      **5.0**  $\pm 8.9\%$  (k=2)

Depth      **1.85**

**Body      2450      MHz       $\epsilon_r = 52.7 \pm 5\%$        $\sigma = 1.95 \pm 5\%$  mho/m**

ConvF X      **4.6**  $\pm 8.9\%$  (k=2)

Boundary effect:

ConvF Y      **4.6**  $\pm 8.9\%$  (k=2)


Alpha      **1.20**

ConvF Z      **4.6**  $\pm 8.9\%$  (k=2)

Depth      **1.60**

## Deviation from Isotropy in HSL

Error ( $\theta, \phi$ ),  $f = 900$  MHz





## Additional Conversion Factors for Dosimetric E-Field Probe

Type:

**ET3DV6**

Serial Number:

**1387**

Place of Assessment:

**Zurich**

Date of Assessment:


**February 28, 2003**

Probe Calibration Date:

**February 26, 2003**

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 900 MHz or at 1800 MHz.

Assessed by:



## Dosimetric E-Field Probe ET3DV6 SN:1387

Conversion factor ( $\pm$  standard deviation)

|         |       |               |                                                                       |
|---------|-------|---------------|-----------------------------------------------------------------------|
| 150 MHz | ConvF | $9.1 \pm 8\%$ | $\epsilon_r = 52.3$<br>$\sigma = 0.76 \text{ mho/m}$<br>(head tissue) |
| 300 MHz | ConvF | $7.9 \pm 8\%$ | $\epsilon_r = 45.3$<br>$\sigma = 0.87 \text{ mho/m}$<br>(head tissue) |
| 450 MHz | ConvF | $7.5 \pm 8\%$ | $\epsilon_r = 43.5$<br>$\sigma = 0.87 \text{ mho/m}$<br>(head tissue) |
| 150 MHz | ConvF | $8.8 \pm 8\%$ | $\epsilon_r = 61.9$<br>$\sigma = 0.80 \text{ mho/m}$<br>(body tissue) |
| 300 MHz | ConvF | $8.0 \pm 8\%$ | $\epsilon_r = 58.2$<br>$\sigma = 0.92 \text{ mho/m}$<br>(body tissue) |
| 450 MHz | ConvF | $7.7 \pm 8\%$ | $\epsilon_r = 56.7$<br>$\sigma = 0.94 \text{ mho/m}$<br>(body tissue) |

## APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS

# 450 MHz System Performance Check & DUT Evaluation (Face)

## Measured Fluid Dielectric Parameters (Brain)

January 12, 2004

| Frequency      | e'      | e''     |
|----------------|---------|---------|
| 350.000000 MHz | 46.8833 | 41.1822 |
| 360.000000 MHz | 46.6829 | 40.4934 |
| 370.000000 MHz | 46.5548 | 39.8537 |
| 380.000000 MHz | 46.4548 | 39.2972 |
| 390.000000 MHz | 46.1992 | 38.8222 |
| 400.000000 MHz | 45.7239 | 38.3405 |
| 410.000000 MHz | 45.4139 | 37.7172 |
| 420.000000 MHz | 45.1125 | 37.2033 |
| 430.000000 MHz | 44.8457 | 36.6404 |
| 440.000000 MHz | 44.6187 | 36.1453 |
| 450.000000 MHz | 44.3511 | 35.7544 |
| 460.000000 MHz | 44.1648 | 35.3406 |
| 470.000000 MHz | 43.9987 | 35.0047 |
| 480.000000 MHz | 43.8447 | 34.6986 |
| 490.000000 MHz | 43.5069 | 34.2966 |
| 500.000000 MHz | 43.2780 | 33.8595 |
| 510.000000 MHz | 43.0345 | 33.3922 |
| 520.000000 MHz | 42.8825 | 33.0263 |
| 530.000000 MHz | 42.7320 | 32.6414 |
| 540.000000 MHz | 42.5632 | 32.2180 |
| 550.000000 MHz | 42.3999 | 31.9265 |

# 450 MHz DUT Evaluation (Body)


## Measured Fluid Dielectric Parameters (Muscle)

January 12, 2004

| Frequency      | e'      | e''     |
|----------------|---------|---------|
| 350.000000 MHz | 58.9798 | 43.4844 |
| 360.000000 MHz | 58.7030 | 42.7060 |
| 370.000000 MHz | 58.5375 | 41.9721 |
| 380.000000 MHz | 58.3557 | 41.2991 |
| 390.000000 MHz | 58.2456 | 40.5582 |
| 400.000000 MHz | 58.1104 | 39.8978 |
| 410.000000 MHz | 57.9321 | 39.3166 |
| 420.000000 MHz | 57.7663 | 38.6567 |
| 430.000000 MHz | 57.5473 | 38.0555 |
| 440.000000 MHz | 57.4121 | 37.5907 |
| 450.000000 MHz | 57.1941 | 37.1136 |
| 460.000000 MHz | 57.0500 | 36.6787 |
| 470.000000 MHz | 56.8956 | 36.2537 |
| 480.000000 MHz | 56.6869 | 35.7572 |
| 490.000000 MHz | 56.6032 | 35.3948 |
| 500.000000 MHz | 56.4448 | 34.9917 |
| 510.000000 MHz | 56.2751 | 34.5887 |
| 520.000000 MHz | 56.1179 | 34.2142 |
| 530.000000 MHz | 55.9763 | 33.8823 |
| 540.000000 MHz | 55.9071 | 33.4548 |
| 550.000000 MHz | 55.7736 | 33.1522 |



## APPENDIX F - SAR TEST SETUP & DUT PHOTOGRAPHS

**FACE-HELD SAR TEST SETUP PHOTOGRAPHS**  
2.5 cm Separation Distance from Front of Radio to Planar Phantom  
with Whip Antenna (P/N: ATU-5F)






**FACE-HELD SAR TEST SETUP PHOTOGRAPHS**  
2.5 cm Separation Distance from Front of Radio to Planar Phantom  
with Whip Antenna (P/N: ATU-5D)






**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**  
1.0 cm Belt-Clip Separation Distance to Planar Phantom  
with Whip Antenna (P/N: ATU-5F) & Speaker-Microphone (P/N: MH-50)



**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**  
1.0 cm Belt-Clip Separation Distance to Planar Phantom  
with Whip Antenna (P/N: ATU-5D) & Speaker-Microphone (P/N: MH-50)



## DUT PHOTOGRAPHS



with Whip Antenna  
(P/N: ATU-5D)



with Whip Antenna  
(P/N: ATU-5F)



with Whip Antenna  
(P/N: ATU-5D)



with Whip Antenna  
(P/N: ATU-5F)



## DUT PHOTOGRAPHS



Front of DUT



Back of DUT



Back of DUT with Belt-Clip



Top End of DUT



Bottom End of DUT

## DUT PHOTOGRAPHS



Left Side of DUT with Belt-Clip



Right Side of DUT with Belt-Clip



Belt-Clip Accessory



## DUT PHOTOGRAPHS



Radio with Battery Removed



NiCd Battery Pack



Whip Antenna (P/N: ATU-5D)



Whip Antenna (P/N: ATU-5F)

## DUT PHOTOGRAPHS



with Speaker-Microphone Accessory (P/N: MH-50)