

FCC Test Report

Product Name	IP COMMUNICATION TERMINAL
Model No	IP100H
FCC ID	AFJ357600

Applicant	ICOM Incorporated
Address	1-1-32 Kamiminami, Hirano-ku, Osaka, 547-0003

Date of Receipt	Dec. 26, 2013
Issued Date	Mar. 06, 2014
Report No.	1410008R-RFUSP05V00
Report Version	V1.0



The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by TAF or any agency of the U.S. Government.

Test Report Certification

Issued Date: Mar. 06, 2014

Report No.: 1410008R-RFUSP05V00



Product Name	IP COMMUNICATION TERMINAL
Applicant	ICOM Incorporated
Address	1-1-32 Kamiminami, Hirano-ku, Osaka, 547-0003
Manufacturer	ICOM Incorporated
Model No.	IP100H
FCC ID.	AFJ357600
EUT Rated Voltage	DC 7.4V by battery
EUT Test Voltage	AC 120V/60Hz
Trade Name	ICOM
Applicable Standard	FCC CFR Title 47 Part 15 Subpart E: 2012 ANSI C63.10: 2009, FCC KDB-789033
Test Result	Complied

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by TAF or any agency of the U.S. Government.

Documented By : Jinn Chen
(Senior Adm. Specialist / Jinn Chen)

Tested By : Jack Hsu
(Engineer / Jack Hsu)

Approved By : Vincent Lin
(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION.....	5
1.1. EUT Description.....	5
1.2. Operational Description	7
1.3. Tested System Details.....	8
1.4. Configuration of tested System	8
1.5. EUT Exercise Software	9
1.6. Test Facility	10
2. Conducted Emission.....	11
2.1. Test Equipment.....	11
2.2. Test Setup	11
2.3. Limits	12
2.4. Test Procedure	12
2.5. Uncertainty	12
2.6. Test Result of Conducted Emission.....	13
3. Maximum conducted output power	15
3.1. Test Equipment.....	15
3.2. Test Setup	15
3.3. Limits	16
3.4. Test Procedure	16
3.5. Uncertainty	16
3.6. Test Result of Maximum conducted output power.....	17
4. Peak Power Spectral Density.....	25
4.1. Test Equipment.....	25
4.2. Test Setup	25
4.3. Limits	25
4.4. Test Procedure	26
4.5. Uncertainty	26
4.6. Test Result of Peak Power Spectral Density	27

5.	Peak Excursion	33
5.1.	Test Equipment.....	33
5.2.	Test Setup	33
5.3.	Limits	33
5.4.	Test Procedure	34
5.5.	Uncertainty	34
5.6.	Test Result of Peak Excursion.....	35
6.	Radiated Emission	44
6.1.	Test Equipment.....	44
6.2.	Test Setup	44
6.3.	Limits	45
6.4.	Test Procedure	46
6.5.	Uncertainty	46
6.6.	Test Result of Radiated Emission.....	47
7.	Band Edge	69
7.1.	Test Equipment.....	69
7.2.	Test Setup	69
7.3.	Limits	70
7.4.	Test Procedure	70
7.5.	Uncertainty	71
7.6.	Test Result of Band Edge	72
8.	Frequency Stability.....	87
8.1.	Test Equipment.....	87
8.2.	Test Setup	87
8.3.	Limits	87
8.4.	Test Procedure	87
8.5.	Uncertainty	87
8.6.	Test Result of Frequency Stability.....	88
9.	EMI Reduction Method During Compliance Testing	89

Attachment 1: EUT Test Photographs
Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	IP COMMUNICATION TERMINAL
Trade Name	ICOM
FCC ID.	AFJ357600
Model No.	IP100H
Frequency Range	802.11a/n-20MHz: 5180-5240MHz 802.11n-40MHz: 5190-5230MHz
Number of Channels	802.11a/n-20MHz: 4, n-40MHz: 2
Data Rate	802.11a/g: 6-54Mbps, 802.11n: up to 150Mbps
Channel Control	Auto
Type of Modulation	802.11a/n:OFDM, BPSK, QPSK, 16QAM, 64QAM
Antenna Type	Monopole / Dipole Antenna
Antenna Gain	Refer to the table "Antenna List"
Contain Module	TAIYO / WYSBMVGX4

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain	Remark
1	Exceltek	N/A	Dipole	2.0 dBi for 5.15~5.25GHz	External Antenna
2	TAIYO YUDEN	AH 104N2450D1	Monopole	2.4 dBi for 5.15~5.25GHz	Internal Antenna

Note: The antenna of EUT is conform to FCC 15.203

802.11a/n-20MHz Center Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 36:	5180 MHz	Channel 40:	5200 MHz	Channel 44:	5220 MHz	Channel 48:	5240 MHz

802.11n-40MHz Center Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency
Channel 38:	5190 MHz	Channel 46:	5230 MHz

Note:

1. This device is an IP COMMUNICATION TERMINAL with a built-in 2.4GHz and 5GHz Band WLAN transceiver this report for 5Ghz Band.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
4. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11a is 6Mbps, 802.11n-20BW is 7.2Mbps and 802.11n-40BW are 15Mbps)
5. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart E for Unlicensed National Information Infrastructure devices.

Test Mode	Mode 1: Transmit (802.11a-6Mbps) Mode 2: Transmit (802.11n-20BW 7.2Mbps) Mode 3: Transmit (802.11n-40BW 15Mbps)
-----------	---


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	PPT	N/A	Non-Shielded, 1.8m
2	USB Cloning Cable	iCOM	OPC-478UC	N/A	N/A
3	Adapter Cable	iCOM	OPC-2144	N/A	N/A
4	Microphone & Earphone	iCOM	HS-99	N/A	N/A
5	Charger	iCOM	BC-202	N/A	N/A

Signal Cable Type	Signal cable Description
A Mini USB to USB Cable	Non-Shielded, 1.5m, with one ferrite core bonded.
B USB Cloning Cable	Non-Shielded, 0.6m
C Adapter Cable	Non-Shielded, 0.225m
D Microphone & Earphone Cable	Non-Shielded, 1.2m

1.4. Configuration of tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4
- (2) Execute program “MFG_Tool V1.0.0.0” on the Notebook PC.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Start transmits continually.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site: <http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site: <http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195

Site Name: Quietek Corporation
Site Address: No.5-22, Ruishukeng,
Linkou Dist. New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Conducted Emission


2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2013	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2014	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2014	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2014	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2014	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBUV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks : In the above table, the tighter limit applies at the band edges.

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10, 2009 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

The EUT was setup to ANSI C63.10, 2009; tested to DTS test procedure of FCC KDB-789033 for compliance to FCC 47CFR Subpart E requirements.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

Product : IP COMMUNICATION TERMINAL
Test Item : Conducted Emission Test
Power Line : Line 1
Test Mode : Mode 3: Transmit (802.11n-40BW 15Mbps) (5190MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV	dB	dBuV
LINE 1					
Quasi-Peak					
0.189	9.558	36.550	46.108	-18.778	64.886
0.259	9.581	29.900	39.481	-23.405	62.886
0.388	9.587	25.280	34.867	-24.333	59.200
0.615	9.598	16.400	25.998	-30.002	56.000
5.373	9.770	17.830	27.600	-32.400	60.000
14.521	10.140	23.310	33.450	-26.550	60.000
Average					
0.189	9.558	18.880	28.438	-26.448	54.886
0.259	9.581	13.770	23.351	-29.535	52.886
0.388	9.587	20.190	29.777	-19.423	49.200
0.615	9.598	9.680	19.278	-26.722	46.000
5.373	9.770	11.890	21.660	-28.340	50.000
14.521	10.140	19.880	30.020	-19.980	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : IP COMMUNICATION TERMINAL
 Test Item : Conducted Emission Test
 Power Line : Line 2
 Test Mode : Mode 3: Transmit (802.11n-40BW 15Mbps) (5190MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV	dB	dBuV
LINE 2					
Quasi-Peak					
0.177	9.588	36.550	46.138	-19.091	65.229
0.209	9.589	28.280	37.869	-26.445	64.314
0.287	9.603	21.770	31.373	-30.713	62.086
0.361	9.599	20.280	29.879	-30.092	59.971
5.240	9.800	24.080	33.880	-26.120	60.000
14.713	10.213	24.830	35.043	-24.957	60.000
Average					
0.177	9.588	9.770	19.358	-35.871	55.229
0.209	9.589	18.820	28.409	-25.905	54.314
0.287	9.603	3.070	12.673	-39.413	52.086
0.361	9.599	15.660	25.259	-24.712	49.971
5.240	9.800	17.240	27.040	-22.960	50.000
14.713	10.213	21.670	31.883	-18.117	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

3. Maximun conducted output power

3.1. Test Equipment


	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Power Meter	Anritsu	ML2495A/6K00003357	May, 2013
X	Power Sensor	Anritsu	MA2411B/0738448	Jun., 2013
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2013

Note:


1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

3.2. Test Setup

26dBc Occupied Bandwidth



Conduction Power Measurement



3.3. Limits

- (1) For the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $4 \text{ dBm} + 10\log B$, where B is the 26-dB emission bandwidth in MHz. If transmitting antenna of directional gain greater than 6 dBi are used, the Maximum conducted output power shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.
- (2) For the band 5.25-5.35 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10\log B$, where B is the 26-dB emission bandwidth in MHz. If transmitting antenna of directional gain greater than 6 dBi are used, the Maximum conducted output power shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.
- (3) For the band 5.725-5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1W or $17 \text{ dBm} + 10\log B$, where B is the 26-dB emission bandwidth in MHz. If transmitting antenna of directional gain greater than 6 dBi are used, the Maximum conducted output power shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.

3.4. Test Procedure

As an alternative to FCC KDB-789033, the EUT maximum conducted output power was measured with an average power meter employing a video bandwidth greater than 6dB BW of the emission under test. Maximum conducted output power was read directly from the meter across all data rates, and across three channels within each sub-band. Special care was used to make sure that the EUT was transmitting in continuous mode. This method exceeds the limitations of FCC KDB-789033, and provides more accurate measurements.

The Maximum conducted output power using KDB 789033 section E)3)b) Method PM-G (Measurement using a gated RF average power meter).

3.5. Uncertainty

$\pm 1.27 \text{ dB}$

3.6. Test Result of Maximum conducted output power

Product : IP COMMUNICATION TERMINAL
Test Item : Maximum conducted output power
Test Site : No.3 OATS
Test Mode : Mode 1: Transmit (802.11a-6Mbps)

Cable loss=1dB		Maximum conducted output power								
Channel No.	Frequency (MHz)	Data Rate (Mbps)								Required Limit
		6	9	12	18	24	36	48	54	
		Measurement Level (dBm)								
36	5180	9.54	--	--	--	--	--	--	--	<17dBm
44	5220	9.68	9.5	9.44	9.38	9.33	9.27	9.21	9.19	<17dBm
48	5240	9.51	--	--	--	--	--	--	--	<17dBm

Note: Maximum conducted output power Value =Reading value on average power meter + cable loss


Maximum conducted output power Measurement:

Channel Number	Frequency (MHz)	26dB Bandwidth (MHz)	Output Power (dBm)	Output Power Limit	
				(dBm)	dBm+10log(BW)
36	5180	19.8	9.54	17	16.97
44	5220	19.9	9.68	17	16.99
48	5240	19.8	9.51	17	16.97


Note: Power Output Value =Reading value on average power meter + cable loss

26dBc Occupied Bandwidth:


Channel 36



Channel 40



Channel 48



Product : IP COMMUNICATION TERMINAL
Test Item : Maximum conducted output power
Test Site : No.3 OATS
Test Mode : Mode 2: Transmit (802.11n-20BW 7.2Mbps)

Cable loss=1dB		Maximum conducted output power								
Channel No.	Frequency (MHz)	Data Rate (Mbps)								Required Limit
		7.2	14.4	21.7	28.9	43.3	57.8	65	72.2	
		Measurement Level (dBm)								
36	5180	8.16	--	--	--	--	--	--	--	<17dBm
44	5220	8.35	8.27	8.22	8.18	8.14	8.08	8.02	7.98	<17dBm
48	5240	8.80	--	--	--	--	--	--	--	<17dBm


Note: Maximum conducted output power Value =Reading value on average power meter + cable loss

Maximum conducted output power Measurement:


Channel Number	Frequency (MHz)	26dB Bandwidth (MHz)	Output Power (dBm)	Output Power Limit	
				(dBm)	dBm+10log(BW)
36	5180	20.15	8.16	17	17.04
44	5220	20.20	8.35	17	17.05
48	5240	20.25	8.80	17	17.06

Note: Power Output Value =Reading value on average power meter + cable loss


26dBc Occupied Bandwidth: Channel 36



Channel 44



Channel 48



Product : IP COMMUNICATION TERMINAL
Test Item : Maximum conducted output power
Test Site : No.3 OATS
Test Mode : Mode 3: Transmit (802.11n-40BW 15Mbps)

Cable loss=1dB		Maximum conducted output power								
Channel No.	Frequency (MHz)	Data Rate (Mbps)								Required Limit
		15	30	45	60	90	120	135	150	
		Measurement Level (dBm)								
38	5190	8.42	8.31	8.25	8.19	8.15	8.11	8.08	8.01	<17dBm
46	5230	8.56	--	--	--	--	--	--	--	<17dBm


Note: Maximum conducted output power Value =Reading value on average power meter + cable loss

Maximum conducted output power Measurement:


Channel Number	Frequency (MHz)	26dB Bandwidth (MHz)	Output Power (dBm)	Output Power Limit	
				(dBm)	dBm+10log(BW)
38	5190	41	8.42	17	20.13
46	5230	41.2	8.56	17	20.15

Note: Power Output Value =Reading value on average power meter + cable loss

26dBc Occupied Bandwidth: Channel 38



Channel 46



4. Peak Power Spectral Density


4.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2013
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2013
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2013

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

4.2. Test Setup



4.3. Limits

- (4) For the band 5.15-5.25 GHz, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antenna of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.
- (5) For the band 5.25-5.35 GHz, the peak power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antenna of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.
- (6) For the band 5.725-5.825 GHz, the peak power spectral density shall not exceed 17 dBm in any 1-MHz band. If transmitting antenna of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.

4.4. Test Procedure

The EUT was setup to ANSI C63.10, 2009; tested to DTS test procedure of FCC KDB-789033 for compliance to FCC 47CFR Subpart E requirements.

The Peak Power Spectral Density using KDB 789033 section F) procedure, Create an average power spectrum for the EUT operating mode being tested by following the instructions in section E)2) for measuring maximum conducted output power using a spectrum analyzer.

SA-1 method is selected to run the test.

4.5. Uncertainty


± 1.27 dB

4.6. Test Result of Peak Power Spectral Density


Product : IP COMMUNICATION TERMINAL
 Test Item : Peak Power Spectral Density
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11a-6Mbps)

Channel Number	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
36	5180	-1.940	<4	Pass
44	5220	-2.240	<4	Pass
48	5240	-1.760	<4	Pass


Channel 36:



Channel 44:




Channel 48:




Product : IP COMMUNICATION TERMINAL
 Test Item : Peak Power Spectral Density
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11n-20BW 7.2Mbps)

Channel Number	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
36	5180	-4.110	<4	Pass
44	5220	-3.400	<4	Pass
48	5240	-2.960	<4	Pass


Channel 36



Channel 44




Channel 48




Product : IP COMMUNICATION TERMINAL
 Test Item : Peak Power Spectral Density
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit (802.11n-40BW 15Mbps)

Channel Number	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
38	5190	-6.220	<4	Pass
46	5230	-6.040	<4	Pass

Channel 38



Channel 46



5. Peak Excursion

5.1. Test Equipment


	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2013
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2013
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2013

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

5.2. Test Setup

Conduction Power Measurement



5.3. Limits

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the peak transmit power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

5.4. Test Procedure

The EUT was setup to ANSI C63.10, 2009; tested to DTS test procedure of FCC KDB-789033 for compliance to FCC 47CFR Subpart E requirements.

Step 1: Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth.

Step 2: Find the maximum of the peak-max-hold spectrum.

(Set RBW = 1 MHz, VBW $\geq$ 3 MHz, Detector = peak, Trace mode = max-hold,

Allow the sweeps to continue until the trace stabilizes, Use the peak search function to find the peak of the spectrum.)

Step 3: Use the procedure found under KDB-789033 F) to measure the PPSD.

Step 4: Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD.

5.5. Uncertainty


± 1.27 dB



5.6. Test Result of Peak Excursion


Product : IP COMMUNICATION TERMINAL
 Test Item : Peak Excursion
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11a-6Mbps)

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Measurement Level (dB)	Required Limit (dB)	Result
36	5180	6	7.650	<13	Pass
		12	7.620	<13	Pass
		24	7.710	<13	Pass
		54	7.520	<13	Pass

Channel 44:







Product : IP COMMUNICATION TERMINAL
 Test Item : Peak Excursion
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11n-20BW 7.2Mbps)

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Measurement Level (dB)	Required Limit (dB)	Result
36	5180	MCS (0)	7.630	<13	Pass
		MCS (2)	7.560	<13	Pass
		MCS (4)	7.590	<13	Pass
		MCS (7)	7.680	<13	Pass

Channel 44:

