




Report No.: CQASZ20250300543E-02



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



5.7 Radiated Spurious Emission & Restricted bands

5.7.1 Spurious Emiss	ions									
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205									
Test Method:	ANSI C63.10 2013									
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)									
Receiver Setup:	Frequency		Detector	RBW		VBW	Remark			
	0.009MHz-0.090MH	z	Peak	10kHz	z	30kHz	Peak			
	0.009MHz-0.090MH	z	Average	10kHz	z	30kHz	Average			
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	z	30kHz	Quasi-peak			
	0.110MHz-0.490MH	z	Peak	10kHz	z	30kHz	Peak			
	0.110MHz-0.490MH	Z	Average	10kHz	z	30kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	z	30kHz	Quasi-peak			
	30MHz-1GHz		Quasi-peak	100 kH	lz	300kHz	Quasi-peak			
	Above 1GHz		Peak	1MHz	-	3MHz	Peak			
			Peak	1MHz	<u>-</u>	10Hz	Average			
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	F	Remark	Measuremen distance (m			
	0.009MHz-0.490MHz	2	400/F(kHz)	-		-	300			
	0.490MHz-1.705MHz	24	1000/F(kHz)	-		-	30			
	1.705MHz-30MHz		30	-		-	30			
	30MHz-88MHz		100	40.0	40.0 Quasi-peak		3			
	88MHz-216MHz		150	43.5	Qu	ıasi-peak	3			
	216MHz-960MHz		200	46.0	Qu	ıasi-peak	3			
	960MHz-1GHz		500	54.0	Qu	ıasi-peak	3			
	Above 1GHz		500	54.0	A	verage	3			
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.									









Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz

Figure 3. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

Note: For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both




	horizontal and vertical polarizations of the antenna are set to make the measurement.
	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
	e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
	 f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz)
	h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
	i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation. Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of data type and GFSK modulation is the worst case.
	For below 1GHz part, through pre-scan, the worst case is the highest channel.
	Only the worst case is recorded in the report.
Test Results:	Pass






Radiated Emission below 1GHz







30MHz~1GHz, the worst case		
Test mode:	Transmitting mode	Vertical





Report No.: CQASZ20250300543E-02

Transmitter Emission above 1GHz

Worse case	mode:	GFSK(1	Mbps)	Test chann	nel:	Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	.,,,,,	H/V	(m)	(Degree)
2390	54.80	-9.2	45.60	74	-28.40	Peak	Н	1.5	339
2400	55.27	-9.39	45.88	74	-28.12	Peak	Η	1.5	318
4804	53.04	-4.33	48.71	74	-25.29	Peak	Н	1.5	164
7206	50.01	1.01	51.02	74	-22.98	Peak	Н	1.5	284
2390	53.40	-9.2	44.20	74	-29.80	Peak	٧	1.5	138
2400	50.88	-9.39	41.49	74	-32.51	Peak	V	1.5	54
4804	52.64	-4.33	48.31	74	-25.69	Peak	V	1.5	234
7206	51.09	1.01	52.10	74	-21.90	Peak	٧	1.5	208

Worse case	mode:	GFSK(1	Mbps)	Test chann	nel:	I: Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V	(m)	(Degree)
4880	50.24	-4.11	46.13	74	-27.87	peak	Н	1.5	42
7320	48.89	1.51	50.40	74	-23.60	peak	Η	1.5	14
4880	52.01	-4.11	47.90	74	-26.10	peak	٧	1.5	245
7320	48.96	1.51	50.47	74	-23.53	peak	V	1.5	108

Worse case	mode:	GFSK(1	Mbps)	Test channel:		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V	(m)	(Degree)		
2483.5	54.82	-9.29	45.53	74	-28.47	Peak	Н	1.5	26		
4960	51.25	-4.04	47.21	74	-26.79	Peak	Н	1.5	286		
7440	49.40	1.57	50.97	74	-23.03	Peak	Н	1.5	260		
2483.5	57.22	-9.29	47.93	74	-26.07	Peak	٧	1.5	265		
4960	49.92	-4.04	45.88	74	-28.12	Peak	٧	1.5	147		
7440	51.11	1.57	52.68	74	-21.32	Peak	>	1.5	189		



Report No.: CQASZ20250300543E-02

Worse case	mode:	GFSK(2	Mbps)	Test chann	nel:	Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V	(m)	(Degree)
2390	55.54	-9.2	46.34	74	-27.66	Peak	H	1.5	288
2400	57.11	-9.39	47.72	74	-26.28	Peak	Н	1.5	151
4804	52.51	-4.33	48.18	74	-25.82	Peak	Н	1.5	221
7206	50.35	1.01	51.36	74	-22.64	Peak	Η	1.5	13
2390	52.37	-9.2	43.17	74	-30.83	Peak	٧	1.5	169
2400	52.13	-9.39	42.74	74	-31.26	Peak	>	1.5	105
4804	54.59	-4.33	50.26	74	-23.74	Peak	٧	1.5	166
7206	50.46	1.01	51.47	74	-22.53	Peak	V	1.5	360

Worse case	mode:	GFSK(2	GFSK(2Mbps) Test char		nel: Middle				
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V	(m)	(Degree)
4880	50.34	-4.11	46.23	74	-27.77	peak	Н	1.5	100
7320	48.59	1.51	50.10	74	-23.90	peak	Η	1.5	183
4880	52.23	-4.11	48.12	74	-25.88	peak	٧	1.5	150
7320	50.91	1.51	52.42	74	-21.58	peak	V	1.5	39

Worse case	mode:	GFSK(2	Mbps)	Test chann	nel:	Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		H/V	(m)	(Degree)
2483.5	54.41	-9.29	45.12	74	-28.88	Peak	Н	1.5	227
4960	50.96	-4.04	46.92	74	-27.08	Peak	Н	1.5	298
7440	49.40	1.57	50.97	74	-23.03	Peak	Н	1.5	303
2483.5	57.87	-9.29	48.58	74	-25.42	Peak	٧	1.5	286
4960	49.60	-4.04	45.56	74	-28.44	Peak	٧	1.5	53
7440	48.36	1.57	49.93	74	-24.07	Peak	V	1.5	112


Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

















7 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details OF EUT for Photographs of The EUT.

*** END OF REPORT ***