

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5839US-1

Date : ____July, 10, 2003____ Tested by : ____Greg_Barbato____ Approved by : _Ken_Addy_____

Test Sample (model) : ____5839US-1_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	76.14	1.2	17.91	57876.2	12.5%	7234.5	7292
690	H	36.00	2	22.81	1097.7	12.5%	137.2	729
1035	H	34.17	2.6	25.69	1327.4	12.5%	165.9	500
1380	H	32.50	3	25.51	1123.3	12.5%	140.4	500
1725	H	34.50	3.5	26.25	1631.2	12.5%	203.9	729
2070	H	25.00	3.9	28.31	725.3	12.5%	90.7	729
2415	H	25.00	4.3	28.57	782.5	12.5%	97.8	729
2760	H	23.00	4.7	29.52	726.1	12.5%	90.8	729
3105	H	22.00	4.9	30.83	770.0	12.5%	96.3	729
3405	H	22.00	5.1	32.4	944.1	12.5%	118.0	729
4000								