



TEST REPORT

No. I14Z47312-EMC01

for

TCT Mobile Limited

HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone

Model Name: 4037A

FCC ID: RAD510

with

Hardware Version: PIO

Software Version: v9H2N

Issued Date: Jul. 18th, 2014

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel: +86(0)10-62304633-2561, Fax: +86(0)10-62304633-2504 Email:welcome@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS.....	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS	11

1. Test Laboratory

1.1. Testing Location

Location A

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan Bei Road, Haidian District, Beijing, P.R. China
Postal Code: 100191

1.2. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: Jul. 9th, 2014
Testing End Date: Jul. 17th, 2014

1.4. Signature



Qu Pengfei
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name:	TCT Mobile Limited
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China.
City:	Shanghai
Postal Code:	201203
Country:	China
Contact Person:	Gong Zhizhou
Contact Email	zhizhou.gong@jrdcom.com
Telephone:	0086-21-61460890
Fax:	0086-21-61460602

2.2. Manufacturer Information

Company Name:	TCT Mobile Limited
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China.
City:	Shanghai
Postal Code:	201203
Country:	China
Telephone:	0086-21-61460890
Fax:	0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone
Model Name	4037A
FCC ID	RAD510
Extreme vol. Limits	3.4VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	014104000200026	PIO	v9H2N

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	TCT-B-2302
AE2	USB cable	/	TCT-DC-0670
AE3	USB cable	/	TCT-DC-0653
AE4	USB cable	/	/
AE5	USB cable	/	/
AE6	USB cable	/	/
AE7	Travel charger	/	TCT-CHR-1390

AE1

Model	CAB60B0004C1 (TLi014A1)
Manufacturer	BYD
Capacitance	1400 mAh
Nominal voltage	3.7V

AE2、AE3

Model	CDA3122002C1
Manufacturer	JUWEI
Length of cable	96.5cm

AE4

Model	CDA3122002C2
Manufacturer	Shenhua
Length of cable	/

AE5

Model	CDA3122005C2
Manufacturer	Shenhua
Length of cable	/

AE6

Model	CDA3122005C1
Manufacturer	JUWEI
Length of cable	/

AE7

Model	CBA3007AG3C1
Manufacturer	BYD
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1 + AE2 + AE7	Charger
Set.2	EUT1+ AE1 + AE2	USB

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	10-1-13 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low - Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2009

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail
Location Column	A/B/C/D	The test is performed in test location A, B, C or D which are described in section 1.1 of this report

Clause	List	Clause in FCC rules	Verdict	Location
1	Radiated Emission	15.109(a)	P	A
2	Conducted Emission	15.107(a)	P	A

7. Test Equipments Utilized

NO.	Description	TYPE	SERIESNUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1.	Test Receiver	ESCI 7	100948	R&S	2014-07-18	1 year
2.	Spectrum Analyzer	FSV	101047	R&S	2015-07-03	1 year
3.	Universal Radio Communication Tester	CMU200	109914	R&S	2015-04-13	1 year
4.	LISN	ESH2-Z5	829991/012	R&S	2015-04-14	1 year
5.	EMI Antenna	VULB 9163	9163-234	Schwarzbeck	2016-09-15	3 years
6.	EMI Antenna	3115	6914	ETS-Lindgren	2014-12-16	3 years
7.	Test Receiver	ESCI	100344	R&S	2015-03-03	1 year
8.	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
9.	Monitor	E178FPc	CN-OWR979-64 180-7AJ-D2MS	DELL	N/A	N/A
10.	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
11.	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A	N/A
12.	Mouse	M-UAE119	LZ935220ZRC	Lenovo	N/A	N/A

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 - 2009, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Limit from CFR Part 15.109(a)

Frequency range (MHz)	Field strength limit ($\mu\text{V/m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): $U = 4.3 \text{ dB}$, $k=2$.

Measurement results for Set.1:

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17887.906	62.0	-18.5	45.6	34.900	Vertical
17956.438	61.7	-17.7	45.6	33.800	Vertical
17899.594	61.7	-18.5	45.6	34.600	Vertical
17888.438	61.4	-18.5	45.6	34.300	Vertical
17875.156	61.3	-18.5	45.6	34.200	Vertical
17877.813	61.3	-18.5	45.6	34.200	Vertical

Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17874.625	49.8	-18.5	45.6	22.700	Horizontal
17886.844	49.8	-18.5	45.6	22.700	Vertical
17875.156	49.7	-18.5	45.6	22.600	Vertical
17908.625	49.7	-18.5	45.6	22.600	Vertical
17890.563	49.6	-18.5	45.6	22.500	Vertical
17888.438	49.6	-18.5	45.6	22.500	Vertical

Measurement results for Set.2:

USB Mode/ Peak detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17858.156	61.6	-18.5	45.6	34.500	Vertical
17861.344	61.5	-18.5	45.6	34.400	Vertical
17849.125	61.4	-18.5	45.6	34.300	Vertical
17876.750	61.3	-18.5	45.6	34.200	Vertical
17885.781	61.2	-18.5	45.6	34.100	Horizontal
17890.031	61.1	-18.5	45.6	34.000	Vertical

USB Mode/ Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17888.969	49.9	-18.5	45.6	22.800	Vertical
17896.938	49.9	-18.5	45.6	22.800	Vertical
17901.188	49.8	-18.5	45.6	22.700	Vertical
17875.156	49.8	-18.5	45.6	22.700	Vertical
17887.906	49.8	-18.5	45.6	22.700	Horizontal
17891.094	49.7	-18.5	45.6	22.600	Vertical

Charging Mode, Set.1




Figure A.1 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
31.636250	18.8	100.0	H	-30.0	-19.3	11.2	30.0




Figure A.2 Radiated Emission from 1GHz to 18GHz

USB Mode, Set.2




Figure A.3 Radiated Emission from 30MHz to 1GHz




Figure A.4 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission (§15.107(a))

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2009, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U = 2.9 \text{ dB}$, $k=2$.

Charging Mode, Set.1




Figure A.5 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	55.7	GND	L1	9.8	9.8	65.5
0.199500	52.5	GND	L1	9.8	11.2	63.6
0.244500	48.8	GND	L1	9.8	13.2	61.9
0.276000	45.0	GND	L1	9.8	15.9	60.9
0.352500	33.4	GND	L1	9.8	25.5	58.9
2.706000	40.2	GND	L1	9.7	15.8	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	41.9	GND	L1	9.8	13.6	55.5
0.199500	38.8	GND	L1	9.8	14.9	53.6
0.240000	36.8	GND	L1	9.8	15.3	52.1
0.280500	35.6	GND	L1	9.8	15.2	50.8
0.357000	29.4	GND	N	9.8	19.4	48.8
2.818500	28.9	GND	L1	9.7	17.1	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

USB Mode, Set.2




Figure A.6 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.213000	46.8	GND	L1	9.8	16.3	63.1
0.280500	41.6	GND	L1	9.8	19.2	60.8
0.424500	39.4	GND	N	9.8	17.9	57.4
0.564000	42.7	GND	N	9.8	13.3	56.0
0.987000	35.7	GND	L1	9.7	20.3	56.0
2.116500	34.0	GND	L1	9.7	22.0	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.177000	45.4	GND	L1	9.8	9.2	54.6
0.213000	43.7	GND	L1	9.8	9.4	53.1
0.276000	37.1	GND	L1	9.8	13.8	50.9
0.316500	35.4	GND	L1	9.8	14.4	49.8
0.559500	35.4	GND	N	9.8	10.6	46.0
18.298500	38.4	GND	L1	9.4	11.6	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

END OF REPORT