

SPECIFICATION

SHEET FOR APPROVAL

(Revision: R: A0)

	CUSTOMER(客户名称)	群创光电	
	CS P/N(客户机种)	D40F-J09	T40F
	PART NAME(品名)	WIFI-1 antenna	L=190mm
	FREQUENCY(频率)	2.4G~2.5G/5.15G~5.85G	
	ZTX NO.(物料编号)	2.00005686	
	DATE(日期)	2022-07-14	

ZHONG TIAN XUN TECHNOLOGY CO., LTD				
MANAGER CHECKED	MANAGER CHECKED	ME CHECKED	RF CHECKED	LISTER
		韦英俊	韦进	



深圳市中天迅通信技术有限公司

SHENZHEN ZHONGTIAN XUN Communication Technology Co., Ltd.

地址: 深圳市宝安区石岩镇石龙大道 34 号(腾达工业园) 邮编: 518000

电话: 0755-27588320 传真: 0755-27588045 <http://www.chinaztx.com>

Address: Tenada Industrial Park. Shilong Avenue. Shivan Town. Baoan District. Shenzhen

ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022

Rev: R:A0

ZTX P/N :D40F-J09 WIFI-1 antenna

Editor:

Page 1 of 14

Revision history

Version	Date	Status
A0	2022-07-14	first version



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 2 of 14

Index

		Revision history	1
		Index	2
1		Mechanical Specification	3
	1-1	Mechanical Specification (WIFI-1 天线)	3
2		Test equipment	4
3		Antenna test data	5
	3-1	VSWR	5
	3-2	Return loss plot	5
	3-3	Smith Chart	6
	3-4	No-source test data	6~7
	3-5	Environment treatment	7
	3-6	Directional drawing of horizontal plane of&3D radiation drawing	8~9
4		Environment Characteristic	10
5		The packing way	11
		attached sheet : UL report	12~14



ANTENNA SPECIFICATION


CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 3 of 14

1. Mechanical Specification

1-1 Mechanical Configuration (WIFI-1 天线)



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022




Rev: R:A0

ZTX P/N :D40F-J09 WIFI-1 antenna

Editor:

Page 4 of 14


2. Test equipment



Owned 6 microwave dark room, equipped 2 sets world leading France Satimo SG24 OTA certification test systems (one in SHENZHEN, another one in Shanghai), ETS OTA Standard test system, Blue test reverberation test system which is High repeatability, high accuracy and high resolution. It can quickly provide accurate test reports, fully meet the CITA standards.

Testing range:

Support active, passive testing of
GSM/CDMA/WCDMA/TD-
SCDMA/LTE/WIFI/WLAN/WiMax/BT
/GPS/MIMO/UWB within 0.4-6G.



ANTENNA SPECIFICATION


CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:


Rev: R:A0
Page 5 of 14

3.Antenna test data

3-1 VSWR



3-2 Return loss plot




ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 6 of 14

3-3 Smith Chart



3-4 No-source test data

Frequency	Efficiency		Peak Gain	Frequency	Efficiency		Peak Gain
Mhz	%	dB	dB	Mhz	%	dB	dB
2400	49.66	-3.04	4.21	5150	40.86	-3.89	3.88
2410	52.42	-2.81	4.56	5200	41.79	-3.79	4.05
2420	54.07	-2.67	4.77	5250	41.85	-3.78	4.16
2430	56.46	-2.48	4.88	5300	43.88	-3.58	4.44
2440	55.86	-2.53	4.92	5350	48.55	-3.14	5.24
2450	56.30	-2.49	4.93	5400	48.51	-3.14	5.36
2460	51.83	-2.85	4.57	5450	52.81	-2.77	5.48
2470	50.97	-2.93	4.35	5500	51.63	-2.87	5.25
2480	48.15	-3.17	4.17	5550	53.81	-2.69	5.35
2490	46.76	-3.30	4.23	5600	52.86	-2.77	5.33
2500	43.12	-3.65	3.94	5650	53.33	-2.73	5.28
				5700	53.68	-2.70	5.41
				5750	57.27	-2.42	5.90
				5800	57.36	-2.41	6.08
				5850	55.59	-2.55	5.99



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 7 of 14


	XY plane		ZY plane		ZX plane	
Frequeny [MHz]	Peak Gain [dBi]	Average Gain [dBi]	Peak Gain [dBi]	Average Gain [dBi]	Peak Gain [dBi]	Average Gain [dBi]
2400	-0.351	-4.406	1.732	-4.672	-0.324	-5.841
2450	-0.643	-3.125	2.218	-3.238	-0.098	-4.286
2500	-0.429	-2.691	2.084	-2.649	0.528	-4.661
5150	0.933	-5.235	0.773	-6.531	1.891	-6.178
5500	1.104	-5.702	0.542	-6.424	1.296	-6.339
5850	1.559	-4.271	0.601	-6.189	1.617	-5.604

3-5 Environment treatment


N/A

3-6 Directional drawing of horizontal plane of&3D radiation drawing

2400MHz



2450MHz




ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna


ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 8 of 14


2500MHz




5150MHz



5500MHz



5850MHz



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna


ApplicationDate:JUL,14,2022

Rev: R:A0

ZTX P/N :D40F-J09 WIFI-1 antenna

Editor:

Page 9 of 14



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 10 of 14

4.Environment Characteristic

NO.	ITEM	TEST CONDITION	SPECIFICATION
4-1	High Temperature/Humidity Storage Test(non operating)	1.Temperature: $+70 \pm 2^{\circ}\text{C}$ 2.Humidity: $90 \sim 95\% \text{RH}$ 3.Time: 48hrs	No material deformation is allowed.
4-2	Low Temperature/Humidity Storage Test(non operating)	1.Temperature: $-30 \pm 2^{\circ}\text{C}$ 2.Humidity: $0\% \text{RH}$ 3.Time:48hrs	The VSWR, Gain, Radiation Pattern must be met specifications after these test.



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 11 of 14

5.The packing way

深圳市中天迅通信股份有限公司

SHENZHEN ZHONGTIAN XUN Communication Technology Co., Ltd.

包装规范

产品名称	产品型号	文件编号	版本	工序序号/名称	工序工时	日产量		
WIFI天线	D40F-J09 (T40F)	ZTX-QD-WI	A1	包装/装箱	/	/		
    图1：确认数量/贴内标签 图2：装箱 图3：贴外箱标签/附出货检验报告 图4：封箱				作业方法（自检该工序作业合格后. 方能流入下一道工序			注意事项	
				1. 每40PCS用橡皮筋包扎装入（240*160mm）封口袋；每5袋（200PCS）产品用封口PE袋（230*330mm）包装/贴标签含（物料名称，物料编码，数量，日期）				
				2. 将包装好的产品装入箱内，箱底/面用纸板隔开；纸箱规格（45*32.5*21cm）每箱（2000pcs）尾数除外；				
				3. 贴外箱标签，贴于外箱的右上角，标签内容包含（生产厂家，型号，产品名称，客户编码，数量，订单号，日期，QA检验）；				
				4. 纸箱用胶纸以“工”字型封箱。				



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022

Rev: R:A0

ZTX P/N :D40F-J09 WIFI-1 antenna

Editor:

Page 12 of 14

attached sheet: UL report

UL Style Page

页码, 1/2

[Click here to go to UL's iQSM for Appliance Wiring Materials Database](#)

UNDERWRITERS LABORATORIES	APPLIANCE WIRING MATERIAL
Subj.758	Section 1 Page 1354
	Issued:1964-02-19
	Revised:2009-04-30
Style 1354	Coaxial Cable.

Rating	60, 80 deg C, 30 Vac, Horizontal flame.
--------	---

Conductor	44 AWG min., material not specified.
-----------	--------------------------------------

Insulation	2 mils minimum at any point, 125 mils maximum. The insulation may be: Extruded solid or cellular PE, FRPE, PP, PFA, FEP, ECTFE, PTFE, ETFE, or combination thereof with or without irradiation; or tape wrapped solid or cellular PTFE, PFA, or FEP. Applied as a spiral wrapped thread (5 mils minimum, 40 mils maximum) and enclosed in a tube of insulation.
------------	---

Assembly	Insulated conductor with optional inner covering, optional inner shield, optional middle covering, required outer shield and required outer covering.
----------	---

Shield	Optional. Outer Shield required.
--------	----------------------------------

Covering	Optional Inner Covering - Extruded PVC, PFA, Polyamide, Polyester, PVDF, FEP, PTFE, ECTFE, ETFE, PE, XLPE, XLFRPE or FRPE; lacquered braids; heat sealed PTFE, PFA or FEP tape; Polyester or Polyester-Polyethylene film. Thicknesses not specified. Optional Middle Covering - Extruded PVC, PFA, PP, Polyamide, Polyester, PVDF, FEP, PTFE, ECTFE, ETFE, PE, XLPE, XLFRPE or FRPE; lacquered braids; heat sealed PTFE, PFA or FEP tape; Polyester or Polyester-Polyethylene film. Thicknesses not specified. Required Outer Covering - Extruded Irradiated PE, Irradiated PVC, Polyurethane, PVC, PFA, PP, Polyamide, Polyester, PVDF, FEP, PTFE, ECTFE, ETFE, PE, XLPE, XLFRPE or FRPE; lacquered braids; heat sealed PTFE, PVC, PFA or FEP tape; Polyester or Polyester-Polyethylene film. Thicknesses not specified.
----------	---

<http://data.ul.com/link/stylepage.aspx?style=1354>

2010-7-1



深圳市中天迅通信技术股份有限公司
SHENZHEN ZHONGTIAN XUN Communication Technology Co., Ltd.

ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 antenna
ZTX P/N :D40F-J09 WIFI-1 antenna

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 13 of 14

UL Style Page

页码, 2/2

Standard	Appliance Wiring Material UL 758.
Marking	General.
Use	Internal wiring of Class 2 circuits of electronic equipment or as insulated single in jacketed multiconductor cables.



ANTENNA SPECIFICATION

CUS P/N :D40F-J09 WIFI-1 天线
ZTX P/N :D40F-J09 WIFI-1 天线

ApplicationDate:JUL,14,2022
Editor:

Rev: R:A0
Page 14 of 14

AVLV2.E318898 - Appliance Wiring Material - Component | UL Product iQ

2020/6/23 上午10:05

UL Product iQ™



AVLV2.E318898 - Appliance Wiring Material - Component Appliance Wiring Material - Component

See General Information for Appliance Wiring Material - Component

SHENYU COMMUNICATION TECHNOLOGY INC
275 E Waihuan Rd
Jiangyin, Jiangsu 214400 CHINA

E318898

Table of Recognized Styles

Single-conductor, thermoplastic insulation.							
1226	1354	1708	1766	1882	10008	10248	
1227	1371	1709	1847	1886	10011	10362	
1330	1538	1710	1857	1887	10064	10518	
1331	1577	1723	1858	1901	10072	11085	
1332	1591	1726	1859	1927	10111	11149	
1333	1592	1727	1860	10005	10231	11180	
Multiple-conductor, thermoplastic insulation.							
20276	21100	21533					

Style(s) 11149 can be assigned the IEC 60332-2 flammability rating

Marking: Company name, voltage rating, temperature rating, conductor size, conductor material if other than copper, and use.

Last Updated on 2020-04-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

