

# RF EXPOSURE **EVALUATION REPORT**

APPLICANT ShenZhen Gospell Smarthome Electronic Co., Ltd.

PRODUCT NAME HD Outdoor WiFi Camera

MODEL NAME T5925HCA

TRADE NAME N/A

N/A **BRAND NAME** 

FCC ID TW5T5925HCA

47CFR 2.1091

STANDARD(S) KDB 447498 D01 General RF Exposure Guidance

v06

**ISSUE DATE** 2017-09-26

## SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# **DIRECTORY**

TEST REPORT DECLARATION	- 3
1. TECHNICAL INFORMATION	<u>. 3</u>
1.1. IDENTIFICATION OF APPLICANT·······	4
1.2. IDENTIFICATION OF MANUFACTURER	-4
1.3. EQUIPMENT UNDER TEST (EUT)	. 4
1.3.1. PHOTOGRAPHS OF THE EUT	
1.3.2. IDENTIFICATION OF ALL USED EUT	5
1.4. APPLIED REFERENCE DOCUMENTS	
2. DEVICE CATEGORY AND RF EXPOSURE LIMIT	-6
3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER	<u>. 7</u>
4. RF EXPOSURE EVALUATION	- 8
ANNEX C GENERAL INFORMATION	9

Change History						
Issue Date Reason for change						
1.0 2017-09-26 First edition						



# **TEST REPORT DECLARATION**

Applicant	ShenZhen Gospell Smarthome Electronic Co., Ltd.		
Applicant Address	5Floor/Block 2, Vision (SZ) Park, Hi-Tech Industrial Park, Shenzhen, China		
Manufacturer	ShenZhen Gospell Smarthome Electronic Co., Ltd.		
Manufacturer Address	East of 01st-04st Floor,Block A,No.1 Industrial park,Fenghuanggang,South of No.1 Baotian Road,Xixiang street,Bao'an District,Shenzhen City,Guangdong Province 518126,P.R.China		
Product Name	HD Outdoor WiFi Camera		
Model Name	T5925HCA		
Brand Name	N/A		
HW Version	T5925YM02		
SW Version	E_900.T5925HCA.009.116		
Test Standards	47CFR 2.1091; KDB 447498 D01 General RF Exposure Guidance v06		
Issue Date	2017-09-26		
SAR Evaluation	Not Required		

Tested by	:	Peny Funci	
·		Peng Fuwei (Test engineer)	
		D 11	

Approved by

Peng Huarui (Supervisor)





# 1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

# 1.1. Identification of Applicant

Company Name:	ShenZhen Gospell Smarthome Electronic Co., Ltd.		
Address:	5Floor/Block 2, Vision (SZ) Park, Hi-Tech Industrial Park, Shenzhen, China		

#### 1.2. Identification of Manufacturer

Company Name:	ShenZhen Gospell Smarthome Electronic Co., Ltd.			
Address:	East of 01st-04st Floor,Block A,No.1 Industrial park,Fenghuanggang,South			
	of No.1 Baotian Road,Xixiang street,Bao'an District,Shenzhen			
	City,Guangdong Province 518126,P.R.China			

# 1.3. Equipment Under Test (EUT)

Model Name:	T5925HCA
Trade Name:	N/A
Brand Name:	N/A
Hardware Version:	T5925YM02
Software Version:	E_900.T5925HCA.009.116
Frequency Bands:	802.11.b/g/n20/n40
Modulation Mode:	802.11b:DSSS; 802.11g/n20/n40:OFDM
Antenna type:	Dipole Antenna
Development Stage:	Identical prototype





## 1.3.1. Photographs of the EUT

#### 1. EUT view



#### 1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Hardware Version		Software Version	
1#	T5925YM02	E_900.T5925HCA.009.116	

## 1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title			
1	47 CFR§2.1091	Radiofrequency Radiation Exposure Evaluation: mobile			
		devices			
2	KDB 447498 D01v06	General RF Exposure Guidance			



#### 2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

#### **Mobile Devices:**

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

#### **GENERAL POPULATION / UNCONTROLLED EXPOSURE**

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m) 3) Limits for General	Magnetic field strength (A/m) Population/Uncontro	Power density (mW/cm²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz



<sup>\* =</sup> Plane-wave equivalent power density



# 3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

# 1. 2.4G Wifi Average output power

		Frequenc	Output Power(dBm)		
Band	Channel	y (MHz)	802.11B	802.11G	802.11N 20
	1	2412	16.73	12.47	12.52
Wifi	6	2437	16.78	15.08	15.08
	11	2462	17.22	13.41	13.20

Band	Channel	Frequenc y (MHz)	Output Power(dBm) 802.11n40
	3	2422	10.15
Wifi	6	2437	14.26
	9	2452	10.54



# **4 RF EXPOSURE EVALUATION**

#### Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Antenna Gain (dBi)	Conducted Average Power (dBm)	Time-averaging EIRP (mW)	Power density (mW/cm²)	Limit for MPE (mW/cm²)
2.4GHz	2462	1.0	17.22	66.37	0.013	2.722

1. MPE calculation method

Power Density = EIRP/ $4\pi R^2$ 

Where: EIRP = P·G

P = Peak out power G = Antenna gain

R = Separation distance (20cm)





# **ANNEX C GENERAL INFORMATION**

#### 1. Identification of the Responsible Testing Laboratory

1. Identification of the Responsible resting Edsoratory				
Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.			
Department:	Morlab Laboratory			
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang			
	Road, Block 67, BaoAn District, ShenZhen, GuangDong			
	Province, P. R. China			
Responsible Test Lab Manager:	Mr. Su Feng			
Telephone:	+86 755 36698555			
Facsimile:	+86 755 36698525			

## 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

\*\*\*\* END OF REPORT \*\*\*\*

