

RF TEST REPORT

Product Name: Botslab Video Doorbell 2 Pro (Wi-Fi HomeBase)

Model Name: R811SH

FCC ID: 2A22Z-R810H

Issued For : Botslab Inc.

919 North Market Street, Suite 950, Wilmington, New Castle, Delaware, USA

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number:	LGT25C014HA01
Sample Received Date:	Mar. 06, 2025
Date of Test:	Mar. 11, 2025 ~ Apr. 08, 2025
Date of Issue:	Apr. 09, 2025

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant:	Botslab Inc.
Address:	919 North Market Street, Suite 950, Wilmington, New Castle, Delaware, USA
Manufacture:	Botslab Inc.
Address:	919 North Market Street, Suite 950, Wilmington, New Castle, Delaware, USA
Product Name:	Botslab Video Doorbell 2 Pro (Wi-Fi HomeBase)
Trademark:	Botslab
Model Name:	R811SH
Sample Status:	Normal

APPLICABLE STANDARDS					
STANDARD	TEST RESULTS				
FCC 47 CFR §2.1091 KDB 447498 D01 General RF Exposure Guidance v06	PASS				

Prepared by:

Zane Shan

Zane Shan Engineer

Approved by:

tali

Vita Li Technical Director





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	5
2.FCC 47CFR § 2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	7
2.4 CLASSIFICATION	7
2.5 TEST RESULT	8
APPENDIX I - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	9



Revision History

Rev.	Issue Date	Revisions
00	Apr. 09, 2025	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Botslab Video Doorbell 2 Pro (Wi-Fi HomeBase)				
Trademark:	Botslab	Botslab			
Model Name:	R811SH				
Series Model:	N/A				
Model Difference:	N/A				
Frequency Bands:	2.4G WLAN 802.11b/g/n(20MHz): 2412~2462MHz 802.11n(40MHz):2422~2452MHz				
Rating:	Input: AC 100-240V, 50/60Hz, 0.3A Max				
Hardware Version:	R811-V3.1				
Software Version:	1.00.046-20240903				

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.				
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China				
Accreditation Certificate	A2LA Certificate No.: 6727.01				
	FCC Registration No.: 746540				
	CAB ID: CN0136				



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1207 (b).

1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density					
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)					
Limits for Occupational / controlled Exposures								
0.3-3.0	614	1.63	*(100)					
3.0-30	1842/f	4.89/f	*(900/f²)					
30-300	61.4	0.163	1.0					
300 - 1500			F/300					
1500 – 100000			5.0					
Limits for General population / Uncontrolled Exposure								
0.3-1.34	614	1.63	*(100)					
1.34-30	824/f	2.19/f	*(180/f²)					
30-300	27.5	0.073	0.2					
300 - 1500			F/1500					
1500 – 100000			1.0					

F= Frequency in MHz

* = Plane-wave equivalent power density.

Friss Formula

Friss Transmission Formula: $Pd = (Pout * G) / (4*pi*r^2)$

Where

 $Pd = power density in mW/cm^{2}$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.5 TEST RESULT

Turn up Result

Mode	Turn up Power
2.4G WIFI-802.11b	14.5±1dBm
2.4G WIFI-802.11g	14±1dBm
2.4G WIFI-802.11n(HT20)	13±1dBm
2.4G WIFI-802.11n(HT40)	12±1dBm

The MPE result of worst mode:

		Mox	Mox		ANT Gain				
RF Function	Frequency (MHz)	Turn up Power	Turn up Power	ANT Gain	(gain of antenna	Power Density	Limit (mW/cm²)	Ratio	Result
		(dBm)	(mW)	(dBi)	in linear scale)	(mW/cm²)			
2.4G WIFI	2412	15.50	35.48	1.88	1.54	0.011	1	0.011	Pass

Note:

1. The Maximum Power Density is less than the limit, complies with the exemption requirements.



APPENDIX I - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Note: Please see the attached R811SH_EUT Photos.

* * * * * END OF THE REPORT * * * * *