

COO:China
原産國：中國 / Pays d'origine : Chine
Mfg. Date / Date de fabrication: YYYYMMDD
Mfg. Site: Shenzhen FuLian FuGui Precision Industry Co., Ltd



MAC: XXXXXXXXXXXX



TAN: 68-XXXXXX-XX XX



PID/VID: CS-BPRO-XX VXX



SN: XXXXXXXXXXXX



5GHz帯 (W52, W53) 及び 6GHz帯 (LPI) :
屋内利用限定(5.2GHz帯高出力データ通信シ
ステムの基地局や中継局との通信を除く)



R 217-231071

R C-29620 E503R-NZ 2.4 DS/ OF 4

This device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.

FCC ID: LDK0401B2757

IC: 2461N-0401B2757

HVIN: TTC4-01 07100725-1



Designed by Cisco / 思科研发 / Conçu par Cisco
Product name / 品名 / Nom du Produit:
Cisco Room Bar Pro / 视频会议终端
Model / 型号 / Modèle: TTC4-01
Manufacturer / 制造商 / Fabricant:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134, USA
www.cisco.com



CAN ICES-3(A)/NMB-3(A)

Complies with
IMDA standards
DB101992



Warning: Shock hazard - Do not open
AVIS: Risque de choc électrique -
Ne pas ouvrir 警告：电击危险-不要打开

Apparatet må tilkoples jordet stikkontakt. Apparaten skall
anslutas till jordat uttag. Laite on liitettävä suojakoskettimilla
varustettuun pistorasiaan. Apparatets stikprop skal tilsluttes
en stikkontakt med jord, som giver forbindelse til stik-
proppens jord. 此设备需要接地
Power input (輸入/Entrée): 2.0-1.5A, 100-240V AC, 50-60Hz



56-107276-03-A0