

TO QUANTA COMPUTER CORPORATION
SPECIFICATION FOR APPROVAL

CUSTOMER DWG. NO./PART NO.: TBD REV.: N/A

DESCRIPTION: RF CABLE ASS'Y

FOXCONN PROD. NO.: WDAN-Q1KT6002 REV.: AX1

ATTACHMENTS:

- | | |
|--------------------------------------|---------------------|
| 1. RF CABLE ASSEMBLY DRAWING | <u>315-0900-126</u> |
| 2. DESIGN REVIEW FOR MATERIAL LIST.. | <u>ML-126</u> |
| 3. PART DRAWING | <u>SGX0001-00</u> |
| | <u>703-3000-290</u> |
| | <u>014-0000-153</u> |
| | <u>040-0000-896</u> |
| | <u>080-0000-620</u> |

PLEASE RETURN TO US ONE COPY OF COVER PAGE OF THE
"SPECIFICATION FOR APPROVAL " WITH YOUR APPROVED SIGNATURES

APPROVED SIGNATURES		




Hon Hai Precision Industry Co., Ltd.

2. TZU YU ST., TU-CHEN, TAIPEI HSIEN, 23606,
TAIWAN, R.O.C
TEL: (02) 2683466 (02) 2681477
TAIWAN, R.O.C
FAX: (02) 2687795 (02) 2683225
TLX. 32349 FOXCONNHH
UNIFORM INVOICE NUMBER: 04541302

Approved by: Sheng Checked by: _____ Prepared by: Paul Zhou

FILE NO.: SFA-126 REVISION NO.: AX1 DATE: 3. 7, 2002



DESIGN REVIEW FOR MATERIAL LIST

QUANTA P/N : TBD

NO : ML-126

DESCRIPTION : RF CABLE ASS'Y

PAGE : 1/1

ITEM	DESCRIPTION	SUPPLIER/AGENCY						QUANTA PART NUMBER	QUANTITY	REMARK
		SUPPLIER	SUPPLIER PART NO.	FOXCONN PART NO.	AVL	UL SUBMIT	CSA SUBMIT			
1	COAXIAL CABLE	HITACHI OR	HCM-40309/1	014-3031-153		N/A	N/A		A/R	
		ACTUONE	703-3000-290	703-3000-290		N/A	N/A		A/R	
2	RF CONN.	FOXCONN	SGX0001-00	SGX0001-00		N/A	N/A		1 PC	
3	PCB (LEFT)	FOXCONN	040-0002-896	040-0002-896		N/A	N/A		1 PC	
4	HEAT SHRINK TUBE	FOXCONN	080-2501-620	080-2501-620		N/A	N/A		3 PCS	

APPROVED BY: Sheng Tai 3/7/2002

CHECKED BY: _____


PREPARED BY: Paul Zhou 3/7/2002

ELECTRICAL		
IMPEDANCE	50	ohms
CAPACITANCE	30.5	pF/ft
CONDUCTOR RESISTANCE	860	ohms/KM

FREQUENCY (MHz)	ATTENUATION (dB/10ft)
500	3
1000	5
2000	8
3000	10

RATINGS	
TEMPERATURE:	200°C/105°C
VOLTAGE:	30V
UL STYLE:	1894/1943

REV	ECN No.	APPD.	DATE
A	MC-01-0847	VINCENT	3/28/01
B	MC-01-0847	ALLEN	4/13/01
C	MC-01-1942		



NOTES

- 1.PRIMARY INSULATION CONCENTRICITY = 85% MIN
2. NN : JACKET COLOR CODE
00--BLACK 01--BROWN 02--RED 03--ORANGE
04--YELLOW 05--GREEN 06--BLUE 07--PURPLE
08--GRAY 09--WHITE 10--CLEAR 99--NATURAL
- 3 BRAIDING COVERAGE TO BE 95 % MIN.
- 4.DIELECTRIC STRENGTH:1.25KVAC/min
- 5 JACKET CONCENTRICITY = 80% MIN

4	A/R	902-***1-*24	JACKET INSULATION, FEP #
3	A/R	904-44**--616	6ENDS/ 44 AWG TINNED PLATED BRAIDING
2	A/R	902-***1-*24	PRIMARY INSULATION, FEP #
1	A/R	904-30**--851	30 AWG, SOLID SILVER PLATED COPPER CLAD STEEL
ITEM	QTY	PART No	DESCRIPTION


BILL OF MATERIALS			
	UNITS	NAME(INTENDED USE)	FOXCONN
	mm	COAXIAL CABLE	HON HAI PRECISION IND CO.,LTD
	MATERIAL	PART No (INTENDED USE)	TITLE
	SEE BOM	703-30NN-290	RF CABLE
	FINISH	DESIGN .	30 AWG, CONSTRUCTION
	SEE NOTES	DWG No.	703-3000-290
	QTY	CHECKED	SCALE SHEET REV.
		DRAFTER	NONE 1/1 C

THESE DRAWINGS AND SPECS. ARE THE PROPERTY OF HON HAI PRECISION IND CO. LTD AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO. LTD

REV.	ECN.	NO	APPD
D	MC001768	Loi	5/12/00

NOTES:

1. CAPACITANCE: 30.5 pF/FT.
2. CONDUCTOR RESISTANCE: 264 OHMS/M' AT 20°C.
3. CONDUCTOR: 30 AWG, SOLID SP COPPER WELD 0.010" NOM. OD.
4. INSULATION: 30AWG, FEP, 0.031" OD., 0.0107" AVG WALL.
5. BRAID SHIELD: 30AWG, 6 ENDS 44 AWG TINNED COPPER, 95% MIN. COVERAGE.
6. JACKET: 30AWG, FEP, 0.050" ± 0.002" OD., 0.004" AVG WALL.
7. TEMPERATURE RATING: -70°C ~ +200°C.
8. NO MARKING.



014-3031-153	HITACHI HCM-40309/1	30AWG	BLACK
FOXCONN P/N	VENDOR & P/N	AWG	JACKET COLOR

X ±	X' ±	UNITS [INCH]	NAME(INTENDED USE)	FOXCONN HDN HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.								
.X ±	.X' ±	MAT'L	PART NO.(INTENDED USE)	TITLE COAXIAL CABLE								
.XX ± 0.05	.XX' ±	FINISH	APPD: Sheng Tai	DWG NO: 014-0000-153								
.XXX ±	.XXX' ±		CHKD:	 <table><tr><td>SCALE</td><td>SHEET</td><td>REV</td></tr><tr><td>N/A</td><td>1/1</td><td>D</td></tr></table>			SCALE	SHEET	REV	N/A	1/1	D
SCALE	SHEET		REV									
N/A	1/1	D										
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HDN HAI PRECISION IND CO., LTD AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HDN HAI PRECISION IND CO., LTD			Q'TY									
			DR:Duke Du 1/17/2001									

SCALE 10.000

GENERAL SPECIFICATION:


1. CONTACT RESISTANCE: 20 MILIOHMS MAX.
2. INSULATION RESISTANCE: 500 MEGOHMS MIN.
3. WITHSTAND VOLTAGE 200 Vac
4. CONNECTOR V.S.W.R.: 1.3 OR LESS AT DC TO 3 GHz
5. OPERATION TEMPERATURE: -40°C TO 90°C

RF CABLE ASSEMBLY MATERIAL:

1. CONTACT: COPPER ALLOY, GOLD PLATING
2. HOUSING: THERMOPLASTIC, UL 94V-0 RATED
3. METAL SHELL: COPPER ALLOY, SILVER PLATING
4. CABLE: 30AWG&32AWG SOLID COAXIAL CABLE.
5. PART NO. MATRX: SGX0001-00

REV.	ECN. NO.	APPD.
X2		D, KD

A
B
C
D
E



2	WIRE	703-3000-291	30AWG SOLD COAXIAL CABLE	A/R
1	RF CONN.	SGX0001-00	FOXCONN: EP01-025-001	1 PCS
ITEM	PART NAME	FOXCONN PART NO.	EQUIVALENT VENDOR & PART NO.	Q'TY



$\times . \pm$	$\times . \pm$	UNITS	mm	NAME(INTENDED USE)	FOXCONN
$\times \pm 0.1$	$\times \pm$	MAT'L		SGX0001-00	HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.
$\times \times \pm 0.1$	$\times \times \pm$	SEE NOTES		PART NO.(INTENDED USE)	TITLE:
$\times \times \times \pm$	$\times \times \times \pm$	FINISH		SGX0001-00	RF CABLE ASSEMBLY
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.		Q'TY		APPD: D, KD	DWG NO:
				CHKD:	EP01-025-001
				DR: D, KD 12/2/00	
				SCALE	SHEET
				10:1	1/1
				REV.	X2

1 2 3 4 5 6 7

REV	ECN.	NO	APPD.
A			


NOTES:

1. ALL DIMENSIONS SHALL BE INTERPRETED PER ANSI Y14.5M-1982.
2. DIMENSIONS MARKED ▼ SHALL BE CHECKED.
3. PCB'S MATERIAL : FR-4 THICKNESS 0.8MM.



2	040-0002-896	II
1	040-0001-896	I
ITEM	P/N	TYPE

X ±	X* ±	UNITS	mm	NAME(INTENDED USE)	FOR QUANTA KT6
.X ± ±0.2	X* ±	MAT'L		PART NO.(INTENDED USE)	
.XX ± ±0.1	XX* ±	FINISH		APPD.	Sheng Tai 3/7/02
.XXX ±	XXX* ±	Q'TY		CHKD:	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.				DR:	Paul Zhou 3/7/02
				DWG NO.: 040-0000-896	
				SCALE	SHEET
				N/A	1/1
				REV	A



NOTES:

▲ UL MARKING.

2. RATING : UL 224, 125°C, 600V, VW-1
CSA, 125°C, 600V, OFT

3. DIELECTRIC STRENGTH : 500 V/MIL

4. VOLUME RESISTIVITY : 10^{14} OHM-CM.

5. TENSILE STRENGTH : 10.3 MPa (1500 psi) MIN..

6. PART NO. MATRIX: 080- A B CC - 620

A: EQUIVALENT VENDER
& PRODUCT

A=0: SUMITUBE F2-*

A=1: FAVORTRON FVC-2-*

A=2: SUMITUBE F32-*

A=3: CHANGBAO 102-*

A=4: SUMITUBE F4-*

A=5: HB T*ø

CC: INSIDE DIMENSION ID.

B: COLOR

B=0: BLACK.

B=1: WHITE.

B=2: RED.

B=3: BLUE.

B=4: GREEN.


B=5: YELLOW.

B=6: ORANGE.

B=7: PURPLE.

B=8: GRAY

REV.	ECN.	NO.	APPD.
A	HC95121	JEFF C.	1/20/95
B	HC96190	C. CHEN	2/7/96
C	HC96670	C. CHEN	5/7/96
D	HC961695	CHARLES	
E	HC971231	C. CHEN	6/18/97
F	MC991918	LAI	5/31/99
G	MC993360	LAI	10/16/99
H	MCD01163	LAI	4/11/2000
K			



X.±	X°.±	UNITS mm	NAME(INTENDED USE)	FOXCONN HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.
.X± 0.2	.X°.±	MAT'L	PART NO.(INTENDED USE)	
.XX± 0.15	.XX°.±	FINISH	APPD: H.C.ZHENG 6/15'2001	TITLE: HEAT SHRINKABLE TUBE
.XXX±	.XXX°.±		CHKD:	DWG NO.: 080-0000-620
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND CO., LTD.		Q'TY	DR: H.C.ZHENG 6/15'2001	  SCALE N/A SHEET 1/2 REV. K

		1		2		3		4	
								REV.	ECN. NO. APPD
A									A
B									B
C									C
D									D
E									E

080-**-25-620	0.8	0.13	0.4	0.20
080-**-24-620	14.0	0.30	7.0	0.64
080-**-23-620	1.0	0.20	0.5	0.33
080-**-22-620	50.0	0.40	25.0	0.87
080-**-21-620	38.0	0.40	19.0	0.87
080-**-20-620	30.0	0.40	15.0	0.87
080-**-19-620	25.0	0.40	12.5	0.87
080-**-18-620	22.0	0.40	11.0	0.77
080-**-17-620	20.0	0.35	10.0	0.77
080-**-16-620	18.0	0.35	9.0	0.77
080-**-15-620	16.0	0.30	8.0	0.69
080-**-14-620	12.0	0.25	6.0	0.56
080-**-13-620	11.0	0.25	5.5	0.56
080-**-12-620	10.0	0.25	5.0	0.56
080-**-11-620	9.0	0.25	4.5	0.56
080-**-10-620	8.0	0.25	4.0	0.56
080-**-09-620	7.0	0.25	3.5	0.56
080-**-08-620	6.0	0.25	3.0	0.56
080-**-07-620	5.0	0.25	2.5	0.56
080-**-06-620	4.0	0.25	2.0	0.44
080-**-05-620	3.5	0.25	1.75	0.44
080-**-04-620	3.0	0.25	1.50	0.44
080-**-03-620	2.5	0.25	1.25	0.44
080-**-02-620	2.0	0.25	1.00	0.44
080-**-01-620	1.5	0.20	0.75	0.36
Part Number 	Inside Diameter, Di (min.)	Wall Thickness, T (nomi.)	Inside Diameter, Di (max.)	Wall Thickness, T (min.)
	As Supplied		After Shrinkage	

X.±	X°.±	UNITS mm	NAME(INTENDED USE)	FOXCONN HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.
.X± 0.2	.X°.±	MAT'L	PART NO.(INTENDED USE)	
.XX± 0.15	.XX°.±	FINISH	APPD: H.C.ZHENG 6/15'2001	TITLE: HEAT SHRINKABLE TUBE
.XXX±	.XXX°.±		CHKD:	DWG NO.: 080-0000-620
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.		Q'TY	DR: H.C.ZHENG 6/15'2001	 
				SCALE SHEET REV. N/A 2/2 K