

Measurement of Maximum Permissible Exposure

1. Foreword

In adopt with the Human Exposure IEEE C95.1, and according to the FCC 1.1310. The *Maximum Permissible Exposure (MPE)* is obligated to measure in order to prove the safety of radiation harmfulness to the human body.

The *Gain* of the antenna used is measured in an *anechoic chamber*. The *maximum total power to the antenna* is to be recorded. By adopting the ***Friis Transmission Formula*** and the *power gain of the antenna*, we can find the distance right away from the product, where the limit of the MPE is.

2. Description of EUT

FCC ID	: NDD9572060304
Product name	: Wireless LAN Access Point
Model name	: as Appendix A of Test Report
Classification	: Mobile Device (i) Under normal use condition, the antenna is at least 20cm away from the user; (ii) Warning statement for keeping 20cm separation distance and the prohibition of operating next to the person has been printed in the user' s manual
Frequency Range	: 2.412 GHz ~ 2.462GHz
Supported Channel	: 11 Channels
Modulation Skill	: DBPSK, DQPSK, CCK
Power Type	: Powered by Adapter Model: DVR-1250-B11 I/P: 120VAC, 60Hz ; O/P: 12VDC, 500mA

3. Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	100	6
3.0-30	1842/f	4.89/f	900/f ²	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	100	30
1.34-30	824/f	2.19/f	180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

[The EUT is tested in transmit and receive modes and in the first, middle and the last channel separately. The following shows only our observation have the greatest emissions.]

According to OET BULLETIN 56 Fourth Edition/August 1999, Equation for Predicting RF Fields:

$$\text{Friis Transmission Formula: } S = \frac{PG}{4pR^2} = \frac{66.374 \times 1.585}{4p(20)^2} = 0.0209 \text{ mW/cm}^2$$

$$\text{Estimated safe separation: } R = \sqrt{\frac{PG}{4p}} = \sqrt{\frac{66.374 \times 1.584}{4p}} = 2.894 \text{ cm}$$

Remarks: "The safe estimated separation that the user must maintain from the antenna is at least 2.894cm."

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

The Numeric gain G of antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

$$G = \text{Log}^{-1} (2.0 / 10) = 1.585$$

Input Output Enterprise Corp.	PRODUCT SPECIFICATION	DOC. No: WL-TL-17 DATE: 25-MAR-02 REV. : C
---	----------------------------------	--

PRODUCT NAME

2.4G ANTENNA WITH RP SMA

PART NUMBER



W205-108-D200

Signed By Customers

Approved By:

供應商: 垠旺精密股份有限公司

TEL:02-2917-7528;FAX:02-2912-1659

台北縣新店市寶興路 37 號 3 樓

Input Output Enterprise Corp.	PRODUCT SPECIFICATION 2.4 G ANTENNA WITH RP-SMA PLUG	DOC. No: WL-TL-17 DATE: 25-MAR-02 REV. : C
---	--	--

W205-108-D200 2.4G ANTENNA
SPECIFICATION

1. Electrical Properties

- 1-1 Frequency Range2.4~2.5GHz
- 1-2 Impedance.....50 Ohms nominal
- 1-3 V.S.W.R.....2.0 (Max.)
- 1-4 Return Loss.....-10.0 dB(Max.)
- 1-5 Max. Gain.....2.0dBi
- 1-6 Polarization..... Vertical
- 1-7 Admitted Power.....1W
- 1-8 Electrical Wave.....1/4 λ Dipole

2. Mechanical Properties

- 2-1 Connector.....Reverse SMA Plug
- 2-2 Cable.....RG178
- 2-3 Antenna Body.....T.P.R.
- 2-4 Operating Temperature Range.....-20°C ~ +50°C
- 2-5 Storage Temperature Range..... -20°C ~ +50°C

Input Output
Enterprise Corp.

PRODUCT SPECIFICATION

2.4 G ANTENNA WITH RP-SMA PLUG

DOC. No: WL-TL-17

DATE: 25-MAR-02

REV. : C

