




Figure 389: Spurious Emissions at Antenna Terminal 64QAM, 751.5MHz,
B.W. 5MHz, Sub Carrier 30kHz




Figure 390: Spurious Emissions at Antenna Terminal 64QAM, 765.5MHz,
B.W. 5MHz, Sub Carrier 30kHz




Figure 391: Spurious Emissions at Antenna Terminal 64QAM, 733MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 392: Spurious Emissions at Antenna Terminal 64QAM, 751.5MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 393: Spurious Emissions at Antenna Terminal 64QAM, 763MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 394: Spurious Emissions at Antenna Terminal 64QAM, 733MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 395: Spurious Emissions at Antenna Terminal 64QAM, 751.5MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 396: Spurious Emissions at Antenna Terminal 64QAM, 763MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 397: Spurious Emissions at Antenna Terminal 64QAM, 735.5MHz,
B.W. 15MHz, Sub Carrier 15kHz




Figure 398: Spurious Emissions at Antenna Terminal 64QAM, 735.5MHz,
B.W. 15MHz, Sub Carrier 30kHz




Figure 399: Spurious Emissions at Antenna Terminal 256QAM, 730.5MHz,
B.W. 5MHz, Sub Carrier 15kHz




Figure 400: Spurious Emissions at Antenna Terminal 256QAM, 751.5MHz,
B.W. 5MHz, Sub Carrier 15kHz




Figure 401: Spurious Emissions at Antenna Terminal 256QAM, 730.5MHz, B.W. 5MHz, Sub Carrier 15kHz




Figure 402: Spurious Emissions at Antenna Terminal 256QAM, 730.5MHz, B.W. 5MHz, Sub Carrier 30kHz




Figure 403: Spurious Emissions at Antenna Terminal 256QAM, 751.5MHz, B.W. 5MHz, Sub Carrier 30kHz




Figure 404: Spurious Emissions at Antenna Terminal 256QAM, 765.5MHz, B.W. 5MHz, Sub Carrier 30kHz




Figure 405: Spurious Emissions at Antenna Terminal 256QAM, 867MHz, B.W. 10MHz, Sub Carrier 15kHz




Figure 406: Spurious Emissions at Antenna Terminal 256QAM, 751.5MHz, B.W. 10MHz, Sub Carrier 15kHz




Figure 407: Spurious Emissions at Antenna Terminal 256QAM, 763MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 408: Spurious Emissions at Antenna Terminal 256QAM, 733MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 409: Spurious Emissions at Antenna Terminal 256QAM, 751.5 MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 410: Spurious Emissions at Antenna Terminal 256QAM, 763MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 411: Spurious Emissions at Antenna Terminal 256QAM, 735.5MHz,
B.W. 15MHz, Sub Carrier 15kHz




Figure 412: Spurious Emissions at Antenna Terminal 256QAM, 735.5MHz,
B.W. 15MHz, Sub Carrier 30kHz




Figure 413: Spurious Emissions at Antenna Terminal QPSK, 730.5MHz,
B.W. 5MHz, Sub Carrier 15kHz




Figure 414: Spurious Emissions at Antenna Terminal QPSK, 751.5MHz,
B.W. 5MHz, Sub Carrier 15kHz




Figure 415: Spurious Emissions at Antenna Terminal QPSK, 765.5MHz,
B.W. 5MHz, Sub Carrier 15kHz




Figure 416: Spurious Emissions at Antenna Terminal QPSK, 864.5MHz,
B.W. 5MHz, Sub Carrier 30kHz




Figure 417: Spurious Emissions at Antenna Terminal QPSK, 751.5MHz,
B.W. 5MHz, Sub Carrier 30kHz




Figure 418: Spurious Emissions at Antenna Terminal QPSK, 765.5MHz,
B.W. 5MHz, Sub Carrier 30kHz




Figure 419: Spurious Emissions at Antenna Terminal QPSK, 733MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 420: Spurious Emissions at Antenna Terminal QPSK, 751.5MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 421: Spurious Emissions at Antenna Terminal QPSK, 763MHz,
B.W. 10MHz, Sub Carrier 15kHz




Figure 422: Spurious Emissions at Antenna Terminal QPSK, 733MHz,
B.W. 10MHz, Sub Carrier 30kHz




Figure 423: Spurious Emissions at Antenna Terminal QPSK, 751.5MHz,
B.W. 10MHz, Sub Carrier 30kHz






Figure 424: Spurious Emissions at Antenna Terminal QPSK, 763MHz,
B.W. 10MHz, Sub Carrier 30kHz



**Figure 425: Spurious Emissions at Antenna Terminal QPSK, 735.5MHz,
B.W. 15MHz, Sub Carrier 15kHz**



**Figure 426: Spurious Emissions at Antenna Terminal QPSK, 735.5MHz,
B.W. 15MHz, Sub Carrier 30kHz**



12.5 Test Equipment Used; Spurious Emissions at Antenna Terminals

Instrument	Manufacturer	Model	Serial Number	Calibration	
				Last Calibration Date	Next Calibration Due
EXA signal Analyzer	Keysight	UXA N9040B	MY56080119	January 31, 2020	January 31, 2022
EXG Vector Signal Generator	Agilent Technologies	N5172B	MY53051952	January 17, 2019	January 17, 2022
40 dB Attenuator	Weinschel Associates	WA 39-40-33	-	November 1, 2020	November 1, 2021
RF Coaxial Cable	Huber-Suner	SLLS210B	-	November 1, 2020	November 1, 2021

Table 44 Test Equipment Used



13 Spurious Emissions at Antenna Terminals - 4G

13.1 Test Specification

FCC Part 27, Subpart C, Sections 27.53

13.2 Test Procedure

(Temperature (20°C)/ Humidity (48%RH))

The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator and an appropriate coaxial cable (max loss=44dB).

13.3 Test Limit

The power of any emission outside of the authorized operating frequency ranges (728 -768MHz) must be attenuated below the transmitting power (P) by a factor of $43 + 10 \log (P)$ dB.

13.4 Test Results

JUDGEMENT: Passed

See additional information in Figure 427 to Figure 447.




Figure 427: Spurious Emissions at Antenna Terminal 16QAM, 730.5MHz,
B.W. 5MHz




Figure 428: Spurious Emissions at Antenna Terminal 16QAM, 751.5MHz,
B.W. 5MHz




Figure 429: Spurious Emissions at Antenna Terminal 16QAM, 765.5MHz,
B.W. 5MHz




Figure 430: Spurious Emissions at Antenna Terminal 16QAM, 733MHz,
B.W. 10MHz




Figure 431: Spurious Emissions at Antenna Terminal 16QAM, 751.5MHz,
B.W. 10MHz




Figure 432: Spurious Emissions at Antenna Terminal 16QAM, 763MHz,
B.W. 10MHz




Figure 433: Spurious Emissions at Antenna Terminal 16QAM, 735.5MHz,
B.W. 15MHz




Figure 434: Spurious Emissions at Antenna Terminal 64QAM, 730.5MHz,
B.W. 5MHz




Figure 435: Spurious Emissions at Antenna Terminal 64QAM, 751.5MHz,
B.W. 5MHz




Figure 436: Spurious Emissions at Antenna Terminal 64QAM, 765.5MHz, B.W. 5MHz




Figure 437: Spurious Emissions at Antenna Terminal 64QAM, 733MHz, B.W. 10MHz




Figure 438: Spurious Emissions at Antenna Terminal 64QAM, 751.5MHz, B.W. 10MHz




Figure 439: Spurious Emissions at Antenna Terminal 64QAM, 763MHz,
B.W. 10MHz




Figure 440: Spurious Emissions at Antenna Terminal 64QAM, 735.5MHz,
B.W. 15MHz




Figure 441: Spurious Emissions at Antenna Terminal QPSK, 730.5MHz,
B.W. 5MHz




Figure 442: Spurious Emissions at Antenna Terminal QPSK, 751.5MHz,
B.W. 5MHz




Figure 443: Spurious Emissions at Antenna Terminal QPSK, 765.5MHz,
B.W. 5MHz




Figure 444: Spurious Emissions at Antenna Terminal QPSK, 733MHz,
B.W. 10MHz




Figure 445: Spurious Emissions at Antenna Terminal QPSK, 751.5MHz,
B.W. 10MHz




Figure 446: Spurious Emissions at Antenna Terminal QPSK, 763MHz,
B.W. 10MHz




Figure 447: Spurious Emissions at Antenna Terminal QPSK, 735.5MHz,
B.W. 15MHz



13.5 Test Equipment Used; Spurious Emissions at Antenna Terminals

Instrument	Manufacturer	Model	Serial Number	Calibration	
				Last Calibration Date	Next Calibration Due
EXA signal Analyzer	Keysight	UXA N9040B	MY56080119	January 31, 2020	January 31, 2022
EXG Vector Signal Generator	Agilent Technologies	N5172B	MY53051952	January 17, 2019	January 17, 2022
40 dB Attenuator	Weinschel Associates	WA 39-40-33	-	November 1, 2020	November 1, 2021
RF Coaxial Cable	Huber-Suner	SLLS210B	-	November 1, 2020	November 1, 2021

Table 45 Test Equipment Used

14 Spurious Radiated Emission

14.1 Test Specification

FCC, Part 27, Subpart C, Section 27.53

14.2 Test Procedure

(Temperature (23°C)/ Humidity (47%RH))

The test method was based on ANSI/TIA-603-D: 2010, Section 2.2.12 Unwanted Emissions: Radiated Spurious (substation method)

For measurements between 0.009MHz-30MHz:

The E.U.T was tested inside the shielded room at a distance of 3 meters and the E.U.T was placed on a non-metallic table, 1.5 meters above the ground. The frequency range 0.009MHz-30MHz was scanned. The readings were maximized by the turntable azimuth between 0-360°, and the antenna polarization.

The emissions were measured at a distance of 3 meters.

For measurements between 30.0MHz-1.0GHz:

A preliminary measurement to characterize the E.U.T was performed inside the shielded room at a distance of 3 meters, using peak detection mode and broadband antennas. The preliminary measurements produced a list of the highest emissions. The E.U.T was then transferred to the open site, and placed on a remote-controlled turntable. The E.U.T was placed on a non-metallic table, 0.8 meters above the ground. The frequency range 30.0MHz -1.0GHz was scanned and the list of the highest emissions was verified and updated accordingly.

The readings were maximized by adjusting the antenna height between 1-4 meters, the turntable azimuth between 0-360°, and the antenna polarization.

The emissions were measured at a distance of 3 meters.

For measurements between 1.0GHz-8.0GHz:

The E.U.T was tested inside the shielded room at a distance of 3 meters and the E.U.T was placed on a non-metallic table, 1.5 meters above the ground. The frequency range 1.0GHz -8.0GHz was scanned. The readings were maximized by the turntable azimuth between 0-360°, and the antenna polarization.

The emissions were measured at a distance of 3 meters.

RMS detector was used for this test.

Testing was performed when the RF port was connected to 50 Ω termination

Evaluation was performed for all possible modulations, bandwidths, and sub carriers.

14.3 Test Limit

The power of any emission outside of the authorized operating frequency ranges (728-768MHz) must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB, yielding -13dBm

14.4 Test Results

JUDGEMENT: Passed

No emissions were detected above the EMI receiver noise level which is at least 20 dB below the limit.



14.5 Test Instrumentation Used; Radiated Measurements

Instrument	Manufacturer	Model	Serial Number	Calibration	
				Last Calibration Date	Next Calibration Due
EMI Receiver	HP	8542E	3906A00276	March 11, 2020	March 31, 2021
RF Filter Section	HP	85420E	3705A00248	March 11, 2020	March 31, 2021
EMI Receiver	R&S	ESCI7	100724	March 9, 2020	March 31, 2021
Spectrum Analyzer	HP	8593EM	3826A00265	March 9, 2020	March 31, 2021
Active Loop Antenna	EMCO	6502	9506-2950	February 5, 2019	February 28, 2021
Antenna Biconical	EMCO	3110B	9912-3337	May 21, 2019	May 31, 2021
Antenna Log Periodic	EMCO	3146	9505-4081	May 31, 2018	May 31, 2021
Horn Antenna 1G-18G	ETS	3115	29845	May 31, 2018	May 31, 2021
Low Noise Amplifier	Narda	LNA-DBS-0411N313	013	August 23, 2020	August 31, 2021
Low Noise Amplifier	Sophia Wireless	LNA 28-B	232	August 24, 2020	August 31, 2021
Vector Signal Generator	VIAVI	MTS 5800	WMNK0071690263	July 1, 2018	July 1, 2021
Semi Anechoic Civil Chamber	ETS	S81	SL 11643	NCR	NCR
Antenna Mast	ETS	2070-2	-	NCR	NCR
Turntable	ETS	2087	-	NCR	NCR
Mast & Table Controller	ETS/EMCO	2090	9608-1456	NCR	NCR

Table 46 Test Equipment Used

15 Spurious Radiated Emission for 1559-1610 MHz Band

15.1 Test Specification

FCC, Part 90, Subpart C, Section 27.53 (f)

15.2 Test Procedure

(Temperature (20°C)/ Humidity (48%RH))

The test method was based on ANSI/TIA-603-D: 2010, Section 2.2.12 Unwanted Emissions: Radiated Spurious (substitution method)

The E.U.T was tested inside the shielded room at a distance of 3 meters and the E.U.T was placed on a non-metallic table, 1.5 meters above the ground. The frequency range 1559-1610 MHz was scanned. The readings were maximized by the turntable azimuth between 0-360°, and the antenna polarization. The emissions were measured at a distance of 3 meters.

RMS detector was used for this test.

The test was performed for all modulation, bandwidths and sub carriers operating in the band: 758-768MHz

Testing was performed when the RF port was connected to a typical antenna provided by the customer.

15.3 Test Limit

All emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz(-40dBm/MHz) equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW (-50dBm/MHz EIRP for discrete emissions of less than 700 Hz bandwidth

15.4 Test Results

No emissions were detected above the EMI receiver noise level which is at least 6 dB below the limit.

Judgement: Passed



15.5 Test Instrumentation Used; Radiated Measurements

Instrument	Manufacturer	Model	Serial Number	Calibration	
				Last Calibration Date	Next Calibration Due
EXA signal Analyzer	Keysight	UXA N9040B	MY56080119	January 31, 2020	January 31, 2022
EXG Vector Signal Generator	Agilent Technologies	N5172B	MY53051952	January 17, 2019	January 17, 2022
Semi Anechoic Civil Chamber	ETS	S81	SL 11643	NCR	NCR
Horn Antenna 1G-18G	ETS	3115	29845	May 31, 2018	May 31, 2021
Antenna Mast	ETS	2070-2	-	NCR	NCR
Turntable	ETS	2087	-	NCR	NCR
Mast & Table Controller	ETS/EMCO	2090	9608-1456	NCR	NCR

Table 47 Test Equipment Used

16 Out-of-Band Rejection

16.1 Test Specification

KDB 935210 D05 v01r01, Section 3.3

16.2 Test Procedure

(Temperature (21°C)/ Humidity (35%RH))

The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator and an appropriate coaxial cable (max Loss= 40.7 dB).

The signal and spectrum analyzer frequency range was set to $\pm 250\%$ of the passband, Dwell time set to approximately 10msec.

RBW was set between 1% to 5% of the E.U.T passband and VBW set to $\geq 3 \times \text{RBW}$.

16.3 Test Limit

N/A

16.4 Test Results

JUDGEMENT:

Passed




Figure 448. — Out-of-Band Rejection Plot



16.5 Test Equipment Used; Out-of-Band Rejection

Instrument	Manufacturer	Model	Serial Number	Calibration	
				Last Calibration Date	Next Calibration Due
EXA signal Analyzer	Keysight	UXA N9040B	MY56080119	January 31, 2020	January 31, 2022
EXG Vector Signal Generator	Agilent Technologies	N5172B	MY53051952	January 17, 2019	January 17, 2022
40 dB Attenuator	Weinschel Associates	WA 39-40-33	-	November 1, 2020	November 1, 2021
RF Coaxial Cable	Huber-Suner	SLLS210B	-	November 1, 2020	November 1, 2021

Table 48 Test Equipment Used



17 APPENDIX A - CORRECTION FACTORS

17.1 Correction factors for RF OATS Cable 35m

ITL #1784

Frequency (MHz)	Cable loss (dB)
10.0	0.3
20.0	0.2
50.0	-0.1
100.0	-0.6
200.0	-1.2
500.0	-2.3
1000.0	-3.6



17.2 Correction factors for RF OATS Cable 10m
ITL #1794

Frequency(MHz)	Cable loss(dB)
10.0	-0.3
20.0	-0.3
50.0	-0.5
100.0	-0.7
200.0	-1.1
500.0	-1.8
1000.0	-2.7



17.3 Correction factors for

Horn Antenna

**Model: SWH-28
at 1 meter range.**

FREQUENCY (GHz)	APE (dB /m)	Gain (dB1)
18.0	40.3	16.1
19.0	40.3	16.3
20.0	40.3	16.1
21.0	40.3	16.3
22.0	40.4	16.8
23.0	40.5	16.4
24.0	40.5	16.6
25.0	40.5	16.7
26.0	40.6	16.4

17.4 Correction factors for Horn Antenna

Model: 3115

Antenna serial number: 29845

3 meter range

f(GHz)	AF(dB/m)	GA(dB)
0.75	25	3
1G	23.5	7
1.5G	26	8
2G	29	7
2.5G	27.5	10
3G	30	10
3.5G	31.5	10
4G	32.5	9.5
4.5G	32.5	10.5
5G	33	10.5
5.5G	35	10.5
6G	36.5	9.5
6.5G	36.5	10
7G	37.5	10
7.5G	37.5	10
8G	37.5	11
8.5G	38	11
9G	37.5	11.5
9.5G	38	11.5
10G	38.5	11.5
10.5G	38.5	12
11G	38.5	12.5
11.5G	38.5	13
12G	38	13.5
12.5G	38.5	13
13G	40	12
13.5G	41	12
14G	40	13
14.5G	39	14
15G	38	15.5
15.5G	37.5	16
16G	37.5	16
16.5G	39	15
17G	40	15
17.5G	42	13.5
18G	42.5	13



17.5 Correction factors for Log Periodic Antenna
EMCO, Model 3146,
Serial #9505-4081

Frequency [MHz]	AF [dB/m]
200.0	11.47
250.0	12.06
300.0	14.77
400.0	15.77
500.0	18.01
600.0	18.84
700.0	20.93
800.0	21.27
900.0	22.44
1000.0	24.10



17.6 Correction factors for Biconical Antenna
EMCO, Model 3110B,
Serial #9912-3337

Frequency [MHz]	AF [dB/m]
30.0	14.18
35.0	13.95
40.0	12.84
45.0	11.23
50.0	11.10
60.0	10.39
70.0	9.34
80.0	9.02
90.0	9.31
100.0	8.95
120.0	11.53
140.0	12.20
160.0	12.56
180.0	13.49
200.0	15.27



17.7 Correction factors for ACTIVE LOOP ANTENNA

Model 6502

S/N 9506-2950

f(MHz)	MAF(dBs/m)	AF(dB/m)
0.01	-33.1	18.4
0.02	-37.2	14.3
0.03	-38.2	13.3
0.05	-39.8	11.7
0.1	-40.1	11.4
0.2	-40.3	11.2
0.3	-40.3	11.2
0.5	-40.3	11.2
0.7	-40.3	11.2
1	-40.1	11.4
2	-40	11.5
3	-40	11.5
4	-40.1	11.4
5	-40.2	11.3
6	-40.4	11.1
7	-40.4	11.1
8	-40.4	11.1
9	-40.5	11
10	-40.5	11
20	-41.5	10
30	-43.5	8