



FCC Test Report

Report No.: OKA-ESH-P22120819B-2

FCC ID: 2AYF8-YBES800

Product: Electric Scooter

Model: ES800

Received Date: Dec.14, 2022

Test Date: Dec.14, 2022 to Jan.16, 2023

Issued Date: Feb.15, 2023

Applicant: Zhejiang Okai Vehicle Co., Ltd.

Address: No. 9, Xinxing Road, Xinbi Town, Jinyun County, Zhejiang, China

Manufacturer: Zhejiang Okai Vehicle Co., Ltd.

Address: No. 9, Xinxing Road, Xinbi Town, Jinyun County, Zhejiang, China

Issued By: BUREAU VERITAS ADT (Shanghai) Corporation

Lab Address: No. 829, Xinzhuang Road, Shanghai, P.R.China (201612)

**FCC Registration /
Designation Number:** 176467/ CN1213



Test Lab
Cert 2343.01

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Test Instruments	7
2.2 Measurement Uncertainty	8
2.3 Modification Record	8
3 General Information	9
3.1 General Description of EUT	9
3.2 Description of Test Modes	10
3.2.1 Test Mode Applicability:	11
3.2.2 Test Condition:	12
3.3 Description of Support Units	16
3.4 General Description of Applied Standards	16
4 Test Procedure and Results	17
4.1 AC Power Conducted Emission	17
4.1.1 Limits	17
4.1.2 Test Procedures	17
4.1.3 Deviation from Test Standard	17
4.1.4 Test Setup	18
4.1.5 EUT Operating Conditions	18
4.1.6 Test Results	19
4.2 Minimum 6dB Bandwidth	23
4.2.1 Limit	23
4.2.2 Test Setup	23
4.2.3 Test Procedures	23
4.2.4 Deviation of Test Standard	23
4.2.5 Test Results	24
4.3 Conducted Output Power	29
4.3.1 Limit	29
4.3.2 Test Setup	29
4.3.3 Test Procedures	29
4.3.4 Deviation of Test Standard	29
4.3.5 Test Results	30
4.4 Power Spectral Density	33

4.4.1	Limit	33
4.4.2	Test Setup.....	33
4.4.3	Test Procedures.....	33
4.4.4	Deviation of Test Standard	33
4.4.5	Test Results	34
4.5	Conducted Band Edges Measurement	37
4.5.1	Limit	37
4.5.2	Test Setup.....	37
4.5.3	Test Procedures.....	37
4.5.4	Deviation of Test Standard	37
4.5.5	Test Results	38
4.6	Conducted Spurious Emissions	41
4.6.1	Limit	41
4.6.2	Test Setup.....	41
4.6.3	Test Procedures.....	41
4.6.4	Deviation of Test Standard	41
4.6.5	Test Results	42
4.7	Emissions in restricted frequency bands	49
4.7.1	Test Limit	49
4.7.2	Test Procedure Reference.....	50
4.7.3	Test Procedures.....	50
4.7.4	Test Setup.....	51
4.7.5	Test Results	52
4.8	Radiated Emission Measurement	58
4.8.1	Limits	58
4.8.2	Test Procedures.....	58
4.8.3	Deviation from Test Standard	59
4.8.4	Test Setup.....	60
4.8.5	EUT Operating Conditions.....	61
4.8.6	Test Results	61
5	Pictures of Test Arrangements.....	71



Release Control Record

Issue No.	Description	Date Issued
OKA-ESH-P22120819B-2	Original release	Feb.15, 2023



1 Certificate of Conformity

Product: Electric Scooter

Brand: OKAI

Model: ES800

Applicant: Zhejiang Okai Vehicle Co., Ltd.

Test Date: Dec.14, 2022 to Jan.16, 2023

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2020

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Yuan Zhang
Yuan ZHANG

Project Engineer

, Date:

Feb.15, 2023

Approved by :



Sean YU

RF Supervisor

, Date:

Feb.15, 2023

2 Summary of Test Results

The EUT has been tested according to the following specifications:

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.203	Antenna Requirement	PASS	No antenna connector is used.
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	Minimum 6dB Bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.247(d)	Conducted Band Edges Measurement	PASS	Meet the requirement of limit.
15.247(d)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
15.247(d)	Emissions in restricted frequency bands	PASS	Meet the requirement of limit.
15.205 / 15.209 / 15.247(d)	Radiated Emissions Measurement	PASS	Meet the requirement of limit.

2.1 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Loop Antenna	ETS-LINDGREN	6502	E1A1039	Jul.23,22	Jul.22,23
Hybrid Antenna(25MHz-1.5GHz)	Schwarzbeck	VULB9168	E1A1012	Jul.26, 21	Jul.25, 23
Horn Antenna(1GHz -18GHz)	Schwarzbeck	BBHA9120D	E1A1017	Jul.25, 22	Jul.24, 24
Double Ridge Horn Antenna(18G-40G)	COM-POWER	AH-840	E1A1040	Jul.25, 22	Jul.24, 24
Pre-Amplifier(100kHz-1.3GHz)	Agilent	8447D	E1A2001	Mar.03, 22	Mar.02, 23
Pre-Amplifier(0.5GHz-18GHz)	EMCI	EMC184045SE	E1A2009	Aug.04, 22	Aug.03, 23
Pre-Amplifier(18GHz-40GHz)	EMCI	EMC051845SE	E1A2008	Aug.04, 22	Aug.03, 23
EMI test receiver	R&S	ESR7	E1R1005	Mar.03, 22	Mar.02, 23
Spectrum Analyzer	Keysight	N9030B	E1S1003	Sep.14, 22	Sep.13, 23
Spectrum Analyzer	Keysight	N9020A	E1S1004	Mar.03, 22	Mar.02, 23
EMI test receiver	R&S	ESR3	E1R1008	Jun.20, 22	Jun.19, 23
LISN	R&S	ENV216	E1L1011	Jun.20, 22	Jun.19, 23
Humidity&Temp Tester	Baolima	WS508	E1H1011	Apr. 01, 22	Mar.31, 23
RF Control Unit	Toscend	JS0806-2	E1C5003	N/A	N/A
Test Software	Toscend	JS32-CE	N/A	N/A	N/A
Test Software	Toscend	JS32-RE	N/A	N/A	N/A
Test Software	Toscend	JS1120-3	N/A	N/A	N/A

2.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Expanded Uncertainty ($k=2$) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.36 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.47 dB
	6GHz ~ 18GHz	3.75 dB
	18GHz ~ 40GHz	3.30 dB

2.3 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Electric Scooter
Brand	OKAI
Test Model	ES800
Power Rating	Powered by battery; AC Adaptor: Input: 100-240VAC, 50/60Hz, 2,5A (Max.) Output: 58.8VDC, 4.0A
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 5.0
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Gain	-0.7dBi

Note:

1. For more details, please refer to the User's manual of the EUT.
2. The cable loss of the cable from EUT will be compensated in the test data.

3.2 Description of Test Modes

40 channels are provided for Bluetooth LE.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
0	2402 MHz	20	2442 MHz
1	2404 MHz	21	2444 MHz
2	2406 MHz	22	2446 MHz
3	2408 MHz	23	2448 MHz
4	2410 MHz	24	2450 MHz
5	2412 MHz	25	2452 MHz
6	2414 MHz	26	2454 MHz
7	2416 MHz	27	2456 MHz
8	2418 MHz	28	2458 MHz
9	2420 MHz	29	2460 MHz
10	2422 MHz	30	2462 MHz
11	2424 MHz	31	2464 MHz
12	2426 MHz	32	2466 MHz
13	2428 MHz	33	2468 MHz
14	2430 MHz	34	2470 MHz
15	2432 MHz	35	2472 MHz
16	2434 MHz	36	2474 MHz
17	2436 MHz	37	2476 MHz
18	2438 MHz	38	2478 MHz
19	2440 MHz	39	2480 MHz

3.2.1 Test Mode Applicability:

EUT Configure Mode	Applicable to				Description
	RE ≥ 1G	RE < 1G	PLC	APCM	
-	√	√	√	√	-

Where **RE ≥ 1G**: Radiated Emission above 1GHz **RE < 1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.
- ☒ For different antenna gain, select high gain antenna for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0, 19, 39	GFSK

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0	GFSK

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0	GFSK

Antenna Port Conducted Measurement

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0, 19, 39	GFSK

3.2.2 Test Condition:


Applicable to	Normal Environmental Conditions	Normal Input Power
RE ≥ 1G	23deg. C, 58%RH	Powered by battery
RE < 1G	23deg. C, 58%RH	Powered by battery, AC 120V 60Hz, AC230V 50Hz
PLC	23deg. C, 58%RH	AC 120V 60Hz, AC230V 50Hz
APCM	25deg. C, 60%RH	Powered by battery

3.3 Duty Cycle of Test Signal


Test Mode	Antenna	Channel [MHz]	Duty Cycle [%]	10log(1/x) Factor[dB]
BLE_1M	Ant1	2402	85.60	0.68
		2440	85.60	0.68
		2480	85.60	0.68
BLE_2M	Ant1	2402	57.45	2.41
		2440	57.75	2.38
		2480	57.75	2.38

Note: Duty Cycle Factor= $10 \cdot \log[1/\text{Duty Cycle}(\%)*100]$, Duty Cycle= $T_{\text{on}}/T_{\text{period}} * 100\%$


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10:2020

All relaxed test items have been performed and recorded as per the above standard.

4 Test Procedure and Results

4.1 AC Power Conducted Emission

4.1.1 Limits

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.1.2 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.1.3 Deviation from Test Standard

No deviation.

4.1.4 Test Setup



Note: 1.Support units were connected to second LISN.


For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.5 EUT Operating Conditions

Same as 4.1.6.

4.1.6 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Power supply	AC 120V, 60Hz		
Test Mode	Charging		




Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading Value [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading Value [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1590	9.77	36.95	46.72	65.52	18.80	21.40	31.17	55.52	24.35	L1	PASS
2	0.2805	9.64	38.78	48.42	60.80	12.38	32.61	42.25	50.80	8.55	L1	PASS
3	0.4560	9.59	32.91	42.50	56.77	14.27	23.04	32.63	46.77	14.14	L1	PASS
4	0.6315	9.52	23.92	33.44	56.00	22.56	10.52	20.04	46.00	25.96	L1	PASS
5	1.0365	9.49	26.53	36.02	56.00	19.98	12.02	21.51	46.00	24.49	L1	PASS
6	1.8150	9.63	24.02	33.65	56.00	22.35	10.55	20.18	46.00	25.82	L1	PASS

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value - Emission level
4. Correction factor = Insertion loss + Cable loss
5. QP/AV Value= QP/AV Reading Value+ Correction factor

Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Power supply	AC 120V, 60Hz		
Test Mode	Charging		




Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1638	9.76	48.32	65.27	16.95	34.41	55.27	20.86	ENV216_N	PASS
2	0.2708	9.61	48.87	61.09	12.22	38.77	51.09	12.32	ENV216_N	PASS
3	0.4754	9.59	41.46	56.42	14.96	33.24	46.42	13.18	ENV216_N	PASS
4	0.6684	9.48	38.62	56.00	17.38	28.16	46.00	17.84	ENV216_N	PASS
5	0.8512	9.51	37.11	56.00	18.89	24.09	46.00	21.91	ENV216_N	PASS
6	1.2454	9.53	35.84	56.00	20.16	23.50	46.00	22.50	ENV216_N	PASS
7	1.6305	9.57	35.23	56.00	20.77	23.05	46.00	22.95	ENV216_N	PASS

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value - Emission level
4. Correction factor = Insertion loss + Cable loss
5. QP/AV Value= QP/AV Reading Value+ Correction factor

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Power supply	AC 230V, 50Hz		
Test Mode	Charging		




Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading Value [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading Value [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1595	9.77	42.74	52.51	65.49	12.98	24.57	34.34	55.49	21.15	L1	PASS
2	0.2854	9.63	37.62	47.25	60.66	13.41	29.69	39.32	50.66	11.34	L1	PASS
3	0.4524	9.59	31.72	41.31	56.83	15.52	19.98	29.57	46.83	17.26	L1	PASS
4	0.5658	9.55	26.92	36.47	56.00	19.53	9.77	19.32	46.00	26.68	L1	PASS
5	0.8633	9.46	26.90	36.36	56.00	19.64	14.75	24.21	46.00	21.79	L1	PASS
6	1.5889	9.59	22.63	32.22	56.00	23.78	6.22	15.81	46.00	30.19	L1	PASS

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value - Emission level
4. Correction factor = Insertion loss + Cable loss
5. QP/AV Value= QP/AV Reading Value+ Correction factor

Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Power supply	AC 230V, 50Hz		
Test Mode	Charging		



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading Value [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading Value [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1682	9.76	38.58	48.34	65.05	16.71	15.90	25.66	55.05	29.39	N	PASS
2	0.2355	9.69	28.71	38.40	62.25	23.85	13.79	23.48	52.25	28.77	N	PASS
3	0.4503	9.58	32.19	41.77	56.87	15.10	20.21	29.79	46.87	17.08	N	PASS
4	0.6563	9.49	27.78	37.27	56.00	18.73	14.10	23.59	46.00	22.41	N	PASS
5	1.0535	9.51	25.51	35.02	56.00	20.98	11.73	21.24	46.00	24.76	N	PASS
6	1.8862	9.60	21.20	30.80	56.00	25.20	7.78	17.38	46.00	28.62	N	PASS
7	5.5320	9.73	13.48	23.21	60.00	36.79	3.04	12.77	50.00	37.23	N	PASS

REMARKS:


1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value - Emission level
4. Correction factor = Insertion loss + Cable loss
5. QP/AV Value= QP/AV Reading Value+ Correction factor

4.2 Minimum 6dB Bandwidth

4.2.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.2.2 Test Setup



4.2.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 8.2).

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., $RBW = 100 \text{ kHz}$, $VBW \geq 3 \cdot RBW$, peak detector with maximum hold) is implemented by the instrumentation function.

4.2.4 Deviation of Test Standard

No deviation.

4.2.5 Test Results

Test Mode	Antenna	Channel [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.664	2401.668	2402.332	≥ 0.5	PASS
		2440	0.684	2439.660	2440.344	≥ 0.5	PASS
		2480	0.692	2479.652	2480.344	≥ 0.5	PASS
BLE_2M	Ant1	2402	1.088	2401.448	2402.536	≥ 0.5	PASS
		2440	1.112	2439.444	2440.556	≥ 0.5	PASS
		2480	1.132	2479.452	2480.584	≥ 0.5	PASS

99% Occupied Channel Bandwidth


Test Mode	Antenna	Channel [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0245	2401.494	2402.519	---	PASS
		2440	1.0119	2439.498	2440.510	---	PASS
		2480	1.0082	2479.501	2480.509	---	PASS
BLE_2M	Ant1	2402	2.0256	2401.000	2403.026	---	PASS
		2440	2.0519	2438.994	2441.046	---	PASS
		2480	2.0293	2479.005	2481.035	---	PASS

DTS Bandwidth

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440




BLE_2M_Ant1_2480




Occupied Channel Bandwidth


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480




4.3 Conducted Output Power

4.3.1 Limit

For systems using digital modulation in the 2400 – 2483.5 MHz bands: 1 Watt (30 dBm)

4.3.2 Test Setup



4.3.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 9.2.2.4).

- a) Set RBW $\geq$ DTS bandwidth
- b) Set VBW $\geq$ 3 RBW.
- c) Set Span $\geq$ 3 RBW.
- d) Sweep time = auto couple.
- e) Detector = peak
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.


4.3.4 Deviation of Test Standard

No deviation.


4.3.5 Test Results

Test Mode	Antenna	Channel [MHz]	Power [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	-1.98	<=30	PASS
		2440	-0.46	<=30	PASS
		2480	-0.61	<=30	PASS
BLE_2M	Ant1	2402	-1.85	<=30	PASS
		2440	-0.27	<=30	PASS
		2480	-0.54	<=30	PASS


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480




4.4 Power Spectral Density

4.4.1 Limit

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.4.2 Test Setup



4.4.3 Test Procedures

The power output per FCC § 15.247(e) was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 10.5) for compliance to FCC 47CFR 15.247 requirements.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.4.4 Deviation of Test Standard

No deviation.


4.4.5 Test Results

Test Mode	Antenna	Channel [MHz]	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-18.65	≤ 8	PASS
		2440	-17.07	≤ 8	PASS
		2480	-17.17	≤ 8	PASS
BLE_2M	Ant1	2402	-19.18	≤ 8	PASS
		2440	-17.7	≤ 8	PASS
		2480	-18.05	≤ 8	PASS


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480

