

CETECOM ICT Services GmbH

Radio Satellite Communication

Untertürkheimer Straße 6-10 . D-66117 Saarbrücken

Telefon: +49 (0)681 598-9100

Telefax: -9075

RSC14

issue test report consist of 76 Pages

Page 1 (76)



Accredited Bluetooth™ Test Facility (BQTF)

Test report no.: 1_0138-06-05/01
FCC Part 15.247 / CANADA RSS-210
NPL-1

CETECOM – ICT Services GmbH
Untertürkheimerstr. 6-10
66117 Saarbrücken, Germany

Telephone: + 49 (0) 681 / 598-0
Fax: + 49 (0) 681 / 9075

Table of Contents

1 General information

1.1 Notes

1.2 Testing laboratory

1.3 Details of applicant

1.4 Application details

1.5 Test item

1.6 Test standards

2 Technical test

2.1 Summary of test results

2.2 Test report

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Telephone : + 49 681 598 - 9100

Telefax : + 49 681 598 - 9075

E-mail : Harro.Ames@ict.cetecom.de

Internet : www.cetecom.de

Accredited testing laboratory

DAR-registration number : TTI-P-G 166/98-30

Accredited Bluetooth™ Test Facility (BQTF)

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc. and licensed to CETECOM

1.3 Details of applicant

Name : Nokia Mobile Phones
Street : Wilhelm-Runge-Str. 11
City : D-89081 Ulm
Country : Germany
Telephone : +49 (0) 731 505-08
Telefax : +49 (0) 731 505-68 06
Contact : Mr. Thomas Raitmayer
Telephone : +49 (0) 731 505-67 28

1.4 Application details

Date of receipt of application : 21.01.2002
Date of receipt of test item : 28.01.2002
Date of test : 31.01.-01.02.2002

1.5 Test item

Type of equipment : **Triple Band Mobile with integrated Bluetooth module**
Type designation : **NPL-1 with DCH-8D, ACP-12E**
Manufacturer : applicant
Street :
City :
Country :
Serial number : See photographs

Additional informations:

Frequency : 2400 – 2483.5 MHz
Type of modulation : 1M00FXD / 79M8FXD (FHSS)
Number of channels : 79
Antenna : integral antenna / print antenna
Power supply : 3,6V DC Li-polymer Battery
Output power : EIRP: 2.04mW
Temperature range :

1.6 Test standards: **FCC Part 15 §15.247**
CANADA RSS-210

2 Technical test

2.1 Summary of test results

The radiated measurements were performed vertical and horizontal over the whole frequency range. We start at 1 m high with vertical receiving antenna and rotate the dish continuously. During rotation we use the antenna lift system to vary the high from 1 to 4 m. So we find maximum radiation output. At this points we do manual remeasurements. After this we do the same measurements in horizontal position of the receiving antenna. This (horizontal and vertical) is made for all the three planes of the test sample. We use the maximum received results.

The detector function and selection of bandwidth are according ANSI C63.2-1996 item 8.2.1 and ANSI C63.4-1992 Item 4.2.

Antennas are conform with ANSI C63.2-1996 item 15.

150 kHz - 30 MHz: Quasi Peak measurement, 9kHz Bandwidth, passive loop antenna.

30 MHz - 200 MHz: Quasi Peak measurement, 120KHz Bandwidth, biconical antenna

200MHz - 1GHz: Quasi Peak measurement, 120KHz Bandwidth, log periodic antenna

1GHz: Average, RBW 1MHz, VBW 10 MHz, waveguide horn

The product fullfills also the requirements for CANACA RSS-210

No deviations from the technical specification(s) were ascertained in the course of the tests performed.


Final verdict : PASS

Technical responsibility for area of testing :

11.08.01 RSC 8411 Berg M.

Date Section Name

Signature




Technical responsibility for area of testing :

11.08.01 RSC8412 Hausknecht D.

Date Section Name

Signature



2.2 Testreport

TEST REPORT

Testreport no. : 1_0138-06-05/01

TEST REPORT REFERENCE

LIST OF MEASUREMENTS

Paragraph	PARAMETER TO BE MEASURED	PAGE
	Transmitter parameters	
§ 15.204	Antenna gain	7
§ 15.247 (a)	Carrier frequency separation	8
§ 15.247 (a)	Number of hopping channels	9
§ 15.247 (a)	Time of occupancy (dwell time)	11
§ 15.247 (d)	Power spectral density (Inquiry/Page mode)	16
§ 15.247 (a)(1)	Spectrum bandwidth of a FHSS System	17
§ 15.247 (b)(2)	Maximum peak output power	21
§15.247	Band edge compliance	26
§ 15.247 (c)(1)	Emission limitations	34
	Receiver parameters	
§ 15.109	Spurious radiations - Radiated	53
§ 15.207	Conducted emissions	60
	Test equipment listing	62
	Photographs of the equipment	64

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Antenna Gain

SUBCLAUSE § 15.204

The gain is ± 2.0 dBi

(measured effective radiated power over dipole – measured conducted power with a temporary RF-connector)

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

-

Test report nr.: 1_0138-06-05/01

Issue date: 2002-02-06

Page 8 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

Carrier frequency separation

\$15.247(a)



Marker 1 [T1] RBW 50 kHz RF Att 10 dB
 Ref Lvl 2.26 dBm VBW 50 kHz
 9 dBm 2.44100501 GHz SWT 5 ms Unit dBm



Date: 1.FEB.2002 08:50:54

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

Number of hopping channels

§15.247(a)

Channel 1 - 38

	Delta 1 [T1]	RBW	500 kHz	RF Att	10 dB
	Ref Lvl	1.55 dB	VBW	500 kHz	
	9 dBm	38.07214429 MHz	SWT	5 ms	Unit
					dBm



Date: 1.FEB.2002 08:56:48

The number of hopping channels is 79.

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

Number of hopping channels

Channel 39 - 79

§15.247(a)


 Delta 1 [T1] RBW 500 kHz RF Att 10 dB
 Ref Lvl -0.64 dB VBW 500 kHz
 9 dBm 39.28657315 MHz SWT 5 ms Unit dBm



Date: 1.FEB.2002 08:59:12

The number of hopping channels is 79.

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Time of occupancy (dwell time) for DH1


§15.247(a)

The system makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 79 channels. So you have each channel 10.13 times per second and for 30 seconds you have 303.9 times of appearance .

Each tx-time per appearance is 435.0701 µs.

So we have $303.9 * 435.0701 \mu s = 132.218 \text{ ms}$ per 30 seconds.

	Delta 2 [T1]	RBW	1 MHz	RF Att	10 dB
Ref Lvl	-5.66 dB	VBW	1 MHz		
9 dBm	1.258918 ms	SWT	2 ms	Unit	dBm



Date: 1.FEB.2002 10:04:12

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E
Ambient temperature : 23,6°C
Relative humidity : 33%


Time of occupancy (dwell time) for DH3 §15.247(a)

A DH3 Packets need 3 time slots for transmit and 1 for receiving, then the system makes worst case 400 hops per second with 79 channels. So you have each channel 5.1 times per second and for 30 seconds you have 153 times of appearance .

Each tx-time per appearance is 1.67756 ms.

So we have 153 * 1.67756 ms = 256.667 ms per 30 seconds.

	Delta 2 [T1]	RBW	1 MHz	RF Att	10 dB
Ref Lvl	-0.17 dB	VBW	1 MHz		
9 dBm	3.747896 ms	SWT	5 ms	Unit	dBm



Date: 1.FEB.2002 10:09:01

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%


Time of occupancy (dwell time) for DH5

\$15.247(a)

At DH5 Packets you need 5 time slots for transmit and 1 for receiving, so the system makes worst case 266,7 hops per second with 79 channels. So you have each channel 3.36 times per second and for 30 seconds you have 100,8 times of appearance .

Each tx-time per appearance is 2.93006 ms.

So we have $100,8 * 2.93006 \text{ ms} = 295.35 \text{ ms}$ per 30 seconds.



Date: 1.FEB.2002 10:22:55

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Time of occupancy (dwell time) for page mode /Inquiry mode (TX-on time) §15.247(a)

At paging mode the system makes first hopping with 16 channels. One sequence(called train A) lasts 10 ms. Every 1.28s frequencies change and a second train A starts with different frequencies. After max $7 \cdot 1.28$ s 16 new more distance frequencies (Train B) are used.

So we have in the worst case (same frequency is in every train) the following time scedule.


First: $7 \cdot 128 \cdot 10$ ms. For the next 7 seconds train B with other frequencies.

Then train A and B changes frequently.

⇒ so we have $7 \cdot 128 \cdot 130.461 \mu$ s, then 8.96 s other frequencies, then again $7 \cdot 128 \cdot 130.461 \mu$ s

⇒ together in 30 s maximal 2 sequences =>maximal 0.234 s per 30 second period.

Page mode (TX-on time) / Inquiry mode (TX-on time)



Date: 1.FEB.2002 09:56:55

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED


(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Page mode (complete sequence) / Inquiry mode (complete sequence)



Date: 1.FEB.2002 09:54:24

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01

Issue date: 2002-02-06

Page 16 (76)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Power Spectral density (Hybrid system in Inquiry mode / Page scan)

\$15.247(d)



Date: 1.FEB.2002 10:28:08

Power density : -50.22 dBm/Hz = -15.42 dBm / 3 KHz

Correction factor from dBm/Hz to dBm/3KHz is +34,8 dB

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 17 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Spectrum Bandwidth of a FHSS System

§15.247(a)

20 dB bandwidth

TEST CONDITIONS		20 dB BANDWIDTH (kHz)		
Frequency (MHz)		2402	2441	2480
T _{nom} (23)°C	V _{nom} (3,6)V	895.792	925.852	913.828
Measurement uncertainty		±1kHz		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)

RBW: 10 kHz / VBW 10 kHz

LIMIT

SUBCLAUSE §15.247(a) (1)

The maximum 20dB bandwidth shall be at maximum 1000 KHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01

Issue date: 2002-02-06

Page 18 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

Spectrum Bandwidth of a FHSS System

§15.247(a)

20 dB bandwidth

Channel 1



Date: 1.FEB.2002 11:06:48

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

Spectrum Bandwidth of a FHSS System

§15.247(a)

20 dB bandwidth

Channel 2



Date: 1.FEB.2002 11:18:07

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

Spectrum Bandwidth of a FHSS System
20 dB bandwidth

§15.247(a)

Channel 3:



Date: 1.FEB.2002 11:21:43

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 21 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

MAXIMUM PEAK OUTPUT POWER (conducted)

SUBCLAUSE § 15.247 (b) (1)

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (mW)			
Frequency (MHz)		2402		2442	2480
T _{nom} (25)°C	V _{nom} (3,6)V	PK	1.109	1.622	1.386
		AV	0.982	1.435	1.225
De facto EIRP (Antenna gain +2.0 dBi)		1.759 (+2.45 dBm)		2.570 (+4.10 dBm)	2.061 (+3.14 dBm)
Measurement uncertainty		±3dB			

RBW / VBW : 3 MHz

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

MAXIMUM PEAK OUTPUT POWER

SUBCLAUSE § 15.247 (b) (1)

(conducted)

Channel 1



Marker 1 [T1]

RBW 3 MHz RF Att 10 dB

Ref Lvl

0.45 dBm

VBW 10 MHz

4 dBm


2.40215631 GHz

SWT

5 ms

Unit

dBm



Date: 1.FEB.2002 11:26:08

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

MAXIMUM PEAK OUTPUT POWER

SUBCLAUSE § 15.247 (b) (1)

(conducted)

Channel 2



Date: 1.FEB.2002 11:23:59

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

MAXIMUM PEAK OUTPUT POWER

SUBCLAUSE § 15.247 (b) (1)

(conducted)

Channel 3



Marker 1 [T1]

RBW 3 MHz RF Att 10 dB

Ref Lvl

1.41 dBm

VBW 3 MHz

4 dBm


2.47986774 GHz

SWT

5 ms

Unit

dBm



Date: 1.FEB.2002 11:23:31

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

**MAXIMUM PEAK OUTPUT POWER
(RADIATED)**

SUBCLAUSE § 15.247 (b) (1)

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (mW)		
Frequency (MHz)		2402	2441	2480
T _{nom} (23,5)°C	V _{nom} (3,6)V	2.037	2.042	1.671
Maximum deviation from output power under extreme test conditions (dBc)		not applicable	not applicable	not applicable
Measurement uncertainty		±3dB		

RBW/VBW : 3 MHz

Measured at a distance of 3m

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance of conducted emissions

§15.247 (c)

Low frequency section (hopping off)



Date: 1.FEB.2002 11:45:09

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

Band-edge compliance of conducted emissions

§15.247 (c)

Low frequency section (hopping on)


 Ref Lvl 111 dBµV
 Marker 1 [T1] 60.25 dBµV
 2.39992986 GHz
 RBW 100 kHz
 VBW 100 kHz
 SWT 5 ms
 RF Att 10 dB
 Unit dBµV



Date: 1.FEB.2002 11:47:33

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01

Issue date: 2002-02-06

Page 28 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance of conducted emissions

§15.247 (c)

high frequency section (hopping off)



Date: 1.FEB.2002 11:52:35

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance of conducted emissions

§15.247 (c)

high frequency section (hopping on)




Date: 1.FEB.2002 11:50:18

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance radiated



Limit Line 54 dBμV/m


REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance radiated



This measurement was made to show that the behavior of the system is conform to

FCC 15.205 (restricted bands)


REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance radiated



This measurement was made to show that the behavior of the system is conform to

FCC 15.205 (restricted bands)


REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

Band-edge compliance radiated



This measurement was made to show that the behavior of the system is conform to FCC 15.205 (restricted bands)

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

EMISSION LIMITATIONS					
f (MHz)		amplitude of emission (dBm)	limit max. allowed emmission power	actual attenuation below frequency of operation (dB)	results
2402		+0.45	30 dBm	-	Operating frequency
all peaks <<limit			-20 dBc	see plot	complies
2441		+2.10	30 dBm	-	Operating frequency
all peaks <<limit			-20 dBc	see plot	complies
2480		+1.41	30 dBm		Operating frequency
all peaks <<limit			-20 dBc	see plot	complies
Measurement uncertainty		± 3dB			

RBW : 100 kHz VBW: 1 MHz

For emissions that fall into restricted bands you find the radiated emissions later in the report.

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

Channel 1: 30 MHz - 25 GHz

	Ref Lvl	Marker 1 [T1]	RBW	100 kHz	RF Att	10 dB
	91 dBμV	56.33 dBμV	VBW	1 MHz		
		2.40215631 GHz	SWT	6.4 s	Unit	dBμV



Date: 1.FEB.2002 11:31:41

RBW:100 kHz / VBW: 1MHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01

Issue date: 2002-02-06

Page 36 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

Channel 2: 30 MHz – 25 GHz



Date: 1.FEB.2002 11:35:18

RBW:100 kHz / VBW: 1MHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

Channel 3: 30 MHz – 25 GHz



Date: 1.FEB.2002 11:36:32

RBW:100 kHz / VBW: 1MHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 38 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

SPURIOUS RADIATED EMISSION

§ 15.247 (c) (1)

Channel 0 (2402 MHz)

Data File : /10138_15.DOC

29 Jan 2002

No	EMISSION	SPEC	MEASUREMENTS			POL	SITE		CORR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE		HGT	AZM		
		LIMIT					cm	deg	FACTOR	
		dBuV		dB					dB	
1	56.8	29.5	17.0	-12.6	PK	V	100	0	N/T	
2	150.8	33.0	22.8	-10.2	PK	V	100	0	N/T	

Channel 39 (2441 MHz)

Data File : /10138_20.DOC

29 Jan 2002

No	EMISSION	SPEC	MEASUREMENTS			POL	SITE		CORR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE		HGT	AZM		
		LIMIT					cm	deg	FACTOR	
		dBuV		dB					dB	
1	55.9	29.5	17.9	-11.6	PK	V	97	0	N/T	
2	151.5	33.0	22.4	-10.6	PK	V	97	33	N/T	

Channel 78 (2480 MHz)

Data File : /10138_25.DOC

29 Jan 2002

No	EMISSION	SPEC	MEASUREMENTS			POL	SITE		CORR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE		HGT	AZM		
		LIMIT					cm	deg	FACTOR	
		dBuV		dB					dB	
1	57.9	29.5	17.7	-11.8	PK	V	97	313	N/T	
2	149.9	33.0	22.2	-10.8	PK	V	97	260	N/T	

N/T in CORR FACTOR column denotes a non-traceable signal.

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : NPL-1with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 44 (76)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 51 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter)

CLAUSE § 15.247 (c) (1)

Channel 1-3 (this is valid for all 3 channels)

Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 34.26 dBμV VBW 10 MHz
 98 dBμV 18.00000000 GHz SWT 34 ms Unit dBμV



Date: 1.FEB.2002 11:57:29

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
 (for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 52 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

EMISSION LIMITATIONS (Transmitter)

CLAUSE § 15.247 (c) (1)

Channel 1-3 (this is valid for all 3 channels)


 Ref Lvl 98 dBµV
 Marker 1 [T1] 34.48 dBµV
 18.00000000 GHz
 RBW 1 MHz RF Att 0 dB
 VBW 10 MHz
 SWT 40 ms Unit dBµV



Date: 1.FEB.2002 11:57:00

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 1_0138-06-05/01 Issue date: 2002-02-06 Page 53 (76)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

RECEIVER SPURIOUS RADIATION Radiated

§ 15.109

Data File : /10138_35.DOC

30 Jan 2002

No	EMISSION	SPEC	MEASUREMENTS			SITE			CORR	COMMENTS
	FREQUENCY MHz	LIMIT dBuV	ABS	dLIM dB	MODE	POL	HGT cm	AZM deg	FACTOR dB	
1	54.7	29.5	18.3	-11.2	PK	V	97	0	N/T	
2	156.3	33.0	23.4	-9.6	PK	V	97	0	N/T	

N/T in CORR FACTOR column denotes a non-traceable signal.

SPURIOUS EMISSIONS LEVEL (µV/m)								
CH 1 / 2 / 3								
f (MHz)	Detector	Level (µV/m)	f (MHz)	Detector	Level (µV/m)	f (MHz)	Detector	Level (µV/m)
4659.4	AV	31.4						
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Measurement distance see table

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C

Relative humidity : 33%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

RECEIVER SPURIOUS RADIATION

§ 15.109

Peak 12 – 18 GHz


 Ref Lvl 34.48 dBµV
 98 dBµV 18.00000000 GHz
 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 VBW 10 MHz
 SWT 34 ms Unit dBµV



Date: 1.FEB.2002 11:58:48

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E

Ambient temperature : 23,6°C


Relative humidity : 33%

RECEIVER SPURIOUS RADIATION

§ 15.109

Peak 18 – 25 GHz


 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 34.48 dBµV VBW 10 MHz
 98 dBµV 18.00000000 GHz SWT 40 ms Unit dBµV



Date: 1.FEB.2002 11:58:29

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

CONDUCTED EMISSIONS

§ 15.207

Line-L1



Frequency	Peak	QP	Lim	QP	DelLim-QP	Avg	Lim	Avg	DelLim-Avg
MHz	dBuV		dBuV	dBuV	dB		dBuV	dBuV	dB
0.644329	32.67		48.00	18.55	-29.45		48.00	9.37	-38.63
0.805171	24.74		48.00	13.29	-34.71		48.00	-4.15	-52.15
7.257418	29.02		48.00	11.95	-36.05		48.00	-2.48	-50.48
8.799101	28.05		48.00	7.91	-40.09		48.00	2.50	-45.50
20.161127	21.60		48.00	0.76	-47.24		48.00	-10.68	-58.68

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : NPL-1 with DCH-8D, ACP-12E


Ambient temperature : 23,6°C

Relative humidity : 33%

CONDUCTED EMISSIONS

§ 15.207

Line N



Frequency MHz	Peak dBuV	QP	Lim dBuV	QP dBuV	DelLim-QP dB	Avg Lim dBuV	Avg dBuV	DelLim-Avg dB
0.530047	29.81	48.00	26.55	-21.45	48.00	10.35	-37.65	
0.654387	24.43	48.00	18.68	-29.32	48.00	2.65	-45.35	
4.593020	28.89	48.00	11.69	-36.31	48.00	-4.40	-52.40	
5.132519	28.12	48.00	13.01	-34.99	48.00	-5.80	-53.80	
11.643269	26.32	48.00	4.62	-43.38	48.00	-8.69	-56.69	

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	8566 A	Hewlett-Packard	1925A00257
02	Analyzer Display	8566 A	Hewlett-Packard	1925A00860
03	Oscilloscope	7633	Tektronix	230054
04	Radio Analyzer	CMTA 54	Rohde & Schwarz	894 043/010
05	System Power Supply	6038 A	Hewlett-Packard	2848A07027
06	Signal Generator	8111 A	Hewlett-Packard	2215G00867
07	Signal Generator	8662 A	Hewlett-Packard	2224A01012
08	Funktionsgenerator	AFGU	Rohde & Schwarz	862 480/032
09	Regeltrenntrafo	MPL	Erfi	91350
10	Netznachbildung	NNLA 8120	Schwarzbeck	8120331
11	Relais-Matrix	PSU	Rohde & Schwarz	893 285/020
12	Power-Meter	436 A	Hewlett-Packard	2101A12378
13	Power-Sensor	8484 A	Hewlett-Packard	2237A10156
14	Power-Sensor	8482 A	Hewlett-Packard	2237A00616
15	Modulationsmeter	9008	Racal-Dana	2647
16	Frequenzzähler	5340 A	Hewlett-Packard	1532A03899
17	Absorber Schirmkabine	---	MWB	87400/002
18	Spectrum Analyzer	85660 B	Hewlett-Packard	2747A05306
19	Analyzer Display	85662 A	Hewlett-Packard	2816A16541
20	Quasi Peak Adapter	85650 A	Hewlett-Packard	2811A01131
21	RF-Preselector	85685 A	Hewlett-Packard	2833A00768
22	Biconical Antenne	3104	Emco	3758
23	Log. Per. Antenne	3146	Emco	2130
24	Double Ridge Horn	3115	Emco	3088
25	EMI-Testreceiver	ESAI	Rohde & Schwarz	863 180/013
26	EMI-Analyzer-Display	ESAI-D	Rohde & Schwarz	862 771/008
27	Biconical Antenne	HK 116	Rohde & Schwarz	888 945/013
28	Log. Per. Antenne	HL 223	Rohde & Schwarz	825 584/002
29	Relais-Switch-Unit	RSU	Rohde & Schwarz	375 339/002
30	Highpass	HM985955	FSY Microwave	001
31	Amplifier	P42-GA29	Tron-Tech	B 23602
32	Absorber Schirmkabine		Frankonia	
33	Steuerrechner	PSM 7	Rohde & Schwarz	834 621/004
34	EMI Test Receiver	ESMI	Rohde & Schwarz	827 063/010
35	EMI Test Receiver	Display	Rohde & Schwarz	829 808/010

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
36	Controler	HD 100	Deisel	100/322/93
37	Relais Matrix	PSN	Rohde & Schwarz	829 065/003
38	Control Unit	GB 016 A2	Rohde & Schwarz	344 122/008
39	Relais Switch Unit	RSU	Rohde & Schwarz	316 790/001
40	Power Supply	6032A	Hewlett Packard	2846A04063
41	Spektrum Monitor	EZM	Rohde & Schwarz	883 720/006
42	Meßempfänger	ESH 3	Rohde & Schwarz	890 174/002
43	Meßempfänger	ESVP	Rohde & Schwarz	891 752/005
44	Biconi Ant. 20-300MHz	HK 116	Rohde & Schwarz	833 162/011
45	Logper Ant. 0.3-1 GHz	HL 223	Rohde & Schwarz	832 914/010
46	Amplifier 0.1-4 GHz	AFS4	Miteq Inc.	206461
47	Logper Ant. 1-18 GHz	HL 024 A2	Rohde & Schwarz	342 662/002
48	Polarisationsnetzwerk	HL 024 Z1	Rohde & Schwarz	341 570/002
49	Double Ridge G Horn Antenne 1-26.5 GHz	3115	EMCO	9107-3696
50	Microw. Sys. Amplifier 0.5- 26.5 GHz	8317A	Hewlett Packard	3123A00105
51	Audio Analyzer	UPD	Rohde & Schwarz	1030.7500.04
52	Steuerrechner	PSM 7	Rohde & Schwarz	883 086/026
53	DC V-Netzwerk	ESH3-Z6	Rohde & Schwarz	861 406/005
54	DC V-Netzwerk	ESH3-Z6	Rohde & Schwarz	893 689/012
55	AC 2 Phasen V- Netzwerk	ESH3-Z5	Rohde & Schwarz	861 189/014
56	AC 2 Phasen V- Netzwerk	ESH3-Z5	Rohde & Schwarz	894 981/019
57	AC-3 Phasen V- Netzwerk	ESH2-Z5	Rohde & Schwarz	882 394/007
58	Stromversorgung	6032A	Rohde & Schwarz	2933A05441
59	HF-Test Empfänger	ESVP.52	Rohde & Schwarz	881 487/021
60	Spectrum Monitor	EZM	Rohde & Schwarz	883 086/026
61	HF-Test Empfänger	ESH3	Rohde & Schwarz	881 515/002
62	Relais Matrix	PSU	Rohde & Schwarz	882 943/029
63	Relais Matrix	PSU	Rohde & Schwarz	828 628/007
64	Spectrum Analyzer	FSIQ 26	Rohde & Schwarz	119.6001.27
65	Spectrum Analyzer	HP 8565E	Hewlett Packard	3473A00773
66				