

RF Exposure Report

Report No.: MFBDBQ-WTW-P22030274

FCC ID: JUP-TD540

Test Model: TD540-W

Series Model: TD540

Received Date: Mar. 18, 2022

Date of Evaluation: May 26, 2022

Issued Date: Jun. 14, 2022

Applicant: Trimble Inc.

Address: 935 Stewart Drive, Sunnyvale, CA 94085, USA.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6
4 Conclusion	6

Release Control Record

Issue No.	Description	Date Issued
MFBDDBQ-WTW-P22030274	Original Release	Jun. 14, 2022

1 Certificate of Conformity

Product: 10" Touch Display

Brand: Trimble

Test Model: TD540-W

Series Model: TD540

Sample Status: Engineering Sample

Applicant: Trimble Inc.

Date of Evaluation: May 26, 2022

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Gina Liu, **Date:** Jun. 14, 2022
Gina Liu / Specialist

Approved by : Jeremy Lin, **Date:** Jun. 14, 2022
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

Maximum measured transmitter power:

Frequency (MHz)	Electric field (dBuV/m) @3m	Max. Power EIRP (dBm)	Max. Power EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
13.56	59.80	-35.43	0.0002864	0.00000006	0.978

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	2412-2462	20.97	5.57	20	0.090	1.00
	5180-5240	20.76	7.15	20	0.123	1.00
	5260-5320	21.06	7.15	20	0.132	1.00
	5500-5700	21.03	7.15	20	0.131	1.00
	5745-5825	22.41	7.15	20	0.180	1.00
BT EDR	2402-2480	3.57	2.68	20	0.001	1.00
BT LE	2402-2480	3.62	2.68	20	0.001	1.00

Note:

1. The EUT contains certified WLAN+BT module (Brand: AzureWave, Model: AW-CM276NF, FCC ID: TLZ-CM276NF).
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
3. Calculate SAR test exclusion thresholds from condition "3" formulas.
4. Field Strength (dBuV/m@3m) = Field Strength (dBuV/m@30m) + 40*log(30/3).
5. Max Power (dBm) = Field Strength of Fundamental (dBuV/m@3m) – 95.23,
Max Power (mW) = $10^{(\text{Max power (dBm)}/10)}$

4 Conclusion

Both of the WLAN, BT and NFC can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

For WLAN and BT density data, please refer to report no.: MFBECO-WTW-P20100054F

$$\text{WLAN 5GHz} + \text{BT} + \text{NFC} = 0.180/1 + 0.001/1 + 0.00000006/0.978 = 0.181$$

$$\text{WLAN 2.4GHz} + \text{BT} + \text{NFC} = 0.090/1 + 0.001/1 + 0.00000006/0.978 = 0.091$$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---