



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 <http://www.sz-ctc.org.cn>

TEST REPORT

Report No. : **CTC20240361E10**

FCC ID : **2APN5ZBBRIDGEU**

IC : **29127-ZBBRIDGEU**

Applicant : **Shenzhen Sonoff Technologies Co.,Ltd.**

Address : 3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

Manufacturer : Shenzhen Sonoff Technologies Co.,Ltd.

Address : 3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

Product Name : **Zigbee Bridge**

Trade Mark :  , Sonoff

Model/Type reference : ZBBridge-U

Listed Model(s) : /

Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS-247 Issue 3**

Date of receipt of test sample : Feb. 18, 2024

Date of testing : Feb. 18, 2024 to Apr. 17, 2024

Date of issue : Apr. 28, 2024

Result : **PASS**

Compiled by:

(Printed name+signature)


Jim Jiang



Supervised by:

(Printed name+signature)

Eric Zhang



Approved by:

(Printed name+signature)

Totti Zhao



This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The Test Result in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely corresponds to the test sample.



Table of Contents

Page

1. TEST SUMMARY	3
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION	3
1.3. TEST DESCRIPTION.....	3
1.4. TEST FACILITY	4
1.5. MEASUREMENT UNCERTAINTY	5
1.6. ENVIRONMENTAL CONDITIONS.....	5
2. GENERAL INFORMATION	6
2.1. CLIENT INFORMATION	6
2.2. GENERAL DESCRIPTION OF EUT	6
2.3. ACCESSORY EQUIPMENT INFORMATION	7
2.4. OPERATION STATE	8
2.5. MEASUREMENT INSTRUMENTS LIST	10
3. TEST ITEM AND RESULTS	12
3.1. CONDUCTED EMISSION.....	12
3.2. RADIATED EMISSION.....	15
3.3. BAND EDGE EMISSIONS (RADIATED)	32
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED)	49
3.5. DTS BANDWIDTH.....	66
3.6. PEAK OUTPUT POWER	76
3.7. POWER SPECTRAL DENSITY	78
3.8. DUTY CYCLE	84
3.9. ANTENNA REQUIREMENT.....	90



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Operation within the bands 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz.

[RSS-247 Issue 3](#): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

[RSS-Gen Issue 5](#): General Requirements for Compliance of Radio Apparatus.

[ANSI C63.10-2013](#): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

1.2. Report Version

Revised No.	Report No.	Date of issue	Description
01	CTC20240361E10	Apr. 28, 2024	Original

1.3. Test Description

FCC Part 15 Subpart C (15.247) / RSS-247 Issue 3				
Test Item	Standard Section		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203	RSS-Gen 6.8	Pass	Jim Jiang
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Seth Chen
Conducted Band Edge and Spurious Emissions	15.247(d)	RSS-247 5.5	Pass	Jim Jiang
Radiated Band Edge and Spurious Emissions	15.205&15.209&15.247(d)	RSS-247 5.5	Pass	Jim Jiang
6dB Bandwidth	15.247(a)(2)	RSS-247 5.2 (a)	Pass	Jim Jiang
Conducted Max Output Power	15.247(b)(3)	RSS-247 5.4 (d)	Pass	Jim Jiang
Power Spectral Density	15.247(e)	RSS-247 5.2 (b)	Pass	Jim Jiang
Transmitter Radiated Spurious	15.209&15.247(d)	RSS-247 5.5&RSS-Gen 8.9	Pass	Jim Jiang

Note:

- The measurement uncertainty is not included in the test result.
- N/A: means this test item is not applicable for this device according to the technology characteristic of device.



1.4. Test Facility

Address of the report laboratory

CTC Laboratories, Inc.

Add: 2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.



1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.

Test Items	Measurement Uncertainty	Notes
DTS Bandwidth	$\pm 0.0196\%$	(1)
Maximum Conducted Output Power	± 0.686 dB	(1)
Maximum Power Spectral Density Level	± 0.743 dB	(1)
Band-edge Compliance	± 1.328 dB	(1)
Unwanted Emissions In Non-restricted Freq Bands	9kHz-1GHz: ± 0.746 dB 1GHz-26GHz: ± 1.328 dB	(1)
Conducted Emissions 9kHz~30MHz	± 3.08 dB	(1)
Radiated Emissions 30~1000MHz	± 4.51 dB	(1)
Radiated Emissions 1~18GHz	± 5.84 dB	(1)
Radiated Emissions 18~40GHz	± 6.12 dB	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.6. Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15 °C to 35 °C
Relative Humidity:	20 % to 75 %
Air Pressure:	101 kPa



2. GENERAL INFORMATION

2.1. Client Information

Applicant:	Shenzhen Sonoff Technologies Co.,Ltd.
Address:	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Sonoff Technologies Co.,Ltd.
Address:	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

2.2. General Description of EUT

Product Name:	Zigbee Bridge
Trade Mark:	 SONOFF , Sonoff
Model/Type reference:	ZBBridge-U
Listed Model(s):	/
Model Difference:	/
Power Supply:	Input: 5V---1A
RF Module:	6223A-SRD
Hardware Version:	V1.2
Software Version:	V1.0.0
2.4G WiFi	
Modulation:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/ n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Operation Frequency:	802.11b/ g/ n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Channel Number:	802.11b/ g/ n(HT20): 11 channels 802.11n(HT40): 7 channels
Channel Separation:	5MHz
Antenna Type:	SUS Antenna
Directional Gain:	2.5dBi



2.3. Accessory Equipment Information

Equipment Information			
Name	Model	S/N	Manufacturer
Notebook	ThinkPad T460s	/	Lenovo
Cable Information			
Name	Shielded Type	Ferrite Core	Length
USB Cable	Unshielded	NO	120cm
Test Software Information			
Name	Version	/	/
adb tool	/	/	/



2.4. Operation State

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

Operation Frequency List:

Channel	Frequency (MHz)
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note: CH 01~CH 11 for 802.11b/g/n(HT20), CH 03~CH 09 for 802.11n(HT40).

Data Rated:

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Test Mode	Data Rate (worst mode)
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)/(HT40)	HT-MCS0



Test Mode:

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

The worse case configurations:

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band		
Test Software	adb tool	
Modulation Mode	Test Channel	Attenuation
802.11b	01	58
	06	58
	11	58
802.11g	01	58
	06	58
	11	58
802.11n(HT20)	01	58
	06	58
	11	58
802.11n(HT40)	03	58
	06	58
	09	58



2.5. Measurement Instruments List

Tonscend RF Test System					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 21, 2025
2	Spectrum Analyzer	R&S	FSV40-N	101654	Aug. 07, 2024
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 12, 2024
4	MXA Signal Analyzer	Keysight	N9020A	MY46471737	Dec. 12, 2024
5	MXA Signal Analyzer	Keysight	N9020A	MY52091402	Aug. 22, 2024
6	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 12, 2024
7	PSG Analog Signal Generator	Agilent	E8257D	MY46521908	Dec. 12, 2024
8	EXG Analog Signal Generator	Keysight	N5173B	MY59100842	Dec. 12, 2024
9	MXG Vector Signal Generator	Keysight	N5182B	MY59100212	Dec. 12, 2024
10	USB Wideband Power Sensor	Keysight	U2021XA	MY55130004	Mar. 21, 2025
11	USB Wideband Power Sensor	Keysight	U2021XA	MY55130006	Mar. 21, 2025
12	Wideband Radio Communication Tester	R&S	CMW500	102257	May 25, 2024
13	Wideband Radio Communication Tester	R&S	CMW500	102414	Dec. 12, 2024
14	RF Control Unit	Tonscend	JS0806-2	/	Aug. 22, 2024
15	High and low temperature test chamber	ESPEC	MT3035	/	Mar. 21, 2025

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9163	01026	Dec. 18, 2024
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Sep. 25, 2025
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 12, 2024
4	Broadband Amplifier	SCHWARZBECK	BBV9743B	259	Dec. 12, 2024
5	Mirowave Broadband Amplifier	SCHWARZBECK	BBV9718C	111	Dec. 12, 2024
6	3m chamber 3	YIHENG	EE106	/	Aug. 28, 2026
7	Test Software	FARA	EZ-EMC	FA-03A2	/



Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	LISN	R&S	ENV216	101112	Dec. 12, 2024
2	LISN	R&S	ENV216	101113	Dec. 12, 2024
3	EMI Test Receiver	R&S	ESCS30	100353	Dec. 12, 2024
4	ISN CAT6	Schwarzbeck	NTFM 8158	CAT6-8158-0046	Dec. 12, 2024
5	ISN CAT5	Schwarzbeck	NTFM 8158	CAT5-8158-0046	Dec. 12, 2024
6	Test Software	R&S	EMC32	6.10.10	/

Note: 1. The Cal. Interval was one year.

2. The Cal. Interval was three years of the antenna.

3. The cable loss has been calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207 / RSS-Gen 8.8

Frequency (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration



Test Procedure


1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm / 50 μH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Test Voltage:	AC 120V/60Hz
Terminal:	Line
Remark:	Only worse case is reported

**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.478500	45.4	1000.00	9.000	On	L1	9.5	11.0	56.4	
1.581000	42.5	1000.00	9.000	On	L1	9.5	13.5	56.0	
2.067000	41.8	1000.00	9.000	On	L1	9.5	14.2	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.483000	40.0	1000.00	9.000	On	L1	9.5	6.3	46.3	
1.612500	35.7	1000.00	9.000	On	L1	9.5	10.3	46.0	
2.067000	33.1	1000.00	9.000	On	L1	9.5	12.9	46.0	

Emission Level = Read Level + Correct Factor



Test Voltage:	AC 120V/60Hz
Terminal:	Neutral
Remark:	Only worse case is reported



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.271500	35.5	1000.00	9.000	On	N	9.4	25.6	61.1	
1.558500	29.0	1000.00	9.000	On	N	9.4	27.0	56.0	
2.031000	26.2	1000.00	9.000	On	N	9.4	29.8	56.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.483000	21.5	1000.00	9.000	On	N	9.4	24.8	46.3	
0.834000	25.2	1000.00	9.000	On	N	9.4	20.8	46.0	
23.127000	25.7	1000.00	9.000	On	N	9.5	24.3	50.0	

Emission Level = Read Level + Correct Factor

3.2. Radiated Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.209 / RSS-Gen 8.9


Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Frequency Range (MHz)	dBμV/m (at 3 meters)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBμV/m)=20log Emission Level (μV/m).


Test Configuration



Below 30MHz Test Setup



30-1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;



(2) 9k – 150kHz:

RBW=300 Hz, VBW=1 kHz, Sweep=auto, Detector function=peak, Trace=max hold

(3) 0.15M – 30MHz:

RBW=10 kHz, VBW=30 kHz, Sweep=auto, Detector function=peak, Trace=max hold

(4) 30M - 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

(5) From 1 GHz to 10th harmonic:

RBW=1MHz, VBW=3MHz Peak detector for Peak value.

RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.

Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result


9 kHz~30 MHz

From 9 kHz to 30 MHz: The conclusion is PASS.

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




30MHz-1GHz





Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.9940	44.60	-15.73	28.87	40.00	-11.13	QP
2 *	49.8814	48.44	-15.80	32.64	40.00	-7.36	QP
3	231.7179	50.66	-16.79	33.87	46.00	-12.13	QP
4	298.2681	51.38	-15.12	36.26	46.00	-9.74	QP
5	796.1830	39.52	-5.43	34.09	46.00	-11.91	QP
6	896.9965	39.57	-4.06	35.51	46.00	-10.49	QP

Remarks:

- Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Margin value = Level -Limit value



Above 1GHz

Ant. Pol.		Horizontal						
Test Mode:		TX 802.11b Mode 2412MHz						
Remark:		No report for the emission which more than 20 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	
1	4822.667	52.81	2.01	54.82	74.00	-19.18	peak	
2 *	4822.667	49.54	2.01	51.55	54.00	-2.45	AVG	
3	7235.333	44.48	10.03	54.51	74.00	-19.49	peak	
4	7235.333	37.92	10.03	47.95	54.00	-6.05	AVG	
5	8696.250	39.64	11.21	50.85	74.00	-23.15	peak	
6	10278.583	39.20	13.71	52.91	74.00	-21.09	peak	
7	11195.083	38.48	14.76	53.24	74.00	-20.76	peak	
8	12413.167	37.94	15.53	53.47	74.00	-20.53	peak	
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value								

Ant. Pol.		Vertical						
Test Mode:		TX 802.11b Mode 2412MHz						
Remark:		No report for the emission which more than 20 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	
1	4822.667	50.63	2.01	52.64	74.00	-21.36	peak	
2	7235.333	41.61	10.03	51.64	74.00	-22.36	peak	
3	8003.000	39.94	10.86	50.80	74.00	-23.20	peak	
4	9577.500	39.55	12.59	52.14	74.00	-21.86	peak	
5	10815.167	39.02	14.47	53.49	74.00	-20.51	peak	
6 *	12479.750	37.94	15.72	53.66	74.00	-20.34	peak	
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value								



Ant. Pol.	Horizontal						
Test Mode:	TX 802.11b Mode 2437MHz						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4873.583	51.40	2.09	53.49	74.00	-20.51	peak
2	7309.750	44.45	10.07	54.52	74.00	-19.48	peak
3 *	7309.750	41.26	10.07	51.33	54.00	-2.67	AVG
4	8704.083	40.71	11.22	51.93	74.00	-22.07	peak
5	9785.083	39.41	12.92	52.33	74.00	-21.67	peak
6	10533.167	39.18	13.98	53.16	74.00	-20.84	peak
7	12593.333	37.21	16.05	53.26	74.00	-20.74	peak
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							

Ant. Pol.	Vertical						
Test Mode:	TX 802.11b Mode 2437MHz						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1501.333	58.94	-6.88	52.06	74.00	-21.94	peak
2	4873.583	49.76	2.09	51.85	74.00	-22.15	peak
3	7313.667	45.85	10.07	55.92	74.00	-18.08	peak
4 *	7313.667	41.76	10.07	51.83	54.00	-2.17	AVG
5	9142.750	39.31	12.18	51.49	74.00	-22.51	peak
6	11163.750	38.74	14.75	53.49	74.00	-20.51	peak
7	12436.667	37.79	15.59	53.38	74.00	-20.62	peak
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							



Ant. Pol.		Horizontal						
Test Mode:		TX 802.11b Mode 2462MHz						
Remark:		No report for the emission which more than 20 dB below the prescribed limit.						
	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
	1	4924.500	52.39	2.16	54.55	74.00	-19.45	peak
	2 *	4924.500	48.17	2.16	50.33	54.00	-3.67	AVG
	3	7388.083	44.93	10.09	55.02	74.00	-18.98	peak
	4	7388.083	39.59	10.09	49.68	54.00	-4.32	AVG
	5	9150.583	38.81	12.20	51.01	74.00	-22.99	peak
	6	10380.417	38.97	13.86	52.83	74.00	-21.17	peak
	7	11065.833	38.57	14.70	53.27	74.00	-20.73	peak
	8	11974.500	37.82	15.41	53.23	74.00	-20.77	peak
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value								

Ant. Pol.	Vertical						
Test Mode:	TX 802.11b Mode 2462MHz						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2692.000	47.90	-2.70	45.20	74.00	-28.80	peak
2	4924.500	50.05	2.16	52.21	74.00	-21.79	peak
3 *	7384.167	43.77	10.09	53.86	74.00	-20.14	peak
4	9655.833	40.47	12.70	53.17	74.00	-20.83	peak
5	11543.667	38.31	15.03	53.34	74.00	-20.66	peak
6	12616.833	37.35	16.12	53.47	74.00	-20.53	peak
Remarks:							
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor							
2.Margin value = Level -Limit value							



Ant. Pol.	Horizontal
Test Mode:	TX 802.11g Mode 2412MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4807.000	42.84	2.00	44.84	74.00	-29.16	peak
2	6397.167	40.48	7.05	47.53	74.00	-26.47	peak
3	7846.333	39.99	10.52	50.51	74.00	-23.49	peak
4	9675.417	39.82	12.73	52.55	74.00	-21.45	peak
5	11343.917	38.55	14.83	53.38	74.00	-20.62	peak
6 *	12722.583	37.39	16.37	53.76	74.00	-20.24	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11g Mode 2412MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1195.833	54.87	-7.73	47.14	74.00	-26.86	peak
2	3945.333	42.39	0.33	42.72	74.00	-31.28	peak
3	6553.833	38.95	7.46	46.41	74.00	-27.59	peak
4	8852.917	39.79	11.48	51.27	74.00	-22.73	peak
5	10967.917	38.64	14.63	53.27	74.00	-20.73	peak
6 *	11931.417	38.39	15.33	53.72	74.00	-20.28	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11g Mode 2437MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3487.083	49.83	-1.28	48.55	74.00	-25.45	peak
2	4807.000	41.50	2.00	43.50	74.00	-30.50	peak
3	7254.917	38.70	10.04	48.74	74.00	-25.26	peak
4	9213.250	39.03	12.38	51.41	74.00	-22.59	peak
5	11473.167	38.52	14.93	53.45	74.00	-20.55	peak
6 *	12479.750	38.02	15.72	53.74	74.00	-20.26	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11g Mode 2437MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4873.583	41.96	2.09	44.05	74.00	-29.95	peak
2	7176.583	38.53	9.89	48.42	74.00	-25.58	peak
3	8849.000	38.92	11.47	50.39	74.00	-23.61	peak
4	10157.167	39.39	13.49	52.88	74.00	-21.12	peak
5	11265.583	38.66	14.79	53.45	74.00	-20.55	peak
6 *	12468.000	38.03	15.69	53.72	74.00	-20.28	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11g Mode 2462MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4920.583	42.23	2.15	44.38	74.00	-29.62	peak
2	6538.167	39.55	7.42	46.97	74.00	-27.03	peak
3	7399.833	39.44	10.10	49.54	74.00	-24.46	peak
4	9240.667	37.92	12.40	50.32	74.00	-23.68	peak
5	10470.500	39.40	13.93	53.33	74.00	-20.67	peak
6 *	12397.500	37.98	15.50	53.48	74.00	-20.52	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11g Mode 2462MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.500	45.94	2.16	48.10	74.00	-25.90	peak
2	6401.083	40.46	7.07	47.53	74.00	-26.47	peak
3	8351.583	40.79	10.49	51.28	74.00	-22.72	peak
4	9585.333	39.04	12.60	51.64	74.00	-22.36	peak
5	10783.833	38.80	14.43	53.23	74.00	-20.77	peak
6 *	12495.417	37.60	15.77	53.37	74.00	-20.63	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT20) Mode 2412MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5089.000	40.55	2.53	43.08	74.00	-30.92	peak
2	8053.917	39.23	10.73	49.96	74.00	-24.04	peak
3	9154.500	39.54	12.22	51.76	74.00	-22.24	peak
4	9937.833	38.99	13.11	52.10	74.00	-21.90	peak
5	10713.333	38.55	14.28	52.83	74.00	-21.17	peak
6 *	12111.583	37.82	15.60	53.42	74.00	-20.58	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT20) Mode 2412MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2797.750	48.64	-2.60	46.04	74.00	-27.96	peak
2	4932.333	43.01	2.17	45.18	74.00	-28.82	peak
3	6408.917	39.84	7.09	46.93	74.00	-27.07	peak
4	7536.917	40.22	10.08	50.30	74.00	-23.70	peak
5 *	10740.750	39.13	14.34	53.47	74.00	-20.53	peak
6	12726.500	36.78	16.38	53.16	74.00	-20.84	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT20) Mode 2437MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.500	42.01	2.16	44.17	74.00	-29.83	peak
2	7204.000	39.24	10.02	49.26	74.00	-24.74	peak
3	8277.167	39.86	10.43	50.29	74.00	-23.71	peak
4	9268.083	38.88	12.43	51.31	74.00	-22.69	peak
5	10842.583	38.83	14.50	53.33	74.00	-20.67	peak
6 *	12260.417	37.92	15.65	53.57	74.00	-20.43	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT20) Mode 2437MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4916.667	42.34	2.15	44.49	74.00	-29.51	peak
2	7975.583	39.61	10.81	50.42	74.00	-23.58	peak
3	8833.333	39.89	11.46	51.35	74.00	-22.65	peak
4	9847.750	38.72	12.99	51.71	74.00	-22.29	peak
5	11394.833	38.57	14.85	53.42	74.00	-20.58	peak
6 *	12652.083	37.33	16.20	53.53	74.00	-20.47	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT20) Mode 2462MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.500	43.14	2.16	45.30	74.00	-28.70	peak
2	6318.833	40.22	6.74	46.96	74.00	-27.04	peak
3	7952.083	40.05	10.76	50.81	74.00	-23.19	peak
4	9228.917	38.85	12.39	51.24	74.00	-22.76	peak
5	10431.333	39.24	13.91	53.15	74.00	-20.85	peak
6 *	12099.833	37.91	15.59	53.50	74.00	-20.50	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT20) Mode 2462MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2789.917	44.65	-2.60	42.05	74.00	-31.95	peak
2	4924.500	41.35	2.16	43.51	74.00	-30.49	peak
3	6377.583	39.28	6.97	46.25	74.00	-27.75	peak
4	8523.917	39.80	10.80	50.60	74.00	-23.40	peak
5	10302.083	39.47	13.74	53.21	74.00	-20.79	peak
6 *	11669.000	38.31	15.11	53.42	74.00	-20.58	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3929.667	41.65	0.26	41.91	74.00	-32.09	peak
2	6522.500	39.00	7.37	46.37	74.00	-27.63	peak
3	7877.667	38.95	10.59	49.54	74.00	-24.46	peak
4	8802.000	40.45	11.41	51.86	74.00	-22.14	peak
5	11120.667	38.56	14.73	53.29	74.00	-20.71	peak
6 *	11994.083	37.95	15.44	53.39	74.00	-20.61	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3976.667	42.25	0.45	42.70	74.00	-31.30	peak
2	6424.583	39.69	7.13	46.82	74.00	-27.18	peak
3	7971.667	39.22	10.81	50.03	74.00	-23.97	peak
4	8766.750	39.44	11.34	50.78	74.00	-23.22	peak
5	10000.500	38.87	13.18	52.05	74.00	-21.95	peak
6 *	11966.667	38.06	15.39	53.45	74.00	-20.55	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2437MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3980.583	41.03	0.46	41.49	74.00	-32.51	peak
2	7211.833	38.88	10.03	48.91	74.00	-25.09	peak
3	7995.167	39.63	10.86	50.49	74.00	-23.51	peak
4	10298.167	38.85	13.74	52.59	74.00	-21.41	peak
5	11700.333	37.65	15.11	52.76	74.00	-21.24	peak
6 *	12452.333	37.33	15.65	52.98	74.00	-21.02	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2437MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3921.833	41.29	0.24	41.53	74.00	-32.47	peak
2	5950.667	39.79	5.48	45.27	74.00	-28.73	peak
3	7987.333	40.06	10.83	50.89	74.00	-23.11	peak
4	9162.333	40.07	12.24	52.31	74.00	-21.69	peak
5	10525.333	39.56	13.97	53.53	74.00	-20.47	peak
6 *	12299.583	38.02	15.61	53.63	74.00	-20.37	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2452MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5633.417	40.24	4.25	44.49	74.00	-29.51	peak
2	7223.583	38.60	10.03	48.63	74.00	-25.37	peak
3	8551.333	39.70	10.88	50.58	74.00	-23.42	peak
4	9232.833	40.13	12.39	52.52	74.00	-21.48	peak
5 *	10779.917	38.92	14.42	53.34	74.00	-20.66	peak
6	12346.583	37.73	15.55	53.28	74.00	-20.72	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2452MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2789.917	48.14	-2.60	45.54	74.00	-28.46	peak
2	6322.750	38.92	6.75	45.67	74.00	-28.33	peak
3	7916.833	39.97	10.68	50.65	74.00	-23.35	peak
4	9217.167	39.37	12.38	51.75	74.00	-22.25	peak
5	10482.250	38.99	13.93	52.92	74.00	-21.08	peak
6 *	12393.583	37.65	15.50	53.15	74.00	-20.85	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value


3.3. Band Edge Emissions (Radiated)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d) / RSS-247 5.5

Restricted Frequency Band (MHz)	(dB μ V/m) (at 3m)	
	Peak	Average
2310 ~ 2390	74	54
2483.5 ~ 2500	74	54

Test Configuration




Test Procedure


1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.


Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.8 Duty Cycle.


Test Mode


Please refer to the clause 2.4.


**Test Result**












































3.4. Band Edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d) / RSS-247 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW $\geq$ RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold.
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.

Test Result

Conducted Band edge

Test Mode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	2.82	-29.95	≤ -17.18	PASS
		High	2462	4.00	-38.36	≤ -16.00	PASS
11G	Ant1	Low	2412	-2.90	-32.46	≤ -22.9	PASS
		High	2462	-1.00	-42.48	≤ -21.00	PASS
11N20SISO	Ant1	Low	2412	-3.32	-33.15	≤ -23.32	PASS
		High	2462	-2.42	-43.01	≤ -22.42	PASS
11N40SISO	Ant1	Low	2422	-5.27	-34.94	≤ -25.27	PASS
		High	2452	-4.75	-37.68	≤ -24.75	PASS



Test Graphs:


11B Ant1 Low 2412



11B Ant1 High 2462



11G Ant1 Low 2412




11G Ant1 High 2462

CTC Laboratories, Inc.


2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



11N20SISO Ant1 Low 2412



11N20SISO Ant1 High 2462



11N40SISO Ant1 Low 2422

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059




Fax: (86)755-27521011 Http://www.sz-ctc.org.cn
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>

**Conducted Spurious Emission**

Test Mode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	1.51	1.51	---	PASS
			30~1000	1.51	-68.65	≤-18.49	PASS
			1000~26500	1.51	-47.81	≤-18.49	PASS
		2437	Reference	2.34	2.34	---	PASS
			30~1000	2.34	-68.07	≤-17.66	PASS
			1000~26500	2.34	-48.53	≤-17.66	PASS
		2462	Reference	3.47	3.47	---	PASS
			30~1000	3.47	-68.18	≤-16.53	PASS
			1000~26500	3.47	-47.61	≤-16.53	PASS
11G	Ant1	2412	Reference	-3.03	-3.03	---	PASS
			30~1000	-3.03	-68.13	≤-23.03	PASS
			1000~26500	-3.03	-48.05	≤-23.03	PASS
		2437	Reference	-5.29	-5.29	---	PASS
			30~1000	-5.29	-68.40	≤-25.29	PASS
			1000~26500	-5.29	-47.71	≤-25.29	PASS
		2462	Reference	-1.49	-1.49	---	PASS
			30~1000	-1.49	-68.54	≤-21.49	PASS
			1000~26500	-1.49	-48.43	≤-21.49	PASS
11N20SISO	Ant1	2412	Reference	-7.20	-7.20	---	PASS
			30~1000	-7.20	-68.41	≤-27.20	PASS
			1000~26500	-7.20	-48.55	≤-27.20	PASS
		2437	Reference	-5.27	-5.27	---	PASS
			30~1000	-5.27	-68.57	≤-25.27	PASS
			1000~26500	-5.27	-47.90	≤-25.27	PASS
		2462	Reference	-2.15	-2.15	---	PASS
			30~1000	-2.15	-68.74	≤-22.15	PASS
			1000~26500	-2.15	-48.16	≤-22.15	PASS
11N40SISO	Ant1	2422	Reference	-6.30	-6.30	---	PASS
			30~1000	-6.30	-68.43	≤-26.30	PASS
			1000~26500	-6.30	-48.67	≤-26.30	PASS
		2437	Reference	-6.28	-6.28	---	PASS
			30~1000	-6.28	-68.43	≤-26.28	PASS
			1000~26500	-6.28	-47.29	≤-26.28	PASS
		2452	Reference	-5.78	-5.78	---	PASS
			30~1000	-5.78	-67.57	≤-25.78	PASS
			1000~26500	-5.78	-47.87	≤-25.78	PASS



Test Graphs:





CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



CTC Laboratories, Inc.


2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 <http://www.sz-ctc.org.cn>




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



11B Ant1 2462 30~1000



11B Ant1 2462 1000~26500



11G Ant1 2412 0~Reference

CTC Laboratories, Inc.


2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



11G Ant1 2412 30~1000



11G Ant1 2412 1000~26500



11G Ant1 2437 0~Reference

CTC Laboratories, Inc.


2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 <http://www.sz-ctc.org.cn>




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



11G Ant1 2437 30~1000



11G Ant1 2437 1000~26500



11G Ant1 2462 0-Reference

CTC Laboratories, Inc.


2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



11G Ant1 2462 30~1000



11G Ant1 2462 1000~26500



11N20SISO_Ant1_2412_0~Reference

CTC Laboratories, Inc.


2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



11N20SISO_Ant1_2412_30~1000



11N20SISO_Ant1_2412_1000~26500



11N20SISO_Ant1_2437_0~Reference

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>