

FCC ID: KA2E15A1
Report No.: T210319W02-RP1

Page: 1 / 119
Rev.: 00

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

Test Standard	FCC Part 15.247
Product name	(1) AX1500 Wi-Fi 6 AI Range Extender; (2) AX1500 Mesh Range Extender
Brand Name	D-Link
Model No.	E15
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:



Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T210319W02-RP1

Page: 2 / 119

Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 10, 2021	Initial Issue	ALL	May Lin

Table of contents

1. GENERAL INFORMATION.....	4
1.1 EUT INFORMATION.....	4
1.2 EUT CHANNEL INFORMATION.....	5
1.3 ANTENNA INFORMATION.....	5
1.4 MEASUREMENT UNCERTAINTY	6
1.5 FACILITIES AND TEST LOCATION.....	7
1.6 INSTRUMENT CALIBRATION	7
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT	9
1.8 TEST METHODOLOGY AND APPLIED STANDARDS.....	9
2. TEST SUMMARY.....	10
3. DESCRIPTION OF TEST MODES.....	11
3.1 THE WORST MODE OF OPERATING CONDITION	11
3.2 THE WORST MODE OF MEASUREMENT.....	12
3.3 EUT DUTY CYCLE	13
4. TEST RESULT.....	14
4.1 AC POWER LINE CONDUCTED EMISSION.....	14
4.2 6DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%).....	17
4.3 OUTPUT POWER MEASUREMENT	35
4.4 POWER SPECTRAL DENSITY	38
4.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION.....	48
4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION.....	74
APPENDIX 1 - PHOTOGRAPHS OF EUT	A-1

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	D-Link Corporation 14420 Myford Road Suite 100, Irvine, California 92606, United States
Manufacturer	Amigo Technology Inc. No.82, Gongye 2nd Rd., Annan Dist., Tainan City 709 Tainan, Taiwan.
Equipment	(1) AX1500 Wi-Fi 6 AI Range Extender; (2) AX1500 Mesh Range Extender
Model Name	E15
Model Discrepancy	N/A
Trade Name	D-Link
Received Date	March 19, 2021
Date of Test	March 31 ~ June 15, 2021
Power Supply	Power from AC 120V, 60Hz

Remark:

1. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT 20: 2412MHz ~ 2462MHz 802.11n HT 40: 2422MHz ~ 2452MHz
Modulation Type	1. IEEE 802.11b mode: CCK 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT 20 MHz mode : OFDM 4. IEEE 802.11n HT 40 MHz mode : OFDM
Number of channel	1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT 20 MHz mode : 11 Channels 4. IEEE 802.11n HT 40 MHz mode : 7 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
<input type="checkbox"/> 1 MHz or less	1	Middle
<input type="checkbox"/> 1 MHz to 10 MHz	2	1 near top and 1 near bottom
<input checked="" type="checkbox"/> More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/> Dipole <input type="checkbox"/> Coils <input checked="" type="checkbox"/> embedded antenna
Antenna Gain	Chain 0: 3.1 dBi Chain 1: 3.1 dBi Power Directional Gain: 6.11 dBi
Antenna connector	MHF compatible

Notes:

- Power Directional Gain = $10 \cdot \log \{ [10^{(Ant1/20)} + 10^{(Ant2/20)} + \dots + 10^{(Ant N /20)}]^2 / N \text{ ANT} \}$ dBi
- Two dipole detachable Antennas used which uses a unique coupling to the EUT meeting rule 15.203.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

Report No.: T210319W02-RP1

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Jerry Chang	-
Radiation	Ray Li	-
RF Conducted	Dally Hong	-

Remark: The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309.

1.6 INSTRUMENT CALIBRATION

Test Date before May 20, 2021

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	09/07/2020	09/06/2021
Power Meter	Anritsu	ML2487A	6K00003260	05/21/2020	05/20/2021
Power Sensor	Anritsu	MA2490A	032910	05/21/2020	05/20/2021
Software	Radio Test Software.				

Test Date after May 20, 2021

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
Power Meter	Anritsu	ML2496A	S0013633	11/06/2020	11/05/2021
Power Sensor	Anritsu	MA2491A	1207368	11/06/2020	11/05/2021
Power Sensor	Anritsu	MA2491A	1207365	11/06/2020	11/05/2021
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	09/07/2020	09/06/2021
Software	Radio Test Software.				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/08/2021	02/07/2022
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Horn Antenna	ETS LINDGREN	3116	00026370	12/11/2020	12/10/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/24/2021	02/23/2022
Coaxial Cable	EMCI	EMC105	190914+327109/4	09/19/2020	09/18/2021
K Type Cable	Huber+Suhner	SUCOFLEX 102	29406/2	12/09/2020	12/08/2021
K Type Cable	Huber+Suhner	SUCOFLEX 102	22470/2	12/09/2020	12/08/2021
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/06/2021	01/05/2022
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	09/30/2020	09/29/2021
Loop Ant	COM-POWER	AL-130	121051	04/07/2021	04/06/2022
Pre-Amplifier	EMEC	EM330	060609	02/24/2021	02/23/2022
Pre-Amplifier	HP	8449B	3008A00965	12/25/2020	12/24/2021
Pre-Amplifier	MITEQ	AMF-6F-1800400 0-37-8P	985646	09/02/2020	09/01/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180419c				

AC Power Line Conducted Emission Test Room					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/29/2020	06/28/2021
EMI Test Receiver	R&S	ESCI	100064	07/17/2020	07/16/2021
LISN	SCHAFFNER	NNB 41	03/10013	02/02/2021	02/01/2022
Software	EZ-EMC(CCS-3A1-CE)				

Remark: Each piece of equipment is scheduled for calibration once a year.



Report No.: T210319W02-RP1

Page: 9 / 119

Rev.: 00

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	NB(G)	Lenovo	IBM 1951	N/A	CJ6UPA3489WL
2	NB(L)	Toshiba	PORTEGE R30-A	N/A	PD97260H

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 662911 D01.

2. TEST SUMMARY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	Pass
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d)	4.6	Radiation Band Edge	Pass
15.247(d)	4.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b mode :1Mbps IEEE 802.11g mode :6Mbps IEEE 802.11n HT20 mode :MCS8 IEEE 802.11n HT40 mode :MCS8
Test Channel Frequencies	IEEE 802.11b mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11g mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT20 mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT40 mode : 1. Lowest Channel : 2422MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2452MHz
Operation Transmitter	IEEE 802.11b mode : 2T2R IEEE 802.11g mode : 2T2R IEEE 802.11n HT20 mode : 2T2R IEEE 802.11n HT40 mode : 2T2R

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.
2. The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the power and PSD across all data rates, bandwidths, and modulations. The device supports SISO and MIMO at 802.11b/g/n20/n40 mode, per pre-test, MIMO 2TX mode was the worst and reported.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by AC 120V
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by AC (120V)
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Worst Position	<input type="checkbox"/> Placed in fixed position. <input type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input checked="" type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane) <input type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by AC (120V)
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Y-Plane) were recorded in this report.
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

3.3 EUT DUTY CYCLE


Temperature: 22.3°C

Test date: March 31, 2021

Humidity: 45% RH

Tested by: Dally Hong

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	99.15	0.04	0.12	0.01
802.11g	99.57	0.02	0.12	0.01
802.11n HT20	85.71	0.67	0.77	1.00
802.11n HT40	99.49	0.02	0.12	0.01



4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a)(2),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Pass.

Report No.: T210319W02-RP1


Test Data

Test Mode:	Mode 1	Temp/Hum	25.3(°C)/ 48.3%RH
Phase:	Line	Test Date	June 11, 2021
Test Voltage:	120Vac, 60Hz	Test Engineer	Jack Chen



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (d uV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.4460	22.03	13.65	10.29	32.32	23.94	56.95	46.95	-24.63	-23.01	Pass
0.4540	23.67	14.87	10.29	33.96	25.16	56.80	46.80	-22.84	-21.64	Pass
0.5300	20.70	12.09	10.29	30.99	22.38	56.00	46.00	-25.01	-23.62	Pass
0.5420	25.09	15.26	10.29	35.38	25.55	56.00	46.00	-20.62	-20.45	Pass
0.5540	22.69	13.16	10.29	32.98	23.45	56.00	46.00	-23.02	-22.55	Pass
0.5620	22.80	13.32	10.29	33.09	23.61	56.00	46.00	-22.91	-22.39	Pass

Test Mode:	Mode 1	Temp/Hum	25.3(°C)/ 48.3%RH
Phase:	Neutral	Test Date	June 11, 2021
Test Voltage:	120Vac, 60Hz	Test Engineer	Jack Chen



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.5060	19.02	10.40	10.29	29.31	20.69	56.00	46.00	-26.69	-25.31	Pass
0.5140	20.66	13.15	10.29	30.95	23.44	56.00	46.00	-25.05	-22.56	Pass
0.5220	19.25	13.20	10.29	29.54	23.49	56.00	46.00	-26.46	-22.51	Pass
0.5420	25.29	20.62	10.29	35.58	30.91	56.00	46.00	-20.42	-15.09	Pass
0.5500	23.46	18.15	10.29	33.75	28.44	56.00	46.00	-22.25	-17.56	Pass
0.5660	19.89	15.09	10.29	30.18	25.38	56.00	46.00	-25.82	-20.62	Pass

4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

According to §15.247(a)(2),

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------


Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



4.2.4 Test Result

Temperature: 22.3°C **Test date:** March 31, 2021
Humidity: 45% RH **Tested by:** Dally Hong

Temperature: 23.2°C **Test date:** April 01, 2021
Humidity: 53% RH **Tested by:** Dally Hong

Test mode: IEEE 802.11b mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
Low	2412	15.5427	15.9334	10.087	10.087	≥500
Mid	2437	15.4993	15.8466	10.1304	10.1304	
High	2462	15.4993	15.8466	10.1304	10.1304	


Test mode: IEEE 802.11g mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
Low	2412	21.7511	18.6252	17.3043	16.5217	≥500
Mid	2437	20.8394	17.2793	16.5217	16.5652	
High	2462	18.4949	18.0173	16.5652	16.5652	


Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
Low	2412	21.6208	18.7120	17.6087	17.6087	≥500
Mid	2437	20.2750	18.3647	17.6087	17.6087	
High	2462	19.6671	18.5818	17.6522	17.6087	


Test mode: IEEE 802.11n HT 40 MHz mode / 2422-2452 MHz						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
Low	2422	41.5630	39.7106	36.522	36.406	≥500
Mid	2437	43.7627	40.9841	36.29	36.29	
High	2452	39.0159	36.4689	36.29	36.29	


Test Data


6dB BANDWIDTH
























Test Data


BANDWIDTH 99%




















4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b),

Peak output power :

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm) and the e.i.r.p. shall not exceed 4Watt(36 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	<input type="checkbox"/> Antenna not exceed 6 dBi : 30dBm <input checked="" type="checkbox"/> Antenna with DG greater than 6 dBi : [Limit = 30 – (DG – 6)] <input type="checkbox"/> Point-to-point operation :
-------	---


Average output power : For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup



Report No.: T210319W02-RP1

4.3.4 Test Result

Temperature: 22.3°C

Test date: March 31, 2021

Humidity: 45% RH

Tested by: Dally Hong

Peak output power :

Test Mode: IEEE 802.11b Mode

CH	Freq. (MHz)	Data Rate	Power Set		Peak Output Power (dBm)		Total Peak Output Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
1	2412	1	51	61	24.21	23.90	27.07	29.89	PASS
6	2437	1	52	61	24.25	23.73	27.01		PASS
11	2462	1	52	61	24.23	23.62	26.95		PASS

Test Mode: IEEE 802.11g Mode

CH	Freq. (MHz)	Data Rate	Power Set		Peak Output Power (dBm)		Total Peak Output Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
1	2412	6	49	55	26.06	25.12	28.63	29.89	PASS
6	2437	6	57	63	26.74	25.27	29.08		PASS
11	2462	6	49	54	25.78	25.57	28.69		PASS

Test Mode: IEEE 802.11n HT 20 MHz Mode

CH	Freq. (MHz)	Data Rate	Power Set		Peak Output Power (dBm)		Total Peak Output Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
1	2412	MCS8	45	51	24.63	25.16	27.91	29.89	PASS
6	2437	MCS8	57	63	26.58	24.97	28.86		PASS
11	2462	MCS8	46	51	25.01	25.24	28.14		PASS

Test Mode: IEEE 802.11n HT 40 MHz Mode

CH	Freq. (MHz)	Data Rate	Power Set		Peak Output Power (dBm)		Total Peak Output Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
3	2422	MCS8	41	47	24.77	24.11	27.46	29.89	PASS
6	2437	MCS8	57	63	26.48	25.09	28.85		PASS
9	2452	MCS8	49	55	26.20	25.67	28.95		PASS

Average output power :

Test Mode: IEEE 802.11b Mode

CH	Freq. (MHz)	Data Rate	Power Set		Avg. Output Power (dBm)		Max. Avg. Output include tune up tolerance Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
1	2412	1	51	61	22.37	22.46	25.43	29.89	PASS
6	2437	1	52	61	22.48	22.29	25.40		PASS
11	2462	1	52	61	22.32	22.18	25.26		PASS

Test Mode: IEEE 802.11g Mode

CH	Freq. (MHz)	Data Rate	Power Set		Avg. Output Power (dBm)		Max. Avg. Output include tune up tolerance Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
1	2412	6	49	55	19.41	18.34	21.92	29.89	PASS
6	2437	6	57	63	21.97	21.45	24.73		PASS
11	2462	6	49	54	19.10	18.70	21.91		PASS

Test Mode: IEEE 802.11n HT 20 MHz Mode

CH	Freq. (MHz)	Data Rate	Power Set		Avg. Output Power (dBm)		Max. Avg. Output include tune up tolerance Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
1	2412	MCS8	45	51	17.07	20.95	22.44	29.89	PASS
6	2437	MCS8	57	63	21.85	20.97	24.44		PASS
11	2462	MCS8	46	51	17.84	17.48	20.67		PASS

Test Mode: IEEE 802.11n HT 40 MHz Mode

CH	Freq. (MHz)	Data Rate	Power Set		Avg. Output Power (dBm)		Max. Avg. Output include tune up tolerance Power (dBm)	Limit (dBm)	RESULT
			Chain0	Chain1	Chain0	Chain1	(dBm)		
3	2422	MCS8	41	47	16.20	15.91	19.07	29.89	PASS
6	2437	MCS8	57	63	22.03	21.36	24.72		PASS
9	2452	MCS8	49	55	19.83	19.24	22.56		PASS

4.4 POWER SPECTRAL DENSITY

4.4.1 Test Limit

According to §15.247(e),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


Limit	<input type="checkbox"/> Antenna not exceed 6 dBi : 8dBm <input checked="" type="checkbox"/> Antenna with DG greater than 6 dBi : [Limit = 8 – (DG – 6)] <input type="checkbox"/> Point-to-point operation :
-------	---

4.4.2 Test Procedure

Test method Refer as ANSI C63.10:2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 30kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

4.4.3 Test Setup



Report No.: T210319W02-RP1

4.4.4 Test Result

Temperature: 24.1°C Test date: April 07, 2021

Humidity: 47% RH Tested by: Dally Hong

Temperature: 22.5°C Test date: June 15, 2021

Humidity: 51.7% RH Tested by: Dally Hong


Test mode: IEEE 802.11b mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	Total PPSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2412	-7.61	-8.6	-5.07	7.89
Mid	2437	-8.29	-8.35	-8.29	
High	2462	-8.79	-8.97	-5.87	


Test mode: IEEE 802.11g mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	Total PPSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2412	-7.33	-8	-4.64	7.89
Mid	2437	-7.6	-8.02	-4.79	
High	2462	-7.15	-8.19	-4.63	


Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz					
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	Total PPSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2412	-7.13	-7.75	-4.42	7.89
Mid	2437	-7.19	-7.65	-4.40	
High	2462	-7.74	-8.04	-4.88	


Test mode: IEEE 802.11n HT 40 MHz mode / 2422-2452 MHz					
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	Total PPSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2422	-7.49	-10.84	-5.84	7.89
Mid	2437	-7.72	-10.65	-5.93	
High	2452	-7.91	-10.29	-5.93	


Test Data




















4.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d),

In any 100 kHz bandwidth outside the authorized frequency band,


Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.5.2 Test Procedure

Test method Refer as KDB 662911 D01, ANSI C63.10:2013.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup



4.5.4 Test Result

Temperature:	22.3°C	Test date:	March 31, 2021
Humidity:	45% RH	Tested by:	Dally Hong
Temperature:	23.2°C	Test date:	April 01, 2021
Humidity:	53% RH	Tested by:	Dally Hong
Temperature:	24.1°C	Test date:	April 07, 2021
Humidity:	47% RH	Tested by:	Dally Hong
Temperature:	22.5°C	Test date:	June 15, 2021
Humidity:	51.7% RH	Tested by:	Dally Hong

Report No.: T210319W02-RP1

Test Data

