

FCC Test Report

Report No. AGC12533220402FE10

FCC ID : 2AIKSTRANSMITTER

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Tank Transmitter

BRAND NAME : MARES

MODEL NAME : Tank Transmitter

APPLICANT: MARES SPA

DATE OF ISSUE : Aug. 20, 2022

STANDARD(S) : FCC Part 15 Subpart C

REPORT VERSION: V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Page 2 of 28

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug. 20, 2022	Valid	Initial Release



TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	7
3. TEST ENVIRONMENT	8
3.1 ADDRESS OF THE TEST LABORATORY	8
3.2 TEST FACILITY	8
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	10
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	
4.2 EUT EXERCISE	11
4.3 CONFIGURATION OF TESTED SYSTEM	11
4.4 EQUIPMENT USED IN TESTED SYSTEM	11
4.5 SUMMARY OF TEST RESULTS	12
5. DESCRIPTION OF TEST MODES	13
6. FIELD STRENGTH OF FUNDAMENTAL	14
6.1 PROVISIONS APPLICABLE	14
6.3 FIELD STRENGTH CALCULATION	16
6.4 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	17
6.5 MEASUREMENT RESULTS	18
7. 20 dB BANDWIDTH	24
7.1 PROVISIONS APPLICABLE	24
7.2 MEASUREMENT PROCEDURE	24
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	24
7.4 MEASUREMENT RESULTS	25
8. AC POWER LINE CONDUCTED EMISSION TEST	26
8.1 LIMITS OF LINE CONDUCTED EMISSION TEST	26
8.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	26



Page 4 of 28

ΔΡΕ	PENDIX B: PHOTOGRAPHS OF TEST EUT	2
APF	PENDIX A: PHOTOGRAPHS OF TEST SETUP	. 28
	8.5 MEASUREMENT RESULTS	. 27
	8.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	. 27
	8.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	. 27



1. GENERAL INFORMATION

Applicant	MARES SPA
Address SALITA BONSEN, 4 16035 RAPALLO (GE) ITALY	
Manufacturer MARES SPA	
Address	SALITA BONSEN, 4 16035 RAPALLO (GE) ITALY
Factory	MARES SPA
Address	SALITA BONSEN, 4 16035 RAPALLO (GE) ITALY
Product Designation Tank Transmitter	
Brand Name	MARES
Test Model Tank Transmitter	
Date of Test Jun. 16, 2022 to Aug. 20, 2022	
Deviation from Standard No any deviation from the test method	
Test Result Pass	
Test Report Form No	AGCTR-ER-FCCV1.0

Prepared By	Thea Yuang	
	Thea Huang (Project Engineer)	Aug. 20, 2022
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Aug. 20, 2022
Approved By	Max Zhang	
-	Max Zhang (Authorized Officer)	Aug. 20, 2022



Page 6 of 28

2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	100
Software Version	V1.0
Operation Frequency	134KHz
Modulation Type	ASK
Number of channels	1
Field Strength of Fundamental	54.94dBuV/m (Max)
Antenna Designation	Coil Antenna
Antenna Gain	2.15dBi
Power Supply	DC 3.6V by battery

2.2 TEST FREQUENCY LIST

Channel Number	Frequency
01	134KHz



Page 7 of 28

2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AIKSTRANSMITTER** filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title		
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	FCC 47 CFR Part 15	Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		

2.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7 ANTENNA REQUIREMENT

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a brokenantenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.15 dBi.



Page 8 of 28

3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 9 of 28

3.3 ENVIRONMENTAL CONDITIONS

NORMAL CONDITIONS	EXTREME CONDITIONS	
15 - 35	-20 - 50	
20 % - 75 %	20 % - 75 %	
86 - 106	86 - 106	
	15 - 35 20 % - 75 %	

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



Page 10 of 28

3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Wideband Antenna	SCHWARZBEC K	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
Test Software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



Page 11 of 28

4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

Test Accessories Come From The Laboratory

☐ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	Tank Transmitter	Tank Transmitter	2AIKSTRANSMITTER	EUT



Page 12 of 28

4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.209(a)(f)	Radiated Spurious Emission	Pass
3	§15.215(c)	20dB Bandwidth	Pass
4	§15.205(a)	Restricted Bands of Operation	Pass
5	§15.207	AC Power Line Conducted Emission	N/A

Note: 1.N/A means not applicable

2. The device under test is battery-powered and does not require evaluation of AC Power Line Conducted Emission.



Page 13 of 28

5. DESCRIPTION OF TEST MODES

Summary table of Test Cases					
Test Item	Equipment type / Modulation				
rest item	TX:134KHz/ ASK				
Radiated Test Cases	Mode 1: TX 134KHz				

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.



Page 14 of 28

6. FIELD STRENGTH OF FUNDAMENTAL

6.1 PROVISIONS APPLICABLE

Test Requirement:	FCC Part15 C Section 15.209								
Test Method:	ANSI C63.10:2013								
Test Frequency Range:	9kHz to 1GHz								
Test site:	Measurement Dista	nce: 3m							
	Frequency	Detector	RBW	VBW	Value				
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak				
Receiver setup:	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak				
iteceivei setup.	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak				
	Above 4CUz	Peak	1MHz	3MHz	Peak				
	Above 1GHz	Peak	1MHz	10Hz	Average				

Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
Above IGHZ	74.00	Peak Value

Remark: (

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 15 of 28

6.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Page 16 of 28

6.3 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF where FS = Field Strength in $dB\mu V/m$ RR = RA - AG - AV in $dB\mu V$

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m.

This value in dBµV/m was converted to its corresponding level in µV/m.

 $RA = 52.0 dB\mu V/m$

AF = 7.4 dB/m $RR = 18.0 \text{ dB}\mu\text{V}$ CF = 1.6 dB LF = 9.0 dB

CF = 1.6 dB LF = 9.0 AG = 29.0 dB

AV = 5.0 dB

FS = RR + LF $FS = 18 + 9 = 27 \text{ dB}\mu\text{V/m}$

Level in μ V/m = Common Antilogarithm [(27 dB μ V/m)/20] = 22.4 μ V/m

Magnetic field strength calculation (9 kHz – 30 MHz)

When the limit is in terms of magnetic field, the following equation applies:

 $H[dB(\mu A/m)] = V[dB(\mu V)] + LC[dB] - GPA[dB] + AFH[dB(S/m)]$

Where,

H is the magnetic field strength (to be compared with the limit),

V is the voltage level measured by the receiver or spectrum analyzer,

LC is the cable loss,

GPA is the gain of the preamplifier (if used), and

AFH is the magnetic antenna factor.

If the "electrical" antenna factor is used instead, the above equation becomes:

 $H[dB(\mu A/m)] = V[dB(\mu V)] + LC[dB] - GPA[dB] + AFE[dB(m-1)] - 51.5[dB\Omega]$


where AFE is the "electric" antenna factor, as provided by the antenna calibration laboratory.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






6.4 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)


RADIATED EMISSION TEST SETUP 9KHz-30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.






6.5 MEASUREMENT RESULTS

ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 9KHz-150KHz

	<u>_</u>	LECTRICFI	ELD IEST II	N THE FRE	QUENCY RAN	GE 9KHZ-	-150KHZ	
EUT		Tank Transmitter			Model Name		Tank Transmitter	
Temperature		21°C			Relative Humidity		53%	
Pressure		985hPa			Test Voltage		Normal V	oltage
Test Mode		Mode 1			Antenna		Face	
130.0	ßuV/m							
							Limit Març	
70								
								6
								, S
				3				
		~~~	<b>*</b> ~~~~	anno	your warming	nown	5	
	$\sim$						many war	mend Men
10.0								
0.009			Reading	Correct	Measure-			0.150
No.	Mk.	Freq.	Level	Factor	ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		0.0179	6.58	27.76	34.34	122.0	-87.66	peak
2		0.0276	10.68	27.03	37.71	118.5	-80.79	peak
3		0.0372	12.72	26.31	39.03	116.0	-77.05	peak
4		0.0605	8.37	24.57	32.94	112.1	-79.20	peak
			4.00	22.20	27.28	108.8	-81.57	peak
5		0.0909	4.98	22.30	21.20	100.0	-01.57	peak

**RESULT: PASS** 






**ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 9KHz-150KHz** 

	ELECTRIC F	IELD 1E91 II	V IIIL FREG	ZULING I KAIN	GL SKIIZ	13011112	
EUT	Tank Trans	Tank Transmitter			Model Name		nsmitter
Temperature	perature 21°C			Relative Humidity		53%	
Pressure	essure 985hPa			Test Voltage		Normal V	oltage/
Test Mode Mode 1		Antenna Side					
130.0 dB	130.0 dBuV/m						
70	<u>1</u>	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	mmm	manin	550	Limi	
10.0			(MHz)			- Trapan	0.150
		Reading	Correct	Measure-			0.100
No.	Mk. Freq.	Level	Factor	ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	MHz 0.0118	dBuV 0.01	dB 28.21		dBuV/m 125.3	dB -97.15	Detector
1 2				dBuV/m			
2	0.0118	0.01	28.21	dBuV/m 28.22	125.3	-97.15	peak
	0.0118 0.0205	0.01 7.59	28.21 27.56	dBuV/m 28.22 35.15	125.3 120.9	-97.15 -85.75	peak peak
3	0.0118 0.0205 0.0374	0.01 7.59 12.32	28.21 27.56 26.29	dBuV/m 28.22 35.15 38.61	125.3 120.9 116.0	-97.15 -85.75 -77.43	peak peak peak

**RESULT: PASS** 






# **ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 150KHz-30MHz**

	EL	ECTRIC FIE	LD TEST IN	THE FREC	QUENCY RANG	<b>3E 150KH</b>	z-30MHz	
EUT		Tank Transm	nitter		Model Name		Tank Tran	nsmitter
Temperature		21°C			Relative Humidity 53%			
Pressure		985hPa	Test Voltage	e Normal Voltage				
Test Mode Mode 1					Antenna		Face	
120.0 df	BuV/m						Limit:	
60	1		\$	33	man	~~~~**	Marg	6
0.0								
0.150		0.5		(MHz)	5			30.000
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		0.2494	0.16	21.34	21.50	100.0	-78.57	peak
2		0.9459	1.95	21.25	23.20	68.09	-44.89	peak
3		1.8414	0.37	21.98	22.35	69.54	-47.19	peak
4		4.4284	3.55	22.85	26.40	69.54	-43.14	peak
5	*	9.6024	7.10	24.27	31.37	69.54	-38.17	peak
6		21.0947	2.96	25.00	27.96	69.54	-41.58	peak

**RESULT: PASS** 






	El	LECTRIC FI	ELD TEST IN	THE FRE	QUENCY RANG	GE 150KH	lz-30MHz		
EUT		Tank Transı	mitter		Model Name		Tank Tran	smitter	
Temperature		21°C			Relative Humidity		53%		
Pressure		985hPa			Test Voltage		Normal Voltage		
Test Mode		Mode 1			Antenna		Side		
0.0	BuV/m	*		2	33	**************************************	Limit	5	
0.150		0.		(MHz)	5			30.000	
No.	Mk.	Freq.	Reading Level	Correct Factor		Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	
1		0.3490	1.55	21.16	22.71	96.95	-74.24	peak	
2		1.3938	2.02	21.61	23.63	64.72	-41.09	peak	
3		2.8365	2.23	22.36	24.59	69.54	-44.95	peak	
4		4.4284	2.95	22.85	25.80	69.54	-43.74	peak	
5	*	9.4035	8.90	24.22	33.12	69.54	-36.42	peak	
6		20.6470	4.48	25.05	29.53	69.54	-40.01	peak	

# **RESULT: PASS**

# **NOTES:**


- 1. Quasi-Peak detector is used for frequency below 30MHz.
- 2. Negative value in the margin column shows emission below limit.
- 3. All measurements were made with 0.6m loop antenna at 3m distance. All emissions are below the QP limit.
- 4. Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB)
- 5. Loop antenna is used for the emission under 30MHz.





	RADIATE	D EMISSION E	BELOW 1GH	Z		
EUT	Tank Transmitter		Model Nam	ne	Tank Tra	ansmitter
Temperature	22°C		Relative Humidity 53%			
Pressure	985hPa		Test Voltage		Normal \	Voltage
Test Mode	Mode 1		Antenna		Horizont	al
32 1	2	www.			Limit: Margin:	5
water day of the second and the second	And and an annual street, and are	- Adrian	Mark Company			
-8		79000	300	400	500 600 700	1000 000
-8 30.000 40 50	60 70 80  Reading	(MHz) Correct	300 Measure- ment	400 Limit	500 600 700 Over	1000.000
-8 30.000 40 50 No. Mk. F	60 70 80	(MHz)			Over	1000.000
-8 30.000 40 50 No. Mk. F	Reading Level	(MHz) Correct Factor	Measure- ment	Limit	Over	
No. Mk. F	Reading Freq. Level MHz dBuV	(MHz) Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over	Detector
No. Mk. F	Reading Level MHz dBuV 2991 5.66	(MHz) Correct Factor dB 14.70	Measure- ment dBuV/m 20.36	Limit dBuV/m 40.00	Over dB -19.64	Detector peak
No. Mk. F	Reading Level MHz dBuV 2991 5.66 6005 5.81 8351 6.59	Correct Factor dB 14.70 17.08	Measure- ment dBuV/m 20.36 22.89	Limit dBuV/m 40.00 40.00	Over dB -19.64 -17.11	Detector peak peak
No. Mk. F  1 39.2 2 69.6 3 140.8	Reading Level MHz dBuV 2991 5.66 6005 5.81 8351 6.59 9318 7.05	(MHz) Correct Factor dB 14.70 17.08	Measure- ment dBuV/m 20.36 22.89 24.17	Limit dBuV/m 40.00 40.00 43.50	Over  dB  -19.64  -17.11  -19.33	Detector peak peak peak

**RESULT: PASS** 



peak

peak

peak

peak



#### **RADIATED EMISSION BELOW 1GHz**

RADIATED EMISSION BELOW 1GHZ									
EUT	Tank Transmitter	Model Name	Tank Transmitter						
Temperature	22°C	Relative Humidity	53%						
Pressure	985hPa	Test Voltage	Normal Voltage						
Test Mode	Mode 1	Antenna	Vertical						
72.0 dBuV/m									
			Limit: — Margin: —						
32 -8 30.000 40 50	60 70 80 (MHz)								
	Reading Correct	t Measure-							
No. Mk. F	Freq. Level Factor		Over						
-	MHz dBuV dB	dBuV/m dBuV/m	dB Detector						
1 43 7	2017 5.13 14.54	19.67 40.00	20.22 pook						
1 43.	2017 5.15 14.54	19.07 40.00	-20.33 peak						

# **RESULT: PASS**

3

5

134.0882

234.1683

383.9318

629.4772

**Note:** 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

5.47

5.08

7.15

5.59

- 2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.
- 3. The "Factor" value can be calculated automatically by software of measurement system.

18.15

17.66

19.06

25.01

23.62

22.74

26.21

30.60

43.50

46.00

46.00

46.00

-19.88

-23.26

-19.79

-15.40



Page 24 of 28

# 7. 20 dB BANDWIDTH

# 7.1 PROVISIONS APPLICABLE


N/A


#### 7.2 MEASUREMENT PROCEDURE

Set the parameters of SPA as below:

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were used.
- 4. Span: 50kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

# 7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)








#### 7.4 MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and -20dB Bandwidth								
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (MHz)	Pass or Fail			
ASK	0.134	23.600	26.76	N/A	Pass			

# Test Graphs of Occupied Bandwidth & - 20dB Bandwidth







# 8. AC POWER LINE CONDUCTED EMISSION TEST


# **8.1 LIMITS OF LINE CONDUCTED EMISSION TEST**

Frequency	Maximum RF Line Voltage	
	Q.P. (dBµV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

# 8.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





Page 27 of 28

#### 8.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

#### 8.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

#### **8.5 MEASUREMENT RESULTS**

Note: 1.N/A means not applicable

2. The device under test is battery-powered and does not require evaluation of AC Power Line Conducted Emission.



Page 28 of 28

# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC12533220402AP02

APPENDIX B: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC12533220402AP03

----END OF REPORT----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.