



# MAXIMUM PERMISSIBLE EXPOSURE EVALUATION REPORT

**Applicant: Magnadyne Corporation** 

Address: 1111 W. Victoria Street Compton, CA 90220 USA

Product Name: Wireless/LTE Repeater

FCC ID: ZGM-RVLINK

Standard(s):	47 CFR §1.1310, 47 CFR §2.1091, 47 CFR §15.247(i), 47 CFR §15.407(f)
<b>Report Number:</b>	2402W44990E-RF-00D
<b>Report Date:</b>	2024/10/15

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Peopo Yun

Reviewed By: Pedro Yun Title: Project Engineer

fron Cas

Approved By: Ivan Cao Title: EMC Manager

**Bay Area Compliance Laboratories Corp. (Dongguan)** No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China

> Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: The information marked  $\blacktriangle$  is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with  $\bigstar$ . This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

## CONTENTS

1. GENERAL INFORMATION  4    1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST  4    2. RF EXPOSURE EVALUATION (MPE)  5    2.1 RF EXPOSURE EVALUATION  6    2.1.1 Applicable Standard  6    2.1.2 Calculation formula:  7    2.1.3 Calculated Data:  6	DOCUMENT REVISION HISTORY	3
2. RF EXPOSURE EVALUATION (MPE)	1. GENERAL INFORMATION	4
2. RF EXPOSURE EVALUATION (MPE)	1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	4
2.1.1 Applicable Standard	2. RF EXPOSURE EVALUATION (MPE)	5
2.1.2 Calculation formula:		
2.1.3 Calculated Data:	2.1.1 Applicable Standard	5
EXHIBIT A - EUT PHOTOGRAPHS	2.1.3 Calculated Data:	6
	EXHIBIT A - EUT PHOTOGRAPHS	7

### **DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision	
1.0	2402W44990E-RF-00D	Original Report	2024/10/15	

Report Template Version: FCC §2.1091-V1.0

### **1. GENERAL INFORMATION**

### 1.1 General Description Of Equipment under Test

EUT Name:	Wireless/LTE Repeater			
EUT Model:	RV2480			
Multiple Model:	RV2460			
Rated Input Voltage:	DC 12V from adapter			
EUT Received Date:	2024/8/22			
EUT Received Status:	Good			
Note: The multiple models are electrically identical with the test model. Please refer to the declaration letter for				
more detail, which was provided by manufacturer.				

### 2. RF EXPOSURE EVALUATION (MPE)

#### 2.1 RF Exposure Evaluation

#### 2.1.1 Applicable Standard

According to subpart 15.247(i) ,15.407(f) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)			
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30			
30–300	27.5	0.073	0.2	30			
300-1500	/	/	f/1500	30			
1500-100,000	/	/	1.0	30			

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### **2.1.2 Calculation formula:**

Prediction of power density at the distance of the applicable MPE limit

 $S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

 $\mathbf{R}$  = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$

Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	( <b>mW</b> )			
2.4G Module	2412-2462	3.62	2.30	28.5	707.95	30.00	0.144	1.0
2.4G +5G	2412-2462	4.08	2.56	28.5	707.95	30.00	0.160	1.0
2.40 +50 Module	5150-5250	2.62	1.83	18.5	70.79	30.00	0.011	1.0
Wiodule	5725-5850	3.31	2.14	21	125.89	30.00	0.024	1.0
WCDMA B2	1850-1910	2.12	1.63	25	316.23	30.00	0.046	1.0
WCDMA B4	1710-1755	1.53	1.42	25	316.23	30.00	0.040	1.0
WCDMA B5	824-849	-0.13	0.97	25	316.23	30.00	0.027	0.55
LTE B2	1850-1910	2.12	1.63	25	316.23	30.00	0.046	1.0
LTE B4	1710-1755	1.53	1.42	25	316.23	30.00	0.040	1.0
LTE B5	824-849	-0.13	0.97	25	316.23	30.00	0.027	0.55
LTE B12	699-716	-5.3	0.30	25	316.23	30.00	0.008	0.47
LTE B13	777-787	-2.19	0.60	25	316.23	30.00	0.017	0.52
LTE B14	788-798	-1.89	0.65	25	316.23	30.00	0.018	0.53
LTE B66	1710-1780	3.22	2.10	25	316.23	30.00	0.059	1.0
LTE B71	663-698	-6.55	0.22	25	316.23	30.00	0.006	0.44
Note: The device IC: 10224A-201		fied WV	VAN module,	FCC ID: 2	XMR201808	BEC25AF, cert	ified on 08/03	3/2021,

#### 2.1.3 Calculated Data:

#### Note:

The Conducted output power including Tune-up Tolerance provided by manufacturer.

#### Simultaneous transmission:

2.4G Module and 2.4G +5G Module 2.4G Wifi can't transmit simultaneously, but 2.4G Module, 2.4G +5G Module 5G Wifi and WWAN can transmit simultaneously:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \le 1$$

 $S_{2.4G\ Module}/S_{limit-\ 2.4G\ Module}+S_{2.4G\ +5G\ Module}/S_{limit-\ 2.4G\ +5G\ Module}+S_{WWAN}/S_{limit-\ WWAN}$ 

=0.144/1.0+0.024/1.0+0.059/1.0

=0.227

< 1.0

Result: Compliant. The device compliant Simultaneous transmission at 30cm distances.

### **EXHIBIT A - EUT PHOTOGRAPHS**

Please refer to the attachment 2402W44990E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2402W44990E-RF-INP EUT INTERNAL PHOTOGRAPHS.

\*\*\*\*\* END OF REPORT \*\*\*\*\*

Report Template Version: FCC §2.1091-V1.0