Revision: 2

Issue Date: March 29, 2021 Final Test Date: February 23, 2021







Test Report - FCC PART 1.1310 / MPE Prepared For: Fiplex Communications Inc.

Approved for Release By:

Signature: Bruno Charlor

Name & Title: Bruno Clavier, General Manager

Date of Signature

(YYYY-MM-DD): 2021-02-23

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Table of Contents

1.	C	USTOMER INFORMATION	. 3
2.		OCATION OF TESTING	
	2.1 2.2	TEST LABORATORY TESTING WAS PERFORMED, REVIEWED BY	3
		EST SAMPLE(S) (EUT/DUT)	
	3.1	Description of the EUT	5
4.	TE	EST METHODS & APPLICABLE REGULATORY LIMITS	. 6
	4.1 4. 4.2	Test methods/Standards/Guidance:	6 6
5.	RI	F EXPOSURE RESULTS	. 8
6.	Н	ISTORY OF TEST REPORT CHANGES.	9



1. Customer Information

Applicant: Fiplex Communications Inc.

Address: 2101 NW 79th Ave.

MIAMI FL 33122

Contact: Mr. Fernando Sommariva

Telephone: 305-884-8991

Email address: fernando.sommariva@fiplex.com

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

2.2 Testing was performed, reviewed by

Dates of Testing: February 12, 2021 – February 23, 2021

Signature:

Name & Title: Franklin Rose, EMC Specialist

Date of Signature

(YYYY-MM-DD): 2021-02-23

Signature:

Sr. EMC Engineer EMC-003838-NE

Name & Title: Tim Royer, EMC Engineer

Date of Signature

(YYYY-MM-DD): 2021-02-23

3. Test Sample(s) (EUT/DUT)

The test sample was received: February 12, 2021

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

dentification					
FCC ID:	P3TDH14-6B, PHTDH14-6A				
Brief Description	DAS Centric UV - Remote 3037				
Type of Modular	n/a				
Model(s) #	DH14EA-R1-AVUT-NDND-3037				
Serial Number	20210040FU				

Technical Characteristics							
Technology	DAS Industrial Signal Booster Remote Unit						
Frequency Range	150.8 - 173.4 MHz; and 450 - 512 MHz						
RF O/P Power (Max.)	VHF DL: 30 dBm (1 W); UHF DL: 37 dBm (5 W)						
Modulation	n/a						
Bandwidth & Emission Class	11K3F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 9K80F1D, 9K80F1E						
Number of Channels	Variable.						
Duty Cycle	100%						
Antenna Type	n/a						
Antenna Gain (for each ant.)	0 dBi						
Antenna Connector	N						
Voltage Rating (AC or Batt.)	120 V AC or 28 V DC (internally)						

Antenna Characteristics							
Frequency Range Mode / BW Antenna Gain							
n/a	n/a	0 dBi					

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging Time (minutes)						
A Limits for Occupational/Controlled Exposure										
0.3-3.0	614	1.63	*(100)	≤6						
3.0-30	1842/f	4.89/f	*(900/f²)	<6						
30-300	61.4	0.163	1.0	<6						
300-1,500			f/300	<6						
1,500-100,000			5	<6						
	B Limits for Ge	eneral Population/Uncontr	rolled Exposure							
0.3-1.34	614	1.63	*(100)	<30						
1.34-30	824/f	2.19/f	*(180/f ²)	<30						
30-300	27.5	0.073	0.2	<30						
300-1,500			f/1500	<30						
1,500-100,000			1.0	<30						

4.2 Equations

POWER DENSITY

E(V/m) = SQRT (30 * P * G) / d

 $Pd(W/m^2) = E^2 / 377$

 $S = EIRP / (4 * Pi * D^2)$

Where:

S = Power density, in mW/cm^2 EIRP = Equivalent Isotropic Radiated Power, in mW D = Separation distance in cm

Power density is converted from units of <u>mW/cm^2</u> to units of <u>W/m^2</u> by multiplying by 10.

DISTANCE

$$D = SQRT (EIRP / (4 * Pi * S))$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm^2

SOURCE-BASED DUTY CYCLE (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

Source-based time-average EIRP = (DC / 100) * EIRP

Where:

DC = Duty Cycle in % as applicable. EIRP = Equivalent Isotropic radiated Power, in mW

5. RF Exposure Results

Transmitter Type: Fixed Mount, SISO, Non-colocated TX

(1 possible RF pathway)

VH	VHF Band, Uplink									
	quency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
	8-173.4 MHz	20	32.00	0.00	100%	1.58	0.315 mW/cm2	0.2 mW/cm2	1 mW/cm2	25.11

UHF Band, Downlink									
Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
450-512 MHz	20	39.00	0.00	100%	7.94	1.58 mW/cm2	0.3 mW/cm2	1.5 mW/cm2	45.90

RESULT: Passes Limit at Distance: 45.90 cm

6. History of Test Report Changes

Test Report#	Revision #	Description	Date of Issue
TR_0726-21_FCC_MPE_1	1	Initial release	March 19, 2021
TR_0726-21_FCC_MPE_2	2	Clerical Updates	March 29, 2021

END OF TEST REPORT