



TEST REPORT

Test report no.: 1-5045/17-01-04



Testing laboratory

CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.ctcadvanced.com>
e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-03

Applicant

Continental Automotive GmbH

Heinrich-Hertz-Str. 45
78052 Villingen-Schwenningen / GERMANY
Phone: +49 7721 94 72-0
Fax: +49 772 167-792802
Contact: Marion Grüner
e-mail: Marion.Gruener@continental-corporation.com
Phone: +49 772 167-2802

Manufacturer

Continental Automotiva Guadalajara Mexico, S.A. de C.V.
Periferico Sur #7999-D. Santa Maria Tequepexpan
45601 Jalisco, Tlaquepaque / MEXICO

Test standard/s

47 CFR Part 15

Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

RSS - 247 Issue 2

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: Display Controller Subsystem
Model name: Multiview Media Display
FCC ID: 2AJW5MVMDISPLAY
IC: 21979-MVMDISPLAY
Frequency: DTS band 2400 MHz to 2483.5 MHz
Technology tested: WLAN
Antenna: Integrated antenna
Power supply: 12.0 DC by external power supply
Temperature range: -40°C to +60°C



This test report is electronically signed and valid without handwritten signature. For verification of the electronic signature, the public keys can be requested at the testing laboratory.

Test report authorized:

p.o.

Andreas Luckenbill
Lab Manager
Radio Communications & EMC

Test performed:

Mihail Dorongovskij
Lab Manager
Radio Communications & EMC

1 Table of contents

| | | |
|---------|---|----|
| 1 | Table of contents..... | 2 |
| 2 | General information | 3 |
| 2.1 | Notes and disclaimer | 3 |
| 2.2 | Application details | 3 |
| 2.3 | Test laboratories sub-contracted | 3 |
| 3 | Test standard/s and references..... | 4 |
| 4 | Test environment | 5 |
| 5 | Test item | 5 |
| 5.1 | General description..... | 5 |
| 5.2 | Additional information | 5 |
| 6 | Description of the test setup | 6 |
| 6.1 | Shielded semi anechoic chamber | 7 |
| 6.2 | Shielded fully anechoic chamber | 8 |
| 6.3 | Radiated measurements > 18 GHz | 9 |
| 6.4 | Conducted measurements with peak power meter & spectrum analyzer..... | 10 |
| 7 | Sequence of testing | 11 |
| 7.1 | Sequence of testing radiated spurious 9 kHz to 30 MHz | 11 |
| 7.2 | Sequence of testing radiated spurious 30 MHz to 1 GHz | 12 |
| 7.3 | Sequence of testing radiated spurious 1 GHz to 18 GHz..... | 13 |
| 7.4 | Sequence of testing radiated spurious above 18 GHz | 14 |
| 8 | Measurement uncertainty..... | 15 |
| 9 | Summary of measurement results | 16 |
| 10 | Additional comments..... | 17 |
| 11 | Additional EUT parameter..... | 18 |
| 12 | Measurement results | 19 |
| 12.1 | Antenna gain..... | 19 |
| 12.2 | Identify worst case data rate..... | 20 |
| 12.3 | Maximum output power | 21 |
| 12.4 | Band edge compliance radiated | 22 |
| 12.5 | Spurious emissions radiated below 30 MHz | 26 |
| 12.6 | Spurious emissions radiated 30 MHz to 1 GHz | 33 |
| 12.7 | Spurious emissions radiated above 1 GHz | 44 |
| 13 | Observations | 57 |
| Annex A | Glossary | 57 |
| Annex B | Document history | 58 |
| Annex C | Accreditation Certificate | 58 |

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

| | |
|------------------------------------|------------------|
| Date of receipt of order: | 2018-03-07 |
| Date of receipt of test item: | 2018-03-06 |
| Start of test: | 2018-03-06 |
| End of test: | 2018-04-04 |
| Person(s) present during the test: | Mr. Tom Gollasch |

2.3 Test laboratories sub-contracted

None

3 Test standard/s and references

| Test standard | Date | Description |
|-------------------|---------------|---|
| 47 CFR Part 15 | -/- | Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices |
| RSS - 247 Issue 2 | February 2017 | Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices |
| RSS - Gen Issue 4 | November 2014 | Spectrum Management and Telecommunications Radio Standards Specifications - General Requirements and Information for the Certification of Radio Apparatus |

| Guidance | Version | Description |
|---------------------|---------|---|
| DTS: KDB 558074 D01 | v04 | Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 |
| ANSI C63.4-2014 | -/- | American national standard for methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz |
| ANSI C63.10-2013 | -/- | American national standard of procedures for compliance testing of unlicensed wireless devices |

4 Test environment

| | | | |
|---------------------------|---|--|--|
| Temperature | : | T _{nom} T _{max} T _{min} | +20 °C during room temperature tests No test under extreme temperature conditions required. No test under extreme temperature conditions required. |
| Relative humidity content | : | | 35 % |
| Barometric pressure | : | | 1002 hpa |
| Power supply | : | V _{nom} V _{max} V _{min} | 12.0 V by external power supply No test under extreme voltage conditions required. No test under extreme voltage conditions required. |

5 Test item

5.1 General description

| | | |
|----------------------------|---|---|
| Kind of test item | : | Display Controller Subsystem |
| Type identification | : | Multiview Media Display |
| HMN | : | -/- |
| PMN | : | Multiview Media |
| HVIN | : | A2C100372 |
| FVIN | : | -/- |
| S/N serial number | : | Radiated unit: BCT-7276512-18113004 Conducted unit: BCT-7276512-18046018 |
| HW hardware status | : | TBD |
| SW software status | : | RF test software |
| Frequency band | : | DTS band 2400 MHz to 2483.5 MHz |
| Type of radio transmission | : | DSSS, OFDM |
| Use of frequency spectrum | : | |
| Type of modulation | : | (D)BPSK, (D)QPSK, 16 – QAM, 64 – QAM |
| Number of channels | : | 11 |
| Antenna | : | Integrated antenna |
| Power supply | : | 12.0 V DC by external power supply |
| Temperature range | : | -40°C to +60°C |

5.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup- and EUT-photos are included in test report:

1-5045/17-01-01_AnnexA
1-5045/17-01-01_AnnexB
1-5045/17-01-01_AnnexD

6 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

| | | | |
|-----|--|-----|--|
| k | calibration / calibrated | EK | limited calibration |
| ne | not required (k, ev, izw, zw not required) | zw | cyclical maintenance (external cyclical maintenance) |
| ev | periodic self verification | izw | internal cyclical maintenance |
| Ve | long-term stability recognized | g | blocked for accredited testing |
| vk! | Attention: extended calibration interval | | |
| NK! | Attention: not calibrated | *) | next calibration ordered / currently in progress |

6.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter

$$FS = UR + CL + AF$$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

$$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \mu V/m)$$

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|--|------------------|---------------|------------|-----------|---------------------|------------------|------------------|
| 1 | A | Switch-Unit | 3488A | HP | 2719A14505 | 300000368 | ev | -/- | -/- |
| 2 | A | DC power supply, 60Vdc, 50A, 1200 W | 6032A | HP | 2920A04466 | 300000580 | ne | -/- | -/- |
| 3 | A | Meßkabine 1 | HF-Absorberhalle | MWB AG 300023 | -/- | 300000551 | ne | -/- | -/- |
| 4 | A | EMI Test Receiver | ESCI 3 | R&S | 100083 | 300003312 | k | 15.12.2017 | 14.12.2018 |
| 5 | A | Antenna Tower | Model 2175 | ETS-Lindgren | 64762 | 300003745 | izw | -/- | -/- |
| 6 | A | Positioning Controller | Model 2090 | ETS-Lindgren | 64672 | 300003746 | izw | -/- | -/- |
| 7 | A | Turntable Interface-Box | Model 105637 | ETS-Lindgren | 44583 | 300003747 | izw | -/- | -/- |
| 8 | A | TRILOG Broadband Test-Antenna 30 MHz - 3 GHz | VULB9163 | Schwarzbeck | 295 | 300003787 | k | 25.04.2016 | 25.04.2018 |

6.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter

$$FS = UR + CA + AF$$

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:


$$FS \text{ [dB}\mu\text{V/m]} = 40.0 \text{ [dB}\mu\text{V/m]} + (-35.8) \text{ [dB]} + 32.9 \text{ [dB/m]} = 37.1 \text{ [dB}\mu\text{V/m]} (71.61 \mu\text{V/m})$$

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|--|---------------------------------|----------------------|------------|-----------|---------------------|------------------|------------------|
| 1 | A, B, C | DC power supply, 60Vdc, 50A, 1200 W | 6032A | HP | 2818A03450 | 300001040 | v IKI! | 12.12.2017 | 11.12.2020 |
| 2 | C | Active Loop Antenna 9 kHz to 30 MHz | 6502 | EMCO | 2210 | 300001015 | k | 07.07.2017 | 06.07.2019 |
| 3 | A, B, C | Anechoic chamber | FAC 3/5m | MWB / TDK | 87400/02 | 300000996 | ev | -/- | -/- |
| 4 | A, B | Double-Ridged Waveguide Horn Antenna 1-18.0GHz | 3115 | EMCO | 9107-3697 | 300001605 | v IKI! | 14.02.2017 | 13.02.2019 |
| 5 | A, B, C | Switch / Control Unit | 3488A | HP | * | 300000199 | ne | -/- | -/- |
| 6 | B | Band Reject filter | WRCG2400/2483-2375/2505-50/10SS | Wainwright | 11 | 300003351 | ev | -/- | -/- |
| 7 | A, B, C | EMI Test Receiver 20Hz- 26,5GHz | ESU26 | R&S | 100037 | 300003555 | k | 20.12.2017 | 19.12.2018 |
| 8 | B | Highpass Filter | WHK1.1/15G-10SS | Wainwright | 3 | 300003255 | ev | -/- | -/- |
| 9 | B | Highpass Filter | WHKX7.0/18G-8SS | Wainwright | 19 | 300003790 | ne | -/- | -/- |
| 10 | A, B | Broadband Amplifier 0.5-18 GHz | CBLU5184540 | CERNEX | 22049 | 300004481 | ev | -/- | -/- |
| 11 | B | Broadband Amplifier 5-13 GHz | CBLU5135235 | CERNEX | 22010 | 300004491 | ev | -/- | -/- |
| 12 | A, B, C | 4U RF Switch Platform | L4491A | Agilent Technologies | MY50000037 | 300004509 | ne | -/- | -/- |
| 13 | A, B, C | NEXIO EMV-Software | BAT EMC V3.16.0.49 | EMCO | -/- | 300004682 | ne | -/- | -/- |
| 14 | A, B, C | PC | ExOne | F+W | -/- | 300004703 | ne | -/- | -/- |

6.3 Radiated measurements > 18 GHz

Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

$$FS = UR + CA + AF$$

(FS-field strength; UR-voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)

Example calculation:


$$FS \text{ [dB}\mu\text{V/m]} = 40.0 \text{ [dB}\mu\text{V/m]} + (-60.1) \text{ [dB]} + 36.74 \text{ [dB/m]} = 16.64 \text{ [dB}\mu\text{V/m]} \text{ (6.79 } \mu\text{V/m)}$$

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|--|-------------------|----------------|------------------|-----------|---------------------|------------------|------------------|
| 1 | A | Microwave System Amplifier, 0.5-26.5 GHz | 83017A | HP | 00419 | 300002268 | ev | -/- | -/- |
| 2 | A | Std. Gain Horn Antenna 18.0-26.5 GHz | 638 | Narda | -/- | 300000486 | k | 13.12.2017 | 12.12.2019 |
| 3 | A | Signal Analyzer 40 GHz | FSV40 | R&S | 101042 | 300004517 | k | 16.01.2018 | 15.01.2019 |
| 4 | A | RF-Cable | ST18/SMAm/SMAm/48 | Huber & Suhner | Batch no. 127377 | 400001183 | ev | -/- | -/- |
| 5 | A | DC-Blocker 0.1-40 GHz | 8141A | Inmet | -/- | 400001185 | ev | -/- | -/- |

6.4 Conducted measurements with peak power meter & spectrum analyzer

Conducted measurements normal conditions



$$OP = AV + CA$$

(OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

$$OP \text{ [dBm]} = 6.0 \text{ [dBm]} + 11.7 \text{ [dB]} = 17.7 \text{ [dBm]} \text{ (58.88 mW)}$$

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|---|---------------------------------------|---------------------------|------------------|-----------|---------------------|------------------|------------------|
| 1 | A | Signal Analyzer 40 GHz | FSV40 | R&S | 101042 | 300004517 | k | 16.01.2018 | 15.01.2019 |
| 2 | A | DC-Blocker 0.1-40 GHz | 8141A | Inmet | -/- | 400001185 | ev | -/- | -/- |
| 3 | A | Hygro-Thermometer | -/-, 5-45°C, 20-100rF | -/- | -/- | 400000108 | ev | -/- | -/- |
| 4 | A | PC-WLAN Tester | Intel Core i3 3220/3.3 GHz, Prozessor | -/- | 2V2403033A4523 | 300004589 | ne | -/- | -/- |
| 5 | A | Teststand | Teststand Custom Sequence Editor | National Instruments GmbH | -/- | 300004590 | ne | -/- | -/- |
| 6 | A | PowerSplitter/Combiner 150-6000MHz N-Type | ZB3PD-63-N+ | Mini-Circuits | -/- | 400000451 | ev | -/- | -/- |
| 7 | A | RF-Cable | ST18/SMAm/SMAm/60 | Huber & Suhner | Batch no. 606844 | 400001181 | ev | -/- | -/- |
| 8 | A | Coax Attenuator 10 dB 2W 0-40 GHz | MCL BW-K10-2W44+ | Mini Circuits | -/- | 400001186 | ev | -/- | -/- |
| 9 | A | Synchron Power Meter | SPM-4 | CTC | 1 | 400001294 | ev | -/- | -/- |

7 Sequence of testing

7.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*)Note: The sequence will be repeated three times with different EUT orientations.

7.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

8 Measurement uncertainty

| Measurement uncertainty | |
|--|---|
| Test case | Uncertainty |
| Antenna gain | ± 3 dB |
| Power spectral density | ± 1.5 dB |
| DTS bandwidth | ± 100 kHz (depends on the used RBW) |
| Occupied bandwidth | ± 100 kHz (depends on the used RBW) |
| Maximum output power | ± 1.5 dB |
| Detailed spurious emissions @ the band edge - conducted | ± 1.5 dB |
| Band edge compliance radiated | ± 3 dB |
| Spurious emissions conducted | ± 3 dB |
| Spurious emissions radiated below 30 MHz | ± 3 dB |
| Spurious emissions radiated 30 MHz to 1 GHz | ± 3 dB |
| Spurious emissions radiated 1 GHz to 12.75 GHz | ± 3.7 dB |
| Spurious emissions radiated above 12.75 GHz | ± 4.5 dB |
| Spurious emissions conducted below 30 MHz (AC conducted) | ± 2.6 dB |

9 Summary of measurement results

| | |
|-------------------------------------|--|
| <input type="checkbox"/> | No deviations from the technical specifications were ascertained |
| <input type="checkbox"/> | There were deviations from the technical specifications ascertained |
| <input checked="" type="checkbox"/> | This test report is only a partial test report. The content and verdict of the performed test cases are listed below. |

| TC Identifier | Description | Verdict | Date | Remark |
|---------------|-----------------------------------|------------|------------|--|
| RF-Testing | CFR Part 15 RSS - 247, Issue 2 | See table! | 2018-05-02 | Delta test according to customer demand. |

| Test specification clause | Test case | Guideline | Temperature conditions | Power source voltages | Mode | C | NC | NA | NP | Remark |
|--|---|--|------------------------|-----------------------|-----------|-------------------------------------|--------------------------|-------------------------------------|-------------------------------------|--------|
| §15.247(b)(4) RSS - 247 / 5.4 (f)(ii) | Antenna gain | -/- | Nominal | Nominal | DSSS | -/- | | | | -/- |
| §15.35 | Duty cycle | -/- | Nominal | Nominal | DSSS OFDM | -/- | | | | -/- |
| §15.247(e) RSS - 247 / 5.2 (b) | Power spectral density | KDB 558074 DTS clause: 10.2 | Nominal | Nominal | DSSS OFDM | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | -/- |
| §15.247(a)(2) RSS - 247 / 5.2 (a) | DTS bandwidth | KDB 558074 DTS clause: 8.1 | Nominal | Nominal | DSSS OFDM | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | -/- |
| RSS Gen clause 4.6.1 | Occupied bandwidth | -/- | Nominal | Nominal | DSSS OFDM | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | -/- |
| §15.247(b)(3) RSS - 247 / 5.4 (d) | Maximum output power | KDB 558074 DTS clause: 9.1.2 | Nominal | Nominal | DSSS OFDM | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 | Detailed spurious emissions @ the band edge – cond. | -/- | Nominal | Nominal | DSSS OFDM | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | -/- |
| §15.205 RSS - 247 / 5.5 RSS - Gen | Band edge compliance cond. & rad. | KDB 558074 DTS clause: 13.3.2 and clause 12.2.2 | Nominal | Nominal | DSSS OFDM | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 | TX spurious emissions cond. | KDB 558074 DTS clause: 11.1 & 11.2 11.3 | Nominal | Nominal | DSSS OFDM | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | -/- |
| §15.209(a) RSS-Gen | TX spurious emissions rad. below 30 MHz | -/- | Nominal | Nominal | DSSS OFDM | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 RSS-Gen | TX spurious emissions rad. 30 MHz to 1 GHz | -/- | Nominal | Nominal | DSSS OFDM | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 RSS-Gen | TX spurious emissions rad. above 1 GHz | -/- | Nominal | Nominal | DSSS OFDM | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.109 RSS-Gen | RX spurious emissions rad. 30 MHz to 1 GHz | -/- | Nominal | Nominal | RX / idle | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.109 RSS-Gen | RX spurious emissions rad. above 1 GHz | -/- | Nominal | Nominal | RX / idle | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.107(a) §15.207 | Conducted emissions < 30 MHz | -/- | Nominal | Nominal | DSSS OFDM | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | -/- |

Notes:

| | | | | | | | |
|----------|-----------|-----------|---------------|-----------|----------------|-----------|---------------|
| C | Compliant | NC | Not compliant | NA | Not applicable | NP | Not performed |
|----------|-----------|-----------|---------------|-----------|----------------|-----------|---------------|

10 Additional comments

Reference documents: None

Special test descriptions: Power setting 16 was used for all tests.

Configuration descriptions: None

Provided channels:

Channels with 20 MHz channel bandwidth:

| channel number & center frequency | | | | | | | | | | | | | |
|-----------------------------------|-------------|------|------|------|------|-------------|------|------|------|------|-------------|-----|-----|
| channel | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | -/- | -/- |
| f _c / MHz | 2412 | 2417 | 2422 | 2427 | 2432 | 2437 | 2442 | 2447 | 2452 | 2457 | 2462 | -/- | -/- |

Note: The channels used for the tests are marked in bold in the list.

11 Additional EUT parameter

- Test mode: ☐ No test mode available
lperf was used to ping another device with the largest support packet size
- ☒ Test mode available
Special software is used.
EUT is transmitting pseudo random data by itself
- Modulation types: ☒ Wide Band Modulation (None Hopping – e.g. DSSS, OFDM)
- ☐ Frequency Hopping Spread Spectrum (FHSS)
- Antennas and transmit operating modes: ☒ Operating mode 1 (single antenna)
- *Equipment with 1 antenna,*
 - *Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,*
 - *Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)*
- ☐ Operating mode 2 (multiple antennas, no beamforming)
- *Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously but without beamforming.*
- ☐ Operating mode 3 (multiple antennas, with beamforming)
- *Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously with beamforming.
In addition to the antenna assembly gain (G), the beamforming gain (Y) may have to be taken into account when performing the measurements.*

12 Measurement results

12.1 Antenna gain

Description:

The antenna gain of the complete system is calculated by the difference of radiated power (@ 3 MHz) in EIRP and the conducted power (@ 3 MHz) of the module.

Measurement:

| Measurement parameter | |
|-------------------------|---|
| Detector | Peak |
| Sweep time | Auto |
| Resolution bandwidth | 3 MHz |
| Video bandwidth | 3 MHz / 10 MHz |
| Trace mode | Max hold |
| Test setup | See chapter 6.4 – A (conducted) See chapter 6.2 – A (radiated) |
| Measurement uncertainty | See chapter 8 |

Limits:

| FCC | IC |
|---|----|
| 6 dBi / > 6 dBi output power and power density reduction required | |

Results:

| | lowest channel | middle channel | highest channel |
|--|----------------|----------------|-----------------|
| Conducted power / dBm Measured with DSSS modulation | 13.4 | 12.8 | 13.5 |
| Radiated power / dBm Measured with DSSS modulation | 12.8 | 12.4 | 11.8 |
| Gain / dBi Calculated | -0.6 | -0.4 | -1.7 |

12.2 Identify worst case data rate

Results:

| Modulation scheme / bandwidth | |
|-------------------------------|-----------|
| DSSS / b – mode | 1 Mbit/s* |
| OFDM / g – mode | 6 Mbit/s* |
| OFDM / n HT20 – mode | MCS0* |

* Worst case data rate or modulation scheme declared by the manufacturer

12.3 Maximum output power

Description:

Measurement of the maximum output power conducted and radiated. The measurements are performed using the data rate producing the highest conducted output power.

Measurement:

| Measurement parameter | |
|--------------------------------|------------------------|
| According to DTS clause: 9.1.2 | |
| Peak power meter | |
| Test setup: | See sub clause 6.4 – A |
| Measurement uncertainty | See sub clause 8 |

Limits:

| FCC | IC |
|---|----|
| Conducted: 1.0 W – Antenna gain with max. 6 dBi | |

Results:

| Frequency | Maximum Output Power [dBm] | | |
|--|----------------------------|----------|----------|
| | 2412 MHz | 2437 MHz | 2462 MHz |
| Output power conducted DSSS / b – mode | 15.7 | 15.4 | 16.0 |
| Output power conducted OFDM / g – mode | 21.0 | 20.4 | 21.1 |
| Output power conducted OFDM / n HT20 – mode | 21.1 | 20.5 | 21.0 |

12.4 Band edge compliance radiated

Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to the lowest channel for the lower restricted band and to the highest channel for the upper restricted band. The measurement is repeated for all modulations. Measurement distance is 3 meter.

Measurement:

| | Measurement parameter for peak/average measurements radiated | Measurement parameter for average measurements |
|-------------------------|---|--|
| | | According to DTS clause: 13.3.2 |
| Detector | Peak/Average | RMS |
| Sweep time | Auto | Auto |
| Resolution bandwidth | 1 MHz | 100 kHz |
| Video bandwidth | 3 MHz | 300 kHz |
| Span | See plot | 2 MHz |
| Trace mode | Max. hold | RMS Average over 101 sweeps |
| Analyzer function | -/- | Band power function (Compute the power by integrating the spectrum over 1 MHz) |
| Test setup | See chapter 6.2 – A | |
| Measurement uncertainty | See chapter 8 | |

Limits:


| FCC | IC |
|---|----|
| 74 dB μ V/m @ 3 m (Peak) 54 dB μ V/m @ 3 m (AVG) | |

Results:


| band edge compliance radiated / (dB μ V / m) @ 3 m | | | |
|--|---|---|---|
| | b-mode | g-mode | n HT20-mode |
| Lower band edge | 67.8 dB μ V/m (Peak) 45.3 dB μ V/m (AVG) | 66.6 dB μ V/m (Peak) 50.4 dB μ V/m (AVG) | 69.4 dB μ V/m (Peak) 51.9 dB μ V/m (AVG) |
| Upper band edge | 67.9 dB μ V/m (Peak) 45.1 dB μ V/m (AVG) | 67.3 dB μ V/m (Peak) 50.9 dB μ V/m (AVG) | 67.6 dB μ V/m (Peak) 52.3 dB μ V/m (AVG) |

Plots: b-mode - peak / average

Plot 1: TX mode, lower band edge, vertical & horizontal polarization




Plot 2: TX mode, upper band edge, vertical & horizontal polarization




Plots: g-mode - peak / average

Plot 1: TX mode, lower band edge, vertical & horizontal polarization




Plot 2: TX mode, upper band edge, vertical & horizontal polarization




Plots: n HT20-mode - peak / average

Plot 1: TX mode, lower band edge, vertical & horizontal polarization



Plot 2: TX mode, upper band edge, vertical & horizontal polarization



12.5 Spurious emissions radiated below 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:



| Measurement parameter | |
|-------------------------|--|
| Detector | Peak / Quasi Peak |
| Sweep time | Auto |
| Resolution bandwidth | F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz |
| Video bandwidth | F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz |
| Span | 9 kHz to 30 MHz |
| Trace mode | Max Hold |
| Measured modulation | DSSS b – mode OFDM g – mode OFDM n HT20 – mode |
| Test setup | See chapter 6.2 – C |
| Measurement uncertainty | See chapter 8 |

Limits:


| FCC | | IC |
|-----------------|-----------------------------------|--------------------------|
| Frequency / MHz | Field Strength / (dB μ V / m) | Measurement distance / m |
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30.0 | 30 | 30 |

Results:

| TX spurious emissions radiated < 30 MHz / (dB μ V / m) @ 3 m | | |
|--|----------|--------------------------|
| Frequency / MHz | Detector | Level / (dB μ V / m) |
| All detected peaks are more than 20 dB below the limit. | | |
| | | |


Plots: DSSS**Plot 1:** 9 kHz to 30 MHz, lowest channel**Plot 2:** 9 kHz to 30 MHz, middle channel

Plot 3: 9 kHz to 30 MHz, highest channel




Plots: g-mode (20 MHz nominal channel bandwidth)


Plot 1: 9 kHz to 30 MHz, lowest channel



Plot 2: 9 kHz to 30 MHz, middle channel




Plot 3: 9 kHz to 30 MHz, highest channel




Plots: n HT20-mode (20 MHz nominal channel bandwidth)


Plot 1: 9 kHz to 30 MHz, lowest channel



Plot 2: 9 kHz to 30 MHz, middle channel



Plot 3: 9 kHz to 30 MHz, highest channel



12.6 Spurious emissions radiated 30 MHz to 1 GHz

Description:


Measurement of the radiated spurious emissions and cabinet radiations below 1 GHz.

Measurement:


| Measurement parameter | |
|-------------------------|--|
| Detector | Peak / Quasi Peak |
| Sweep time | Auto |
| Resolution bandwidth | 120 kHz |
| Video bandwidth | 3 x RBW |
| Span | 30 MHz to 1 GHz |
| Trace mode | Max Hold |
| Measured modulation | DSSS b – mode OFDM g – mode OFDM n HT20 – mode RX / Idle – mode |
| Test setup | See chapter 6.1 – A |
| Measurement uncertainty | See chapter 8 |

Limits:


| FCC | | IC |
|--|-----------------------------|--------------------------|
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). | | |
| Frequency / MHz | Field Strength / (dBµV / m) | Measurement distance / m |
| 30 – 88 | 30.0 | 10 |
| 88 – 216 | 33.5 | 10 |
| 216 – 960 | 36.0 | 10 |

Plot: DSSS**Plot 1:** 30 MHz to 1 GHz, vertical & horizontal polarization, lowest channel**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 40.353 | 9.64 | 30.0 | 20.36 | 1000 | 120 | 101.0 | V | 90.0 | 13.2 |
| 44.520 | 9.64 | 30.0 | 20.36 | 1000 | 120 | 170.0 | V | 270.0 | 13.6 |
| 515.416 | 17.81 | 36.0 | 18.19 | 1000 | 120 | 170.0 | V | 0.0 | 18.9 |
| 686.133 | 18.26 | 36.0 | 17.74 | 1000 | 120 | 170.0 | V | 0.0 | 21.4 |
| 767.775 | 19.38 | 36.0 | 16.62 | 1000 | 120 | 101.0 | H | 270.0 | 22.7 |
| 874.960 | 20.95 | 36.0 | 15.05 | 1000 | 120 | 170.0 | H | 0.0 | 23.9 |

Plot 2: 30 MHz to 1 GHz, vertical & horizontal polarization, middle channel**Final results:**


| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 33.227 | 9.80 | 30.0 | 20.20 | 1000 | 120 | 101.0 | H | 180.0 | 12.4 |
| 51.364 | 9.70 | 30.0 | 20.30 | 1000 | 120 | 170.0 | H | 180.0 | 13.6 |
| 61.380 | 7.89 | 30.0 | 22.11 | 1000 | 120 | 101.0 | H | 270.0 | 11.5 |
| 498.054 | 14.52 | 36.0 | 21.48 | 1000 | 120 | 100.0 | V | 180.0 | 18.7 |
| 706.075 | 18.60 | 36.0 | 17.40 | 1000 | 120 | 101.0 | V | 270.0 | 21.7 |
| 898.083 | 20.96 | 36.0 | 15.04 | 1000 | 120 | 101.0 | V | 180.0 | 24.2 |

Plot 3: 30 MHz to 1 GHz, vertical & horizontal polarization, highest channel**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 39.658 | 9.36 | 30.0 | 20.64 | 1000 | 120 | 101.0 | V | 180.0 | 13.2 |
| 52.639 | 9.03 | 30.0 | 20.97 | 1000 | 120 | 101.0 | V | 270.0 | 13.4 |
| 63.938 | 6.75 | 30.0 | 23.25 | 1000 | 120 | 101.0 | V | 0.0 | 11.0 |
| 512.215 | 14.70 | 36.0 | 21.30 | 1000 | 120 | 101.0 | V | 180.0 | 18.9 |
| 721.766 | 18.92 | 36.0 | 17.08 | 1000 | 120 | 98.0 | V | 90.0 | 22.1 |
| 954.568 | 21.11 | 36.0 | 14.89 | 1000 | 120 | 170.0 | H | 270.0 | 24.4 |


Plot: g-mode (20 MHz nominal channel bandwidth)

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization, lowest channel




Final results:

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 33.657 | 8.13 | 30.0 | 21.87 | 1000 | 120 | 101.0 | V | 90.0 | 12.4 |
| 39.866 | 9.46 | 30.0 | 20.54 | 1000 | 120 | 170.0 | H | 270.0 | 13.2 |
| 54.039 | 8.85 | 30.0 | 21.15 | 1000 | 120 | 170.0 | H | 270.0 | 13.2 |
| 482.857 | 14.01 | 36.0 | 21.99 | 1000 | 120 | 98.0 | V | 270.0 | 18.4 |
| 729.817 | 19.18 | 36.0 | 16.82 | 1000 | 120 | 170.0 | V | 270.0 | 22.3 |
| 866.174 | 20.79 | 36.0 | 15.21 | 1000 | 120 | 101.0 | H | 270.0 | 23.7 |

Plot 2: 30 MHz to 1 GHz, vertical & horizontal polarization, middle channel**Final results:**


| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 41.455 | 9.36 | 30.0 | 20.64 | 1000 | 120 | 101.0 | V | 270.0 | 13.3 |
| 44.817 | 9.84 | 30.0 | 20.16 | 1000 | 120 | 101.0 | H | 270.0 | 13.6 |
| 61.939 | 7.79 | 30.0 | 22.21 | 1000 | 120 | 101.0 | V | 90.0 | 11.4 |
| 514.801 | 14.59 | 36.0 | 21.41 | 1000 | 120 | 170.0 | H | 0.0 | 18.9 |
| 726.946 | 19.11 | 36.0 | 16.89 | 1000 | 120 | 98.0 | H | 90.0 | 22.2 |
| 911.916 | 20.87 | 36.0 | 15.13 | 1000 | 120 | 170.0 | V | 90.0 | 24.2 |

Plot 3: 30 MHz to 1 GHz, vertical & horizontal polarization, highest channel**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 39.690 | 9.38 | 30.0 | 20.62 | 1000 | 120 | 170.0 | V | 0.0 | 13.2 |
| 50.807 | 9.94 | 30.0 | 20.06 | 1000 | 120 | 101.0 | H | 180.0 | 13.6 |
| 61.591 | 7.86 | 30.0 | 22.14 | 1000 | 120 | 170.0 | V | 270.0 | 11.5 |
| 515.398 | 18.06 | 36.0 | 17.94 | 1000 | 120 | 170.0 | V | 270.0 | 18.9 |
| 719.167 | 18.90 | 36.0 | 17.10 | 1000 | 120 | 98.0 | H | 90.0 | 22.0 |
| 804.468 | 19.59 | 36.0 | 16.41 | 1000 | 120 | 170.0 | V | 0.0 | 22.8 |


Plot: n HT20-mode (20 MHz nominal channel bandwidth)

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization, lowest channel




Final results:

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 40.722 | 9.74 | 30.0 | 20.26 | 1000 | 120 | 102.0 | V | 180.0 | 13.3 |
| 47.439 | 9.12 | 30.0 | 20.88 | 1000 | 120 | 101.0 | H | 90.0 | 13.7 |
| 49.506 | 9.65 | 30.0 | 20.35 | 1000 | 120 | 101.0 | V | 180.0 | 13.7 |
| 515.612 | 14.63 | 36.0 | 21.37 | 1000 | 120 | 101.0 | H | 0.0 | 18.9 |
| 725.573 | 19.00 | 36.0 | 17.00 | 1000 | 120 | 170.0 | H | 0.0 | 22.2 |
| 868.643 | 20.90 | 36.0 | 15.10 | 1000 | 120 | 101.0 | H | 90.0 | 23.8 |

Plot 2: 30 MHz to 1 GHz, vertical & horizontal polarization, middle channel**Final results:**


| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 36.389 | 9.05 | 30.0 | 20.95 | 1000 | 120 | 170.0 | H | 90.0 | 12.8 |
| 44.778 | 9.79 | 30.0 | 20.21 | 1000 | 120 | 170.0 | V | 270.0 | 13.6 |
| 495.520 | 14.36 | 36.0 | 21.64 | 1000 | 120 | 98.0 | V | 180.0 | 18.6 |
| 681.502 | 18.24 | 36.0 | 17.76 | 1000 | 120 | 98.0 | H | 90.0 | 21.4 |
| 755.223 | 19.53 | 36.0 | 16.47 | 1000 | 120 | 98.0 | V | 270.0 | 22.7 |
| 956.590 | 21.04 | 36.0 | 14.96 | 1000 | 120 | 170.0 | V | 90.0 | 24.4 |

Plot 3: 30 MHz to 1 GHz, vertical & horizontal polarization, highest channel**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 39.912 | 9.46 | 30.0 | 20.54 | 1000 | 120 | 170.0 | V | 180.0 | 13.2 |
| 44.602 | 9.73 | 30.0 | 20.27 | 1000 | 120 | 170.0 | H | 90.0 | 13.6 |
| 494.965 | 14.38 | 36.0 | 21.62 | 1000 | 120 | 170.0 | V | 270.0 | 18.6 |
| 674.192 | 18.10 | 36.0 | 17.90 | 1000 | 120 | 170.0 | H | 270.0 | 21.3 |
| 780.455 | 19.45 | 36.0 | 16.55 | 1000 | 120 | 101.0 | V | 0.0 | 22.7 |
| 877.859 | 20.84 | 36.0 | 15.16 | 1000 | 120 | 170.0 | V | 0.0 | 23.9 |

Plot: RX / Idle mode

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization



Final results:

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 38.046 | 8.42 | 30.0 | 21.58 | 1000 | 120 | 101.0 | V | 270.0 | 13.0 |
| 44.951 | 10.01 | 30.0 | 19.99 | 1000 | 120 | 101.0 | V | 0.0 | 13.6 |
| 513.437 | 14.65 | 36.0 | 21.35 | 1000 | 120 | 170.0 | V | 0.0 | 18.9 |
| 655.811 | 17.91 | 36.0 | 18.09 | 1000 | 120 | 170.0 | H | 270.0 | 21.2 |
| 908.264 | 20.98 | 36.0 | 15.02 | 1000 | 120 | 170.0 | H | 0.0 | 24.2 |
| 989.423 | 21.50 | 44.0 | 22.50 | 1000 | 120 | 170.0 | V | 0.0 | 24.8 |

12.7 Spurious emissions radiated above 1 GHz

Description:

Measurement of the radiated spurious emissions above 1 GHz in transmit mode and receiver / idle mode.

Measurement:

| Measurement parameter | |
|-------------------------|--|
| Detector | Peak / RMS |
| Sweep time | Auto |
| Resolution bandwidth | 1 MHz |
| Video bandwidth | 3 x RBW |
| Span | 1 GHz to 26 GHz |
| Trace mode | Max Hold |
| Measured modulation | DSSS b – mode OFDM g – mode OFDM n HT20-mode RX / Idle – mode |
| Test setup | See chapter 6.2 – B See chapter 6.3 – A |
| Measurement uncertainty | See chapter 8 |

Limits:

| FCC | | IC |
|--|-----------------------------|--------------------------|
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). | | |
| Frequency / MHz | Field Strength / (dBµV / m) | Measurement distance / m |
| Above 960 | 54.0 (AVG) | 3 |
| | 74.0 (peak) | |

Results: b-mode

| TX spurious emissions radiated / dBµV/m @ 3 m | | | | | | | | |
|---|----------|--------------------|---|----------|----------------|---|----------|----------------|
| lowest channel | | | middle channel | | | highest channel | | |
| f / MHz | Detector | Level / dBµV/m | f / MHz | Detector | Level / dBµV/m | f / MHz | Detector | Level / dBµV/m |
| 1056 | Peak | 36.6 | 1056 | Peak | 36.6 | 1056 | Peak | 36.6 |
| | AVG | 28.5 | | AVG | 28.5 | | AVG | 28.5 |
| 2374 | Peak | 54.6 | 2374 | Peak | 54.6 | 2374 | Peak | 54.6 |
| | AVG | 43.1 | | AVG | 43.1 | | AVG | 43.1 |
| 7235 | Peak | No restricted band | 7311 | Peak | 48.7 | 7385 | Peak | 50.6 |
| | AVG | | | 41.6 | AVG | | 45.2 | |
| For emissions above 18 GHz - see plots. | | | For emissions above 18 GHz - see plots. | | | For emissions above 18 GHz - see plots. | | |

Results: g-mode (20 MHz nominal channel bandwidth)


| TX spurious emissions radiated / dBµV/m @ 3 m | | | | | | | | |
|---|----------|--------------------|---|----------|----------------|---|----------|----------------|
| lowest channel | | | middle channel | | | highest channel | | |
| f / MHz | Detector | Level / dBµV/m | f / MHz | Detector | Level / dBµV/m | f / MHz | Detector | Level / dBµV/m |
| 1056 | Peak | 36.6 | 1056 | Peak | 36.6 | 1056 | Peak | 36.6 |
| | AVG | 28.5 | | AVG | 28.5 | | AVG | 28.5 |
| 2374 | Peak | 54.6 | 2374 | Peak | 54.6 | 2374 | Peak | 54.6 |
| | AVG | 43.1 | | AVG | 43.1 | | AVG | 43.1 |
| 7230 | Peak | No restricted band | -/- | Peak | -/- | 7390 | Peak | 51.6 |
| | AVG | | | AVG | -/- | | AVG | 37.3 |
| For emissions above 18 GHz - see plots. | | | For emissions above 18 GHz - see plots. | | | For emissions above 18 GHz - see plots. | | |

Results: n HT20-mode (20 MHz nominal channel bandwidth)


| TX spurious emissions radiated / dBµV/m @ 3 m | | | | | | | | |
|---|----------|--------------------|---|----------|----------------|---|----------|----------------|
| lowest channel | | | middle channel | | | highest channel | | |
| f / MHz | Detector | Level / dBµV/m | f / MHz | Detector | Level / dBµV/m | f / MHz | Detector | Level / dBµV/m |
| 1056 | Peak | 36.6 | 1056 | Peak | 36.6 | 1056 | Peak | 36.6 |
| | AVG | 28.5 | | AVG | 28.5 | | AVG | 28.5 |
| 2374 | Peak | 54.6 | 2374 | Peak | 54.6 | 2374 | Peak | 54.6 |
| | AVG | 43.1 | | AVG | 43.1 | | AVG | 43.1 |
| 7232 | Peak | No restricted band | -/- | Peak | -/- | 7392 | Peak | 51.8 |
| | AVG | | | AVG | -/- | | AVG | 38.4 |
| For emissions above 18 GHz - see plots. | | | For emissions above 18 GHz - see plots. | | | For emissions above 18 GHz - see plots. | | |


Results: RX / idle – mode

| TX spurious emissions radiated / dBµV/m @ 3 m | | |
|---|----------|----------------|
| f / MHz | Detector | Level / dBµV/m |
| 1056 | Peak | 36.6 |
| | AVG | 28.5 |
| For emissions above 18 GHz - see plots. | | |


Plots: DSSS**Plot 1:** Lowest channel, 1 GHz to 18 GHz, vertical & horizontal polarization

The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization

Plot 3: Middle channel, 1 GHz to 18 GHz, vertical & horizontal polarization


The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 4: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization

Date: 4.APR.2018 10:47:13


Plot 5: Highest channel, 1 GHz to 18 GHz, vertical & horizontal polarization


The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization


Plots: g-mode**Plot 1:** Lowest channel, 1 GHz to 18 GHz, vertical & horizontal polarization


The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 2: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization


Plot 3: Middle channel, 1 GHz to 18 GHz, vertical & horizontal polarization

The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 4: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization

Plot 5: Highest channel, 1 GHz to 18 GHz, vertical & horizontal polarization


The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 6: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization

Date: 4.APR.2018 10:54:21


Plots: n HT20-mode**Plot 1:** Lowest channel, 1 GHz to 18 GHz, vertical & horizontal polarization


The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 2: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization


Plot 3: Middle channel, 1 GHz to 18 GHz, vertical & horizontal polarization



The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization

Plot 5: Highest channel, 1 GHz to 18 GHz, vertical & horizontal polarization

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization

Plots: RX / idle mode**Plot 1:** 1 GHz to 18 GHz, vertical & horizontal polarization**Plot 2:** 18 GHz to 26 GHz, vertical & horizontal polarization

Date: 4.APR.2018 10:58:32

13 Observations

No observations except those reported with the single test cases have been made.

Annex A Glossary

| | |
|------------------|--|
| EUT | Equipment under test |
| DUT | Device under test |
| UUT | Unit under test |
| FCC | Federal Communications Commission |
| FCC ID | Company Identifier at FCC |
| IC | Industry Canada |
| PMN | Product marketing name |
| HMN | Host marketing name |
| HVIN | Hardware version identification number |
| FVIN | Firmware version identification number |
| EMC | Electromagnetic Compatibility |
| HW | Hardware |
| SW | Software |
| Inv. No. | Inventory number |
| S/N or SN | Serial number |
| C | Compliant |
| NC | Not compliant |
| NA | Not applicable |
| NP | Not performed |
| PP | Positive peak |
| QP | Quasi peak |
| AVG | Average |
| OC | Operating channel |
| OCW | Operating channel bandwidth |
| OBW | Occupied bandwidth |
| OOB | Out of band |
| DFS | Dynamic frequency selection |
| CAC | Channel availability check |
| OP | Occupancy period |
| NOP | Non occupancy period |
| DC | Duty cycle |
| PER | Packet error rate |
| CW | Clean wave |
| MC | Modulated carrier |
| WLAN | Wireless local area network |
| RLAN | Radio local area network |
| DSSS | Dynamic sequence spread spectrum |
| OFDM | Orthogonal frequency division multiplexing |

Annex B Document history

| Version | Applied changes | Date of release |
|---------|-----------------|-----------------|
| -/- | Initial release | 2018-05-02 |

Annex C Accreditation Certificate

| first page | last page |
|---|--|
|  <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition</p> <p>Accreditation</p>  <p>The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory</p> <p>CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken</p> <p>is competent under the terms of DIN EN ISO/IEC 17025:2005 to carry out tests in the following fields:</p> <p>Telecommunication</p> <p>The accreditation certificate shall only apply in connection with the notice of accreditation of 02.06.2017 with the accreditation number D-PL-12076-01 and is valid until 21.04.2021. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 43 pages.</p> <p>Registration number of the certificate: D-PL-12076-01-03</p> <p>Frankfurt, 02.06.2017</p>  <p>Dipl.-Ing. (FH) Ralf Bömer Head of Division</p> <p><small>See notes enclosed.</small></p> | <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Office Berlin Spittelmarkt 10 10117 Berlin</p> <p>Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main</p> <p>Office Braunschweig Bundesallee 100 38116 Braunschweig</p> <p>The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.</p> <p>No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkKS.</p> <p>The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.</p> <p>The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu</p> |

Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkKS or may be received by CTC advanced GmbH on request

<http://www.dakks.de/as/ast/d/D-PL-12076-01-03.pdf>