


# TEST REPORT

<b>Applicant:</b>	Lightcomm Technology Co., Ltd.		
<b>Address:</b>	UNIT 1306 13/F ARION COMMERCIAL CENTRE,2-12 QUEEN'S ROAD WEST,SHEUNG WAN HK		
<b>Manufacturer:</b>	Lightcomm Technology Co., Ltd.		
<b>Address:</b>	UNIT 1306 13/F ARION COMMERCIAL CENTRE,2-12 QUEEN'S ROAD WEST,SHEUNG WAN HK		
<b>Factory:</b>	Huizhou Hengdu Electronics Co.,Ltd.		
<b>Address:</b>	No.8 Huitai Road,Huinan High-tech Industrial Park,Huiao Avenue,Huizhou,Guangdong,China		
<b>E.U.T.:</b>	Car Multimedia Player		
<b>Model Number:</b>	CVD1662-AJ		
<b>Series Model :</b>	CVD7621-AJ, CVD9662-AJ		
<b>Trade mark:</b>	N/A		
<b>FCC ID:</b>	XMF-CVD1662		
<b>Date of Receipt:</b>	Aug 04, 2024	<b>Date of Test:</b>	Aug 04, 2024- Aug 16, 2024
<b>Test Specification:</b>	FCC 47 CFR Part 15, Subpart C		
<b>Test Result:</b>	The equipment under test was found to be compliance with the requirements of the standards applied.		
<b>Prepared by:</b>	<b>Approved &amp; Authorized Signer:</b>		
			
Jerry Hu/ Engineer	Frank Shen/ Manager		
	Issue Date: August 23, 2024		
This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Dongguan Lepont Service Co., Ltd.			

## TABLE OF CONTENTS

### 1. GENERAL PRODUCT INFORMATION 4

1.1. PRODUCT FUNCTION .....	4
1.2. EUT TECHNICAL DESCRIPTION .....	4
1.3. INDEPENDENT OPERATION MODES .....	5
1.4. GENERAL CONDITION .....	6
1.5. SUPPORT EQUIPMENT .....	6

### 2. TEST STANDARDS AND SITES 7

2.1. DESCRIPTION OF STANDARDS AND RESULTS .....	7
2.2. LIST OF TEST AND MEASUREMENT INSTRUMENTS .....	8
2.3. MEASUREMENT UNCERTAINTY .....	9
2.4. TEST FACILITY .....	9

### 3. SETUP OF EQUIPMENT UNDER TEST 10

3.1. RADIO FREQUENCY TEST SETUP 1 .....	10
3.2. RADIO FREQUENCY TEST SETUP 2 .....	10
3.3. CONDUCTED EMISSION TEST SETUP .....	12
3.4. BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM .....	12

### 4. TEST RESULTS AND MEASUREMENT DATA 13

4.1. DTS (6DB) BANDWIDTH .....	13
4.2. MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	21
4.3. MAXIMUM POWER SPECTRAL DENSITY .....	24
4.4. UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS .....	32
4.5. RADIATED SPURIOUS EMISSION .....	54
4.6. ANTENNA APPLICATION .....	73
4.7. RF EXPOSURE .....	74
4.8. TESTING PHOTO .....	75
4.9. PHOTOGRAPHS OF THE EUT .....	76

Dongguan Lepont Testing Service Co.,Ltd.

## 1. GENERAL PRODUCT INFORMATION

### 1.1. PRODUCT FUNCTION

Refer to Technical Construction Form and User Manual.

### 1.2. EUT TECHNICAL DESCRIPTION

Product Name:	Car Multimedia Player
Model No.:	CVD1662-AJ , CVD7621-AJ, CVD9662-AJ
Test Model No:	CVD1662-AJ
Difference:	The above models are identical in PCB layout, internal structure and circuit. The difference is the model name and size for commercial use.
Sample(s) Status	Engineer sample
IEEE 802.11 WLAN Mode Supported :	<input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11n(40MHz channel bandwidth)
Modulation :	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range :	<input checked="" type="checkbox"/> 2412-2462MHz for 802.11b/g/n(HT20) <input checked="" type="checkbox"/> 2422-2462MHz for 802.11n(HT40)
Number of Channels :	<input checked="" type="checkbox"/> 11 channels for 802.11b/g/n(HT20); <input checked="" type="checkbox"/> 9 channels for 802.11n(HT40);
Antenna Type :	External antenna
Antenna Gain :	2dBi
Power Supply:	DC 12V

### 1.3. INDEPENDENT OPERATION MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Mode	Date Rate	Test Channel
IEEE 802.11b	1Mbps	Low/Middle/High
IEEE 802.11g	6Mbps	Low/Middle/High
IEEE 802.11n HT20	MCS0	Low/Middle/High
IEEE 802.11n HT40	MCS0	Low/Middle/High

#### Frequency and Channel list

Channel List			
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412		
2	2417		
3	2422	3	2422
4	2427	4	2427
5	2432	5	2432
6	2437	6	2437
7	2442	7	2442
8	2447	8	2447
9	2452	9	2452
10	2457	10	2457
11	2462	11	2462
802.11b/g/n(HT20)		802.11n(HT40)	

**1.4. GENERAL CONDITION**

	Temperature	Humidity
Ambient Condition:	22.4 °C	51.2 %RH

**1.5. SUPPORT EQUIPMENT**

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Laptop computer	Lenovo	Xiaoxin Pro IA5HR	PF490VB0

**Notes:**

- 1.All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2.Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 2. TEST STANDARDS AND SITES

### 2.1. DESCRIPTION OF STANDARDS AND RESULTS

The EUT have been tested according to the applicable standards as referenced below.

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d); 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	N/A	
15.203	Antenna Application	PASS	

NOTE1: N/A (Not Applicable)

15.207 only signals conducted onto the AC power lines are required to be measured. The equipment is only DC power supply, so "Power Line Conducted Emissions" is not required.

NOTE2: The report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

## 2.2. LIST OF TEST AND MEASUREMENT INSTRUMENTS

For conducted emission at the mains terminals test(Shielded Room 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
EMI Test Receiver	Rohde & Schwarz	ESHS30	8290501003	Jan. 24, 2024	1 Year	LEP-E002	☑
Artificial Mains Network	Baluelec	LSN016	BL041122050121	Nov. 15, 2023	1 Year	LEP-E067	☑
Shielded Room 1	MR	MR-L05	LEP-E053	Nov. 17, 2022	3 Year	LEP-E053	☑
Test software	EZ-EMC	Fala	LEPONT-03A2	N/A	N/A	N/A	☑
For radiated(9K-30M) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
EMI Test Receiver	Rohde & Schwarz	ESR 3	101849	Jan. 31, 2024	1 Year	LEP-E006	☑
Active Loop Antenna	Schwarzbeck	FMZB 1519C	00008	Jan. 24, 2024	3 Year	LEP-E068	☑
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	☑
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	☑
For radiated(30M-1G) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
EMI Test Receiver	Rohde & Schwarz	ESR 3	101849	Jan. 31, 2024	1 Year	LEP-E006	☑
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	743	Nov. 20, 2022	3 Year	LEP-E005	☑
Signal Amplifier	HP	8447D	1726A01222	Jan. 24, 2024	1 Year	LEP-E007	☑
6dB Attenuator	RswTech	5W 6dB	LEP-E084	Jan. 24, 2024	1 Year	LEP-E084	☑
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	☑
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	☑
For radiated(1-18G) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
Spectrum analyzer	Rohde & Schwarz	FSV40	101412	Jan. 24, 2024	1 Year	LEP-E076	☑
Spectrum analyzer	Agilent	N9020A	MY49100060	Jan. 24, 2024	1 Year	LEP-E020	☑
Horn antenna	Schwarzbeck	BBHA 9120D	01875	Nov. 20, 2022	3 Year	LEP-E024	☑
Preamplifier	Schwarzbeck	BBN 9718B	00010	Jan. 24, 2024	1 Year	LEP-E025	☑
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	☑
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	☑
For radiated(18-40G) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
Spectrum analyzer	Rohde & Schwarz	FSV40	101412	Jan. 24, 2024	1 Year	LEP-E076	☑
Horn antenna+Preamplifier	COM-POWER	AH840	10100020	Sep. 05, 2022	3 Year	LEP-E075	☑
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	☑
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	☑
For RF test							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
Spectrum analyzer	Rohde & Schwarz	FSV40	101412	Jan. 24, 2024	1 Year	LEP-E076	☑
Spectrum analyzer	Agilent	N9020A	MY49100060	Jan. 24, 2024	1 Year	LEP-E020	☑
Vector source	Agilent	N5182A	MY47420382	Jan. 24, 2024	1 Year	LEP-E021	☑
Analog signal source	Agilent	N5171B	MY51350292	Jan. 24, 2024	1 Year	LEP-E022	☑
All instrument	Rohde & Schwarz	CMW 500	1201.002K50	Jan. 24, 2024	1 Year	LEP-E019	☑
High and low temperature chamber	Math-mart	MT-1202-40	LEP-E041	Jan. 24, 2024	1 Year	LEP-E041	☑
control unit	Tonscend	JS0806-2	10165	Jan. 24, 2024	1 Year	LEP-E034	☑
Testing software	Tonscend	JSTS1120-3	Ver 2.6.77.0518	N/A	N/A	N/A	☑



### 2.3. MEASUREMENT UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\%$
Conducted Emissions Test	$\pm 3.08\text{dB}$
Radiated Emission Test	$\pm 4.60\text{dB}$
Power Density	$\pm 0.9\%$
Occupied Bandwidth Test	$\pm 2.3\%$
Band Edge Test	$\pm 1.2\%$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 3.2\%$
Humidity	$\pm 2.5\%$
Measurement Uncertainty for a level of Confidence of 95%	

### 2.4. TEST FACILITY

EMC Lab. : The Laboratory has been assessed and proved to be in compliance with CNAS/CL01  
The Certificate Registration Number is L10100.  
The Laboratory has been assessed and proved to be in compliance with A2LA  
The Certificate Registration Number is 6901.01  
FCC Designation No.: CN1351  
Test Firm Registration No.: 397428  
ISED CAB identifier: CN0151  
Test Firm Registration No.: 20133


Test Location : Dongguan Lepont Testing Service Co., Ltd.

Address : Room 102, Building 11, No.7, Houjie Science And Technology Avenue, Houjie, Dongguan, Guangdong, China

### 3. SETUP OF EQUIPMENT UNDER TEST

#### 3.1. RADIO FREQUENCY TEST SETUP 1

The component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



#### 3.2. RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 32.

Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


#### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 3.3. CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



### 3.4. BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



## 4. TEST RESULTS AND MEASUREMENT DATA

### 4.1. DTS (6DB) BANDWIDTH

#### 4.1.1. Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 4.1.2. Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

#### 4.1.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

#### 4.1.4. Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the VBW  $\geq 3 \times$  RBW (about 300kHz).

Set Span = 2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.


Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.


## Test Results:


Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
802.11b	1	2412	9.989	>500	PASS
	6	2437	9.992	>500	PASS
	11	2462	10.04	>500	PASS
802.11g	1	2412	16.44	>500	PASS
	6	2437	16.44	>500	PASS
	11	2462	16.41	>500	PASS
802.11n (HT20)	1	2412	17.08	>500	PASS
	6	2437	17.15	>500	PASS
	11	2462	17.16	>500	PASS
802.11n (HT40)	3	2422	35.14	>500	PASS
	7	2442	35.13	>500	PASS
	11	2462	35.13	>500	PASS

















## 4.2. MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 4.2.1. Applicable Standard

According to FCC Part 15.247(b)(1) and KDB 558074 D01 15.247 Meas Guidance v05r02


### 4.2.2. Conformance Limit

The maximum conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

### 4.2.3. Test Configuration

Test according to clause 4.2.4 radio frequency test setup 1

### 4.2.4. Test Procedure



#### ■ According to FCC Part 15.247(b)(3)

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

Set the RBW  $\geq$  DTS bandwidth (about 1MHz).

Set VBW  $= 3 \times$  RBW (about 3MHz)

Set the span  $\geq 3 \times$  RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

#### ■ According to FCC Part 15.247(b)(4):

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

- Place the EUT on the desktop and set it to launch mode. Remove the antenna from the EUT and connect the low-loss RF cable from the antenna port to the power meter. Measure the peak power of each channel.

**Test Results**

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
802.11b	1	2412	14.45	30	PASS
	6	2437	14.32	30	PASS
	11	2462	14.11	30	PASS
802.11g	1	2412	14.28	30	PASS
	6	2437	14.31	30	PASS
	11	2462	13.82	30	PASS
802.11n (HT20)	1	2412	13.43	30	PASS
	6	2437	13.70	30	PASS
	11	2462	13.17	30	PASS
802.11n (HT40)	3	2422	11.90	30	PASS
	7	2442	12.52	30	PASS
	11	2462	12.86	30	PASS

All three models have been verified, and the worst data model is CVD1662-AJ; The remaining two models differ by less than 0.5db.



### **4.3. MAXIMUM POWER SPECTRAL DENSITY**

#### **4.3.1. Applicable Standard**

According to FCC Part15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### **4.3.2. Conformance Limit**

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### **4.3.3. Test Configuration**

Test according to clause 3.1 radio frequency test setup 1

#### **4.3.4. Test Procedure**

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to:10 kHz.

Set Detector =Peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level within the RBW.


Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain- 6)





Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	1	2412	-5.108	8	PASS
	6	2437	-5.927	8	PASS
	11	2462	-5.012	8	PASS
802.11g	1	2412	-8.764	8	PASS
	6	2437	-8.048	8	PASS
	11	2462	-7.758	8	PASS
802.11n (HT20)	1	2412	-9.345	8	PASS
	6	2437	-9.138	8	PASS
	11	2462	-8.980	8	PASS
802.11n (HT40)	3	2422	-12.341	8	PASS
	7	2442	-12.553	8	PASS
	11	2462	-11.958	8	PASS


Note: the test RF cable loss is 0.5 dB that had added the result.














#### 4.4. UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

##### 4.4.1. Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

##### 4.4.2. Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

##### 4.4.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

##### 4.4.4. Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

###### **Reference level measurement**

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq 1.5$  times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq 3 \times$  RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.



**Emission level measurement**

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = Peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements . Report the three highest emissions relative to the limit.

**Test Results**


All the antennas and modulation modes were tested, and the worst data for is shown in the table below.

Note: the test RF cable loss is 0.5 dB, we checked all test conducted spurious test data with this loss that complied with FCC rule requirement.






Test Model	PSD(Power Spectral Density) RBW=100kHz, VBW =300 kHz			
	<input checked="" type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
Channel 6: 2437MHz				




Test Model	Unwanted Emissions in non-restricted frequency bands			
	<input checked="" type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
Channel 6: 2437MHz				




Test Model	PSD(Power Spectral Density) RBW=100kHz, VBW =300 kHz
------------	--






Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz
------------	---




Unwanted Emissions in non-restricted frequency bands				
Test Model	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)



Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz			
	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)







Unwanted Emissions in non-restricted frequency bands

Test Model ☐ 802.11b ☒ 802.11g ☐ 802.11n(HT20) ☐ 802.11n(HT40)


Channel 6: 2437MHz




Test Model PSD(Power Spectral Density) RBW=100kHz, VBW =300 kHz



Unwanted Emissions in non-restricted frequency bands				
Test Model	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)



Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input checked="" type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)




Band edge

Test Model

☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)

Channel 1: 2412MHz




Unwanted Emissions in non-restricted frequency bands


Test Model

☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)

Channel 1: 2412MHz




Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input checked="" type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	Channel 6: 2437MHz			




Test Model ☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)

Channel 6: 2437MHz



Test Model ☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)

Channel 11: 2462MHz



Test Model

Band edge

☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)


Channel 11: 2462MHz



Test Model


Unwanted Emissions in non-restricted frequency bands

☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)



Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input checked="" type="checkbox"/> 802.11n(HT40)
	Channel 3: 2422MHz			





Test Model

Band edge

☐ 802.11b ☐ 802.11g ☐ 802.11n(HT20) ☒ 802.11n(HT40)


Channel 3: 2422MHz




Test Model

Unwanted Emissions in non-restricted frequency bands


☐ 802.11b ☐ 802.11g ☐ 802.11n(HT20) ☒ 802.11n(HT40)




Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input checked="" type="checkbox"/> 802.11n(HT40)
	Channel 7: 2442MHz			



Test Model	Unwanted Emissions in non-restricted frequency bands			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input checked="" type="checkbox"/> 802.11n(HT40)
Channel 7: 2442MHz				



Test Model	PSD(Power Spectral Density ) RBW=100kHz, VBW =300 kHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input checked="" type="checkbox"/> 802.11n(HT40)
Channel 11: 2462MHz				



Test Model

Band edge

☐ 802.11b ☐ 802.11g ☐ 802.11n(HT20) ☒ 802.11n(HT40)

Channel 11: 2462MHz





## 4.5. RADIATED SPURIOUS EMISSION

### 4.5.1. Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01  
15.247 MEAS GUIDANCE v05r02

### 4.5.2. Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

#### 4.5.3. Test Configuration

Test according to clause 3.2 radio frequency test setup 2

#### 4.5.4. Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the

hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.  
Repeat above procedures until all frequency measured was complete.

### Test Results:

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Frequency	Factor	Meter Reading	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dB)	(dBμV)	(dBμV/m)	(dBμV/m)	(dB)		H/V
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance}/\text{test distance})$  (dB);

Limit line = Specific limits (dBμV) + distance extrapolation factor

#### ■ Spurious Emission Above 1GHz (1GHz to 25GHz)



All modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

Test mode:		802.11g		Frequency:		Channel 1: 2412MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4825	55.1	0.98	56.08	74	-17.92	peak	V
4842	45.78	0.98	46.76	54	-7.24	AVG	V
7236	38.96	7.66	46.62	74	-27.38	peak	V
7239	29.34	7.67	37.01	54	-16.99	AVG	V
4825	47.35	0.98	48.33	74	-25.67	peak	H
4842	36.43	0.98	37.41	54	-16.59	AVG	H
7236	38.68	7.66	46.34	74	-27.66	peak	H
7239	28.79	7.67	36.46	54	-17.54	AVG	H

Test mode:		802.11g		Frequency:		Channel 6: 2437MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4876	53.48	0.99	54.47	74	-19.53	peak	V
4893	42.92	1	43.92	54	-10.08	AVG	V
1782	54.1	-4.89	49.21	74	-24.79	peak	V
1799	44.4	-4.85	39.55	54	-14.45	AVG	V
7311	38.42	7.64	46.06	74	-27.94	peak	V
7307	28.51	7.64	36.15	54	-17.85	AVG	V
4876	53.19	0.99	54.18	74	-19.82	peak	H
4893	42.98	1	43.98	54	-10.02	AVG	H
1765	57.72	-4.93	52.79	74	-21.21	peak	H
1782	44.92	-4.89	40.03	54	-13.97	AVG	H
7311	38.78	7.64	46.42	74	-27.58	peak	H
7307	28.37	7.64	36.01	54	-17.99	AVG	H


Test mode:		802.11g		Frequency:		Channel 11: 2462MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4927	51.81	1	52.81	74	-21.19	peak	V
4944	40.29	0.99	41.28	54	-12.72	AVG	V
7386	37.97	7.6	45.57	74	-28.43	peak	V
7426	28.29	7.59	35.88	54	-18.12	AVG	V
4927	48.48	1	49.48	74	-24.52	peak	H
4944	37.63	0.99	38.62	54	-15.38	AVG	H
7386	38.41	7.6	46.01	74	-27.99	peak	H
7426	28.39	7.59	35.98	54	-18.02	AVG	H

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## ■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz


All modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

Test Mode:	802.11g	2412MHz	Test Channel	Lowest
Temperature:	23.7℃		Phase:	Vertical
Relative Humidity:	57%		Pressure:	98.3KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2400.000	-2.80	52.89	50.09	74.00	-23.91	peak		
2	2400.230	-2.80	36.68	33.88	54.00	-20.12	AVG	*	

Test Mode:	802.11g	2412MHz	Test Channel	Lowest
Temperature:	23.7°C		Phase:	Horizontal
Relative Humidity:	57%		Pressure:	98.3KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2400.000	-2.80	52.75	49.95	74.00	-24.05	peak		
2	2400.230	-2.80	37.25	34.45	54.00	-19.55	AVG	*	

Test Mode:	802.11g	2462MHz	Test Channel	Highest
Temperature:	23.7℃		Phase:	Vertical
Relative Humidity:	57%		Pressure:	98.3KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-2.48	41.00	38.52	74.00	-35.48	peak		
2	2483.500	-2.48	30.43	27.95	54.00	-26.05	AVG		
3	2477.300	-2.51	47.86	45.35	74.00	-28.65	peak		
4	2477.350	-2.51	32.85	30.34	54.00	-23.66	AVG	*	

Test Mode:	802.11g	2462MHz	Test Channel	Highest
Temperature:	23.7℃		Phase:	Horizontal
Relative Humidity:	57%		Pressure:	98.3KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-2.48	42.79	40.31	74.00	-33.69	peak		
2	2483.500	-2.48	31.13	28.65	54.00	-25.35	AVG		
3	2477.200	-2.51	52.93	50.42	74.00	-23.58	peak		
4	2477.250	-2.51	35.62	33.11	54.00	-20.89	AVG	*	

Test Mode:	802.11N(HT40)	2422MHz	Test Channel	Lowest
Temperature:	23.7℃		Phase:	Vertical
Relative Humidity:	57%		Pressure:	98.3KPa



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2400.000	-2.80	40.29	37.49	74.00	-36.51	peak		
2	2400.000	-2.80	30.70	27.90	54.00	-26.10	AVG	*	
3	2390.880	-2.84	43.07	40.23	74.00	-33.77	peak		
4	2390.880	-2.84	30.37	27.53	54.00	-26.47	AVG		


Test Mode:	802.11N(HT40)	2422MHz	Test Channel	Lowest
Temperature:	23.7℃		Phase:	Horizontal
Relative Humidity:	57%		Pressure:	98.3KPa



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2400.000	-2.80	42.32	39.52	74.00	-34.48	peak		
2	2400.000	-2.80	31.47	28.67	54.00	-25.33	AVG	*	
3	2388.160	-2.85	42.07	39.22	74.00	-34.78	peak		
4	2388.160	-2.85	30.65	27.80	54.00	-26.20	AVG		




Test Mode:	802.11N(HT40)	2462MHz	Test Channel	Highest
Temperature:	23.7℃		Phase:	Vertical
Relative Humidity:	57%		Pressure:	98.3KPa



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-2.48	42.03	39.55	74.00	-34.45	peak		
2	2483.560	-2.48	31.16	28.68	54.00	-25.32	AVG	*	
3	2494.120	-2.46	41.59	39.13	74.00	-34.87	peak		
4	2494.230	-2.46	30.33	27.87	54.00	-26.13	AVG		

Test Mode:	802.11N(HT40)	2462MHz	Test Channel	Highest
Temperature:	23.7℃		Phase:	Horizontal
Relative Humidity:	57%		Pressure:	98.3KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-2.48	44.73	42.25	74.00	-31.75	peak		
2	2483.560	-2.48	32.24	29.76	54.00	-24.24	AVG	*	
3	2498.630	-2.43	42.42	39.99	74.00	-34.01	peak		
4	2498.630	-2.43	30.79	28.36	54.00	-25.64	AVG		

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## ■ Spurious Emission below 1GHz (30MHz to 1GHz)


All antenna modes 2.4G 802.11b/g/n have been tested, and the worst result 802.1g recorded was report as below:

Test Mode:	802.11G	2412MHz	Test Voltage:	DC 12V
Temperature:	24.5℃		Phase:	Vertical
Relative Humidity:	52%		Pressure:	101.4KPa
M/N:	CVD9662-AJ			




No.	Frequency (MHz)	Reading (dBuV/m)	Antenna. (dB/m)	Cable. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	163.7550	11.93	8.98	1.99	22.90	43.50	-20.60	QP	
2	199.9856	10.70	11.4	2.1	24.20	43.50	-19.30	QP	
3	252.9482	9.18	12.34	2.28	23.80	46.00	-22.20	QP	
4	400.4319	11.62	14.97	2.71	29.30	46.00	-16.70	QP	
5	564.6389	13.42	17.27	3.31	34.00	46.00	-12.00	QP	
6	663.4728	12.55	18.66	3.59	34.80	46.00	-11.20	QP	

Test Mode:	802.11G	2412MHz	Test Voltage:	DC 12V
Temperature:	24.5℃		Phase:	Horizontal
Relative Humidity:	52%		Pressure:	101.4KPa
M/N:	CVD9662-AJ			




No.	Frequency (MHz)	Reading (dBuV/m)	Antenna. (dB/m)	Cable. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	88.3421	13.29	10.18	1.43	24.90	43.50	-18.60	QP	
2	164.9074	18.07	9.03	2	29.10	43.50	-14.40	QP	
3	207.1226	14.99	11.09	2.12	28.20	43.50	-15.30	QP	
4	261.0582	11.21	12.48	2.31	26.00	46.00	-20.00	QP	
5	401.8385	11.08	15	2.72	28.80	46.00	-17.20	QP	
6	549.0193	14.53	17.04	3.23	34.80	46.00	-11.20	QP	

Test Mode:	802.11G	2412MHz	Test Voltage:	DC 12V
Temperature:	24.5℃		Phase:	Horizontal
Relative Humidity:	52%		Pressure:	101.4KPa
M/N:	CVD7621-AJ			




No.	Frequency (MHz)	Reading (dBuV/m)	Antenna. (dB/m)	Cable. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	82.6482	14.26	8.69	1.35	24.30	40.00	-15.70	QP	
2	148.9625	13.10	8.42	1.88	23.40	43.50	-20.10	QP	
3	164.9075	12.77	9.03	2	23.80	43.50	-19.70	QP	
4	180.0165	16.18	9.64	2.08	27.90	43.50	-15.60	QP	
5	199.9856	17.90	11.4	2.1	31.40	43.50	-12.10	QP	
6	210.7860	13.38	10.99	2.13	26.50	43.50	-17.00	QP	

Test Mode:	802.11G	2412MHz	Test Voltage:	DC 12V
Temperature:	24.5°C		Phase:	Vertical
Relative Humidity:	52%		Pressure:	101.4KPa
M/N:	CVD7621-AJ			




No.	Frequency (MHz)	Reading (dBuV/m)	Antenna. (dB/m)	Cable. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	49.7068	6.14	14.48	0.88	21.50	40.00	-18.50	QP	
2	108.2667	5.90	12.27	1.63	19.80	43.50	-23.70	QP	
3	199.9856	10.80	11.4	2.1	24.30	43.50	-19.20	QP	
4	393.4723	17.00	14.82	2.68	34.50	46.00	-11.50	QP	
5	497.6765	11.74	16.33	3.13	31.20	46.00	-14.80	QP	
6	547.0977	11.16	17.02	3.22	31.40	46.00	-14.60	QP	

Test Mode:	802.11G	2412MHz	Test Voltage:	DC 12V
Temperature:	24.5°C		Phase:	Vertical
Relative Humidity:	52%		Pressure:	101.4KPa
M/N:	CVD1662-AJ			



No.	Frequency (MHz)	Reading (dBuV/m)	Antenna. (dB/m)	Cable. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	108.6470	9.23	12.24	1.63	23.10	43.50	-20.40	QP	
2	199.9856	8.30	11.4	2.1	21.80	43.50	-21.70	QP	
3	245.9509	9.83	12.22	2.25	24.30	46.00	-21.70	QP	
4	400.4319	16.22	14.97	2.71	33.90	46.00	-12.10	QP	
5	601.4265	13.75	18.24	3.51	35.50	46.00	-10.50	QP	
6	663.4729	11.85	18.66	3.59	34.10	46.00	-11.90	QP	

Test Mode:	802.11G	2412MHz	Test Voltage:	DC 12V
Temperature:	24.5℃		Phase:	Horizontal
Relative Humidity:	52%		Pressure:	101.4KPa
M/N:	CVD1662-AJ			



No.	Frequency (MHz)	Reading (dBuV/m)	Antenna. (dB/m)	Cable. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	93.1132	13.95	11.25	1.5	26.70	43.50	-16.80	QP	
2	108.6470	10.33	12.24	1.63	24.20	43.50	-19.30	QP	
3	180.0165	17.78	9.64	2.08	29.50	43.50	-14.00	QP	
4	199.9856	23.40	11.4	2.1	36.90	43.50	-6.60	QP	
5	400.4319	18.32	14.97	2.71	36.00	46.00	-10.00	QP	
6	601.4265	10.35	18.24	3.51	32.10	46.00	-13.90	QP	



## 4.6. ANTENNA APPLICATION

### 4.6.1. Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.6.2. Result

**PASS.**

The EUT has 1 antenna: an External antenna the gain is 2dBi;



Note:which in accordance to section 15.203, please refer to the internal photos.

#### 4.7. RF EXPOSURE

Remark: refer to MPE test report: Report No.: LP23080282C01-35-1

#### 4.8. TESTING PHOTO


Radiated emission




#### 4.9. PHOTOGRAPHS OF THE EUT

External photos

M/N:CVD1662-AJ




External photos  
M/N:CVD1662-AJ









External photos  
M/N: CVD7621-AJ



External photos  
M/N: CVD9662-AJ





Internal photos






Internal photos



Internal photos



----- END OF REPORT -----