

## **RF Exposure Report**

Report No.: SABEIH-WTW-P21050758

FCC ID: P27-SCE4255W

Test Model: SCE4255W

Received Date: May 19, 2021

Test Date: Aug. 20 to Nov. 8, 2021

Issued Date: Jan. 5, 2022

Applicant: Sercomm Corp.

Address: 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

FCC Registration /

**Designation Number:** 281270 / TW0032





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



## **Table of Contents**

Rele	lease Control Record	
1	Certificate of Conformity	4
2	•	
2.	2.1 Limits For Maximum Permissible Exposure (MPE)	5
2.	2.2 MPE Calculation Formula	5
2.	2.3 Classification	5
	2.4 Antenna Gain	
2.	2.5 Calculation Result of Maximum Conducted Power	6



## **Release Control Record**

Issue No.	Description	Date Issued
SABEIH-WTW-P21050758	Original release.	Jan. 5, 2022



# 1 Certificate of Conformity

**Product:** Englewood

Brand: Sercomm

Test Model: SCE4255W

Sample Status: Engineering sample

Applicant: Sercomm Corp.

**Test Date:** Aug. 20 to Nov. 8, 2021

**Standards:** FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by:	, Date:	Jan. 5, 2022
--------------	---------	--------------

Celia Chen / Supervisor

Jeremy Lin / Project Engineer



## 2 RF Exposure

## 2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = Frequency in MHz; \*Plane-wave equivalent power density

#### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



#### 2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table: (additional as shaded area)

TX Antenna		Antenna Type	Antenna Connector	Antenna Gain (dBi)	Frequency Range
	Ant 1	PIFA	I-PEX	5.30	3.5~3.7GHz
Internal	Ant 2			5.26	
Internal	Ant 3			5.48	
	Ant 4				5.68
	Ant 1		N-Type	5.0	
External	Ant 2	Dipole		5.0	3.5~3.7GHz
External	Ant 3	Dipole		5.0	
	Ant 4			5.0	

Note: The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

#### 2.5 Calculation Result of Maximum Conducted Power

Frequency Band	EIRP	Distance	Power Density (mW/cm <sup>2</sup> )	Limit
(MHz)	(dBm)	(cm)		(mW/cm²)
CBRS band: 3555 ~ 3695	26.53	20	0.0895	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---