

FCC Test Report

(Part 90)

Report No.: RFBBQZ-WTW-P20090593-3

Contain module FCC ID: PY320300503

Test Model: LM1200

Received Date: Sep. 25, 2020

Test Date: Oct. 19 ~ Oct. 24, 2020

Issued Date: Nov. 02, 2020

Applicant: NETGEAR INC.

Address: 350 East Plumeria Drive, San Jose, CA 95134, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Test Site and Instruments	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Configuration of System under Test	8
3.2.1 Description of Support Units	8
3.3 Test Mode Applicability and Tested Channel Detail	9
3.4 EUT Operating Conditions	9
3.5 General Description of Applied Standards	9
4 Test Types and Results	10
4.1 Output Power Measurement	10
4.1.1 Limits of Output Power Measurement	10
4.1.2 Test Procedures	10
4.1.3 Test Setup	11
4.1.4 Test Results	12
4.2 Radiated Emission Measurement	14
4.2.1 Limits of Radiated Emission Measuremen	14
4.2.2 Test Procedure	14
4.2.3 Deviation from Test Standard	14
4.2.4 Test Setup	15
4.2.5 Test Results	16
5 Pictures of Test Arrangements	21
Appendix – Information of the Testing Laboratories	22

Release Control Record

Issue No.	Description	Date Issued
RFBBQZ-WTW-P20090593-3	Original release	Nov. 02, 2020

1 Certificate of Conformity

Product: LTE modem

Brand: Netgear

Test Model: LM1200

Sample Status: Engineering Sample

Applicant: NETGEAR INC.

Test Date: Oct. 19 ~ Oct. 24, 2020

Standards: FCC Part 90, Subpart R

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen, **Date:** Nov. 02, 2020
Pettie Chen / Senior Specialist

Approved by : Bruce Chen, **Date:** Nov. 02, 2020
Bruce Chen / Senior Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 90 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 90.542 (a) (7)	Effective Radiated Power	Pass	Meet the requirement of limit.
2.1053 90.543 (c) & (f)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -14.5dB at 1591.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.04 dB
	30MHz ~ 200MHz	3.59 dB
	200MHz ~ 1000MHz	3.60 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver KEYSIGHT	N9038A	MY55420137	Apr. 16, 2020	Apr. 15, 2021
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Jun. 12, 2020	Jun. 11, 2021
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Nov. 07, 2019	Nov. 06, 2020
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 24, 2019	Nov. 23, 2020
Preamplifier Agilent (Below 1GHz)	8447D	2944A10638	Jun. 08, 2020	Jun. 07, 2021
Preamplifier Agilent (Above 1GHz)	8449B	3008A02367	Feb. 18, 2020	Feb. 17, 2021
RF signal cable HUBER+SUHNER&EMCI	SUCOFLEX 104 & EMC104-SM- SM8000	CABLE-CH9-02 (248780+171006)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable Woken	8D-FB	Cable-CH9-01	Jun. 08, 2020	Jun. 07, 2021
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 01, 2020	May 31, 2021
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
True RMS Clamp Meter Fluke	325	31130711WS	Jun. 06, 2020	Jun. 05, 2021
DC power supply	U8002A	MY56330015	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 9.

3 General Information

3.1 General Description of EUT

Product	LTE modem			
Brand	Netgear			
Test Model	LM1200			
Status of EUT	Engineering Sample			
Power Supply Rating	5 Vdc (Adapter)			
Modulation Type	QPSK, 16QAM			
Operating Frequency	LTE Band 14	Channel Bandwidth 5MHz	790.5MHz ~ 795.5MHz	
		Channel Bandwidth 10MHz	793MHz	
Max. ERP Power	LTE Band 14		QPSK	16QAM
		Channel Bandwidth 5MHz	204.174mW (23.1dBm)	169.824mW (22.3dBm)
		Channel Bandwidth 10MHz	218.776mW (23.4dBm)	165.959mW (22.2dBm)
Antenna Type	Ant. 1: PIFA antenna with -0.38dBi gain Ant. 2: PIFA antenna with -2.67dBi gain			
Antenna Connector	Ant. 1: switch Ant. 2: I-pex			
Accessory Device	Refer to Note			
Cable Supplied	Refer to Note			


Note:

1. This report is a partial report. Only Effective radiated power and Radiated Spurious Emissions were verified and recorded in this report. Other testing data please refer to the original TA Technology (Shanghai) Co., Ltd. report no.: R1806A0301-R4V1 (LTE Module, Brand: Quectel, Model: EC25-AF, FCC ID: XMR201808EC25AF).
2. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
3. The EUT contains following accessory devices.

Adapter	
Brand	Netgear
Model	AD2037320
Input Power	100-240Vac~50/60Hz, 0.3A
Output Power	5.0Vdc, 2.0A

Cable	Brand	Model	Information
USB cable	HOTRON PRECISION	D0017100R20HR	1.0m shielded cable without core
RJ45 Cable 1	EKSON	HS01-C442	1.5m non-shielded cable without core
RJ45 Cable 2	EKSON	HS01-C445	1.5m non-shielded cable without core

3.2 Configuration of System under Test



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Radio Communication Analyzer	Anritsu	MT8821C	6261806803	NA	-
B.	Load	NA	NA	NA	NA	-
C.	Notebook	DELL	E5410	1HC2XM1	FCC Doc Approved	-

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A, C acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN cable	1	1.5	N	0	RJ45, Accessory
2.	LAN cable	1	10	N	0	RJ45, Provided by lab

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X-plane. Following channel(s) was (were) selected for the final test as listed below:

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK / 16QAM	1 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK / 16QAM	1 RB / 0 RB Offset
-	Radiated Emission below 1GHz	23330	23355(795.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission above 1GHz	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

1.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	24deg. C, 66%RH	120Vac, 60Hz	Tank Wu
Radiated Emission	24deg. C, 66%RH	120Vac, 60Hz	Tank Wu

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 90

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

4.1.2 Test Procedures

EIRP / ERP Measurement:

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.2.7


$EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.

$ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.


4.1.3 Test Setup

EIRP / ERP Measurement:

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

ERP Power

Modulation Type: QPSK

LTE Band 14, Channel Bandwidth: 5MHz

Mode		TX channel 23305, 23330, 23355						
Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	790.50	-66.5	89.6	23.1	34.8	-11.7	100	199
2	793.00	-66.5	89.5	23.0	34.8	-11.8	103	197
3	795.50	-66.5	89.5	23.0	34.8	-11.8	106	199
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	790.50	-66.5	84.0	17.5	34.8	-17.3	116	70
2	793.00	-66.5	83.8	17.3	34.8	-17.5	111	76
3	795.50	-66.5	83.8	17.4	34.8	-17.4	110	70

LTE Band 14, Channel Bandwidth: 10MHz

Mode		TX channel 23330						
Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	793.00	-66.5	89.8	23.4	34.8	-11.4	100	201
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	793.00	-66.5	83.7	17.2	34.8	-17.6	116	70

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV/m) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$

Modulation Type: 16QAM

LTE Band 14, Channel Bandwidth: 5MHz

Mode		TX channel 23305, 23330, 23355						
Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBUV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	790.50	-66.5	88.8	22.3	34.8	-12.5	100	196
2	793.00	-66.5	88.8	22.3	34.8	-12.5	102	189
3	795.50	-66.5	88.7	22.2	34.8	-12.6	102	193
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBUV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	790.50	-66.5	83.2	16.8	34.8	-18.0	112	69
2	793.00	-66.5	83.1	16.6	34.8	-18.2	102	77
3	795.50	-66.5	83.0	16.5	34.8	-18.3	108	79

LTE Band 14, Channel Bandwidth: 10MHz

Mode		TX channel 23330						
Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	793.00	-66.5	89.1	22.6	34.8	-12.2	100	199
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	793.00	-66.5	82.8	16.3	34.8	-18.5	110	72

Remarks:

1. $ERP(dBm) = \text{Raw Value}(dBUV/m) + \text{Correction Factor}(dB/m)$
2. $\text{Correction Factor}(dB/m) = \text{Antenna Factor}(dB/m) + \text{Cable Factor}(dB) - \text{Pre-Amplifier Factor}(dB) + 20\log(D) - 104.8 - 2.15$
3. $\text{Margin value} = ERP - \text{Limit value}$

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

Note: Emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals.

{The limits is adjusted to -40dBm (-70dBW)}

4.2.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.5

$EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.

$ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

For Radiated Emission below or equal 1GHz



For Radiated Emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results

Below 1GHz


Channel Bandwidth: 5MHz

Mode	TX channel 23355 (795.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	24deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Tank Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	31.94	-108.2	49.5	-58.7	-13.0	-45.7	100	145
2	49.40	-106.7	51.9	-54.8	-13.0	-41.8	149	135
3	84.32	-111.8	61.0	-50.8	-13.0	-37.8	100	323
4	170.65	-106.4	52.9	-53.5	-13.0	-40.5	125	280
5	300.63	-104.6	42.5	-62.1	-13.0	-49.1	200	236
6	629.46	-97.7	38.1	-59.6	-13.0	-46.6	149	243

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV/m) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$
4. The other ERP levels were very low against the limit.




Mode	TX channel 23355 (795.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	24deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Tank Wu		

Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	30.00	-108.0	59.1	-48.9	-13.0	-35.9	150	198
2	56.19	-106.7	68.0	-38.7	-13.0	-25.7	100	190
3	110.51	-109.5	55.9	-53.6	-13.0	-40.6	150	221
4	159.98	-105.8	48.4	-57.4	-13.0	-44.4	125	171
5	299.66	-104.6	38.6	-66.0	-13.0	-53.0	150	68
6	617.82	-98.0	38.4	-59.6	-13.0	-46.6	101	79

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV/m) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.



Above 1GHz

Channel Bandwidth: 5MHz

Mode	TX channel 23305 (790.5MHz)	Frequency Range	1 ~ 18GHz
Environmental Conditions	24deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Tank Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1581.00	-101.0	46.2	-54.8	-40.0	-14.8	152	107
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1581.00	-101.0	45.9	-55.1	-40.0	-15.1	155	238

Mode	TX channel 23330 (793.0MHz)	Frequency Range	1 ~ 18GHz
Environmental Conditions	24deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Tank Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1586.00	-100.9	46.0	-54.9	-40.0	-14.9	148	118
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1586.00	-100.9	45.7	-55.2	-40.0	-15.2	159	247

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV/m) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

Mode	TX channel 23355 (795.5MHz)	Frequency Range	1 ~ 18GHz
Environmental Conditions	24deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Tank Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1591.00	-100.9	46.4	-54.5	-40.0	-14.5	148	92
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1591.00	-100.9	46.1	-54.8	-40.0	-14.8	157	233

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV/m) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

Channel Bandwidth: 10MHz

Mode	TX channel 23330 (793.0MHz)	Frequency Range	1 ~ 18GHz
Environmental Conditions	24deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Tank Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1586.00	-100.9	46.2	-54.7	-40.0	-14.7	144	123
Antenna Polarity & Test Distance: Vertical at 3 M								
No.	Freq. (MHz)	Correction Factor (dB)	Reading (dBuV/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Ant. Height (m)	Table Angle (deg)
1	1586.00	-100.9	45.9	-55.0	-40.0	-15.0	168	207

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV/m) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---