FCC ID : 2AJOF-3000

1. RF EXPOSURE

1.1.The Requirement

System operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See Section 15.407

1.2.Limit For Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time	
Range	Strength (E)	Strength (H)	(S)	$ E ^2, H ^2$ or S	
(MHz)	(V/m)	(A/m)	(mW/cm^2)	(minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

Limits for General Population/ Uncontrolled Exposure

F = frequency in MHz, * Plane-wave equivalent power density

1.3.MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the antenna is 4.5dBi, the RF power density can be obtained.

1.4.TEST RESULTS

Maximum measured transmitter power

Channel Frequency	Final output power	Final output power	Antenna Gain]	Power Dens At 20cm (mW/cm ²)	5	Power Density	Test
(MHz)	ANT1 (dBm)	ANT2 (dBm)	(Numeric)	Ant 1	Ant 2	Sum	Limit (mW/cm ²)	Results
5190	15.22	15.46	2.818	0.019	0.020	0.039	1.000	Pass
5230	15.04	15.51	2.818	0.018	0.020	0.038	1.000	Pass
5745	15.39	15.98	2.818	0.019	0.022	0.039	1.000	Pass
5785	15.49	15.73	2.818	0.020	0.021	0.041	1.000	Pass
5825	15.12	15.89	2.818	0.018	0.022	0.040	1.000	Pass

Directional	gain= 4.5+1	0log2=7.51
-------------	-------------	------------

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.

1.5.FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, Human proximity to the antenna shall not be less than 20cm(8 inches) during normal operation. Proposed RF exposure safety information to include in User's Manual.