

# <u>TEST REPORT</u>

Applicant:INFINIX MOBILITY LIMITEDEUT Description:Mobile PhoneModel:X6870Brand:InfinixFCC ID:2AIZN-X6870Standards:FCC CFR Title 47 Part 2FCC OFR Title 47 Part 96.472025/02/28Date of Receipt:2025/02/28 to 2025/03/12Date of Issue:2025/03/12

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.

Huangkun Approved By:

ChenChengfu Reviewed By:



# **Revision History**

Rev.	Issue Date	Description	Revised by
01	2025/03/12	Original	ChenChengfu



# **Summary of Test Results**

FCC Part	Test Item	Verdict
§96.47	End user device additional requirements	Pass



# Contents

1	Gen	eral De	scription	5
	1.1	Lal	b Information	5
		1.1.1	Testing Location	5
		1.1.2	Test Facility / Accreditations	5
	1.2	Cli	ent Information	5
		1.2.1	Applicant	5
		1.2.2	Manufacturer	5
	1.3	Pro	oduct Information	6
2	Test	Config	juration	7
	2.1	De	scription of test setup	7
	2.2	Tes	st Environment	7
	2.3	Tes	st RF Cable	7
	2.4	Мо	difications	7
3	Equi	pment	and Measurement Uncertainty	8
	3.1	Tes	st Equipment List	8
	3.2	Ме	asurement Uncertainty	8
4	Test	Result	S	9
	4.1	En	d user Device Additional Requirements.	9
5	Test	Setup	Photos1	0
	Арр	endix.		1





# 1.1 Lab Information

### 1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 Tel.: +86-755-27212361

Contact Email: info@towewireless.com

## 1.1.2 Test Facility / Accreditations

#### A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

#### FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

#### ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory. CAB identifier: CN0152

Company Number: 31000

## **1.2 Client Information**

### 1.2.1 Applicant

Applicant:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG

#### 1.2.2 Manufacturer

Manufacturer:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG



# 1.3 Product Information

EUT Description:	Mobile Phone		
Model:	X6870		
Brand:	Infinix		
Hardware Version:	V1.2		
Software Version:	15.0.1.022SP01	(OP001PF001AZ)WLY241219	203638
SN.:	13890254CK000	)395	
Technical specification:			
	Band	All Frequency	CBSD Work Frequency
Operation Frequency Range:	NR Band n77	3450 to 3980 MHz	3550 to 3700 MHz
	NR Band n78	3450 to 3800 MHz	3550 to 3700 MHz
Antenna Type:	PIFA Antenna		
	Band	Ant (dBi)	
Antenna Gain:	NR Band n77	-3.56	
	NR Band n78	-3.56	
Remark: The above EUT's infor manual for more detailed descri	mation was decla ption.	red by applicant, please refer t	o the specifications or user



# 2 Test Configuration

## 2.1 Description of test setup

Description	Manufacturer	Model	ID
Base Station	Baicells	BSC7048A243	2AG32BSC7048A243
Router	TP Link	TL-WDR6300	/
Laptop	DELL	Latitude 3510	/

## 2.2 Test Environment

Temperature:	24°C ~ 26°C
Relative Humidity	45-56 % RH Ambient
Voltage:	Nominal: 3.91Vdc

## 2.3 Test RF Cable

**For all conducted test items**: The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

## **2.4 Modifications**

No modifications were made during testing.



# 3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable recognized national standards.

# 3.1 Test Equipment List

Radiated Emission					
Description	Manufacturer	Model	SN	Last Due	Cal Due
Signal Analyzer	Keysight	N9020A	US46470468	2024/03/25	2025/03/24
Power Divider	Qotana	DBPD0200001800C	22122900036	2023/04/08	2025/04/07

# 3.2 Measurement Uncertainty

Parameter	U <sub>lab</sub>
Frequency error	371.88Hz

Uncertainty figures are valid to a confidence level of 95%



# 4 Test Results

# 4.1 End user Device Additional Requirements.

#### <u>Limits</u>

End User Devices will operate only after it receives authorization from an associated CBSD, including the frequencies and power limits for their operation.

End User Devices discontinues operation, changes Frequency, and changes its operational power level within 10 s of receiving instructions from its associated CBSD.

#### Test Procedure

KDB 940660 D01 Part 96 CBRS Eqpt v02, WINNF-TS-0122 V1.0.2

#### Test Setup



#### Test Settings

Based on the End user device additional requirements. During the test, use a certified Ruckus CBSD device (LTE Base Station FCC ID: 2AG32MBS3100196N, NR Base Station FCC ID: 2AG32BSC7048A243) as a companion device.

- 1. Configure CBSD to operate at 3600MHz~3625MHz, Power level 10dBm/MHz.
- 2. Enable AP service from Ruckus Cloud management
- 3. Check End User Devices Frequency and Power
- 4. Disable AP service from Ruckus Cloud management, check whether the EUT stops transmitting within 10s 5. Repeat step 2 to step 4 with the CBSD operating at 3670MHz~3690MHz, Power level 20dBm/MHz.

#### **Measuring Instruments**

The measuring equipment is listed in the section 3.1 of this test report.

#### Test Result

The detailed test data see: Appendix.



# 5 Test Setup Photos

The detailed test data see: Test Setup Photos

# **Appendix**

GUE





Bandwidth: 60MH	z Setup with fre	equency 3680	MHz and po	ower level 2	0dBm/MHz
Agilent Spectrum Analyzer - Channel Ma L RF 50Ω AC Mech Atten 36 dB	Power CORREC CORREC Figure 4 #IFGain:Low Cent #Atte	SENSE:INT er Freq: 3.680000000 GHz Free Run Avg Ho n: 36 dB	ALIGNAUTO 03 Rac Id: 10/10 Rac	:49:35 PM Mar 12, 2025 dio Std: None dio Device: BTS	Trace/Detector
10 dB/div Ref 20.00 dE	<u>8m</u>				
-10.0	portable and a second and a second	haft	uthray		Clear Write
-20.0 -30.0 -40.0 protrainet-chiefattinghysetting-cond				ntertessente	Average
-60.0					Max Hold
Center 3.68 GHz #Res BW 1 MHz	#	¢VBW 3 MHz		Span 120 MHz Sweep 1 ms	Min Hold
Channel Power 10.81 dBm	1 / 60 MHz	Power Spec -66.9	tral Density 7 dBm /н	z	Detector Average►
					<u>ruce</u> men
MSG			STATUS		
stops transmission	within 10 secor	nds of receivin	g instructio	ns from its a	associated CB
Agilent Spectrum Analyzer - Swept SA μα L RF 50 Ω AC Marker 2 Δ 10.0000 s	CORREC   Trig:	SENSE:INT Avg T	ALIGNAUTO 03 /pe: Log-Pwr	:50:40 PM Mar 12, 2025 TRACE 1 2 3 4 5 6 TYPE WWWWW	Marker
10 dB/div Ref 26.00 dBm	IFGain:Low #Atte	n: 36 dB	ΔΝ	/lkr2 10.00 s -34.02 dB	Select Marker
16.0		X			Normal
-4.00		<u>1Δ2</u>	kak alda arreada arre	2Δ3	Delta
-34.0					Fixed⊳
-64.0			<b>0</b>	Span 0 Hz	
Res BW 3.0 WHZ	#VBW 8.0 W	FUNCTION	Sweep 25.	FUNCTION VALUE	Off
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	-9.275 s (Δ) -0 10.00 s (Δ) -34 12.00 s 4.0	.36 dB .02 dB 9 dBm			Properties►
6 7 8 9 10					More 1 of 2
11				×	

~The End~