Bell Labs



Global Product Compliance Laboratory 600-700 Mountain Avenue Room 5B-108 Murray Hill, New Jersey 07974-0636 USA

# **RF Exposure Assessment Report** (FCC ID: 2AD8UFW2RMBOM1)

Regulation

47 CFR FCC Sections 1.1307 and 1.1310

Client

Nokia Solutions and Networks Oy

Product Evaluated

## Nokia Flexi Zone Multiband Outdoor Micro BTS (MBO) FW2RMOM1 LAA RF Module Operating in Band 46 UNII-3

<u>GPCL Report Number</u> TR2019-0029 MBO LAA FCC MPE

> GPCL Project Number 2019-0029

# Date Issued

February 13, 2019

# TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	SUMMARY OF THE TEST RESULTS	4
3.	GENERAL INFORMATION	4
3.1	Product Descriptions	
3.2	Antenna Information	
4.	<b>REQUIRED EVALUATION AND RESULTS</b>	6
4.1	Regulatory Requirements	
4.2	RF Exposure Assessment	
5.	REFERENCES	9

#### Revisions

Date	Revision	Section	Change

This report is the property of the client. This report shall not be reproduced except in full without the written approval of the Nokia Global Product Compliance Laboratory.

The results documented in this report refer exclusively to the product specified, under the conditions and modes of operation as described herein.

Prepared By:

Signed:

2/13/2019

Date

)19 Signed:

Reviewed By:

2/13/20

Date

R.J. Johnson GPCL Technical Manager

Kaymond f.)

Qin Yu GPCL Compliance Engineer

### **1. ATTESTATION OF TEST RESULTS**

Company Name (Manufacturer)	Nokia Solutions and Network, OY
	2000 W. Lucent Lane
	Naperville, IL 60563
FCC ID	2AD8UFW2MBOM2
Product Name	Flexi Zone Multiband Outdoor Micro BTS (MBO)
	FW2RMBOM1 LAA RF Module
Model Name(s)	MBO LAA: FW2RMBOM1
Test Requirement(s)	47 CFR FCC Sections 15.407, 1.1307 and 1.1310
<b>Other Reference</b> (s)	FCC OET Bulletin 65, KDB 447498 D01
<b>Frequency Band</b>	E-UTRAN Band 46: 5735-5835 MHz (UNII-3)
Test Report Number	TR2019-0029 MBO LAA FCC MPE
Test Laboratory	Global Product Compliance Laboratory
	600-700 Mountain Avenue
	Room 5B-108
	Murray Hill, New Jersey 07974-0636 USA

The above product has been evaluated and found to be in compliance with the Commission's Rules and Regulations set forth in the above standards. The data and the descriptions about the test setup, procedures and configuration presented in this report are accurate.

### 2. SUMMARY OF THE TEST RESULTS

Applied Standard(s): FCC 1.1310					
MBO Configuration         Exposure Environement         Proposed RF Safety           Distance (cm)					
Equipped with either omni-direc antennas or directional antennas provided	General Population/Uncontrolled*	20			

\*FCC Section 15.407(f) specified all UNII devices shall be considered to operate in a "general population/uncontrolled" environment.

### 3. GENERAL INFORMATION

### **3.1 Product Descriptions**

The Nokia Flexi Zone Multiband Outdoor Micro Base Station (MBO) is a small cell that consists of a common digital system module, up to two LTE (Long Term Evolution) RF transceivers in various combinations and optional WiFi AP (Access Point) and Bluetooth (BT) RF transceivers. Each RF transceiver supports 2 Tx/Rx. MBO digital system module supplies baseband signals, the baseband processing, control and timing to the radios.

The FW2RMBOM1 B46 LAA RF Module (MBO LAA) is a LTE Transceiver supporting a carrier bandwidth of 20 MHz and a maximum RF power output capability of 0.5W at each of its 2 MIMO transmit port outputs in the E-UTRAN Band 46 UNII-3 spectrum: 5735-5835MHz.

This RF exposure assessment is on the FW2RMBOM1 B46 LAA RF Module equipped with omnidirectional and directional antennas, respectively. The RF exposure assessment on the configurations of MBO LAA co-located with other RF modules will be provided in a separate MPE (Maximum Permissible Exposure) report.

The FW2RMBOM1 B46 LAA RF Module can only be operated with the antenna with which it is authorized.

The MBO is typically installed on poles or walls in fixed locations. Therefore, MBO is neither a portable nor a mobile wireless device. The specification of MBO LAA in terms of frequency and maximum power are provided below:

Product	Model Name	Technologies	Tx Freq (MHz)	Total Output P <sup>Max</sup> (dBm rms)			
LAA	FW2RMBOM1	LTE-TDD, 20/40MHz BW	5735-5835	30			

 Table 3.1.1 Product Specifications on MBO LAA\*

\*Maximum Total Output Power has taken MIMO into consideration.

### **3.2** Antenna Information

The information on the antennas to be used by EUT were given below:

#### Table 3.2.1 Data of Recommended Omni-Directional LTE Antennas for FW2RMOM1 MBO LAA from Manufacturers

Transmitters Antenna		Model	Max Avg Ant Gain (dBi)	
LAA	Omni-Direc	FA2RA FZ 473121A 5150 ~ 5850MHz	7.5	
LAA	Omni-Direc	FA2RD FZ 474881A, 5150 ~ 5850MHz	10	
LAA	Directional	FA2WA FZ 473461A, 5150 ~ 5925	6	

### 4. REQUIRED EVALUATION AND RESULTS

### 4.1 Regulatory Requirements

The assessment in this report was performed for AZRB RRH Band 46 LAA, operating in 5GHz UNII-1 and UNII-3 bands.

The regulatory requirements for the RF exposure compliance of RF transceivers were specified in 47 CFR FCC Parts 15 and 1.

The FCC 15.407 and 1.1310 sets out the requirements and measurement techniques used to evaluate RF exposure compliance of radiocommunication apparatus:

#### I. FCC Section 15.407(f) RF Exposure Requirements

U-NII devices are subject to the radio frequency radiation exposure requirements specified in FCC Sections 1.1307(b), 2.1091 and 2.1093, as appropriate. *All equipment shall be considered to operate in a "general population/uncontrolled" environment*. Technical information showing the basis for this statement must be submitted to the Commission upon request.

# II. FCC Section 1.1307(b) Evaluation Environmental Assessment Requirement for Equipment Authorization

Commission actions granting construction permits, licenses to transmit or renewals thereof, equipment authorizations or modifications in existing facilities, require the preparation of an Environmental Assessment (EA) if the particular facility, operation or transmitter would cause human exposure to levels of radiofrequency radiation in excess of the limits in FCC Sections 1.1310 and 2.1093.

#### III. FCC Section 1.1310 Radio Frequency Radiation Exposure Limits

At operating frequencies less than or equal to 6 GHz, the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 of Section 1.1310, may be used instead of whole-body SAR limits to evaluate the environmental impact of human exposure to RF radiation as specified in Section 1.1307(b), except for portable devices as defined in § 2.1093 as these evaluations shall be performed according to the SAR provisions in Section 2.1093 of this chapter.

At operating frequencies above 6 GHz, the MPE limits shall be used in all cases to evaluate the environmental impact of human exposure to RF radiation as specified in Section 1.1307(b).

The MPE limits listed in Table 1 of Section 1.1310 are for continuous exposure, that is, for indefinite time periods. Exposure levels higher than the limits are permitted for shorter exposure times, as long as the average exposure over the specified averaging time in Table 1 is less than the limits. Detailed information regarding procedures for evaluating compliance with all of these exposure limits can be found in the FCC's OET Bulletin 65, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields," and in supplements to Bulletin 65.

The exposure limits specified for occupational/controlled exposure and general population/uncontrolled exposure, which are tabulated below shall be met.

Table 4.1.1 Limits for Occupational/Controlled Exposure and General Population/Uncontrolled	d
Exposure (FCC Section 1.1310 Table 1(B))	

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magentic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Average Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)	
(A)	) Limits for Occu	upational/Control	led Exposure		
300 - 1500			f/300	6	
1500 - 100,000			5.0	6	
(B) Limits for General Population/Uncontrolled Exposure					
300 - 1500			f/1500	30	
1500 - 100,000			1.0	30	

Note: f = frequency in MHz.

### 4.2 **RF Exposure Assessment**

The regulatory requirements and limits were provided in Section 4.1. The product specifications on RF transceivers and antennas were provided in Section 3.

The limits at the operation frequencies of transmitters installed in AZRB Base Station were calculated and provided in Table 4.2.1.

Cable 4.2.1 Power Density Limits for Occupational/Controlled Exposure and
General Population/Uncontrolled for MBO LAA

Environment	Frequency Range (MHz)	Min Power Density (S) (mW/cm <sup>2</sup> )
<b>Occupational/Controlled</b>	5735-5835	5
<b>General Population/Uncontrolled</b>	5735-5835	1

Per IEEE C95.3 Annex B Equation (37) or FCC's OST/OET Bulletin Number 65, the appropriate safety distance can be calculated based on the relationship between power density limit and EIRP (equivalent or effective isotopically radiated power), i.e.,

$$S = \frac{EIRP}{4\pi R^2},\tag{1}$$

where S is the power density in  $mW/cm^2$ , R is the distance to the center of radiation of the antenna in cm and EIRP is in mW.

When all transmitters or channels operate simultaneously, the EIRP and thus power density from all transmitters gives the worst-case scenario.

The RF exposure assessment was conducted on the MBO LAA RF Module.

Table 4.2.2(a) Power Density at the Proposed Minimum RF Safety Distance 20cm for Uncontrolled
Exposure with Omni-Directional LTE Antennas

Module	Maxi	Max Avg	Maxi Total	Power	Limit of Power	S/LPD
	Total P <sub>out</sub> (dBm)	Ant Gain (dBi)	EIRP (mW)	Density S (mW/cm <sup>2</sup> )	Density S (mW/cm <sup>2</sup> )	
MBO LAA	26	10	3981.1	0.792	1	0.792
MBO LAA	28.5	7.5	3981.1	0.792	1	0.791

Table 4.2.2(b) Power Density at the Minimum RF Safety Distance 20cm for Uncontrolled Exposure
with Directional LTE Antennas

Module	Maxi	Max Avg	Maxi Total	Power	Limit of Power	S/LPD
	<b>Total Pout</b>	Ant Gain	EIRP	<b>Density S</b>	<b>Density S</b>	
	(dBm)	(dBi)	( <b>mW</b> )	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )	
MBO LAA	30	6	3981.1	0.792	1	0.792

 Table 4.2.3(a) Power Density at the Proposed Minimum RF Safety Distance 20cm for Controlled

 Exposure with Omni-Directional LTE Antennas

Module	Maxi Total P <sub>out</sub> (dBm)	Max Avg Ant Gain (dBi)	Maxi Total EIRP (mW)	Power Density S (mW/cm <sup>2</sup> )	Limit of Power Density S (mW/cm <sup>2</sup> )	S/LPD
MBO LAA	26	10	3981.1	0.792	5	0.158
MBO LAA	28.5	7.5	3981.1	0.792	5	0.158

 Table 4.2.3(b) Power Density at the Minimum RF Safety Distance 20cm for Controlled Exposure with Directional LTE Antennas

Module	Maxi	Max Avg	Maxi Total	Power	Limit of Power	S/LPD
	Total Pout	Ant Gain	EIRP	<b>Density S</b>	<b>Density S</b>	
	(dBm)	(dBi)	( <b>mW</b> )	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )	
MBO LAA	30	6	3981.1	0.792	5	0.158

The maximum EIRP allowed is 36dBm.

Table 4	.2.4 Power	• Density	at the 20	)cm RF Sa	fetv Distance

Exposure Environment	Max EIRP (dBm)	Max EIRP (mW)	RF Safety Distance (cm)	Power Density S (mW/cm <sup>2</sup> )	Limit of Power Density S (mW/cm <sup>2</sup> )	S/LPD
Uncontrolled	36	3981.07	20	0.792	1	0.792
Controlled	36	3981.07	20	0.792	5	0.158

Therefore,

usie 11210 110posed iti Sulety Distu	leeb lot hild o Littit Duild
Exposure	<b>RF</b> Safety Distance
	( <b>cm</b> )
General Population/Uncontrolled	20
Occupational/Controlled	20

#### Table 4.2.5 Proposed RF Safety Distances for MBO LAA Band 46

Only the general population/uncontrolled exposure environment will be considered for UNII devices.

### 5. REFERENCES

- [1]. Title 47 Code of Federal Regulations (CFR) Parts 1, 2 and 15.
- [2]. FCC OET Bulletin 65 and Supplements, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, August 1997
- [3]. KDB 447498 D01, RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices, Oct 2015, V06
- [4]. IEEE C95.3, IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields with Respect to Human Exposure to Such Fields, 100 kHz–300 GHz, 2002 (R2008).