

Report No. : FA050617-02



# **WPT Evaluation Report**

FCC ID	<u>·</u> UZ7CR6080SA
Equipment	<sub>:</sub> 4D Cup
Brand Name	· Zebra
Model Name	<sup>:</sup> CR6080-SA
Applicant	Zebra Technologies Corporation
	1 Zebra Plaza, Holtsville, NY 11742
Standard	: FCC CFR 47 part 1, 1.1307(b) and 1.1310
	KDB 680106 D01v03

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190).

Gua Guarg.

Approved by: Cona Huang / Deputy Manager

**Sporton International Inc.** No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan



## Table of Contents

1.	DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4				
2.	RF EXPOSURE LIMIT INTRODUCTION	5				
3.	MEASUREMENT EQUIPMENT	6				
4.	TEST MODE	7				
5.	RF EXPOSURE EVALUATION	7				
Ap	ppendix A. Test Setup Photo					



### **Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA050617-02	Rev. 01	Initial Report	Sep. 06, 2020



### 1. Description of Equipment Under Test (EUT)

Product Feature & Specification				
EUT Type	4D Cup			
Brand Name	Zebra			
Model Name	CR6080-SA			
FCC ID	7CR6080SA			
Frequency Range	WPC/WPT: 111 KHz ~ 205 KHz			
HW Version	21			
SW Version	21			
MFD	29JUL20			
DUT Stage	Engineering sample			
Test Date	Sep.03, 2020			



### 2. <u>RF Exposure Limit Introduction</u>

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposure									
0.3-3.0	614	1.63	* 100	6					
3.0-30	1842/f	4.89/f	* 900/f <sup>2</sup>	6					
30-300	61.4	0.163	1.0	6					
300-1,500	2019/01/2020/8		f/300	6					
1,500-100,000			5	6					
	(B) Limits for Gene	eral Population/Uncontrolled Ex	posure	· · · · ·					
0.3-1.34	614	1.63	* 100	30					
1.34-30 824/f		2.19/f	* 180/f <sup>2</sup>	30					
30-300	30-300 27.5		0.2	30					
300-1,500		f/1500 30		30					
1,500-100,000			1.0	30					

f = frequency in MHz

\* = Plane-wave equivalent power density

(1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase fully aware in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for transient persons, but they must receive written and/or verbal information (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase exercise control means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.

(2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



### 3. Measurement Equipment

#### **General Note:**

- 1. The test equipment is a 3-axis isotropic probe and the manufacturer is confirm the anisotropicty is less than 1dB.
- 2. For the test probe antenna length is less than 11.5cm, list as below spec.

Instrument	Manufacturer	Model No.	Serial No.	Freq Rang	Last Cal.	Due Date
Electric and Magnetic field Probe-Analyzey	Narda S.T.S / PMM	EHP 200AC	170WX80309	3KHz~30MHz	Jul. 17, 2020	Jul. 16, 2021

Technical speci	Technical specifications of the EHP-200AC Electric and Magnetic Field Analyzer					
	Electric Field Magnetic Field Mode A Magnetic Field Mode B			AUX Input		
Frequency range	(3) 3 kHz + 30 MHz	3 kHz + 300 kHz	30 kHz + 10 (30) MHz	(3) 9 kHz + 30 MHz		
Measurement range	server	8		8 (A.S. 50)		
@10kHz RBW	0,1 + 1000 V/m	0,1 A/m + 1 kA/m	30 mA/m + 300 A/m	-80 + 0 dBm		
with preamplifier ON	0,02 + 200 V/m	20 mA/m + 200 A/m	6 mA/m + 60 A/m	-94 + -14 dBm		
Dynamic range		> 8	0 dB			
Measurement range		>9	4 dB	10 (1000) (1000)		
Resolution	0.01 V/m	1 mA/m	0.1 mA/m	0.01 dB		
Sensitivity @10kHz RBW (*)	0.1 V/m	0.1 A/m	30 mA/m	-80 dBm		
with preamplifier ON	0.02 V/m	20 mA/m	6 mA/m	-94 dBm		
Flatness	0,5 dB 100 kHz = 27 MHz @ 20 V/m	0,8 dB 5 kHz – 300 kHz @ 1 A/m	0,8 dB 30 kHz – 10 MHz @ 166 mA/m	0,4 dB 9 kHz + 30 MHz @ +20dBm		
Anisotropicity @ 300 kHz		0.8 dB				
Linearity @ 300 kHz	0	0,5 dB from F	S to -60 dBFS			
SPAN	2	0 to FUI	LL SPAN			
RBW		1 kHz - 3 kHz - 10 kHz - 3	30 kHz – 100 kHz – 300 kHz	P		
Rejection to E fields		~	20 dB			
Rejection to H fields	> 20 dB	> 20 dB				
Calibration		internal	E <sup>2</sup> PROM			
Temperature error		0,02	dB/°C			
Dimensions	2	92 x 92 :	x 109 mm			
Weight		55	i0 g			
Environmental protection		IF	42			
Preamplifier		selectable O	N/OFF, 14dB			
Units		V/m, A/m, uT,	mW/cm <sup>2</sup> , W/m <sup>2</sup>			
Internal battery		3,7 V - 5,55 Ah L	i-lon, rechargeable			
Operation		> 12	hours			
Recharging time		< 8	nours			
External supply	3	10 + 15 VDC, I =	approx. 560 mA			
Optical fiber connection	up to 40 m (USB-OC)					
Eirmware undeting	up to 80 m (8053-00)					
Colf toot	0	unough the				
Operating temperature	2	automatic at power on				
Operating temperature	-10 to +50°C					
Storage temperature	-20 to +70°C					



### 4. <u>Test Mode</u>

The defice has been tested in the fellowing charging contaitents de belowing					
Test Mode	Test Setup Configuration	Charging Current Condition			
TM1	Test w/ Client Device installed	< 1% Battery status			
TM2	Test w/ Client Device installed	50% Battery status			
ТМЗ	Test w/ Client Device installed	Near 100% Battery status			

This device has been tested in the following charging conditions as below:

### 5. <u>RF Exposure Evaluation</u>

#### General Note:

- 1. The device power transfer frequency is less than 1MHz
- 2. The output power from the coil is less than 15W
- 3. The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
- 4. Client device is placed directly in contact with the transmitter.
- 5. The device is as a desktop WPT as mobile exposure condition, the test guidance is according to KDB 680106
- 6. The equipment under test was placed on a wooden desk inside of shield room. The isotropic field probe was used to measure the field strength for 6 EUT surfaces, and during measurement a separation of 10cm is maintained between EUT surface and the center of the field probe and the test result is less than 50% limit. The detail setup photo please refer to Appendix A.
- 7. Per KDB 680106 D01v03, RF exposure evaluation should be conducted assuming a user separation distance of 10 cm. H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 10 cm measured from the center. of the probe(s) to the edge of the device. Emissions between 50 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 1.63 A/m and aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Position (Distance 10cm)	H-Field Measurement (A/m)						
	Α	В	С	D	E	F	50% of limit
TM1	0.3707	0.4724	0.3624	0.3912	0.4020	0.3664	
TM2	0.3701	0.4573	0.3602	0.3911	0.3981	0.3651	0.815
TM3	0.3689	0.4325	0.3611	0.3893	0.3995	0.3623	

### **Conclusion:**

The field strength limit refers to Part 1.1310 and the test result of exposure evaluation is compliant with 50% of the MPE limit. (H-field: 0.815A/m).