

Xiamen Topstar Co., Ltd.

RF TEST REPORT

Report Type:

FCC Part 15.225 & ISSED RSS-210 RF report

Model:

TSE240V/32AUS-H01R002, TSE240V/40AUS-H01R002,
TSE240V/48AUS-H01R002, TSE240V/32AUS-C01R001,
TSE240V/40AUS-C01R001, TSE240V/48AUS-C01R001,
TSE240V/32AUS-C01R002, TSE240V/40AUS-C01R002,
TSE240V/48AUS-C01R002

REPORT NUMBER:

221100385SHA-001

ISSUE DATE:

January 6, 2023

DOCUMENT CONTROL NUMBER:

TTRF15.225_V1 © 2018 Intertek



Applicant: Xiamen Topstar Co.,Ltd
No.696 Meixi Road, Tong'an District, Xiamen City, Fujian Province, P.R.China

Manufacturer: Xiamen Topstar Lighting Co.,Ltd
676 Meixi Avenue, Tong'an District, Xiamen, China

Factory: Xiamen Topstar Lighting Co.,Ltd
676 Meixi Avenue, Tong'an District, Xiamen, China

FCC ID: 2A9FM-TSE240VAUS

IC: 29702-TSE240VAUS

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2020): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-210 Issue 10 (December 2019): Licence-Exempt Radio Apparatus: Category I Equipment

RSS-Gen Issue 5, Amendment 1 (March 2019): General Requirements for Compliance of Radio Apparatus

PREPARED BY:

REVIEWED BY:



Project Engineer
Sky Yang



Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY	5
MEASUREMENT RESULT SUMMARY	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION	7
1.3 DESCRIPTION OF TEST FACILITY	8
2 TEST SPECIFICATIONS	9
2.1 STANDARDS OR SPECIFICATION	9
2.2 MODE OF OPERATION DURING THE TEST	9
2.3 TEST SOFTWARE LIST	9
2.4 TEST PERIPHERALS LIST	9
2.5 TEST ENVIRONMENT CONDITION	9
2.6 INSTRUMENT LIST	10
2.7 MEASUREMENT UNCERTAINTY	11
3 FUNDAMENTAL EMISSION	12
3.1 LIMIT	12
3.2 MEASUREMENT PROCEDURE	12
3.3 TEST CONFIGURATION	13
3.4 TEST RESULTS OF FUNDAMENTAL EMISSIONS	14
4 SPURIOUS EMISSION	15
4.1 LIMIT	15
4.2 MEASUREMENT PROCEDURE	15
4.3 TEST RESULTS OF RADIATED EMISSIONS	17
5 FREQUENCY STABILITY (TEMPERATURE VARIATION)	20
5.1 TEST LIMIT	20
5.2 TEST CONFIGURATION	20
5.3 TEST PROCEDURE AND TEST SETUP	21
5.4 TEST PROTOCOL	21
6 FREQUENCY STABILITY (VOLTAGE VARIATION)	22
6.1 TEST LIMIT	22
6.2 TEST CONFIGURATION	22
6.3 TEST PROCEDURE AND TEST SETUP	22
6.4 TEST PROTOCOL	23
7 CONDUCTED EMISSIONS	24
7.1 LIMIT	24
7.2 TEST CONFIGURATION	24
7.3 MEASUREMENT PROCEDURE	25
7.4 TEST RESULTS OF CONDUCTED EMISSIONS	26
8 20DB BANDWIDTH	28
8.1 LIMIT	28
8.2 TEST CONFIGURATION	28
8.3 TEST PROCEDURE AND TEST SET UP	29
8.4 TEST PROTOCOL	30

TEST REPORT

9	ANTENNA REQUIREMENT.....	31
----------	---------------------------------	-----------

Revision History

Report No.	Version	Description	Issued Date
221100385SHA-001	Rev. 01	Initial issue of report	January 6, 2023

Measurement result summary

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
Fundamental emission	15.225(a) (b) (c)	RSS 210 B.6	Pass
Spurious emission	15.225(d)	RSS 210 B.6	Pass
Frequency stability	15.225(e)	RSS 210 B.6	Pass
Conducted emissions	15.207	RSS-Gen Issue 5 Clause 8.8	Pass
99% and 20dB Bandwidth	15.215(c)	RSS-Gen Issue 5 Clause 6.6	Pass
Antenna requirement	15.203	RSS-GEN 6.8	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Electric Vehicle AC Charging Station
Type/Model:	TSE240V/32AUS-H01R002, TSE240V/40AUS-H01R002, TSE240V/48AUS-H01R002, TSE240V/32AUS-C01R001, TSE240V/40AUS-C01R001, TSE240V/48AUS-C01R001, TSE240V/32AUS-C01R002, TSE240V/40AUS-C01R002, TSE240V/48AUS-C01R002
Description of EUT:	<p>The EUT is Electric Vehicle AC Charger with RFID Function, it supports WIFI, Bluetooth and LTE function, the wireless module FCC ID is 2AC7Z-ESPC3WROOM and XMR201909EC25AFX, the wireless module IC is 21098-ESPC3WROOM and 10224A-2019EC25AFX. Same components used in those models except for output current.</p> <p>Home Edition model: TSE240V/32AUS-H01R002, TSE240V/40AUS-H01R002, TSE240V/48AUS-H01R002 with WIFI, BLE and RFID.</p> <p>Business Edition model: TSE240V/32AUS-C01R001, TSE240V/32AUS-C01R001, TSE240V/48AUS-C01R001 with WIFI, BLE, RFID and 4G; TSE240V/32AUS-C01R002, TSE240V/40AUS-C01R002, TSE240V/48AUS-C01R002 with WIFI, BLE, RFID.</p> <p>So choose TSE240V/48AUS-C01R001 to test as representative.</p>
Rating:	<p>TSE240V/32AUS-H01R002, TSE240V/32AUS-C01R001, TSE240V/32AUS-C01R002:208-240VAC, 60Hz, 32A, 7.6kW</p> <p>TSE240V/40AUS-H01R002, TSE240V/40AUS-C01R001, TSE240V/40AUS-C01R002:208-240VAC, 60Hz, 40A, 9.6kW</p> <p>TSE240V/48AUS-H01R002, TSE240V/48AUS-C01R001, TSE240V/48AUS-C01R002:208-240VAC, 60Hz, 48A, 11.5kW</p>
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	V5
Hardware Version:	YX-R1-V100
Serial numbers:	22100801-23-05
Sample received date:	November 4, 2022
Date of test:	November 4, 2022 ~ November 5, 2022

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna, 5dBi

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

Fundamental emission, Spurious emission and Conducted emissions tests were sub-contracted.

Name:	Shenzhen STS Testing Services Co.,Ltd.
Address:	A 1/F, Building B, Zhuoke Science Park, No.190, Chongqing Road, Heping Shequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Telephone:	86 755 36886288
The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L7649
	FCC Accredited Lab Designation Number: CN1203
	IC Registration Lab CAB identifier.: CN0086
	A2LA Accreditation Lab Certificate Number: 4338.01

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2020)

ANSI C63.10 (2013)

RSS-210 Issue 10 (December 2019)

RSS-Gen Issue 5, Amendment 1 (March 2019)

2.2 Mode of operation during the test

While testing, the internal modulation and continuously transmission was applied.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No	Description	Band and Model	S/No
1	Programmable AC Electronic Load	WS-AEV-066T	-

2.5 Test environment condition:

Test items	Temperature	Humidity
Radiated emission	26°C	53% RH
Power line conducted emission	27°C	53% RH

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Receiver	R&S	ESR7	TW/C-003	2023-09-26
<input checked="" type="checkbox"/>	LISN	-	NSLK8127	TW/C-013	2023-09-26
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	EMI Receiver	R&S	ESR26	FWXGJC-2016-267-01	2022-11-26
<input checked="" type="checkbox"/>	Bi-log Antenna	R&S	HL562E	FWXGJC-2016-267-06	2023-03-30
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	FMZB 1519B	FWXGJC-2018-015	2024-08-13
<input checked="" type="checkbox"/>	Anechoic chamber	Aimuke	EMCCT-3	FWXGJC-2016-270	2023-04-07
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Spectrum analyzer	Keysight	N9030B	EC 6078	2023-06-04
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Thermo-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2023-03-24
<input checked="" type="checkbox"/>	Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-386	2022-12-27

TEST REPORT

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Expanded Uncertainty (k=2)
Conducted emission at mains ports	9kHz ~ 150kHz	3.52 dB
	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	3.06 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB

3 Fundamental Emission

Test result: Pass

3.1 Limit


Frequencies (MHz)	Limit at 30m (dBuV/m)	Limit at 3m (dBuV/m)
13.110 – 13.410	40.50	80.50
13.410 – 13.553	50.50	90.50
13.553 – 13.567	84.00	124.00
13.567 – 13.710	50.50	90.50
13.710 – 14.010	40.50	80.50

3.2 Measurement Procedure

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to PK Detect Function and Specified Bandwidth with Maximum Hold Mode.


NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**3.3 Test Configuration**

TEST REPORT

3.4 Test Results of Fundamental Emissions



Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector
X	13.56	47.96	20.98	124.00	76.04	PK
Y	13.56	47.82	20.98	124.00	76.18	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

4 Spurious Emission

Test result: Pass

4.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

4.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

TEST REPORT

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. All modes of operation were evaluated and the worst-case emissions were reported

TEST REPORT

4.3 Test Results of Radiated Emissions


The EUT has been tested in all two orthogonal planes, it has the worst case when it is in horizontal position for both below 30MHz & above 30MHz.

Test data below 30MHz:


Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Polarity
0.0136	16.34	19.63	124.93	108.59	X
0.0427	17.29	19.65	115.00	97.71	X
0.0704	16.04	18.93	110.65	94.61	X
0.568	23.12	20.23	72.52	49.40	X
3.224	31.31	20.17	69.50	38.19	X
19.224	28.78	20.98	69.50	40.72	X
0.0238	15.54	20.02	120.07	104.53	Y
0.0526	17.66	19.43	113.18	95.52	Y
0.128	12.95	17.54	105.46	92.51	Y
2.001	34.37	20.40	69.50	35.13	Y
4.836	28.91	20.48	69.50	40.59	Y

TEST REPORT

H



V



TEST REPORT

Test data from 30MHz to 1000MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector
H	189.08	32.12	-20.87	43.50	11.38	PK
H	419.94	38.20	-10.09	46.00	7.80	PK
H	474.26	39.13	-8.85	46.00	6.87	PK
H	569.32	37.79	-5.59	46.00	8.21	PK
H	677.96	33.85	-4.34	46.00	12.15	PK
H	881.66	32.72	-0.66	46.00	13.28	PK
V	40.67	32.29	-18.40	40.00	7.71	PK
V	243.40	37.41	-17.32	46.00	8.59	PK
V	352.04	34.34	-13.02	46.00	11.66	PK
V	419.94	38.85	-10.09	46.00	7.15	PK
V	515.00	37.44	-7.88	46.00	8.56	PK
V	902.03	32.94	-0.40	46.00	13.06	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.


5 Frequency Stability (Temperature Variation)

Test result: PASS

5.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage.

5.2 Test Configuration



5.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.1.

5.4 Test protocol

Voltage (V)	Temp (°C)	Freq measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
240	-20	13.5596	13.56	-0.003	±.01
	-10	13.5593		-0.005	
	0	13.5600		0	
	10	13.5600		0	
	20	13.5600		0	
	30	13.5601		0.001	
	40	13.5595		-0.004	
	50	13.5598		-0.001	

TEST REPORT


6 Frequency Stability (Voltage Variation)

Test result: PASS

6.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2 Test Configuration



6.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.2.

TEST REPORT

6.4 Test protocol

Temp (°C)	Voltage (V)	Freq Measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
20	208	13.5603	13.56	0.002	±0.01
	224	13.5603		0.002	
	240	13.5600		0	

7 Conducted emissions


Test result: Pass

7.1 Limit

Frequency of Emission (MHz)	Conducted Emissions Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

7.2 Test Configuration



TEST REPORT**7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

7.4 Test Results of Conducted Emissions


Test Voltage: 240VAC/60Hz

Test Curve:

L Line



N Line



TEST REPORT

Frequency [MHz]	QP Level [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Level [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Phase
0.155	58.82	65.75	6.93	50.34	55.75	5.41	L
0.186	58.20	64.21	6.01	48.69	54.21	5.53	L
0.227	57.57	62.58	5.00	47.83	52.58	4.74	L
0.402	53.98	57.81	3.84	45.73	47.81	2.08	L
0.429	53.45	57.27	3.82	45.71	47.27	1.56	L
0.875	52.93	56.00	3.07	39.11	46.00	6.89	L
1.842	44.71	56.00	11.29	34.79	46.00	11.21	L
5.789	32.89	60.00	27.11	24.21	50.00	25.79	L
16.670	19.61	60.00	40.39	14.04	50.00	35.96	L
0.168	56.80	65.06	8.26	45.16	55.06	9.90	N
0.200	57.52	63.63	6.11	47.26	53.63	6.37	N
0.308	55.89	60.04	4.15	46.49	50.04	3.55	N
0.434	53.07	57.19	4.12	44.83	47.19	2.35	N
0.456	54.13	56.77	2.64	46.55	46.77	0.22	N
0.906	52.76	56.00	3.24	38.59	46.00	7.41	N
1.946	43.88	56.00	12.12	33.90	46.00	12.10	N
27.123	27.89	60.00	32.11	27.57	50.00	22.43	N
13.560	-	-	-	-	-	-	L
13.560	-	-	-	-	-	-	N

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Correct Factor

3. Margin = Limit - Level

4. If the PK Level is lower than AV limit, the AV test can be elided.

5. the emissions of 13.56MHz are the product's RF signal.


8 20dB Bandwidth

Test result: Pass

8.1 Limit

The 20dB bandwidth should be fallen in the allocated operating frequency range.
No limit for 99% bandwidth.

8.2 Test configuration



8.3 Test procedure and test set up

The measurement was applied in a 3m semi-anechoic chamber.


The center of the loop antenna shall be 1 m above the horizontal metal ground plane.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set RBW = 1 % to 5 % of the OBW
3. Set VBW $\geq 3 \cdot$ RBW
4. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
5. Use the 99 % power bandwidth function of the instrument (if available).
6. the 20dB bandwidth is also measured with the same setting.

8.4 Test protocol

	Lower point (MHz)	Higher point (MHz)	Bandwidth (kHz)	Allocated bandwidth (MHz)
20dB Bandwidth	13.561108	13.561355	0.247	13.553 ~ 13.567
Occupied bandwidth	13.561117	13.561347	0.21	13.553 ~ 13.567



9 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

***** END *****