

---

## Appendix B. Highest Measurement Data

Test Laboratory: DEKRA

Date: 2025/01/24

**204\_WLAN2.4GHz\_802.11b-1M\_CH1\_Left-side\_5mm\_ANT Wifi 1**

Communication System: UID 0, WLAN 2.4G; Frequency: 2412 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.78$  S/m;  $\epsilon_r = 40.41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

**DASY Configuration:**

- Probe: EX3DV4 - SN7631; ConvF(8.22, 8.22, 8.22) @ 2412 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASY52, Version 52.10 (4);

**Configuration/Flat/Area Scan (8x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 1.54 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.338 V/m; Power Drift = 0.17 dB


Peak SAR (extrapolated) = 2.07 W/kg

**SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.454 W/kg**

Smallest distance from peaks to all points 3 dB below = 8.5 mm

Ratio of SAR at M2 to SAR at M1 = 52.5%

Maximum value of SAR (measured) = 1.69 W/kg



Test Laboratory: DEKRA

Date: 2025/01/24

**502\_Bluetooth\_BT-1M\_CH38\_Right-side\_5mm\_ANT Wifi 2**

Communication System: UID 0, BT 1M&amp;3M&amp;BLE; Frequency: 2440 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 2440$  MHz;  $\sigma = 1.82$  S/m;  $\epsilon_r = 40.31$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

**DASY Configuration:**

- Probe: EX3DV4 - SN7631; ConvF(8.22, 8.22, 8.22) @ 2440 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASYS2, Version 52.10 (4);

**Configuration/Flat/Area Scan (7x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.232 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.124 V/m; Power Drift = 0.10 dB


Peak SAR (extrapolated) = 0.475 W/kg

**SAR(1 g) = 0.228 W/kg; SAR(10 g) = 0.099 W/kg**

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 52.1%

Maximum value of SAR (measured) = 0.393 W/kg



Test Laboratory: DEKRA

Date: 2025/01/25

**218\_WLAN5GHz\_802.11ac80-VHT0\_CH58\_Left-side\_5mm\_ANT Wifi 1**

Communication System: UID 0, WLAN 5G; Frequency: 5290 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 5290$  MHz;  $\sigma = 4.8$  S/m;  $\epsilon_r = 36.08$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

**DASY Configuration:**

- Probe: EX3DV4 - SN7631; ConvF(5.79, 5.79, 5.79) @ 5290 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASY52, Version 52.10 (4);

**Configuration/Flat/Area Scan (9x13x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 2.16 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 18.45 V/m; Power Drift = 0.11 dB


Peak SAR (extrapolated) = 3.76 W/kg

**SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.314 W/kg**

Smallest distance from peaks to all points 3 dB below = 7.9 mm

Ratio of SAR at M2 to SAR at M1 = 66.3%

Maximum value of SAR (measured) = 2.37 W/kg



Test Laboratory: DEKRA

Date: 2025/01/25

**231\_WLAN5GHz\_802.11ac80-VHT0\_CH138\_Left-side\_5mm\_ANT Wifi 1**

Communication System: UID 0, WLAN 5G; Frequency: 5690 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 5690$  MHz;  $\sigma = 5.33$  S/m;  $\epsilon_r = 34.98$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

**DASY Configuration:**

- Probe: EX3DV4 - SN7631; ConvF(5.03, 5.03, 5.03) @ 5690 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASYS2, Version 52.10 (4);

**Configuration/Flat/Area Scan (9x13x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 2.35 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 17.49 V/m; Power Drift = -0.17 dB


Peak SAR (extrapolated) = 4.48 W/kg

**SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.328 W/kg**

Smallest distance from peaks to all points 3 dB below = 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 61.6%

Maximum value of SAR (measured) = 2.60 W/kg



Test Laboratory: DEKRA

Date: 2025/01/25

**221\_WLAN5GHz\_802.11ac80-VHT0\_CH171\_Left-side\_5mm\_ANT Wifi 1**

Communication System: UID 0, WLAN 5G; Frequency: 5855 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 5855$  MHz;  $\sigma = 5.55$  S/m;  $\epsilon_r = 34.52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

**DASY Configuration:**

- Probe: EX3DV4 - SN7631; ConvF(5.14, 5.14, 5.14) @ 5855 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASY52, Version 52.10 (4);

**Configuration/Flat/Area Scan (9x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 1.97 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 20.83 V/m; Power Drift = -0.09 dB


Peak SAR (extrapolated) = 3.41 W/kg

**SAR(1 g) = 0.814 W/kg; SAR(10 g) = 0.252 W/kg**

Smallest distance from peaks to all points 3 dB below = 7.9 mm

Ratio of SAR at M2 to SAR at M1 = 61.4%

Maximum value of SAR (measured) = 1.94 W/kg



Test Laboratory: DEKRA

Date: 2025-02-18

**276\_WLAN6GHz\_802.11ax160-HE0\_CH143\_Left-side\_5mm\_ANT Wifi 1**

Communication System: UID 10755-AAC, WLAN; Frequency: 6665.000 MHz

Medium parameters used:  $f = 6665.000$  MHz; Conductivity = 6.23 S/m; Permittivity = 34.1

Phantom section: Flat

## DASY Configuration:

- Probe: EX3DV4 - SN7350; ConvF(5.51, 5.51, 5.62); Calibrated: 2024-12-19
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn916; Calibrated: 2024-12-04
- Phantom: ELI V8.0 (20deg probe tilt)
- Measurement SW: V16.4.0.5005

**Area Scan (68.0 mm x 85.0 mm ):** Measurement grid: 8.5 mm x 8.5 mm

SAR (1 g) = 0.620 W/kg; SAR (10 g) = 0.226 W/kg

**Zoom Scan (22.0 mm x 22.0 mm x 22.0 mm ):** Measurement grid: 3.4 mm x 3.4 mm x 1.4 mm


Power Drift = 0.09 dB

SAR(1 g) = 0.688 W/kg; SAR(10 g) = 0.245 W/kg

psAPD (4.0cm<sup>2</sup>, sq) = 5.47 W/m<sup>2</sup>

Smallest distance from peaks to all points 3 dB below = 8.5

Ratio of SAR at M2 to SAR at M1 = 51.5



12\_WLAN6E\_802.11ax160-HE0\_CH143\_Left-side\_5mm\_Wifi 1  
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
	189.36 x 88.66 x 35.05		Handheld Tablet

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G Air	EDGE RIGHT, 5.00	U-NII-7	WLAN, 10755-AAC	6665.0, 143	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave- 1068	Air	EUmmWV4 - SN9546_F1-55GHz, 2024-04-18	DAE4 Sn916, 2024-12-04

Scan Setup

	5G Scan
Grid Extents [mm]	100.0 x 100.0
Grid Steps [lambda]	0.05 x 0.05
Sensor Surface [mm]	5.0
MAIA	Y

Measurement Results

	5G Scan
Date	2025-02-18
Avg. Area [cm²]	4.00
psPDn+ [W/m²]	4.62
psPDtot+ [W/m²]	4.92
psPDmod+ [W/m²]	5.07
E <sub>max</sub> [V/m]	55.3
Power Drift [dB]	-0.17





## SAR measurement variability

Test Laboratory: DEKRA

Date: 2025/01/24

### 307\_WLAN2.4GHz\_802.11b-1M\_CH1\_Left-side\_5mm\_ANT Wifi 1 - Verify

Communication System: UID 0, WLAN 2.4G; Frequency: 2412 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.78$  S/m;  $\epsilon_r = 40.41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY Configuration:

- Probe: EX3DV4 - SN7631; ConvF(8.22, 8.22, 8.22) @ 2412 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASY52, Version 52.10 (4);

**Configuration/Flat/Area Scan (8x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 1.31 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 31.11 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 2.04 W/kg

**SAR(1 g) = 1.000 W/kg; SAR(10 g) = 0.434 W/kg**

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 51.8%

Maximum value of SAR (measured) = 1.63 W/kg



Test Laboratory: DEKRA

Date: 2025/01/25

**308\_WLAN5GHz\_802.11ac80-VHT0\_CH138\_Left-side\_5mm\_ANT Wifi 1 - Verify**

Communication System: UID 0, WLAN 5G; Frequency: 5690 MHz

Communication System PAR: 0 dB

Medium parameters used:  $f = 5690$  MHz;  $\sigma = 5.33$  S/m;  $\epsilon_r = 34.98$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

**DASY Configuration:**

- Probe: EX3DV4 - SN7631; ConvF(5.03, 5.03, 5.03) @ 5690 MHz; Calibrated: 2024/02/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1651; Calibrated: 2024/02/15
- Phantom: ELI V8.0; Type: QD OVA 004 AA; Serial: 2139
- Measurement SW: DASY52, Version 52.10 (4);

**Configuration/Flat/Area Scan (9x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 1.90 W/kg

**Configuration/Flat/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 22.69 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.99 W/kg

**SAR(1 g) = 0.960 W/kg; SAR(10 g) = 0.291 W/kg**

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 62.2%

Maximum value of SAR (measured) = 2.38 W/kg

