

# FCC Part 15C Measurement and Test Report

For

**AUTOEQUIPS TECH CO., LTD**

**Rm.13, 14F West Tower Coastal Building, Nanshan District, Shenzhen,**

**Guangdong, China**

**FCC ID: 2AGPO-CB213**

<b>FCC Rule(s):</b>	<u>FCC Part 15.247</u>
<b>Product Description:</b>	<u>Digital Wireless System</u>
<b>Tested Model:</b>	<u>CB213</u>
<b>Report No.:</b>	<u>STR15118376I-1</u>
<b>Tested Date:</b>	<u>2015-11-27 to 2016-02-22</u>
<b>Issued Date:</b>	<u>2016-02-22</u>
<b>Tested By:</b>	<u>Jason Su / Engineer</u>
<b>Reviewed By:</b>	<u>Silin Chen / EMC Manager</u>
<b>Approved &amp; Authorized By:</b>	<u>Jandy so / PSQ Manager</u>
<b>Prepared By:</b>	

*Jason Su*  
*Silin Chen*  
*Jandyso*

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 TEST EQUIPMENT LIST AND DETAILS.....	5
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
<b>3. RF EXPOSURE.....</b>	<b>7</b>
3.1 STANDARD APPLICABLE.....	7
3.2 TEST RESULT.....	7
<b>4. ANTENNA REQUIREMENT.....</b>	<b>8</b>
4.1 STANDARD APPLICABLE.....	8
4.2 EVALUATION INFORMATION.....	8
<b>5. FREQUENCY HOPPING SYSTEM REQUIREMENTS.....</b>	<b>9</b>
5.1 STANDARD APPLICABLE.....	9
5.2 FREQUENCY HOPPING SYSTEM.....	9
5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	10
<b>6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION.....</b>	<b>11</b>
6.1 STANDARD APPLICABLE.....	11
6.2 TEST PROCEDURE.....	11
6.3 ENVIRONMENTAL CONDITIONS.....	11
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	12
<b>7. DWELL TIME OF HOPPING CHANNEL.....</b>	<b>14</b>
7.1 STANDARD APPLICABLE.....	14
7.2 TEST PROCEDURE.....	14
7.3 ENVIRONMENTAL CONDITIONS.....	14
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	15
<b>8. 20DB BANDWIDTH.....</b>	<b>19</b>
8.1 STANDARD APPLICABLE.....	19
8.2 TEST PROCEDURE.....	19
8.3 ENVIRONMENTAL CONDITIONS.....	19
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	19
<b>9. RF OUTPUT POWER.....</b>	<b>22</b>
9.1 STANDARD APPLICABLE.....	22
9.2 TEST PROCEDURE.....	22
9.3 ENVIRONMENTAL CONDITIONS.....	22
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	22
<b>10. FIELD STRENGTH OF SPURIOUS EMISSIONS.....</b>	<b>23</b>
10.1 MEASUREMENT UNCERTAINTY.....	23
10.2 STANDARD APPLICABLE.....	23
10.3 TEST PROCEDURE.....	23
10.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	25
10.5 ENVIRONMENTAL CONDITIONS.....	25
10.6 SUMMARY OF TEST RESULTS/PLOTS.....	25
<b>11. OUT OF BAND EMISSIONS.....</b>	<b>33</b>
11.1 STANDARD APPLICABLE.....	33
11.2 TEST PROCEDURE.....	33
11.3 ENVIRONMENTAL CONDITIONS.....	34
11.4 SUMMARY OF TEST RESULTS/PLOTS.....	34

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: AUTOEQUIPS TECH CO., LTD  
Address of applicant: Rm.13, 14F West Tower Coastal Building, Nanshan District, Shenzhen, Guangdong, China  
Manufacturer: Link Force Electronic TECH Co., Ltd  
Address of manufacturer: #34, Zhongkai Hi-Tech Zone, Huizhou City, Guangdong Province, P.R. China

General Description of EUT	
Product Name:	Digital Wireless System
Trade Name:	PSVT
Model No.:	CB213
Adding Model(s):	CB217, CB214(4Tto1R), CB113, CB114, CB313, CB314, CB513, CB514, CB713, CB714, CB126-A, CB126-B, CB127-A
Rated Voltage:	DC12-24V
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model CB213, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2406-2472.5MHz
RF Output Power:	17.44dBm (Conducted)
Modulation:	GFSK
Quantity of Channels:	20
Channel Separation:	3.5MHz
Antenna Type:	SMA-reverse Antenna
Antenna Gain:	3dBi
Lowest Internal Frequency of EUT:	32.768kHz
Device Category:	Fixed Device

## 1.2 Test Standards

The following report is prepared on behalf of the AUTOEQUIPS TECH CO., LTD in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide DA 00-705 for frequency hopping spread spectrum systems shall be performed also.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2406MHz
TM2	Middle Channel	2441MHz
TM3	High Channel	2472.5MHz
TM4	Hopping	2406-2472.5MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

## 1.6 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16
Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.205	Restricted Band of Operation	Compliant
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has a SMA-reverse antenna, fulfill the requirement of this section.



## 5. Frequency Hopping System Requirements

---

### 5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses RF radio which operates in 2406-2472.5 MHz band. RF uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 20 bands in the range 2,406-2,472.5 MHz. All RF devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the RF specification to provide an effective way for a RF radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the RF signal or the RF signal is interfering with another device. The AFH-enabled RF device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an RF system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

### **5.3 EUT Pseudorandom Frequency Hopping Sequence**

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 20, 02, 03, 04, 01, 06, 08, 09, 11, 15, 05, 12, 19, 07, 13, 14, 16, 17, 18, 10

Channel: 20, 01, 03, 04, 06, 08, 09, 11, 15, 05, 12, 19, 07, 13, 02, 14, 16, 17, 18, 10

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 6. Quantity of Hopping Channels and Channel Separation

### 6.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 6.2 Test Procedure

According to the DA 00-705, the number of hopping frequencies test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = the frequency band of operation (2400MHz to 2483.5MHz)

RBW = 100kHz, VBW = 100kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize, observed the band of 2400MHz to 2483.5MHz, than count it out the number of channels for comparing with the FCC rules.

The channel spacing test method as follows:

Set span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto; Detector function = peak; Trace = max hold


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

### 6.3 Environmental Conditions


Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 6.4 Summary of Test Results/Plots


No. of Channel = 20




Channel Spacing (Low CH)



### Channel Spacing (Middle CH)



### Channel Spacing (High CH)



## 7. Dwell Time of Hopping Channel

### 7.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 7.2 Test Procedure

According to the DA 00-705, the dwell time of a hopping channel test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Use the marker-delta function to determine the dwell time

### 7.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 7.4 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).



The test period:  $T = 0.4 \text{ Second} * 20 \text{ Channel} = 8 \text{ s}$

Dwell time = time slot length \* number of pulse in 8s

Modulation	Test Channel	Time Slot Length	Dwell Time	Limit
		ms	ms	ms
GFSK	2406MHz	0.670	21.44	<400
	2441MHz	0.670	21.44	<400
	2472.5MHz	0.670	21.44	<400



*Please refer to the test plots as below:*

Low:







Middle:



High:



## 8. 20dB Bandwidth

### 8.1 Standard Applicable

According to 15.247(a) and 15.215(c). 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 8.2 Test Procedure

According to the DA 00-705, the 20dB bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto; Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.


### 8.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


### 8.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Result
GFSK	2406	843.874	848.5507	Pass
	2441	831.240	830.8975	Pass
	2472.5	820.290	845.3117	Pass


Low Channel:



Middle Channel:



High Channel:



## 9. RF Output Power

### 9.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### 9.2 Test Procedure

According to the DA 00-705, the peak output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, the indicated level is the peak output power (the external attenuation and cable loss shall be considered).

### 9.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

### 9.4 Summary of Test Results/Plots

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2406	16.27	42.36	125
Middle Channel	2441	17.35	54.33	125
High Channel	2472.5	17.44	55.46	125

*Note: the antenna gain of 3dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*

## 10. Field Strength of Spurious Emissions

---

### 10.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 10.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 10.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV



## 10.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

## 10.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 10.6 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

**Plot of Radiated Emissions Test Data (30MHz to 1GHz)**


EUT: *Digital Wireless System*  
 Tested Model: *CB213*  
 Operating Condition: *Transmitting Low Channel (2406MHz)*  
 Comment: *Battery DC24V*

Test Specification: *Horizontal*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	40.2757	43.34	-7.69	35.65	40.00	-4.35	174	100	peak
2	108.6470	47.65	-11.12	36.53	43.50	-6.97	11	100	peak
3	181.2834	48.14	-11.18	36.96	43.50	-6.54	135	100	peak
4	383.9318	45.10	-2.30	42.80	46.00	-3.20	201	100	peak
5	845.0878	36.03	2.18	38.21	46.00	-7.79	154	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.9942	42.40	-7.67	34.73	40.00	-5.27	147	100	peak
2	177.5092	50.05	-11.47	38.58	43.50	-4.92	201	100	peak
3	383.9318	42.64	-2.30	40.34	46.00	-5.66	167	100	peak
4	768.7482	39.24	2.28	41.52	46.00	-4.48	87	100	peak

Operating Condition: Transmitting Middle Channel (2441MHz)


Comment: Battery DC24V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	40.2757	42.34	-7.69	34.65	40.00	-5.35	78	100	peak
2	108.6470	46.65	-11.12	35.53	43.50	-7.97	129	100	peak
3	181.2834	47.14	-11.18	35.96	43.50	-7.54	55	100	peak
4	383.9318	44.10	-2.30	41.80	46.00	-4.20	144	100	peak
5	845.0878	34.53	2.18	36.71	46.00	-9.29	265	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.9942	42.65	-7.67	34.98	40.00	-5.02	341	100	peak
2	176.8878	45.56	-11.50	34.06	43.50	-9.44	201	100	peak
3	383.9318	41.98	-2.30	39.68	46.00	-6.32	156	100	peak
4	768.7482	37.03	2.28	39.31	46.00	-6.69	98	100	peak

Operating Condition: Transmitting High Channel (2472.5MHz)


Comment: Battery DC24V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	40.2757	40.84	-7.69	33.15	40.00	-6.85	165	100	peak
2	108.6470	46.15	-11.12	35.03	43.50	-8.47	201	100	peak
3	181.2834	46.64	-11.18	35.46	43.50	-8.04	126	100	peak
4	383.9318	43.10	-2.30	40.80	46.00	-5.20	59	100	peak
5	845.0878	33.53	2.18	35.71	46.00	-10.29	78	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	39.9942	41.65	-7.67	33.98	40.00	-6.02	265	100	peak
2	180.6488	45.75	-11.28	34.47	43.50	-9.03	55	100	peak
3	383.9318	42.48	-2.30	40.18	46.00	-5.82	154	100	peak
4	768.7482	38.34	2.28	40.62	46.00	-5.38	265	100	peak

### Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2406MHz							
4812	48.67	-0.98	47.69	74	-26.31	H	PK
4812	36.15	-0.98	35.17	54	-18.83	H	AV
7218	43.18	1.34	44.52	74	-29.48	H	PK
7218	33.26	1.33	34.59	54	-19.41	H	AV
4812	60.34	-0.98	59.36	74	-14.64	V	PK
4812	44.64	-0.98	43.66	54	-10.34	V	AV
7218	43.99	1.34	45.33	74	-28.67	V	PK
7218	33.45	1.34	34.79	54	-19.21	V	AV
Middle Channel-2441MHz							
4882	56.57	-0.80	55.77	74	-18.23	H	PK
4882	41.74	-0.80	40.94	54	-13.06	H	AV
7323	43.46	1.39	44.85	74	-29.15	H	PK
7323	32.06	1.40	33.46	54	-20.54	H	AV
4882	56.87	-0.80	56.07	74	-17.93	V	PK
4882	42.23	-0.80	41.43	54	-12.57	V	AV
7323	41.78	1.39	43.17	74	-30.83	V	PK
7323	32.58	1.42	34.00	54	-20.00	V	AV
High Channel-2472.5MHz							
4945	51.60	-0.62	50.98	74	-23.02	H	PK
4945	36.89	-0.62	36.27	54	-17.73	H	AV
7417.5	43.39	1.44	44.83	74	-29.17	H	PK
7417.5	33.20	1.47	34.67	54	-19.33	H	AV
4945	50.01	-0.62	49.39	74	-24.61	V	PK
4945	37.58	-0.62	36.96	54	-17.04	V	AV
7417.5	42.63	1.44	44.07	74	-29.93	V	PK
7417.5	32.22	1.44	33.66	54	-20.34	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.  
The measurements greater than 20dB below the limit from 9kHz to 30MHz.



## 11. Out of Band Emissions

---

### 11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 11.2 Test Procedure

According to the DA 00-705, the band-edge radiated test method as follows.

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2410MHz for low bandedge, 2470MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the DA 00-705, the band-edge conducted test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2380MHz to 2410MHz for low bandedge, 2470MHz to 2500MHz for the high bandedge)

RBW = 100kHz, VBW = 300kHz

Sweep = auto; Detector function = peak; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the limit specified in this section (at least 20dB attenuation).

### 11.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 11.4 Summary of Test Results/Plots

Bandedge (Radiated)


Lowest Bandedge

Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.45	-3.80	38.65	54.00	-15.35	Average Detector
	2310.000	52.85	-3.80	49.05	74.00	-24.95	Peak Detector
2	2373.470	44.06	-3.16	40.90	54.00	-13.10	Average Detector
	2374.130	55.01	-3.15	51.86	74.00	-22.14	Peak Detector
3	2390.000	47.41	-3.00	44.41	54.00	-9.59	Average Detector
	2390.000	55.48	-3.00	52.48	74.00	-21.52	Peak Detector
4	2400.000	59.22	-2.90	56.32	Delta = 57.27 dBc		Average Detector
5	2406.030	116.46	-2.87	113.59			Average Detector


Highest Bandedge  
Horizontal (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2472.500	117.89	-2.53	115.36	/	/	Average Detector
	2472.450	118.11	-2.53	115.58	/	/	Peak Detector
2	2483.500	Delta = 70.92 dBc		44.44	54.00	-9.56	Average Detector
	2483.500			44.66	74.00	-29.34	Peak Detector
3	2488.500	53.37	-2.46	50.91	54.00	-3.09	Average Detector
	2488.550	61.58	-2.46	59.12	74.00	-14.88	Peak Detector
4	2500.000	43.82	-2.40	41.42	54.00	-12.58	Average Detector
	2500.000	55.48	-2.40	53.08	74.00	-20.92	Peak Detector

Bandedge (Conducted)

Lowest Bandedge



Highest Bandedge



\*\*\*\*\* END OF REPORT \*\*\*\*\*