



FCC TEST REPORT

FCC ID:2A2LL-FR4000

Report Number..... : ZKT-240703L7620E

Date of Test..... Jun.27, 2024 to Jul.30, 2024

Date of issue : Sept 14, 2024

Total number of pages 80

Test Result : PASS

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : **FJ Dynamics Co., Ltd.**

Address 21F, Das Tower, No. 28, 1st South Keji Road, Nanshan District, Shenzhen, China

Manufacturer's name : **FJ Dynamics Co., Ltd.**

Address 21F, Das Tower, No. 28, 1st South Keji Road, Nanshan District, Shenzhen, China

Test specification:

Standard FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : **Robotic Lawn Mower**

Trademark : 

Model/Type reference : FR4000

Ratings..... : DC 14.8V



Testing procedure and testing location:

Testing Laboratory.....: **Shenzhen ZKT Technology Co., Ltd.**

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature): Jim.Liu

Reviewer (name + signature).....: Jackson.Fang

Approved (name + signature): Lake Xie





Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS.....	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT.....	8
3.2 DESCRIPTION OF TEST MODES.....	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE).....	9
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD.....	12
4.1.4 TEST SETUP.....	13
4.1.5 EUT OPERATING CONDITIONS.....	13
4.2.1 RADIATED EMISSION LIMITS.....	16
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD.....	17
4.2.4 TEST SETUP.....	17
4.2.5 EUT OPERATING CONDITIONS.....	18
4.2.6 TEST RESULTS	18
5.RADIATED BAND EMISSIONMEASUREMENT	31
5.1 TEST REQUIREMENT:.....	31
5.2 TEST PROCEDURE	31
5.3 DEVIATION FROM TEST STANDARD	31
5.4 TEST SETUP	32
5.5 EUT OPERATING CONDITIONS.....	32
5.6 TEST RESULT	33
6.POWER SPECTRAL DENSITY TEST	36
6.1 APPLIED PROCEDURES / LIMIT.....	36
6.2 TEST PROCEDURE	36
6.3 DEVIATION FROM STANDARD	36
6.4 TEST SETUP	36
6.5 EUT OPERATION CONDITIONS.....	36
6.6 TEST RESULT	37



7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH	44
7.1 APPLIED PROCEDURES / LIMIT.....	44
7.2 TEST PROCEDURE	44
7.3 DEVIATION FROM STANDARD	44
7.4 TEST SETUP	44
7.5 EUT OPERATION CONDITIONS.....	44
7.6 TEST RESULT	45
8.PEAK OUTPUT POWER TEST	53
8.1 APPLIED PROCEDURES/LIMIT.....	53
8.2 TEST PROCEDURE	53
8.3 DEVIATION FROM STANDARD	53
8.4 TEST SETUP	53
8.5 EUT OPERATION CONDITIONS.....	53
8.6 TEST RESULT	54
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	55
9.1 APPLICABLE STANDARD	55
9.2 TEST PROCEDURE	55
9.3 DEVIATION FROM STANDARD	55
9.4 TEST SETUP	55
9.5 EUT OPERATION CONDITIONS.....	55
9.6 TEST RESULTS	55
10. ANTENNA REQUIREMENT	79
11. TEST SETUP PHOTO	80
12. EUT CONSTRUCTIONAL DETAILS	80



1. VERSION

Report No.	Version	Description	Approved
ZKT-240703L7620E	Rev.01	Initial issue of report	Sept 14, 2024



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth& 99% OCB	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

CAB identifier: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8KHz
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Robotic Lawn Mower
Model No.:	FR4000
Model Different.:	N/A
Serial No.:	N/A
Sample ID	ZKT-240703L7620
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/802.11n(HT20): Orthogonal Frequency Division Multiplexing(OFDM)
Antenna Type and Antenna gain:	802.11b/g/n: FPC Antenna Antenna gain: 3.5dBi
Worst Case:	2.4G WIFI 802.11n20
Power supply:	Input:DC 14.8V
SWITCHING POWER ADAPTER:	Input:100-240VAC,50/60Hz,2.5AMAX Output:24VDC,7.5A,180W

Operation Frequency each of channel							
Channel	Frequency	Chann el	Frequency	Chann el	Frequency	Chann el	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	/
Lowest channel	2412MHz	/
Middle channel	2437MHz	/
Highest channel	2462MHz	/

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
-------------------	--



Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:


Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

Test Software	MobaXterm.exe
Power level setup	14

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Nov. 14, 2023	Nov. 13, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	C-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	C-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	C-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	EMI Test Receiver	R&S	ESC13	101393	4.42 SP3	Nov. 02, 2023	Nov. 01, 2024
7	Triple-Loop Antenna	N/A	RF300	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
8	Absorbing Clamp	DZ	ZN23201	15034	N/A	Nov. 07, 2023	Nov. 06, 2024
9	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESC17	101169	4.32	Nov. 02, 2023	Nov. 01, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	N/A	Nov. 13, 2023	Nov. 12, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Nov. 13, 2023	Nov. 12, 2024
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Nov. 13, 2023	Nov. 12, 2024
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Nov. 16, 2023	Nov. 15, 2024
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	N/A	Nov. 02, 2023	Nov. 01, 2024
9	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	N/A	Nov. 02, 2023	Nov. 01, 2024
10	Amplifier (18GHz -40GHz)	Tonscend	DLE-161	097	N/A	Nov. 02, 2023	Nov. 01, 2024
11	Test Cable	N/A	R-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
12	Test Cable	N/A	R-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
13	Test Cable	N/A	R-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
14	Test Cable	N/A	RF-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
15	Test Cable	N/A	RF-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024



16	Test Cable	N/A	RF-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
17	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Nov. 02, 2023	Nov. 01, 2024
18	Signal Generator	Agilent	N5182A	N/A	A.01.87	Nov. 02, 2023	Nov. 01, 2024
19	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Nov. 16, 2023	Nov. 15, 2024
20	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Nov. 02, 2023	Nov. 01, 2024
21	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
22	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
23	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
24	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\
25	Turntable	MF	MF-7802BS	N/A	N/A	\	\
26	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.



4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.4820	9.72	20.02	29.74	46.30	-16.56	AVG
2	0.5260	21.51	20.02	41.53	56.00	-14.47	QP
3	0.6020	21.91	20.04	41.95	56.00	-14.05	QP
4	0.6060	10.82	20.04	30.86	46.00	-15.14	AVG
5	0.6740	21.47	20.07	41.54	56.00	-14.46	QP
6	0.6740	11.32	20.07	31.39	46.00	-14.61	AVG
7	1.8060	13.97	19.99	33.96	56.00	-22.04	QP
8	1.8100	4.36	19.99	24.35	46.00	-21.65	AVG
9	20.1460	8.27	20.17	28.44	50.00	-21.56	AVG
10	20.9940	19.44	20.25	39.69	60.00	-20.31	QP
11	22.6620	8.85	20.42	29.27	50.00	-20.73	AVG
12	23.8900	17.70	20.55	38.25	60.00	-21.75	QP

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor



Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.4830	10.10	20.02	30.12	46.29	-16.17	AVG
2	0.5144	21.58	20.02	41.60	56.00	-14.40	QP
3	0.5955	22.57	20.05	42.62	56.00	-13.38	QP
4	0.6045	10.38	20.04	30.42	46.00	-15.58	AVG
5	0.7215	20.96	20.07	41.03	56.00	-14.97	QP
6	0.7260	9.86	20.07	29.93	46.00	-16.07	AVG
7	2.7735	6.30	19.99	26.29	46.00	-19.71	AVG
8	3.0120	16.43	19.98	36.41	56.00	-19.59	QP
9	4.1010	15.70	19.95	35.65	56.00	-20.35	QP
10	4.1010	4.97	19.95	24.92	46.00	-21.08	AVG
11	18.5820	7.92	20.12	28.04	50.00	-21.96	AVG
12	18.8970	16.63	20.12	36.75	60.00	-23.25	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation


4.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS


Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.




Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode	Working





Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode	Working



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case 802.11n20.

1GHz~25GHz
ANT1

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	52.38	30.55	5.77	24.66	52.26	74.00	-21.74	PK
V	4824.00	43.83	30.55	5.77	24.66	43.71	54.00	-10.29	AV
V	7236.00	51.73	30.33	6.32	24.55	52.27	74.00	-21.73	PK
V	7236.00	43.06	30.33	6.32	24.55	43.60	54.00	-10.40	AV
V	9648.00	49.67	30.85	7.45	24.69	50.96	74.00	-23.04	PK
V	9648.00	44.30	30.85	7.45	24.69	45.59	54.00	-8.41	AV
V	12060.00	52.60	31.02	8.99	25.57	56.14	74.00	-17.86	PK
V	12060.00	43.45	31.02	8.99	25.57	46.99	54.00	-7.01	AV
H	4824.00	50.52	30.55	5.77	24.66	50.40	74.00	-23.60	PK
H	4824.00	43.92	30.55	5.77	24.66	43.80	54.00	-10.20	AV
H	7236.00	53.42	30.33	6.32	24.55	53.96	74.00	-20.04	PK
H	7236.00	42.49	30.33	6.32	24.55	43.03	54.00	-10.97	AV
H	9648.00	51.42	30.85	7.45	24.69	52.71	74.00	-21.29	PK
H	9648.00	43.27	30.85	7.45	24.69	44.56	54.00	-9.44	AV
H	12060.00	51.46	31.02	8.99	25.57	55.00	74.00	-19.00	PK
H	12060.00	43.57	31.02	8.99	25.57	47.11	54.00	-6.89	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	53.11	30.55	5.77	24.66	52.99	74.00	-21.01	PK
V	4874.00	44.25	30.55	5.77	24.66	44.13	54.00	-9.87	AV
V	7311.00	52.58	30.33	6.32	24.55	53.12	74.00	-20.88	PK
V	7311.00	43.31	30.33	6.32	24.55	43.85	54.00	-10.15	AV
V	9748.00	51.12	30.85	7.45	24.69	52.41	74.00	-21.59	PK
V	9748.00	43.44	30.85	7.45	24.69	44.73	54.00	-9.27	AV
V	12185.00	53.18	31.02	8.99	25.57	56.72	74.00	-17.28	PK
V	12185.00	44.26	31.02	8.99	25.57	47.80	54.00	-6.20	AV
H	4874.00	51.79	30.55	5.77	24.66	51.67	74.00	-22.33	PK
H	4874.00	43.73	30.55	5.77	24.66	43.61	54.00	-10.39	AV
H	7311.00	49.76	30.33	6.32	24.55	50.30	74.00	-23.70	PK
H	7311.00	43.22	30.33	6.32	24.55	43.76	54.00	-10.24	AV
H	9748.00	51.67	30.85	7.45	24.69	52.96	74.00	-21.04	PK
H	9748.00	43.24	30.85	7.45	24.69	44.53	54.00	-9.47	AV
H	12185.00	52.12	31.02	8.99	25.57	55.66	74.00	-18.34	PK
H	12185.00	43.78	31.02	8.99	25.57	47.32	54.00	-6.68	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	51.69	30.55	5.77	24.66	51.57	74.00	-22.43	PK
V	4924.00	43.63	30.55	5.77	24.66	43.51	54.00	-10.49	AV
V	7386.00	52.53	30.33	6.32	24.55	53.07	74.00	-20.93	PK
V	7386.00	43.93	30.33	6.32	24.55	44.47	54.00	-9.53	AV
V	9848.00	50.69	30.85	7.45	24.69	51.98	74.00	-22.02	PK
V	9848.00	43.01	30.85	7.45	24.69	44.30	54.00	-9.70	AV
V	12310.00	52.30	31.02	8.99	25.57	55.84	74.00	-18.16	PK
V	12310.00	42.99	31.02	8.99	25.57	46.53	54.00	-7.47	AV
H	4924.00	54.73	30.55	5.77	24.66	54.61	74.00	-19.39	PK
H	4924.00	44.07	30.55	5.77	24.66	43.95	54.00	-10.05	AV
H	7386.00	52.99	30.33	6.32	24.55	53.53	74.00	-20.47	PK
H	7386.00	43.38	30.33	6.32	24.55	43.92	54.00	-10.08	AV
H	9848.00	49.69	30.85	7.45	24.69	50.98	74.00	-23.02	PK
H	9848.00	43.53	30.85	7.45	24.69	44.82	54.00	-9.18	AV
H	12310.00	51.71	31.02	8.99	25.57	55.25	74.00	-18.75	PK
H	12310.00	43.33	31.02	8.99	25.57	46.87	54.00	-7.13	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. The test data shows only the worst case.



802.11g

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	50.79	30.55	5.77	24.66	50.67	74.00	-23.33	PK
V	4824.00	43.21	30.55	5.77	24.66	43.09	54.00	-10.91	AV
V	7236.00	52.33	30.33	6.32	24.55	52.87	74.00	-21.13	PK
V	7236.00	43.22	30.33	6.32	24.55	43.76	54.00	-10.24	AV
V	9648.00	53.84	30.85	7.45	24.69	55.13	74.00	-18.87	PK
V	9648.00	43.31	30.85	7.45	24.69	44.60	54.00	-9.40	AV
V	12060.00	50.65	31.02	8.99	25.57	54.19	74.00	-19.81	PK
V	12060.00	43.18	31.02	8.99	25.57	46.72	54.00	-7.28	AV
H	4824.00	51.17	30.55	5.77	24.66	51.05	74.00	-22.95	PK
H	4824.00	43.16	30.55	5.77	24.66	43.04	54.00	-10.96	AV
H	7236.00	52.03	30.33	6.32	24.55	52.57	74.00	-21.43	PK
H	7236.00	43.10	30.33	6.32	24.55	43.64	54.00	-10.36	AV
H	9648.00	53.03	30.85	7.45	24.69	54.32	74.00	-19.68	PK
H	9648.00	43.65	30.85	7.45	24.69	44.94	54.00	-9.06	AV
H	12060.00	53.69	31.02	8.99	25.57	57.23	74.00	-16.77	PK
H	12060.00	43.73	31.02	8.99	25.57	47.27	54.00	-6.73	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	51.93	30.55	5.77	24.66	51.81	74.00	-22.19	PK
V	4874.00	44.27	30.55	5.77	24.66	44.15	54.00	-9.85	AV
V	7311.00	51.73	30.33	6.32	24.55	52.27	74.00	-21.73	PK
V	7311.00	43.31	30.33	6.32	24.55	43.85	54.00	-10.15	AV
V	9748.00	50.80	30.85	7.45	24.69	52.09	74.00	-21.91	PK
V	9748.00	43.55	30.85	7.45	24.69	44.84	54.00	-9.16	AV
V	12185.00	54.94	31.02	8.99	25.57	58.48	74.00	-15.52	PK
V	12185.00	42.93	31.02	8.99	25.57	46.47	54.00	-7.53	AV
H	4874.00	54.46	30.55	5.77	24.66	54.34	74.00	-19.66	PK
H	4874.00	43.37	30.55	5.77	24.66	43.25	54.00	-10.75	AV
H	7311.00	51.65	30.33	6.32	24.55	52.19	74.00	-21.81	PK
H	7311.00	43.81	30.33	6.32	24.55	44.35	54.00	-9.65	AV
H	9748.00	52.58	30.85	7.45	24.69	53.87	74.00	-20.13	PK
H	9748.00	43.44	30.85	7.45	24.69	44.73	54.00	-9.27	AV
H	12185.00	54.64	31.02	8.99	25.57	58.18	74.00	-15.82	PK
H	12185.00	44.12	31.02	8.99	25.57	47.66	54.00	-6.34	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	52.33	30.55	5.77	24.66	52.21	74.00	-21.79	PK
V	4924.00	44.31	30.55	5.77	24.66	44.19	54.00	-9.81	AV
V	7386.00	52.97	30.33	6.32	24.55	53.51	74.00	-20.49	PK
V	7386.00	43.34	30.33	6.32	24.55	43.88	54.00	-10.12	AV
V	9848.00	52.10	30.85	7.45	24.69	53.39	74.00	-20.61	PK
V	9848.00	43.89	30.85	7.45	24.69	45.18	54.00	-8.82	AV
V	12310.00	51.27	31.02	8.99	25.57	54.81	74.00	-19.19	PK
V	12310.00	43.16	31.02	8.99	25.57	46.70	54.00	-7.30	AV
H	4924.00	51.52	30.55	5.77	24.66	51.40	74.00	-22.60	PK
H	4924.00	43.26	30.55	5.77	24.66	43.14	54.00	-10.86	AV
H	7386.00	50.20	30.33	6.32	24.55	50.74	74.00	-23.26	PK
H	7386.00	43.21	30.33	6.32	24.55	43.75	54.00	-10.25	AV
H	9848.00	54.59	30.85	7.45	24.69	55.88	74.00	-18.12	PK
H	9848.00	43.80	30.85	7.45	24.69	45.09	54.00	-8.91	AV
H	12310.00	53.30	31.02	8.99	25.57	56.84	74.00	-17.16	PK
H	12310.00	43.16	31.02	8.99	25.57	46.70	54.00	-7.30	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.

1GHz~25GHz
ANT2

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	52.32	30.55	5.77	24.66	52.20	74.00	-21.80	PK
V	4824.00	43.95	30.55	5.77	24.66	43.83	54.00	-10.17	AV
V	7236.00	51.63	30.33	6.32	24.55	52.17	74.00	-21.83	PK
V	7236.00	43.29	30.33	6.32	24.55	43.83	54.00	-10.17	AV
V	9648.00	49.22	30.85	7.45	24.69	50.51	74.00	-23.49	PK
V	9648.00	44.30	30.85	7.45	24.69	45.59	54.00	-8.41	AV
V	12060.00	52.90	31.02	8.99	25.57	56.44	74.00	-17.56	PK
V	12060.00	43.94	31.02	8.99	25.57	47.48	54.00	-6.52	AV
H	4824.00	50.78	30.55	5.77	24.66	50.66	74.00	-23.34	PK
H	4824.00	43.92	30.55	5.77	24.66	43.80	54.00	-10.20	AV
H	7236.00	53.82	30.33	6.32	24.55	54.36	74.00	-19.64	PK
H	7236.00	42.95	30.33	6.32	24.55	43.49	54.00	-10.51	AV
H	9648.00	51.61	30.85	7.45	24.69	52.90	74.00	-21.10	PK
H	9648.00	43.52	30.85	7.45	24.69	44.81	54.00	-9.19	AV
H	12060.00	51.71	31.02	8.99	25.57	55.25	74.00	-18.75	PK
H	12060.00	43.33	31.02	8.99	25.57	46.87	54.00	-7.13	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	53.30	30.55	5.77	24.66	53.18	74.00	-20.82	PK
V	4874.00	44.20	30.55	5.77	24.66	44.08	54.00	-9.92	AV
V	7311.00	52.10	30.33	6.32	24.55	52.64	74.00	-21.36	PK
V	7311.00	42.98	30.33	6.32	24.55	43.52	54.00	-10.48	AV
V	9748.00	51.21	30.85	7.45	24.69	52.50	74.00	-21.50	PK
V	9748.00	43.34	30.85	7.45	24.69	44.63	54.00	-9.37	AV
V	12185.00	53.66	31.02	8.99	25.57	57.20	74.00	-16.80	PK
V	12185.00	44.41	31.02	8.99	25.57	47.95	54.00	-6.05	AV
H	4874.00	52.24	30.55	5.77	24.66	52.12	74.00	-21.88	PK
H	4874.00	43.54	30.55	5.77	24.66	43.42	54.00	-10.58	AV
H	7311.00	50.22	30.33	6.32	24.55	50.76	74.00	-23.24	PK
H	7311.00	43.36	30.33	6.32	24.55	43.90	54.00	-10.10	AV
H	9748.00	51.91	30.85	7.45	24.69	53.20	74.00	-20.80	PK
H	9748.00	42.82	30.85	7.45	24.69	44.11	54.00	-9.89	AV
H	12185.00	52.36	31.02	8.99	25.57	55.90	74.00	-18.10	PK
H	12185.00	43.49	31.02	8.99	25.57	47.03	54.00	-6.97	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	51.44	30.55	5.77	24.66	51.32	74.00	-22.68	PK
V	4924.00	43.45	30.55	5.77	24.66	43.33	54.00	-10.67	AV
V	7386.00	52.04	30.33	6.32	24.55	52.58	74.00	-21.42	PK
V	7386.00	43.96	30.33	6.32	24.55	44.50	54.00	-9.50	AV
V	9848.00	50.62	30.85	7.45	24.69	51.91	74.00	-22.09	PK
V	9848.00	43.26	30.85	7.45	24.69	44.55	54.00	-9.45	AV
V	12310.00	51.95	31.02	8.99	25.57	55.49	74.00	-18.51	PK
V	12310.00	42.51	31.02	8.99	25.57	46.05	54.00	-7.95	AV
H	4924.00	54.95	30.55	5.77	24.66	54.83	74.00	-19.17	PK
H	4924.00	44.32	30.55	5.77	24.66	44.20	54.00	-9.80	AV
H	7386.00	52.71	30.33	6.32	24.55	53.25	74.00	-20.75	PK
H	7386.00	43.85	30.33	6.32	24.55	44.39	54.00	-9.61	AV
H	9848.00	49.89	30.85	7.45	24.69	51.18	74.00	-22.82	PK
H	9848.00	43.61	30.85	7.45	24.69	44.90	54.00	-9.10	AV
H	12310.00	51.69	31.02	8.99	25.57	55.23	74.00	-18.77	PK
H	12310.00	42.87	31.02	8.99	25.57	46.41	54.00	-7.59	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. The test data shows only the worst case.



802.11g

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	50.33	30.55	5.77	24.66	50.21	74.00	-23.79	PK
V	4824.00	43.08	30.55	5.77	24.66	42.96	54.00	-11.04	AV
V	7236.00	52.17	30.33	6.32	24.55	52.71	74.00	-21.29	PK
V	7236.00	43.66	30.33	6.32	24.55	44.20	54.00	-9.80	AV
V	9648.00	53.60	30.85	7.45	24.69	54.89	74.00	-19.11	PK
V	9648.00	43.52	30.85	7.45	24.69	44.81	54.00	-9.19	AV
V	12060.00	50.92	31.02	8.99	25.57	54.46	74.00	-19.54	PK
V	12060.00	43.14	31.02	8.99	25.57	46.68	54.00	-7.32	AV
H	4824.00	50.83	30.55	5.77	24.66	50.71	74.00	-23.29	PK
H	4824.00	43.65	30.55	5.77	24.66	43.53	54.00	-10.47	AV
H	7236.00	51.76	30.33	6.32	24.55	52.30	74.00	-21.70	PK
H	7236.00	43.13	30.33	6.32	24.55	43.67	54.00	-10.33	AV
H	9648.00	53.16	30.85	7.45	24.69	54.45	74.00	-19.55	PK
H	9648.00	44.03	30.85	7.45	24.69	45.32	54.00	-8.68	AV
H	12060.00	53.49	31.02	8.99	25.57	57.03	74.00	-16.97	PK
H	12060.00	44.20	31.02	8.99	25.57	47.74	54.00	-6.26	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	51.84	30.55	5.77	24.66	51.72	74.00	-22.28	PK
V	4874.00	44.32	30.55	5.77	24.66	44.20	54.00	-9.80	AV
V	7311.00	51.32	30.33	6.32	24.55	51.86	74.00	-22.14	PK
V	7311.00	43.23	30.33	6.32	24.55	43.77	54.00	-10.23	AV
V	9748.00	50.39	30.85	7.45	24.69	51.68	74.00	-22.32	PK
V	9748.00	43.21	30.85	7.45	24.69	44.50	54.00	-9.50	AV
V	12185.00	54.80	31.02	8.99	25.57	58.34	74.00	-15.66	PK
V	12185.00	42.58	31.02	8.99	25.57	46.12	54.00	-7.88	AV
H	4874.00	54.95	30.55	5.77	24.66	54.83	74.00	-19.17	PK
H	4874.00	43.57	30.55	5.77	24.66	43.45	54.00	-10.55	AV
H	7311.00	51.86	30.33	6.32	24.55	52.40	74.00	-21.60	PK
H	7311.00	43.38	30.33	6.32	24.55	43.92	54.00	-10.08	AV
H	9748.00	52.28	30.85	7.45	24.69	53.57	74.00	-20.43	PK
H	9748.00	43.77	30.85	7.45	24.69	45.06	54.00	-8.94	AV
H	12185.00	54.32	31.02	8.99	25.57	57.86	74.00	-16.14	PK
H	12185.00	44.02	31.02	8.99	25.57	47.56	54.00	-6.44	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	52.81	30.55	5.77	24.66	52.69	74.00	-21.31	PK
V	4924.00	43.89	30.55	5.77	24.66	43.77	54.00	-10.23	AV
V	7386.00	53.17	30.33	6.32	24.55	53.71	74.00	-20.29	PK
V	7386.00	43.55	30.33	6.32	24.55	44.09	54.00	-9.91	AV
V	9848.00	52.17	30.85	7.45	24.69	53.46	74.00	-20.54	PK
V	9848.00	43.45	30.85	7.45	24.69	44.74	54.00	-9.26	AV
V	12310.00	51.10	31.02	8.99	25.57	54.64	74.00	-19.36	PK
V	12310.00	43.43	31.02	8.99	25.57	46.97	54.00	-7.03	AV
H	4924.00	51.39	30.55	5.77	24.66	51.27	74.00	-22.73	PK
H	4924.00	43.37	30.55	5.77	24.66	43.25	54.00	-10.75	AV
H	7386.00	50.62	30.33	6.32	24.55	51.16	74.00	-22.84	PK
H	7386.00	43.54	30.33	6.32	24.55	44.08	54.00	-9.92	AV
H	9848.00	54.40	30.85	7.45	24.69	55.69	74.00	-18.31	PK
H	9848.00	43.83	30.85	7.45	24.69	45.12	54.00	-8.88	AV
H	12310.00	53.13	31.02	8.99	25.57	56.67	74.00	-17.33	PK
H	12310.00	43.12	31.02	8.99	25.57	46.66	54.00	-7.34	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.



802.11n20 (ANT1+ANT2)

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	54.23	30.55	5.77	24.66	54.11	74.00	-19.89	PK
V	4824.00	43.01	30.55	5.77	24.66	42.89	54.00	-11.11	AV
V	7236.00	50.55	30.33	6.32	24.55	51.09	74.00	-22.91	PK
V	7236.00	43.69	30.33	6.32	24.55	44.23	54.00	-9.77	AV
V	9648.00	50.57	30.85	7.45	24.69	51.86	74.00	-22.14	PK
V	9648.00	44.45	30.85	7.45	24.69	45.74	54.00	-8.26	AV
V	12060.00	53.33	31.02	8.99	25.57	56.87	74.00	-17.13	PK
V	12060.00	43.23	31.02	8.99	25.57	46.77	54.00	-7.23	AV
H	4824.00	50.26	30.55	5.77	24.66	50.14	74.00	-23.86	PK
H	4824.00	42.67	30.55	5.77	24.66	42.55	54.00	-11.45	AV
H	7236.00	52.73	30.33	6.32	24.55	53.27	74.00	-20.73	PK
H	7236.00	43.54	30.33	6.32	24.55	44.08	54.00	-9.92	AV
H	9648.00	52.20	30.85	7.45	24.69	53.49	74.00	-20.51	PK
H	9648.00	42.94	30.85	7.45	24.69	44.23	54.00	-9.77	AV
H	12060.00	52.34	31.02	8.99	25.57	55.88	74.00	-18.12	PK
H	12060.00	43.61	31.02	8.99	25.57	47.15	54.00	-6.85	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	51.63	30.55	5.77	24.66	51.51	74.00	-22.49	PK
V	4874.00	43.45	30.55	5.77	24.66	43.33	54.00	-10.67	AV
V	7311.00	52.79	30.33	6.32	24.55	53.33	74.00	-20.67	PK
V	7311.00	44.12	30.33	6.32	24.55	44.66	54.00	-9.34	AV
V	9748.00	51.22	30.85	7.45	24.69	52.51	74.00	-21.49	PK
V	9748.00	42.19	30.85	7.45	24.69	43.48	54.00	-10.52	AV
V	12185.00	52.42	31.02	8.99	25.57	55.96	74.00	-18.04	PK
V	12185.00	42.99	31.02	8.99	25.57	46.53	54.00	-7.47	AV
H	4874.00	51.61	30.55	5.77	24.66	51.49	74.00	-22.51	PK
H	4874.00	43.16	30.55	5.77	24.66	43.04	54.00	-10.96	AV
H	7311.00	53.92	30.33	6.32	24.55	54.46	74.00	-19.54	PK
H	7311.00	44.20	30.33	6.32	24.55	44.74	54.00	-9.26	AV
H	9748.00	50.00	30.85	7.45	24.69	51.29	74.00	-22.71	PK
H	9748.00	44.68	30.85	7.45	24.69	45.97	54.00	-8.03	AV
H	12185.00	53.84	31.02	8.99	25.57	57.38	74.00	-16.62	PK
H	12185.00	43.31	31.02	8.99	25.57	46.85	54.00	-7.15	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	52.71	30.55	5.77	24.66	52.59	74.00	-21.41	PK
V	4924.00	42.14	30.55	5.77	24.66	42.02	54.00	-11.98	AV
V	7386.00	52.76	30.33	6.32	24.55	53.30	74.00	-20.70	PK
V	7386.00	43.68	30.33	6.32	24.55	44.22	54.00	-9.78	AV
V	9848.00	54.89	30.85	7.45	24.69	56.18	74.00	-17.82	PK
V	9848.00	43.79	30.85	7.45	24.69	45.08	54.00	-8.92	AV
V	12310.00	51.59	31.02	8.99	25.57	55.13	74.00	-18.87	PK
V	12310.00	44.09	31.02	8.99	25.57	47.63	54.00	-6.37	AV
H	4924.00	53.09	30.55	5.77	24.66	52.97	74.00	-21.03	PK
H	4924.00	44.33	30.55	5.77	24.66	44.21	54.00	-9.79	AV
H	7386.00	49.55	30.33	6.32	24.55	50.09	74.00	-23.91	PK
H	7386.00	43.01	30.33	6.32	24.55	43.55	54.00	-10.45	AV
H	9848.00	52.49	30.85	7.45	24.69	53.78	74.00	-20.22	PK
H	9848.00	43.88	30.85	7.45	24.69	45.17	54.00	-8.83	AV
H	12310.00	53.39	31.02	8.99	25.57	56.93	74.00	-17.07	PK
H	12310.00	42.24	31.02	8.99	25.57	45.78	54.00	-8.22	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


5.3 DEVIATION FROM TEST STANDARD

No deviation



5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

ANT1

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	54.24	30.22	4.85	23.98	52.85	74.00	PK	PASS
	H	2390.00	45.09	30.22	4.85	23.98	43.70	54.00	AV	PASS
	H	2400.00	54.93	30.22	4.85	23.98	53.54	74.00	PK	PASS
	H	2400.00	43.57	30.22	4.85	23.98	42.18	54.00	AV	PASS
	V	2390.00	54.05	30.22	4.85	23.98	52.66	74.00	PK	PASS
	V	2390.00	44.69	30.22	4.85	23.98	43.30	54.00	AV	PASS
	V	2400.00	53.46	30.22	4.85	23.98	52.85	74.00	PK	PASS
	V	2400.00	43.86	30.22	4.85	23.98	43.70	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.81	30.22	4.85	23.98	53.42	74.00	PK	PASS
	H	2483.50	43.80	30.22	4.85	23.98	42.41	54.00	AV	PASS
	H	2500.00	54.04	30.22	4.85	23.98	52.65	74.00	PK	PASS
	H	2500.00	44.65	30.22	4.85	23.98	43.26	54.00	AV	PASS
	V	2483.50	52.90	30.22	4.85	23.98	51.51	74.00	PK	PASS
	V	2483.50	44.55	30.22	4.85	23.98	43.16	54.00	AV	PASS
	V	2500.00	54.94	30.22	4.85	23.98	53.55	74.00	PK	PASS
	V	2500.00	44.06	30.22	4.85	23.98	42.67	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	54.14	30.22	4.85	23.98	52.75	74.00	PK	PASS
	H	2390.00	44.18	30.22	4.85	23.98	42.79	54.00	AV	PASS
	H	2400.00	54.53	30.22	4.85	23.98	53.14	74.00	PK	PASS
	H	2400.00	44.53	30.22	4.85	23.98	43.14	54.00	AV	PASS
	V	2390.00	53.23	30.22	4.85	23.98	51.84	74.00	PK	PASS
	V	2390.00	44.47	30.22	4.85	23.98	43.08	54.00	AV	PASS
	V	2400.00	54.53	30.22	4.85	23.98	53.14	74.00	PK	PASS
	V	2400.00	45.06	30.22	4.85	23.98	43.67	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.05	30.22	4.85	23.98	52.66	74.00	PK	PASS
	H	2483.50	44.66	30.22	4.85	23.98	43.27	54.00	AV	PASS
	H	2500.00	54.03	30.22	4.85	23.98	52.64	74.00	PK	PASS
	H	2500.00	44.79	30.22	4.85	23.98	43.40	54.00	AV	PASS
	V	2483.50	54.71	30.22	4.85	23.98	53.32	74.00	PK	PASS
	V	2483.50	44.28	30.22	4.85	23.98	42.89	54.00	AV	PASS
	V	2500.00	53.32	30.22	4.85	23.98	51.93	74.00	PK	PASS
	V	2500.00	44.20	30.22	4.85	23.98	42.81	54.00	AV	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limi										



ANT2

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	53.91	30.22	4.85	23.98	52.52	74.00	PK	PASS
	H	2390.00	44.72	30.22	4.85	23.98	43.33	54.00	AV	PASS
	H	2400.00	54.50	30.22	4.85	23.98	53.11	74.00	PK	PASS
	H	2400.00	43.87	30.22	4.85	23.98	42.48	54.00	AV	PASS
	V	2390.00	54.13	30.22	4.85	23.98	52.74	74.00	PK	PASS
	V	2390.00	44.64	30.22	4.85	23.98	43.25	54.00	AV	PASS
	V	2400.00	53.01	30.22	4.85	23.98	51.62	74.00	PK	PASS
	V	2400.00	44.02	30.22	4.85	23.98	42.63	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.55	30.22	4.85	23.98	53.16	74.00	PK	PASS
	H	2483.50	43.36	30.22	4.85	23.98	41.97	54.00	AV	PASS
	H	2500.00	53.73	30.22	4.85	23.98	52.34	74.00	PK	PASS
	H	2500.00	44.72	30.22	4.85	23.98	43.33	54.00	AV	PASS
	V	2483.50	52.57	30.22	4.85	23.98	51.18	74.00	PK	PASS
	V	2483.50	44.69	30.22	4.85	23.98	43.30	54.00	AV	PASS
	V	2500.00	55.17	30.22	4.85	23.98	53.78	74.00	PK	PASS
	V	2500.00	44.56	30.22	4.85	23.98	43.17	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	54.50	30.22	4.85	23.98	53.11	74.00	PK	PASS
	H	2390.00	44.21	30.22	4.85	23.98	42.82	54.00	AV	PASS
	H	2400.00	54.78	30.22	4.85	23.98	53.39	74.00	PK	PASS
	H	2400.00	44.40	30.22	4.85	23.98	43.01	54.00	AV	PASS
	V	2390.00	52.99	30.22	4.85	23.98	51.60	74.00	PK	PASS
	V	2390.00	44.29	30.22	4.85	23.98	42.90	54.00	AV	PASS
	V	2400.00	54.12	30.22	4.85	23.98	52.73	74.00	PK	PASS
	V	2400.00	45.20	30.22	4.85	23.98	43.81	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	53.69	30.22	4.85	23.98	52.30	74.00	PK	PASS
	H	2483.50	44.22	30.22	4.85	23.98	42.83	54.00	AV	PASS
	H	2500.00	53.88	30.22	4.85	23.98	52.49	74.00	PK	PASS
	H	2500.00	44.53	30.22	4.85	23.98	43.14	54.00	AV	PASS
	V	2483.50	54.31	30.22	4.85	23.98	52.92	74.00	PK	PASS
	V	2483.50	44.07	30.22	4.85	23.98	42.68	54.00	AV	PASS
	V	2500.00	53.42	30.22	4.85	23.98	52.03	74.00	PK	PASS
	V	2500.00	44.06	30.22	4.85	23.98	42.67	54.00	AV	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limi										



802.11n20 (MIMO)

802.11n20	Low Channel 2412MHz									
	H	2390.00	53.67	30.22	4.85	23.98	52.28	74.00	PK	PASS
	H	2390.00	45.35	30.22	4.85	23.98	43.96	54.00	AV	PASS
	H	2400.00	54.26	30.22	4.85	23.98	52.87	74.00	PK	PASS
	H	2400.00	44.84	30.22	4.85	23.98	43.45	54.00	AV	PASS
	V	2390.00	53.51	30.22	4.85	23.98	52.12	74.00	PK	PASS
	V	2390.00	45.04	30.22	4.85	23.98	43.65	54.00	AV	PASS
	V	2400.00	54.08	30.22	4.85	23.98	52.69	74.00	PK	PASS
	V	2400.00	44.04	30.22	4.85	23.98	42.65	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	52.88	30.22	4.85	23.98	51.49	74.00	PK	PASS
	H	2483.50	44.86	30.22	4.85	23.98	43.47	54.00	AV	PASS
	H	2500.00	53.45	30.22	4.85	23.98	52.06	74.00	PK	PASS
	H	2500.00	44.60	30.22	4.85	23.98	43.21	54.00	AV	PASS
	V	2483.50	53.16	30.22	4.85	23.98	51.77	74.00	PK	PASS
	V	2483.50	44.59	30.22	4.85	23.98	43.20	54.00	AV	PASS
	V	2500.00	53.51	30.22	4.85	23.98	52.12	74.00	PK	PASS
	V	2500.00	44.12	30.22	4.85	23.98	42.73	54.00	AV	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										



6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS


6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode		

TestMode	Antenna	Frequency[MHz]	Result [dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-8.3	≤8.00	PASS
	Ant2	2412	-8.62	≤8.00	PASS
	Ant1	2437	-9.15	≤8.00	PASS
	Ant2	2437	-8.8	≤8.00	PASS
	Ant1	2462	-8.36	≤8.00	PASS
	Ant2	2462	-6.82	≤8.00	PASS
11G	Ant1	2412	-11.26	≤8.00	PASS
	Ant2	2412	-11.95	≤8.00	PASS
	Ant1	2437	-12.18	≤8.00	PASS
	Ant2	2437	-11.3	≤8.00	PASS
	Ant1	2462	-11.53	≤8.00	PASS
	Ant2	2462	-11.73	≤8.00	PASS
11N20MIMO	Ant1	2412	-11.21	≤8.00	PASS
	Ant2	2412	-10.76	≤8.00	PASS
	total	2412	-7.97	≤7.49	PASS
	Ant1	2437	-11.41	≤8.00	PASS
	Ant2	2437	-11.25	≤8.00	PASS
	total	2437	-8.32	≤7.49	PASS
	Ant1	2462	-11.47	≤8.00	PASS
	Ant2	2462	-11.62	≤8.00	PASS
	total	2462	-8.53	≤7.49	PASS

Remark:

Directional gain = GANT + Array Gain=3.5 dBi+3.01 dBi =6.51 dBi;

Array Gain = 10 log(NANT/NSS) dB (NANT=2;NSS=1)

Limit[dBm/3kHz]=8.00- (Directional gain -6dB) when Directional gain ≥6dB



TEST GRAPHS

11B_Ant1_2412



11B_Ant2_2412



11B_Ant1_2437



11B_Ant2_2437




11B Ant1 2462




11B Ant2 2462




11G Ant1 2412




11G_Ant2_2412




11G_Ant1_2437




11G_Ant2_2437




11G_Ant1_2462



11G_Ant2_2462



11N20MIMO_Ant1_2412




11N20MIMO_Ant2_2412




11N20MIMO_Ant1_2437



11N20MIMO_Ant2_2437



11N20MIMO_Ant1_2462



11N20MIMO_Ant2_2462





7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode		

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	-6dB Occupy Bandwidth [MHz]
11B	Ant1	2412	11.899	8.078
	Ant2	2412	12.013	7.109
	Ant1	2437	11.954	7.091
	Ant2	2437	12.036	7.159
	Ant1	2462	11.938	7.108
	Ant2	2462	12.032	7.124
11G	Ant1	2412	16.461	16.37
	Ant2	2412	16.484	16.39
	Ant1	2437	16.471	16.37
	Ant2	2437	16.468	16.39
	Ant1	2462	16.463	16.41
	Ant2	2462	16.471	16.37
11N20MIMO	Ant1	2412	17.656	17.56
	Ant2	2412	17.520	16.00
	Ant1	2437	17.657	17.58
	Ant2	2437	17.515	15.13
	Ant1	2462	17.652	17.33
	Ant2	2462	17.495	15.17



Test plot as follows:





11B Ant2 2437



11B Ant1 2462



11B Ant2 2462



11G_Ant1_2412



11G_Ant2_2412



11G_Ant1_2437



11G_Ant2_2437



11G_Ant1_2462



11G_Ant2_2462



11N20MIMO_Ant1_2412



11N20MIMO_Ant2_2412



11N20MIMO_Ant1_2437



11N20MIMO_Ant2_2437



11N20MIMO_Ant1_2462



11N20MIMO_Ant2_2462





8. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



8.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz

Test Mode	Antenna	Frequency [MHz]	Peak Power [dBm]	Result [dBm]	Limit [dBm]	Eirp [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	14.84	14.84	≤30.00	18.34	≤36.00	PASS
	Ant2	2412	14.66	14.66	≤30.00	18.16	≤36.00	PASS
	Ant1	2437	14.39	14.39	≤30.00	17.89	≤36.00	PASS
	Ant2	2437	14.60	14.60	≤30.00	18.10	≤36.00	PASS
	Ant1	2462	14.57	14.57	≤30.00	18.07	≤36.00	PASS
	Ant2	2462	14.94	14.94	≤30.00	18.44	≤36.00	PASS
11G	Ant1	2412	19.57	19.57	≤30.00	23.07	≤36.00	PASS
	Ant2	2412	19.18	19.18	≤30.00	22.68	≤36.00	PASS
	Ant1	2437	19.03	19.03	≤30.00	22.53	≤36.00	PASS
	Ant2	2437	19.22	19.22	≤30.00	22.72	≤36.00	PASS
	Ant1	2462	19.02	19.02	≤30.00	22.52	≤36.00	PASS
	Ant2	2462	19.24	19.24	≤30.00	22.74	≤36.00	PASS
11N20MI MO	Ant1	2412	17.61	17.61	≤30.00	21.11	≤36.00	PASS
	Ant2	2412	11.98	11.98	≤30.00	15.48	≤36.00	PASS
	total	2412	---	18.66	≤30.00	22.16	≤35.49	PASS
	Ant1	2437	17.28	17.28	≤30.00	20.78	≤36.00	PASS
	Ant2	2437	12.40	12.40	≤30.00	15.90	≤36.00	PASS
	total	2437	---	18.50	≤30.00	22.00	≤35.49	PASS
	Ant1	2462	17.26	17.26	≤30.00	20.76	≤36.00	PASS
	Ant2	2462	13.72	13.72	≤30.00	17.22	≤36.00	PASS
	total	2462	---	18.85	≤30.00	22.35	≤35.49	PASS

Remark: The results obtained include the antenna gain factor.

Directional gain = GANT + Array Gain=3.5 dBi+0 dBi =3.5 dBi;

Array Gain = 0 dB (i.e., no array gain) for NANT ≤4; (NANT=2)



9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP




9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS




Test plot as follows:





11B_Ant2_High_2462




11G_Ant1_Low_2412



11G_Ant2_Low_2412



11G_Ant1_High_2462



11G_Ant2_High_2462




11N20MIMO_Ant1_Low_2412



11N20MIMO_Ant2_Low_2412



11N20MIMO Ant1 High 2462




11N20MIMO Ant2 High 2462





Test plot as follows:





11B_Ant2_2412_0-Reference



11B_Ant2_2412_30-1000



11B_Ant2_2412_1000-26500



11B_Ant1_2437_0-Reference



11B_Ant1_2437_30-1000



11B_Ant1_2437_1000-26500




11B_Ant2_2437_0-Reference



11B_Ant2_2437_30-1000



11B_Ant2_2437_1000-26500




11B_Ant1_2462_0-Reference



11B_Ant1_2462_30-1000



11B_Ant1_2462_1000-26500



11B_Ant2_2462_0-Reference



11B_Ant2_2462_30-1000



11B_Ant2_2462_1000-26500




11G_Ant1_2412_0-Reference



11G_Ant1_2412_30~1000




11G_Ant1_2412_1000~26500




11G_Ant2_2412_0-Reference



11G_Ant2_2412_30~1000



11G_Ant2_2412_1000~26500




11G_Ant1_2437_0~Reference



11G_Ant1_2437_30~1000



11G_Ant1_2437_1000~26500




11G_Ant2_2437_0-Reference



11G_Ant2_2437_30~1000



11G_Ant2_2437_1000~26500




11G_Ant1_2462_0-Reference



11G_Ant1_2462_30-1000



11G_Ant1_2462_1000-26500




11G_Ant2_2462_0-Reference



11G_Ant2_2462_30~1000



11G_Ant2_2462_1000~26500




11N20MIMO_Ant1_2412_0-Reference



11N20MIMO_Ant1_2412_30-1000



11N20MIMO_Ant1_2412_1000-26500



11N20MIMO_Ant2_2412_0-Reference



11N20MIMO_Ant2_2412_30-1000



11N20MIMO_Ant2_2412_1000-26500




11N20MIMO_Ant1_2437_0-Reference



11N20MIMO_Ant1_2437_30-1000




11N20MIMO_Ant1_2437_1000-26500




11N20MIMO_Ant2_2437_0-Reference



11N20MIMO_Ant2_2437_30-1000



11N20MIMO_Ant2_2437_1000-26500



11N20MIMO_Ant1_2462_0-Reference



11N20MIMO_Ant1_2462_30-1000



11N20MIMO_Ant1_2462_1000-26500



11N20MIMO_Ant2_2462_0-Reference



11N20MIMO_Ant2_2462_30-1000



11N20MIMO_Ant2_2462_1000-26500





10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. A transmitter can only be sold or operated with antennas with which it was approved.	
EUT Antenna:	
The antenna is FPC Antenna, the best case gain of the antenna is 3.5dBi, reference to the appendix II for details	



11. TEST SETUP PHOTO

Reference to the appendix I for details.

12. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****