

< Appendix >

1. Features

General	• Connection with normal telephone • Line interface capability : 2 wire • 3 LED (Power, Battery, Service) • Wall Mountable
Local Tone	• Dial tone • Busy tone • Warning Tone
Hook Flash Operation	• Last Number Redial • End of Digit
User Control	• Received Volume Control : Sstep • Dial Tie Control : 4s ~ 8s • Hook Flash Time(Click Time) Control

2. Technical Specification

Air Interface	- Common air interface standard: IS-95A - Frequency: TX: 824 - 849MHz RX: 869 - 894MHz - TX Output Power: 320mW(25.08dBm) - RX Sensitivity: 104dBm - Vocoder: 8K/13K QCELP 8K EVRC - Channel Bandwidth: CDMA 1.25MHz - Spurious: TX Freq. Band: -61dBm below RX Freq. Band: -81dBm below - MOD/DEMOD: GQPSWQPSK - Frequency Accuracy: Fof300Hz
Battery Back-up	- Type: Ni-Cd - Capacity: 8.4@1.7A - Talk Time: 2 Hours - Standby Time: 20Hours
Connectors for Various Service Support	- RJ-11: standard wire-line telephone : Analog G3 Fax (Optional) - Serial port : Maintenance Purpose : Data Service Purpose (Internet, PC Fax)
Physical	- Dimension (DxWxH) : 226x166x65mm - Weight (including Backup battery): 995g
Environmental	- Operating temperature: -10°C ~ +50°C
Power Supply	- Input Power : 110V ~ 240V(*20)AC, 50/60Hz - Output Power: DC 12V@2A
Accessories	- Power Supply