

Safety Human Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields

RESULT:

Pass

Report No.	: CN23LRWL 004
Test Specification	
Test item	: Typhur Wireless Thermometer
Identification / Type No.	: WT03
FCC ID	: 2A6RN-WTP1000
IC	: 28517-WTP1000
HVIN	: WT03
Test standard	: CFR47 FCC Part 2: Section 2.1093 FCC KDB Publication 447498 v06 RSS-102 Issue 5 February 2021

Measurement Record:

The minimum distance for the EUT is less than 5mm.

For FCC:

Since maximum average output power of the transmitter is 5.90 dBm ≈ 3.89 mW $< \frac{3 \cdot d}{\sqrt{f}} = 9.52$ mW.

Hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01 General RF Exposure Guidance v06.

For IC:

The higher of the maximum e.i.r.p. or conducted power of the transmitter is 5.90 dBm ≈ 3.89 mW, which is below the SAR exclusion threshold level 4 mW ≈ 6.02 dBm.

Hence the EUT is exempted from routine evaluation limits (SAR Evaluation) according to clause 2.5.1 of RSS-102 Issue 5.