




FCC PART 15.247 TEST REPORT

For

Sky Phone LLC

1348 Washington Av.Suite 350 Miami Beach, FL, United States 33139

FCC ID: 2ABOSSKYFUEPLA70

Report Type: Original Report	Product Name: Tablet PC
Test Engineer: <u>Lorin Bian</u>	
Report Number: <u>RDG161025004C</u>	
Report Date: <u>2016-11-25</u>	
Reviewed By: <u>Henry Ding</u> EMC Leader	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65525123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
EXTERNAL CABLE	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	11
APPLICABLE STANDARD	11
FCC §15.203 - ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	13
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST EQUIPMENT LIST AND DETAILS	14
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS	19
TEST DATA	19
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST EQUIPMENT LIST AND DETAILS	23
TEST DATA	23
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST EQUIPMENT LIST AND DETAILS	29
TEST DATA	29
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	31

APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS	31
TEST DATA.....	32
FCC §15.247(e) - POWER SPECTRAL DENSITY	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST EQUIPMENT LIST AND DETAILS	36
TEST DATA.....	36

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Sky Phone LLC** 's product, model number: **Platinum 7.0+(FCC ID: 2ABOSSKYFUEPLA70)** (the "EUT") in this report was a **Tablet PC**, which was measured approximately: 18.7 cm (L) × 10.8 cm (W) × 1.2 cm (H), rated input voltage: DC3.7V battery or DC5V from adapter.

Adapter information:

MODEL: JK050100-S02USU

INPUT: 100-240V~ 50/60Hz 0.3A Max

OUTPUT: DC5V, 1000mA

Note: The series product, model Platinum 7.0+ and YS7 are electrically identical, the differences between them are the model name and color, we selected Platinum 7.0+ for fully testing, the details was explained in the attached declaration letter.

**All measurement and test data in this report was gathered from final production sample, serial number: 161025004 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2016-10-25, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Sky Phone LLC** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ABOSSKYFUEPLA70.

FCC Part 15C DSS submissions with FCC ID: 2ABOSSKYFUEPLA70.

FCC Part 22H, 24E PCE submissions with FCC ID: 2ABOSSKYFUEPLA70.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All of the measurements detailed in this Test Report were performed by Bay Area Compliance Laboratories Corp. (Chengdu).

The Bay Area Compliance Laboratories Corp. Chengdu's measurement Uncertainties (calculated for a k=2 Coverage Factor corresponding to approximately 95% Coverage) were as follows:

-For all of the AC Line Conducted Emissions Tests reported herein: ± 3.17 dB.

-For of all of the Direct Antenna Conducted Emissions Tests reported herein: ± 0.56 dB.

-For of all of the direct Radiated Emissions Tests reported herein are:

30 MHz to 200 MHz: ± 4.7 dB;

200 MHz to 1 GHz: ± 6.0 dB;

1 GHz to 6 GHz: ± 5.13 dB; and,

6 GHz to 40 GHz: ± 5.47 dB.

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.

For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


The worst condition (maximum power) was setting by the engineering mode as following table:

Test Mode	Test Software Version	Engineer Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	53	51	51
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	96	92	92
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	108	105	105

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100%
802.11g	100	100	100%
802.11n ht20	100	100	100%

802.11b




Date: 15.NOV.2016 14:29:20

802.11g



Date: 15.NOV.2016 14:29:56

802.11n ht20




Date: 15.NOV.2016 14:30:19

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	1.0	USB Port of Adater	EUT
Earphone Cable	No	No	1.2	Audio Port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For WiFi mode

The max tune-up conducted power is 9.8 dBm (9.55 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 9.55/5 \cdot (\sqrt{2.462}) = 3.0 \leq 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement for Wifi/BT, and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2015-12-02	2016-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2015-12-02	2016-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
Unknown	Conducted Cable	Unknown	NO.5	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

*** Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data


Environmental Conditions

Temperature:	24.1 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lorin Bian on 2016-11-12.

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
1.408664	47.2	9.000	L1	20.0	8.8	56.0	Compliance
2.059086	48.3	9.000	L1	20.1	7.7	56.0	Compliance
2.104842	46.1	9.000	L1	20.1	9.9	56.0	Compliance
2.164549	48.5	9.000	L1	20.1	7.5	56.0	Compliance
2.601345	49.5	9.000	L1	20.1	6.5	56.0	Compliance
2.653842	48.3	9.000	L1	20.1	7.7	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.486608	40.4	9.000	L1	19.9	5.8	46.2	Compliance
0.542046	43.5	9.000	L1	20.0	2.5	46.0	Compliance
1.191019	40.7	9.000	L1	20.0	5.3	46.0	Compliance
1.408664	40.2	9.000	L1	20.0	5.8	46.0	Compliance
2.059086	39.1	9.000	L1	20.1	6.9	46.0	Compliance
2.653842	39.5	9.000	L1	20.1	6.5	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.539885	45.4	9.000	N	19.9	10.6	56.0	Compliance
1.348086	43.7	9.000	N	20.0	12.3	56.0	Compliance
2.100640	40.9	9.000	N	20.1	15.1	56.0	Compliance
2.155917	42.0	9.000	N	20.1	14.0	56.0	Compliance
2.590970	43.0	9.000	N	20.1	13.0	56.0	Compliance
2.691220	39.6	9.000	N	20.1	16.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.484668	38.4	9.000	N	19.9	7.9	46.3	Compliance
0.538807	40.0	9.000	N	19.9	6.0	46.0	Compliance
0.971429	36.7	9.000	N	19.9	9.3	46.0	Compliance
1.130728	34.6	9.000	N	20.0	11.4	46.0	Compliance
1.186269	35.9	9.000	N	20.0	10.1	46.0	Compliance
1.348086	36.8	9.000	N	20.0	9.2	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Detector	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Detector	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2015-12-02	2016-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2015-12-02	2016-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2015-12-02	2016-12-01
ETS	Horn Antenna	3115	003-6076	2015-12-02	2016-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2015-12-02	2016-12-01
EMCT	Semi-Anechoic Chamber	966	966-1	2015-04-24	2018-04-23
Unknown	RF Cable (below 1GHz)	Unknown	NO.1	2015-11-10	2016-11-09
Unknown	RF Cable (below 1GHz)	Unknown	NO.4	2015-11-10	2016-11-09
Unknown	RF Cable (above 1GHz)	Unknown	NO.2	2015-11-10	2016-11-09

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	38 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-11-08.

Test Mode: Transmitting

30MHz-25GHz:

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	65.83	PK	H	23.50	3.00	0.00	92.33	N/A	N/A
2412	61.08	AV	H	23.50	3.00	0.00	87.58	N/A	N/A
2412	67.17	PK	V	23.50	3.00	0.00	93.67	N/A	N/A
2412	62.53	AV	V	23.50	3.00	0.00	89.03	N/A	N/A
2390	34.35	PK	H	23.57	3.00	0.00	60.92	74.00	13.08
2390	23.02	AV	H	23.57	3.00	0.00	49.59	54.00	4.41
4824	41.5	PK	H	30.84	5.11	26.87	50.58	74.00	23.42
4824	38.95	AV	H	30.84	5.11	26.87	48.03	54.00	5.97
7236	33.32	PK	H	34.77	6.18	26.36	47.91	74.00	26.09
7236	21.01	AV	H	34.77	6.18	26.36	35.60	54.00	18.40
3539	38.74	PK	H	27.16	4.24	26.59	43.55	74.00	30.45
3539	25.96	AV	H	27.16	4.24	26.59	30.77	54.00	23.23
37.03	47.52	QP	V	17.70	0.39	28.53	37.08	40.00	2.92
47.21	53.61	QP	V	10.20	0.38	28.50	35.69	40.00	4.31
Middle Channel: 2437 MHz									
2437	65.41	PK	H	23.41	3.00	0.00	91.82	N/A	N/A
2437	60.94	AV	H	23.41	3.00	0.00	87.35	N/A	N/A
2437	66.8	PK	V	23.41	3.00	0.00	93.21	N/A	N/A
2437	62.21	AV	V	23.41	3.00	0.00	88.62	N/A	N/A
4874	41.36	PK	V	31.00	5.09	26.87	50.58	74.00	23.42
4874	38.78	AV	V	31.00	5.09	26.87	48.00	54.00	6.00
7311	33.17	PK	V	34.92	6.21	26.40	47.90	74.00	26.10
7311	20.88	AV	V	34.92	6.21	26.40	35.61	54.00	18.39
3539	38.64	PK	V	27.16	4.24	26.59	43.45	74.00	30.55
3539	26.05	AV	V	27.16	4.24	26.59	30.86	54.00	23.14
3490	36.93	PK	V	26.94	4.17	26.59	41.45	74.00	32.55
3490	24.32	AV	V	26.94	4.17	26.59	28.84	54.00	25.16
37.03	46.52	QP	V	17.70	0.39	28.53	36.08	40.00	3.92
47.21	52.33	QP	V	10.20	0.38	28.50	34.41	40.00	5.59
High Channel: 2462 MHz									
2462	64.95	PK	H	23.33	2.99	0.00	91.27	N/A	N/A
2462	60.51	AV	H	23.33	2.99	0.00	86.83	N/A	N/A
2462	66.28	PK	V	23.33	2.99	0.00	92.60	N/A	N/A
2462	61.82	AV	V	23.33	2.99	0.00	88.14	N/A	N/A
2483.5	34.42	PK	V	23.26	2.99	0.00	60.67	74.00	13.33
2483.5	24.36	AV	V	23.26	2.99	0.00	50.61	54.00	3.39
4924	41.47	PK	V	31.16	5.07	26.88	50.82	74.00	23.18
4924	38.16	AV	V	31.16	5.07	26.88	47.51	54.00	6.49
7386	32.69	PK	V	35.07	6.25	26.43	47.58	74.00	26.42
7386	20.54	AV	V	35.07	6.25	26.43	35.43	54.00	18.57
3539	38.45	PK	V	27.16	4.24	26.59	43.26	74.00	30.74
3539	25.78	AV	V	27.16	4.24	26.59	30.59	54.00	23.41
37.03	47.02	QP	V	17.70	0.39	28.53	36.58	40.00	3.42
47.21	52.18	QP	V	10.20	0.38	28.50	34.26	40.00	5.74

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	67.92	PK	H	23.50	3.00	0.00	94.42	N/A	N/A
2412	57.26	AV	H	23.50	3.00	0.00	83.76	N/A	N/A
2412	69.25	PK	V	23.50	3.00	0.00	95.75	N/A	N/A
2412	57.89	AV	V	23.50	3.00	0.00	84.39	N/A	N/A
2390	34.9	PK	V	23.57	3.00	0.00	61.47	74.00	12.53
2390	18.34	AV	V	23.57	3.00	0.00	44.91	54.00	9.09
4824	42.81	PK	V	30.84	5.11	26.87	51.89	74.00	22.11
4824	29.38	AV	V	30.84	5.11	26.87	38.46	54.00	15.54
7236	34.98	PK	V	34.77	6.18	26.36	49.57	74.00	24.43
7236	21.65	AV	V	34.77	6.18	26.36	36.24	54.00	17.76
3539	38.33	PK	V	27.16	4.24	26.59	43.14	74.00	30.86
3539	25.95	AV	V	27.16	4.24	26.59	30.76	54.00	23.24
37.03	48.25	QP	V	17.70	0.39	28.53	37.81	40.00	2.19
47.21	51.99	QP	V	10.20	0.38	28.50	34.07	40.00	5.93
Middle Channel: 2437 MHz									
2437	67.71	PK	H	23.41	3.00	0.00	94.12	N/A	N/A
2437	57.06	AV	H	23.41	3.00	0.00	83.47	N/A	N/A
2437	69.03	PK	V	23.41	3.00	0.00	95.44	N/A	N/A
2437	57.99	AV	V	23.41	3.00	0.00	84.40	N/A	N/A
4874	42.39	PK	V	31.00	5.09	26.87	51.61	74.00	22.39
4874	28.91	AV	V	31.00	5.09	26.87	38.13	54.00	15.87
7311	34.71	PK	V	34.92	6.21	26.40	49.44	74.00	24.56
7311	21.42	AV	V	34.92	6.21	26.40	36.15	54.00	17.85
3539	38.25	PK	V	27.16	4.24	26.59	43.06	74.00	30.94
3539	25.72	AV	V	27.16	4.24	26.59	30.53	54.00	23.47
3490	36.73	PK	V	26.94	4.17	26.59	41.25	74.00	32.75
3490	24.18	AV	V	26.94	4.17	26.59	28.70	54.00	25.30
37.03	47.69	QP	V	17.70	0.39	28.53	37.25	40.00	2.75
47.21	52.06	QP	V	10.20	0.38	28.50	34.14	40.00	5.86
High Channel: 2462 MHz									
2462	67.28	PK	H	23.33	2.99	0.00	93.60	N/A	N/A
2462	56.49	AV	H	23.33	2.99	0.00	82.81	N/A	N/A
2462	68.6	PK	V	23.33	2.99	0.00	94.92	N/A	N/A
2462	57.93	AV	V	23.33	2.99	0.00	84.25	N/A	N/A
2483.5	41.01	PK	V	23.26	2.99	0.00	67.26	74.00	6.74
2483.5	23.02	AV	V	23.26	2.99	0.00	49.27	54.00	4.73
4924	42.91	PK	V	31.16	5.07	26.88	52.26	74.00	21.74
4924	29.73	AV	V	31.16	5.07	26.88	39.08	54.00	14.92
7386	38.11	PK	V	35.07	6.25	26.43	53.00	74.00	21.00
7386	24.56	AV	V	35.07	6.25	26.43	39.45	54.00	14.55
3539	38.7	PK	V	27.16	4.24	26.59	43.51	74.00	30.49
3539	25.96	AV	V	27.16	4.24	26.59	30.77	54.00	23.23
37.03	48.29	QP	V	17.70	0.39	28.53	37.85	40.00	2.15
47.21	52.39	QP	V	10.20	0.38	28.50	34.47	40.00	5.53

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	67.81	PK	H	23.50	3.00	0.00	94.31	N/A	N/A
2412	57.02	AV	H	23.50	3.00	0.00	83.52	N/A	N/A
2412	69.13	PK	V	23.50	3.00	0.00	95.63	N/A	N/A
2412	58.37	AV	V	23.50	3.00	0.00	84.87	N/A	N/A
2390	39.78	PK	V	23.57	3.00	0.00	66.35	74.00	7.65
2390	22.26	AV	V	23.57	3.00	0.00	48.83	54.00	5.17
4824	42.48	PK	V	30.84	5.11	26.87	51.56	74.00	22.44
4824	29.02	AV	V	30.84	5.11	26.87	38.10	54.00	15.90
7236	34.81	PK	V	34.77	6.18	26.36	49.40	74.00	24.60
7236	21.48	AV	V	34.77	6.18	26.36	36.07	54.00	17.93
3539	38.58	PK	V	27.16	4.24	26.59	43.39	74.00	30.61
3539	25.54	AV	V	27.16	4.24	26.59	30.35	54.00	23.65
37.03	49.28	QP	V	17.70	0.39	28.53	38.84	40.00	1.16
47.21	53.69	QP	V	10.20	0.38	28.50	35.77	40.00	4.23
Middle Channel: 2437 MHz									
2437	67.75	PK	H	23.41	3.00	0.00	94.16	N/A	N/A
2437	56.84	AV	H	23.41	3.00	0.00	83.25	N/A	N/A
2437	69.06	PK	V	23.41	3.00	0.00	95.47	N/A	N/A
2437	58.2	AV	V	23.41	3.00	0.00	84.61	N/A	N/A
4874	42.16	PK	V	31.00	5.09	26.87	51.38	74.00	22.62
4874	28.66	AV	V	31.00	5.09	26.87	37.88	54.00	16.12
7311	34.7	PK	V	34.92	6.21	26.40	49.43	74.00	24.57
7311	21.33	AV	V	34.92	6.21	26.40	36.06	54.00	17.94
3539	38.74	PK	V	27.16	4.24	26.59	43.55	74.00	30.45
3539	25.67	AV	V	27.16	4.24	26.59	30.48	54.00	23.52
3490	37.07	PK	V	26.94	4.17	26.59	41.59	74.00	32.41
3490	24.31	AV	V	26.94	4.17	26.59	28.83	54.00	25.17
37.03	48.28	QP	V	17.70	0.39	28.53	37.84	40.00	2.16
47.21	54.75	QP	V	10.20	0.38	28.50	36.83	40.00	3.17
High Channel: 2462 MHz									
2462	67.32	PK	H	23.33	2.99	0.00	93.64	N/A	N/A
2462	56.61	AV	H	23.33	2.99	0.00	82.93	N/A	N/A
2462	68.69	PK	V	23.33	2.99	0.00	95.01	N/A	N/A
2462	57.71	AV	V	23.33	2.99	0.00	84.03	N/A	N/A
2483.5	42.63	PK	V	23.26	2.99	0.00	68.88	74.00	5.12
2483.5	23.02	AV	V	23.26	2.99	0.00	49.27	54.00	4.73
4924	41.84	PK	V	31.16	5.07	26.88	51.19	74.00	22.81
4924	28.32	AV	V	31.16	5.07	26.88	37.67	54.00	16.33
7386	34.55	PK	V	35.07	6.25	26.43	49.44	74.00	24.56
7386	21.18	AV	V	35.07	6.25	26.43	36.07	54.00	17.93
3539	38.54	PK	V	27.16	4.24	26.59	43.35	74.00	30.65
3539	25.74	AV	V	27.16	4.24	26.59	30.55	54.00	23.45
37.03	48.28	QP	V	17.70	0.39	28.53	37.84	40.00	2.16
47.21	53.67	QP	V	10.20	0.38	28.50	35.75	40.00	4.25


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2015-12-02	2016-12-01
Unknown	RF Cable	Unknown	C-5	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	26.2 °C
Relative Humidity:	29 %
ATM Pressure:	101 kPa


* The testing was performed by Lorin Bian on 2016-11-15.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.20	≥0.5
	Middle	2437	9.12	≥0.5
	High	2462	9.20	≥0.5
802.11g	Low	2412	15.52	≥0.5
	Middle	2437	16.08	≥0.5
	High	2462	16.32	≥0.5
802.11n ht20	Low	2412	16.96	≥0.5
	Middle	2437	17.04	≥0.5
	High	2462	16.96	≥0.5

802.11b Low Channel




Date: 15.NOV.2016 14:01:48

802.11b Middle Channel




Date: 15.NOV.2016 14:03:41

802.11b High Channel




Date: 15.NOV.2016 14:06:57

802.11g Low Channel




Date: 15.NOV.2016 13:49:00

802.11g Middle Channel




Date: 15.NOV.2016 13:59:16

802.11g High Channel




Date: 15.NOV.2016 13:56:32

802.11n ht20 Low Channel




Date: 15.NOV.2016 14:12:53

802.11n ht20 Middle Channel



Date: 15.NOV.2016 14:11:20

802.11n ht20 High Channel



Date: 15.NOV.2016 14:09:19


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54170074	2016-01-03	2017-01-02
Agilent	P-Series Power Meter	N1912A	MY5000798	2016-01-03	2017-01-02
Unknown	RF Cable	Unknown	C-5	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	26.2 °C
Relative Humidity:	29 %
ATM Pressure:	101 kPa

* The testing was performed by Lorin Bian on 2016-11-15.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	Low	2412	10.85	9.65	30
	Middle	2437	10.87	9.64	30
	High	2462	10.57	9.35	30
802.11g	Low	2412	14.08	9.59	30
	Middle	2437	14.1	9.54	30
	High	2462	13.78	9.33	30
802.11n ht20	Low	2412	14.21	9.39	30
	Middle	2437	14.29	9.51	30
	High	2462	14.07	9.39	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2015-12-02	2016-12-01
Unknown	RF Cable	Unknown	C-5	Each Time	/

*** Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions


Temperature:	26.2 °C
Relative Humidity:	29 %
ATM Pressure:	101 kPa

* The testing was performed by Lorin Bian on 2016-11-15.

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.

802.11b: Band Edge, Left Side




Date: 15.NOV.2016 14:02:47

802.11b: Band Edge, Right Side




Date: 15.NOV.2016 14:08:00

802.11g: Band Edge, Left Side




Date: 15.NOV.2016 13:50:02

802.11g: Band Edge, Right Side




Date: 15.NOV.2016 13:57:35

802.11n ht20 Band Edge, Left Side



Date: 15.NOV.2016 14:13:49

802.11n ht20 Band Edge, Right Side



Date: 15.NOV.2016 14:10:32

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2015-12-02	2016-12-01
Unknown	RF Cable	Unknown	C-5	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	26.2 °C
Relative Humidity:	29 %
ATM Pressure:	101 kPa


* The testing was performed by Lorin Bian on 2016-11-15.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-15.47	≤8
	Middle	2437	-16.63	≤8
	High	2462	-16.18	≤8
802.11g	Low	2412	-17.16	≤8
	Middle	2437	-17.83	≤8
	High	2462	-16.19	≤8
802.11n20	Low	2412	-14.26	≤8
	Middle	2437	-14.09	≤8
	High	2462	-14.54	≤8

Power Spectral Density, 802.11b Low Channel




Date: 15.NOV.2016 14:02:31

Power Spectral Density, 802.11b Middle Channel




Date: 15.NOV.2016 14:04:21

Power Spectral Density, 802.11b High Channel




Date: 15.NOV.2016 14:07:38

Power Spectral Density, 802.11g Low Channel




Date: 15.NOV.2016 13:49:40

Power Spectral Density, 802.11g Middle Channel




Date: 15.NOV.2016 13:59:58

Power Spectral Density, 802.11g High Channel




Date: 15.NOV.2016 13:57:13

Power Spectral Density, 802.11n ht20 Low Channel




Date: 15.NOV.2016 14:13:33

Power Spectral Density, 802.11n ht20 Middle Channel



Date: 15.NOV.2016 14:12:00

Power Spectral Density, 802.11n ht20 High Channel



Date: 15.NOV.2016 14:10:04

***** END OF REPORT *****