

Test Report

Report No. : CQASZ20250200188E-02
Applicant: Shenzhen DO Intelligent Technology Co., Ltd
Address of Applicant: 11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Equipment Under Test (EUT):
Product: Smart Watch
Model No.: GTC1, GTC2, GTC3
Test Model No.: GTC1, GTC2, GTC3
Brand Name: IDO
FCC ID: 2AHFT866
Standards: 47 CFR Part 15, Subpart C
KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2013
Date of Receipt: 2025-02-08
Date of Test: 2025-02-08 to 2025-03-13
Date of Issue: 2025-03-13
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250200188E-02	Rev.01	Initial report	2025-03-13

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	/	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15.247	ANSI C63.10-2013	PASS
20dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Carrier Frequencies Separation	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Hopping Channel Number	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Dwell Time	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Radiated Spurious emissions	47 CFR Part 15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

Note:

AC Power Line Conducted Emission and Radiated Spurious Emissions 1G and below have tested all models and all batteries and provided data, RF project only tested GTC1 because PCB and RF circuit are consistent.

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 ADDITIONAL INSTRUCTIONS	8
4.4 TEST ENVIRONMENT	9
4.5 DESCRIPTION OF SUPPORT UNITS	9
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	10
4.7 TEST LOCATION	11
4.8 TEST FACILITY	11
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	11
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	11
4.11 EQUIPMENT LIST	12
5 TEST RESULTS AND MEASUREMENT DATA	13
5.1 ANTENNA REQUIREMENT	13
5.2 CONDUCTED EMISSIONS	14
5.3 CONDUCTED PEAK OUTPUT POWER	28
5.4 20dB OCCUPIED BANDWIDTH	34
5.5 CARRIER FREQUENCIES SEPARATION	39
5.6 HOPPING CHANNEL NUMBER	43
5.7 DWELL TIME	46
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	55
5.9 SPURIOUS RF CONDUCTED EMISSIONS	62
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	73
5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	75
5.11.1 Radiated Emission below 1GHz	78
5.11.2 Transmitter Emission above 1GHz	90
6 PHOTOGRAPHS - EUT TEST SETUP	93
6.1 RADIATED EMISSION	93
6.2 CONDUCTED EMISSIONS TEST SETUP	94
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	95

4 General Information

4.1 Client Information

Applicant:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Applicant:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Manufacturer:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Factory:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Factory:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China

4.2 General Description of EUT

Product Name:	Smart Watch
Model No.:	GTC1, GTC2, GTC3
Test Model No.:	GTC1, GTC2, GTC3
Trade Mark:	IDO
Software Version:	V1.00.10
Hardware Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.3
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable
Test Software of EUT:	SiFli RF Tool v1.1.6
Antenna Type:	Metal frame antenna
Antenna Gain:	-3.2dBi
Power Supply:	<p>GTC1:</p> <p>Li-ion battery DC 3.85V 350mAh(551925 04) 1#</p> <p>Li-ion battery DC 3.85V 350mAh(551925 16) 2#</p> <p>GTC2:</p> <p>Li-ion battery DC 3.85V 350mAh(551925 04) 3#</p> <p>Li-ion battery DC 3.85V 350mAh(551925 16) 4#</p> <p>GTC3:</p> <p>Li-ion battery DC 3.85V 350mAh(551925 04) 5#</p>

	Li-ion battery DC 3.85V 350mAh(551925 16) 6#
Simultaneous Transmission	<input type="checkbox"/> Simultaneous TX is supported and evaluated in this report. <input checked="" type="checkbox"/> Simultaneous TX is not supported.

Note:

Here the product 1#2# means the product version (model: GTC1), product 3#4# means the (model: GTC2).

product 5#6# means the (model: GTC3).

The difference between product 1#3#5# and product 2#4#6# is that the battery model is different including having different battery supplier.

The difference between product model: GTC1 and product model: GTC2, model: GTC3 is that the screen model and appearance and strap is different including having different screen supplier. The key differences are the appearance and the model number.

These changes do not affect RF performance.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

4.3 Additional Instructions

EUT Test Software Settings:		
Mode:	<input checked="" type="checkbox"/> Special software is used. <input type="checkbox"/> Through engineering command into the engineering mode. engineering command: ***#3646633#**	
EUT Power level:	(Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



The screenshot shows the SiFli_RF_Tool v1.1.6 interface. On the left, there is a sidebar with a dropdown menu set to 'LB56X', radio buttons for 'BLE DUT', 'BT DUT' (selected), and 'CW', a 'COM7' dropdown, a '1000000' dropdown, and a 'CLOSE' button. The main area has four radio buttons: 'TX' (selected), 'RX', '跳频' (Frequency Hopping), and '定频' (Fixed Frequency). Below these are several settings: 'Frequency' set to '2402 MHz - CH 0', 'Packet type' set to 'DH5', 'Packet payload' set to 'PRBS9', 'Data Length' set to '339' (with a 'MAX: 339' label), and 'Power level' set to '10' (with a 'dB' label). At the bottom, there is a 'Stop TX' button and a green status indicator.

4.4 Test Environment

Operating Environment:	
Temperature:	25 °C
Humidity:	54% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	Supplied
Adapter	MI	/	/	CQA

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	3×10^{-8}
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8°C
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2024/9/2	2025/9/1
Spectrum analyzer	R&S	FSU26	CQA-038	2024/9/2	2025/9/1
Spectrum analyzer	R&S	FSU40	CQA-075	2024/9/2	2025/9/1
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2024/9/2	2025/9/1
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2024/9/2	2025/9/1
Preamplifier	EMCI	EMC184055SE	CQA-089	2024/9/2	2025/9/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2024/9/2	2025/9/1
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2024/9/2	2025/9/1
Antenna Connector	CQA	RFC-01	CQA-080	2024/9/2	2025/9/1
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2024/9/2	2025/9/1
Power meter	R&S	NRVD	CQA-029	2024/9/2	2025/9/1
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2024/9/2	2025/9/1
EMI Test Receiver	R&S	ESR7	CQA-005	2024/9/2	2025/9/1
LISN	R&S	ENV216	CQA-003	2024/9/2	2025/9/1
Coaxial cable	CQA	N/A	CQA-C009	2024/9/2	2025/9/1
DC power	KEYSIGHT	E3631A	CQA-028	2024/9/2	2025/9/1

Test software:


	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement


Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:	
<p>The antenna is Metal frame antenna.</p> <p>The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment.</p> <p>This is either permanently attachment or a unique coupling that satisfies the requirement.</p>	

Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

1# Li-ion battery DC 3.85V 350mAh(551925 04)

Measurement Data

Live line:




	Freq	Read		Limit	Over		
	MHz	Level	Factor	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dB		
1	0.465	13.36	9.67	23.03	46.60	-23.57 Average	Line
2	0.465	20.06	9.67	29.73	56.60	-26.87 QP	Line
3	0.635	10.39	9.84	20.23	46.00	-25.77 Average	Line
4	0.635	16.67	9.84	26.51	56.00	-29.49 QP	Line
5 AV	1.260	19.94	10.34	30.28	46.00	-15.72 Average	Line
6 PP	1.260	30.04	10.34	40.38	56.00	-15.62 QP	Line
7	1.295	19.07	10.42	29.49	46.00	-16.51 Average	Line
8	1.295	28.22	10.42	38.64	56.00	-17.36 QP	Line
9	1.350	17.78	10.54	28.32	46.00	-17.68 Average	Line
10	1.350	26.83	10.54	37.37	56.00	-18.63 QP	Line
11	1.420	15.67	10.68	26.35	46.00	-19.65 Average	Line
12	1.420	24.40	10.68	35.08	56.00	-20.92 QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read		Limit	Over		
	MHz	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.470	14.28	9.67	23.95	46.51	-22.56	Average
2	0.470	22.26	9.67	31.93	56.51	-24.58	QP
3	1.035	14.02	9.70	23.72	46.00	-22.28	Average
4	1.035	23.04	9.70	32.74	56.00	-23.26	QP
5	1.205	19.46	9.71	29.17	46.00	-16.83	Average
6	1.205	28.89	9.71	38.60	56.00	-17.40	QP
7 AV	1.240	20.59	9.71	30.30	46.00	-15.70	Average
8 PP	1.240	30.71	9.71	40.42	56.00	-15.58	QP
9	1.285	18.33	9.71	28.04	46.00	-17.96	Average
10	1.285	27.98	9.71	37.69	56.00	-18.31	QP
11	1.355	17.99	9.72	27.71	46.00	-18.29	Average
12	1.355	27.57	9.72	37.29	56.00	-18.71	QP


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

2# Li-ion battery DC 3.85V 350mAh(551925 16)

Measurement Data

Live line:




	Freq	Read		Limit	Over		
	MHz	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	Pol/Phase
1	0.375	11.63	9.58	21.21	48.39	-27.18	Average
2	0.375	18.64	9.58	28.22	58.39	-30.17	QP
3	0.465	12.67	9.67	22.34	46.60	-24.26	Average
4	0.465	20.11	9.67	29.78	56.60	-26.82	QP
5	1.215	18.92	10.24	29.16	46.00	-16.84	Average
6	1.215	27.65	10.24	37.89	56.00	-18.11	QP
7 PP	1.260	20.53	10.34	30.87	46.00	-15.13	Average
8 QP	1.260	30.49	10.34	40.83	56.00	-15.17	QP
9	1.305	18.27	10.45	28.72	46.00	-17.28	Average
10	1.305	28.11	10.45	38.56	56.00	-17.44	QP
11	1.375	18.12	10.59	28.71	46.00	-17.29	Average
12	1.375	27.31	10.59	37.90	56.00	-18.10	QP

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.435	13.06	9.64	22.70	47.16	-24.46	Average	Neutral
2	0.435	20.79	9.64	30.43	57.16	-26.73	QP	Neutral
3	0.550	14.19	9.75	23.94	46.00	-22.06	Average	Neutral
4	0.550	22.15	9.75	31.90	56.00	-24.10	QP	Neutral
5	1.195	19.25	9.71	28.96	46.00	-17.04	Average	Neutral
6	1.195	28.56	9.71	38.27	56.00	-17.73	QP	Neutral
7 AV	1.250	20.61	9.71	30.32	46.00	-15.68	Average	Neutral
8 PP	1.250	31.33	9.71	41.04	56.00	-14.96	QP	Neutral
9	1.285	18.75	9.71	28.46	46.00	-17.54	Average	Neutral
10	1.285	28.51	9.71	38.22	56.00	-17.78	QP	Neutral
11	1.375	18.72	9.72	28.44	46.00	-17.56	Average	Neutral
12	1.375	27.15	9.72	36.87	56.00	-19.13	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

3# Li-ion battery DC 3.85V 350mAh(551925 04)

Measurement Data

Live line:




		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.870	9.77	9.79	19.56	46.00	-26.44	Average	Line
2	0.870	16.46	9.79	26.25	56.00	-29.75	QP	Line
3	1.035	13.12	9.79	22.91	46.00	-23.09	Average	Line
4	1.035	21.31	9.79	31.10	56.00	-24.90	QP	Line
5	1.190	18.03	10.19	28.22	46.00	-17.78	Average	Line
6	1.190	26.64	10.19	36.83	56.00	-19.17	QP	Line
7 AV	1.260	20.06	10.34	30.40	46.00	-15.60	Average	Line
8 PP	1.260	30.25	10.34	40.59	56.00	-15.41	QP	Line
9	1.315	18.10	10.47	28.57	46.00	-17.43	Average	Line
10	1.315	27.73	10.47	38.20	56.00	-17.80	QP	Line
11	1.375	18.26	10.59	28.85	46.00	-17.15	Average	Line
12	1.375	27.10	10.59	37.69	56.00	-18.31	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.450	13.32	9.65	22.97	46.88	-23.91	Average	Neutral
2	0.450	21.93	9.65	31.58	56.88	-25.30	QP	Neutral
3	0.540	13.66	9.74	23.40	46.00	-22.60	Average	Neutral
4	0.540	21.72	9.74	31.46	56.00	-24.54	QP	Neutral
5	1.210	19.52	9.71	29.23	46.00	-16.77	Average	Neutral
6	1.210	29.25	9.71	38.96	56.00	-17.04	QP	Neutral
7 AV	1.255	20.02	9.71	29.73	46.00	-16.27	Average	Neutral
8 PP	1.255	30.28	9.71	39.99	56.00	-16.01	QP	Neutral
9	1.310	18.61	9.72	28.33	46.00	-17.67	Average	Neutral
10	1.310	28.64	9.72	38.36	56.00	-17.64	QP	Neutral
11	1.370	18.22	9.72	27.94	46.00	-18.06	Average	Neutral
12	1.370	27.82	9.72	37.54	56.00	-18.46	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

4# Li-ion battery DC 3.85V 350mAh(551925 16)

Measurement Data

Live line:




	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.385	11.55	9.59	21.14	48.17	-27.03	Average	Line
2	0.385	18.95	9.59	28.54	58.17	-29.63	QP	Line
3	0.745	10.49	9.87	20.36	46.00	-25.64	Average	Line
4	0.745	17.57	9.87	27.44	56.00	-28.56	QP	Line
5	1.215	17.98	10.24	28.22	46.00	-17.78	Average	Line
6	1.215	27.58	10.24	37.82	56.00	-18.18	QP	Line
7 AV	1.250	19.36	10.32	29.68	46.00	-16.32	Average	Line
8 PP	1.250	29.51	10.32	39.83	56.00	-16.17	QP	Line
9	1.295	18.28	10.42	28.70	46.00	-17.30	Average	Line
10	1.295	28.05	10.42	38.47	56.00	-17.53	QP	Line
11	1.385	16.54	10.61	27.15	46.00	-18.85	Average	Line
12	1.385	25.74	10.61	36.35	56.00	-19.65	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.220	12.82	9.58	22.40	52.82	-30.42	Average	Neutral
2	0.220	19.83	9.58	29.41	62.82	-33.41	QP	Neutral
3	0.475	12.57	9.68	22.25	46.43	-24.18	Average	Neutral
4	0.475	21.97	9.68	31.65	56.43	-24.78	QP	Neutral
5	0.555	13.47	9.76	23.23	46.00	-22.77	Average	Neutral
6	0.555	20.96	9.76	30.72	56.00	-25.28	QP	Neutral
7	1.200	18.09	9.71	27.80	46.00	-18.20	Average	Neutral
8	1.200	27.15	9.71	36.86	56.00	-19.14	QP	Neutral
9 AV	1.255	19.37	9.71	29.08	46.00	-16.92	Average	Neutral
10 PP	1.255	29.46	9.71	39.17	56.00	-16.83	QP	Neutral
11	1.315	17.94	9.72	27.66	46.00	-18.34	Average	Neutral
12	1.315	27.55	9.72	37.27	56.00	-18.73	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5# Li-ion battery DC 3.85V 350mAh(551925 04)

Measurement Data

Live line:




	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.295	11.07	9.50	20.57	50.38	-29.81	Average	Line
2	0.295	17.68	9.50	27.18	60.38	-33.20	QP	Line
3	0.460	11.33	9.67	21.00	46.69	-25.69	Average	Line
4	0.460	19.17	9.67	28.84	56.69	-27.85	QP	Line
5	0.550	12.03	9.75	21.78	46.00	-24.22	Average	Line
6	0.550	18.79	9.75	28.54	56.00	-27.46	QP	Line
7	1.205	17.92	10.22	28.14	46.00	-17.86	Average	Line
8	1.205	26.93	10.22	37.15	56.00	-18.85	QP	Line
9 AV	1.265	18.44	10.35	28.79	46.00	-17.21	Average	Line
10 PP	1.265	28.80	10.35	39.15	56.00	-16.85	QP	Line
11	1.365	16.91	10.57	27.48	46.00	-18.52	Average	Line
12	1.365	26.07	10.57	36.64	56.00	-19.36	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read		Limit	Over		
	MHz	Level	Factor	Level	Line	Limit	Remark
		dBuV	dB	dBuV	dBuV	dB	Pol/Phase
1	0.360	12.29	9.56	21.85	48.73	-26.88	Average
2	0.360	20.92	9.56	30.48	58.73	-28.25	QP
3	0.465	12.59	9.67	22.26	46.60	-24.34	Average
4	0.465	21.68	9.67	31.35	56.60	-25.25	QP
5	0.975	13.49	9.72	23.21	46.00	-22.79	Average
6	0.975	21.99	9.72	31.71	56.00	-24.29	QP
7	1.190	18.40	9.71	28.11	46.00	-17.89	Average
8	1.190	27.55	9.71	37.26	56.00	-18.74	QP
9 PP	1.255	19.79	9.71	29.50	46.00	-16.50	Average
10 QP	1.255	29.71	9.71	39.42	56.00	-16.58	QP
11	1.370	17.82	9.72	27.54	46.00	-18.46	Average
12	1.370	27.87	9.72	37.59	56.00	-18.41	QP


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

6# Li-ion battery DC 3.85V 350mAh(551925 16)

Measurement Data

Live line:




	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.335	10.58	9.54	20.12	49.33	-29.21	Average	Line
2	0.335	17.44	9.54	26.98	59.33	-32.35	QP	Line
3	0.700	8.90	9.90	18.80	46.00	-27.20	Average	Line
4	0.700	16.03	9.90	25.93	56.00	-30.07	QP	Line
5	1.085	13.73	9.92	23.65	46.00	-22.35	Average	Line
6	1.085	23.17	9.92	33.09	56.00	-22.91	QP	Line
7	1.230	17.39	10.28	27.67	46.00	-18.33	Average	Line
8	1.230	26.40	10.28	36.68	56.00	-19.32	QP	Line
9 PP	1.300	17.62	10.44	28.06	46.00	-17.94	Average	Line
10 QP	1.300	27.60	10.44	38.04	56.00	-17.96	QP	Line
11	1.370	17.12	10.58	27.70	46.00	-18.30	Average	Line
12	1.370	27.35	10.58	37.93	56.00	-18.07	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:





	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.340	10.85	9.53	20.38	49.20	-28.82	Average	Neutral
2	0.340	19.15	9.53	28.68	59.20	-30.52	QP	Neutral
3	0.430	10.99	9.64	20.63	47.25	-26.62	Average	Neutral
4	0.430	19.68	9.64	29.32	57.25	-27.93	QP	Neutral
5	0.575	12.13	9.78	21.91	46.00	-24.09	Average	Neutral
6	0.575	19.95	9.78	29.73	56.00	-26.27	QP	Neutral
7	1.200	18.41	9.71	28.12	46.00	-17.88	Average	Neutral
8	1.200	27.54	9.71	37.25	56.00	-18.75	QP	Neutral
9 AV	1.255	19.11	9.71	28.82	46.00	-17.18	Average	Neutral
10 PP	1.255	29.33	9.71	39.04	56.00	-16.96	QP	Neutral
11	1.380	16.82	9.72	26.54	46.00	-19.46	Average	Neutral
12	1.380	26.97	9.72	36.69	56.00	-19.31	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	<p>Setup for Power meter measurement method</p>  <p>Setup for Spectrum analyser measurement method</p>  <p><i>Remark: Offset=Cable loss+ attenuation factor.</i></p>
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.64	21.00	Pass
Middle	3.27	21.00	Pass
Highest	2.56	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.23	21.00	Pass
Middle	2.90	21.00	Pass
Highest	2.24	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.69	21.00	Pass
Middle	2.95	21.00	Pass
Highest	2.28	21.00	Pass

Test plot as follows:







2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441




3DH5_Ant1_2480



Date: 13.MAR.2025 10:41:23


5.4 20dB Occupied Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	0.94	1.22	1.18
Middle	0.94	1.21	1.23
Highest	0.94	1.21	1.24


Test plot as follows:






Date: 13.MAR.2025 10:48:16

2DH5_Ant1_2402




Date: 13.MAR.2025 10:52:49

2DH5_Ant1_2441




Date: 13.MAR.2025 10:54:56

2DH5_Ant1_2480




Date: 13.MAR.2025 10:55:58

3DH5_Ant1_2402




Date: 13.MAR.2025 10:57:00

3DH5_Ant1_2441




Date: 13.MAR.2025 10:58:18

3DH5_Ant1_2480



Date: 13.MAR.2025 10:59:00

5.5 Carrier Frequencies Separation


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Hop	1.328	≥ 0.627	PASS
2DH5	Hop	1.017	≥ 0.813	PASS
3DH5	Hop	1.174	≥ 0.827	PASS

Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.94	≥ 0.627
$\pi/4$ DQPSK	1.22	≥ 0.813
8DPSK	1.24	≥ 0.827


Test plot as follows:





Date: 13.MAR.2025 11:39:15


5.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: $Offset = \text{Cable loss} + \text{attenuation factor}$.</p>
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Mode	Hopping channel numbers	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15
8DPSK	79	≥ 15

Test plot as follows:





Date: 13.MAR.2025 11:40:02