

RF EXPOSURE REPORT

for

Model Number: Kontakt.io Card Beacon v1.0

Kontakt.io Card Beacon v1.0 N, N version is with additional
NFC sticker/tag

FCC ID: 2ADAOKONTAKT

Prepared for : Kontakt Micro-Location Sp. z o.o
Address : ul. Stoczniewcow 3, 30-709 Krakow, Poland

Prepared by : Shenzhen BCTC Testing Co., Ltd.
BCTC Building & 1-2F, East of B Building, Pengzhou Industrial,
Address : Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an
District, Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{(min. test separation distance, mm)}} \right]$$

* $[\sqrt{f(\text{GHz})}]$

	tune up power tolerance (dBm)	Maximum Tune up output power (dBm)	max. output power(mW)	Separation distance mm	RF exposure
GFSK	1 ± 1	2	1.58	5	0.49

The Max RF exposure is 0.49.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.