

RF Exposure Evaluation Report

Product : RADAR
Trade mark : Rentokil
Model/Type reference : 304838, 304840
Serial Number : N/A
Report Number : EED32K00213802
FCC ID : 2AK3PGSD-500349
Date of Issue : Oct. 22, 2018
47 CFR Part 1.1307
Test Standards : 47 CFR Part 1.1310
KDB 447498 D01v06
Test result : PASS

Prepared for:

Rentokil Initial 1927 plc
Riverbank, Meadows Business Park, Camberley, GU17 9AB

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Peter
Peter (Test Project)

Compiled by:

Tom - chen
Tom chen (Project Engineer)

Reviewed by:

Kevin Yang
Kevin yang (Reviewer)

Approved by:

Sheek Luo
Sheek Luo (Lab supervisor)

Date:

Oct. 22, 2018



Check No.: 2447667087

2 Version

Version No.	Date	Description
00	Oct. 22, 2018	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Limits.....	6
5.1.2 Test Procedure.....	6
5.1.3 EUT RF Exposure Evaluation.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Rentokil Initial 1927 plc
Address of Applicant:	Riverbank, Meadows Business Park, Camberley, GU17 9AB
Manufacturer:	Rentokil Initial 1927 plc
Address of Manufacturer:	Riverbank, Meadows Business Park, Camberley, GU17 9AB
Factory:	Rentokil Initial 1927 plc
Address of Factory:	Riverbank, Meadows Business Park, Camberley, GU17 9AB

4.2 General Description of EUT

Product Name:	RADAR
Model No.(EUT):	304838, 304840
Trade Mark:	Rentokil
EUT Supports Radios application:	915.25MHz to 927.5MHz

4.3 Product Specification subjective to this standard

Frequency Range:	915.25MHz to 927.5MHz
Modulation Type:	LoRa modulation - CSS modulation(Chirp Spread Spectrum modulation)
Sample Type:	fixed production
Test Power Grade:	N/A
Test Software of EUT:	N/A
Antenna Type:	Integral antenna
Antenna gain:	-3dBi
Power Supply:	4 x LR6/AA Alkaline, 6V
Test Voltage:	4 x LR6/AA Alkaline, 6V
Firmware version of the sample:	2.35(Manufacturer declare)
Hardware version of the sample:	EB3(Manufacturer declare)
Conducted Peak Output Power:	22.55dBm The Conducted Peak Output Power data refer to the report EED32K00213801
Sample Received Date:	Sep. 21, 2018
Sample tested Date:	Sep. 21, 2018 to Oct. 19, 2018

Report No. : EED32K00213802

Page 5 of 8

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	* (100)	6
3.0–30	1842/f	4.89/f	* (900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* (100)	30
1.34–30	824/f	2.19/f	* (180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

5.1.3 EUT RF Exposure Evaluation

Antenna Gain: -3dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Test Model No.: 304838

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Result
Lowest	915.25	22.55	-3	19.55	90.16	20	0.018	1.0	Pass

Test Model No.: 304840

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Result
Lowest	915.25	22.55	-3	19.55	90.16	20	0.018	1.0	Pass

Note: Refer to report No. EED32K00213801 for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32K00213801 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.