

APPENDIX K: PART 0 SAR TEST RESULTS FOR P_{Limit} CALCULATIONS

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

Table K-1
ECI = 4 P_{Limit} Calculations – GPRS Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
PHABLET	GSM 850	GPRS 3 Tx Slots	A	07056	1:2.76	0.00	848.80	251	28.20	Back	0	0.854	26.6	25.6
PHABLET	GSM 850	GPRS 3 Tx Slots	A	07056	1:2.76	-0.15	848.80	251	28.20	Front	0	0.480	29.1	
PHABLET	GSM 850	GPRS 3 Tx Slots	A	07056	1:2.76	-0.03	848.80	251	28.20	Bottom	0	1.070	25.6	
PHABLET	GSM 850	GPRS 3 Tx Slots	A	07056	1:2.76	-0.08	848.80	251	28.20	Right	0	0.481	29.1	
PHABLET	GSM 850	GPRS 3 Tx Slots	A	07056	1:2.76	-0.01	848.80	251	28.20	Left	0	0.066	37.7	
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	GPRS 1900	GPRS 4 Tx Slots	B	08039	1:2.076	0.03	1880.00	661	23.94	Back	0	1.330	21.6	21.6
Phablet	GPRS 1900	GPRS 4 Tx Slots	B	08039	1:2.076	0.05	1880.00	661	23.94	Front	0	0.417	26.7	
Phablet	GPRS 1900	GPRS 4 Tx Slots	B	08039	1:2.076	-0.02	1880.00	661	23.94	Bottom	0	0.502	25.9	
Phablet	GPRS 1900	GPRS 4 Tx Slots	B	08037	1:2.076	0.01	1880.00	661	23.94	Left	0	0.302	28.1	

Table K-2
ECI = 4 P_{Limit} Calculations – UMTS Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	UMTS 850	RMC	A	08039	1:1	0.01	836.60	4183	22.88	Back	0	0.754	26.2	25.8
Phablet	UMTS 850	RMC	A	08039	1:1	0.02	836.60	4183	22.88	Front	0	0.411	28.9	
Phablet	UMTS 850	RMC	A	08039	1:1	0.01	836.60	4183	22.88	Bottom	0	0.822	25.8	
Phablet	UMTS 850	RMC	A	08039	1:1	0.02	836.60	4183	22.88	Right	0	0.379	29.2	
Phablet	UMTS 850	RMC	A	08039	1:1	0.00	836.60	4183	22.88	Left	0	0.087	35.6	
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	UMTS 1750	RMC	B	07056	1:1	0.00	1712.40	1312	20.42	Back	0	1.230	21.6	21.6
Phablet	UMTS 1750	RMC	B	07056	1:1	-0.01	1712.40	1312	20.42	Front	0	0.722	23.9	
Phablet	UMTS 1750	RMC	B	07056	1:1	-0.01	1712.40	1312	20.42	Bottom	0	0.698	24.1	
Phablet	UMTS 1750	RMC	B	07056	1:1	-0.08	1712.40	1312	20.42	Left	0	0.444	26.1	
Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	UMTS 1900	RMC	B	08187	1:1	-0.01	1880.00	9400	20.26	Back	0	21.5	21.5	21.5
Phablet	UMTS 1900	RMC	B	08187	1:1	0.00	1880.00	9400	20.26	Front	0	25.6		
Phablet	UMTS 1900	RMC	B	08187	1:1	-0.01	1880.00	9400	20.26	Bottom	0	25.9		
Phablet	UMTS 1900	RMC	B	08187	1:1	-0.01	1880.00	9400	20.26	Left	0	27.5		

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 1 of 7

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.

Table K-3
ECI = 4 P_{Limit} Calculations – LTE Band 71 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 71	20	QPSK	A	08039	1:1	-0.01	680.50	133297	0.0	24.21	1	99	Back	0	0.814		28.1	28.1
Phablet	LTE Band 71	20	QPSK	A	08039	1:1	-0.03	680.50	133297	0.0	24.21	1	99	Front	0	0.270		32.9	
Phablet	LTE Band 71	20	QPSK	A	08039	1:1	0.00	680.50	133297	0.0	24.21	1	99	Bottom	0	0.594		29.5	
Phablet	LTE Band 71	20	QPSK	A	08039	1:1	-0.03	680.50	133297	0.0	24.21	1	99	Right	0	0.372		31.5	
Phablet	LTE Band 71	20	QPSK	A	08039	1:1	0.01	680.50	133297	0.0	24.21	1	99	Left	0	0.105		37.0	

Table K-4
ECI = 4 P_{Limit} Calculations – LTE Band 12 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 12	10	QPSK	A	08039	1:1	0.00	707.50	23095	0.0	24.57	1	49	Back	0	0.626	29.6	29.6
Phablet	LTE Band 12	10	QPSK	A	08039	1:1	0.02	707.50	23095	0.0	24.57	1	49	Front	0	0.280	33.1	
Phablet	LTE Band 12	10	QPSK	A	08039	1:1	0.00	707.50	23095	0.0	24.57	1	49	Bottom	0	0.542	30.2	
Phablet	LTE Band 12	10	QPSK	A	08039	1:1	-0.09	707.50	23095	0.0	24.57	1	49	Right	0	0.312	32.6	
Phablet	LTE Band 12	10	QPSK	A	08039	1:1	-0.03	707.50	23095	0.0	24.57	1	49	Left	0	0.096	37.8	

Table K-5
ECI = 4 P_{Limit} Calculations – LTE Band 13 Phablet SAR

Exposure	Band/ Mode	Bandwidth [MHz]	Service/ Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 13	10	QPSK	A	07296	1:1	0.03	782.00	23230	0.0	20.41	25	0	Back	0	0.345	27.1	27.1
Phablet	LTE Band 13	10	QPSK	A	07296	1:1	-0.02	782.00	23230	0.0	20.41	25	0	Front	0	0.160	30.5	
Phablet	LTE Band 13	10	QPSK	A	07296	1:1	0.00	782.00	23230	0.0	20.41	25	0	Bottom	0	0.348	27.1	
Phablet	LTE Band 13	10	QPSK	A	07296	1:1	0.05	782.00	23230	0.0	20.41	25	0	Right	0	0.174	30.1	
Phablet	LTE Band 13	10	QPSK	A	07296	1:1	0.09	782.00	23230	0.0	20.41	25	0	Left	0	0.022	39.1	

Table K-6
ECI = 4 P_{Limit} Calculations – LTE Band 14 Phablet SAR

Exposure	Band/ Mode	Bandwidth [MHz]	Service/ Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 14	10	QPSK	A	07296	1:1	-0.04	793.00	23330	0.0	20.23	25	0	Back	0	0.316	27.3	27.0
Phablet	LTE Band 14	10	QPSK	A	07296	1:1	-0.01	793.00	23330	0.0	20.23	25	0	Front	0	0.169	30.1	
Phablet	LTE Band 14	10	QPSK	A	07296	1:1	0.02	793.00	23330	0.0	20.23	25	0	Bottom	0	0.339	27.0	
Phablet	LTE Band 14	10	QPSK	A	07296	1:1	0.05	793.00	23330	0.0	20.23	25	0	Right	0	0.167	30.1	
Phablet	LTE Band 14	10	QPSK	A	07296	1:1	0.10	793.00	23330	0.0	20.23	25	0	Left	0	0.025	38.4	

Table K-7
ECI = 4 P_{Limit} Calculations – LTE Band 26 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 26	15	QPSK	A	08039	1:1	0.01	831.50	26865	0.0	23.53	36	37	Back	0	0.776	26.7	26.5
Phablet	LTE Band 26	15	QPSK	A	08039	1:1	0.01	831.50	26865	0.0	23.53	36	37	Front	0	0.415	29.5	
Phablet	LTE Band 26	15	QPSK	A	08039	1:1	-0.04	831.50	26865	0.0	23.53	36	37	Bottom	0	0.817	26.5	
Phablet	LTE Band 26	15	QPSK	A	08039	1:1	0.03	831.50	26865	0.0	23.53	36	37	Right	0	0.461	29.0	
Phablet	LTE Band 26	15	QPSK	A	08039	1:1	0.01	831.50	26865	0.0	23.53	36	37	Left	0	0.101	35.6	

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 2 of 7

REV 1.1
04/08/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.Info@Element.com.

Table K-8
ECI = 4 P_{Limit} Calculations – LTE Band 66 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 66	20	QPSK	B	08039	1:1	0.01	1720.00	132072	0.0	19.92	50	25	Back	0	0.977	22.1	22.1
Phablet	LTE Band 66	20	QPSK	B	08039	1:1	0.00	1720.00	132072	0.0	19.92	50	25	Front	0	0.474	25.3	
Phablet	LTE Band 66	20	QPSK	B	08039	1:1	0.00	1720.00	132072	0.0	19.92	50	25	Bottom	0	0.487	25.2	
Phablet	LTE Band 66	20	QPSK	B	08039	1:1	0.01	1720.00	132072	0.0	19.92	50	25	Left	0	0.310	27.1	
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 66	20	QPSK	C	07296	1:1	0.01	1720.00	132072	0.0	20.96	50	0	Back	0	0.862	23.7	23.7
Phablet	LTE Band 66	20	QPSK	C	07296	1:1	-0.02	1720.00	132072	0.0	20.96	50	0	Front	0	0.068	34.7	
Phablet	LTE Band 66	20	QPSK	C	07296	1:1	-0.13	1720.00	132072	0.0	20.96	50	0	Top	0	0.012	42.3	
Phablet	LTE Band 66	20	QPSK	C	07296	1:1	-0.01	1720.00	132072	0.0	20.96	50	0	Left	0	0.263	28.9	

Table K-9
ECI = 4 P_{Limit} Calculations – LTE Band 25 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 25	20	QPSK	B	08039	1:1	-0.01	1882.50	26365	0.0	20.23	1	0	Back	0	1.220	21.5	21.5
Phablet	LTE Band 25	20	QPSK	B	08039	1:1	0.01	1882.50	26365	0.0	20.23	1	0	Front	0	0.446	25.8	
Phablet	LTE Band 25	20	QPSK	B	08039	1:1	-0.01	1882.50	26365	0.0	20.23	1	0	Bottom	0	0.527	25.1	
Phablet	LTE Band 25	20	QPSK	B	08039	1:1	0.04	1882.50	26365	0.0	20.23	1	0	Left	0	0.371	26.6	
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 25	20	QPSK	C	07056	1:1	0.01	1882.50	26365	0.0	20.60	50	0	Back	0	1.490	21.0	21.0
Phablet	LTE Band 25	20	QPSK	C	07056	1:1	0.03	1882.50	26365	0.0	20.60	50	0	Front	0	0.261	28.5	
Phablet	LTE Band 25	20	QPSK	C	07056	1:1	0.02	1882.50	26365	0.0	20.60	50	0	Top	0	0.099	32.8	
Phablet	LTE Band 25	20	QPSK	C	07056	1:1	0.00	1882.50	26365	0.0	20.60	50	0	Left	0	0.966	22.9	

Table K-10
ECI = 4 P_{Limit} Calculations – LTE Band 30 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 30	10	QPSK	B	07999	1:1	0.03	2310.00	27710	0.0	18.82	1	0	Back	0	1.780	19.3	19.3
Phablet	LTE Band 30	10	QPSK	B	07999	1:1	0.16	2310.00	27710	0.0	18.82	1	0	Front	0	0.629	23.8	
Phablet	LTE Band 30	10	QPSK	B	07999	1:1	0.04	2310.00	27710	0.0	18.82	1	0	Bottom	0	0.613	24.0	
Phablet	LTE Band 30	10	QPSK	B	07999	1:1	0.00	2310.00	27710	0.0	18.82	1	0	Left	0	0.561	24.3	

Table K-11
ECI = 4 P_{Limit} Calculations – LTE Band 7 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 7	20	QPSK	B	07999	1:1	-0.01	2510.00	20850	0.0	19.63	50	0	Back	0	1.090	21.4	21.4
Phablet	LTE Band 7	20	QPSK	B	07999	1:1	-0.02	2510.00	20850	0.0	19.63	50	0	Front	0	0.692	23.3	
Phablet	LTE Band 7	20	QPSK	B	07999	1:1	0.01	2510.00	20850	0.0	19.63	50	0	Bottom	0	0.719	23.2	
Phablet	LTE Band 7	20	QPSK	B	07999	1:1	-0.02	2510.00	20850	0.0	19.63	50	0	Left	0	0.425	25.5	

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 3 of 7

Table K-12
ECI = 4 P_{Limit} Calculations – LTE Band 41 Phablet SAR

Exposure	Band / Mode	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 41	QPSK	B	07056	1:1.58	0.01	2680.00	41490	26.79	1	50	Back	0	1.780	22.8	22.8
Phablet	LTE Band 41	QPSK	B	07056	1:1.58	0.01	2680.00	41490	26.79	1	50	Front	0	0.936	25.6	
Phablet	LTE Band 41	QPSK	B	07056	1:1.58	-0.01	2680.00	41490	26.79	1	50	Bottom	0	0.891	25.8	
Phablet	LTE Band 41	QPSK	B	07056	1:1.58	-0.05	2680.00	41490	26.79	1	50	Left	0	0.795	26.3	

Table K-13
ECI = 4 P_{Limit} Calculations – LTE Band 48 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	LTE Band 48	20	QPSK	F	09847	1:1.58	0.02	3690.00	56640	0.0	22.55	1	99	Back	0	1.230	22.7	22.7
Phablet	LTE Band 48	20	QPSK	F	09847	1:1.58	0.05	3690.00	56640	0.0	22.55	1	99	Front	0	0.398	27.6	
Phablet	LTE Band 48	20	QPSK	F	09847	1:1.58	0.01	3690.00	56640	0.0	22.55	1	99	Top	0	0.367	27.9	
Phablet	LTE Band 48	20	QPSK	F	09847	1:1.58	0.02	3690.00	56640	0.0	22.55	1	99	Left	0	0.933	23.9	

Table K-14
ECI = 4 P_{Limit} Calculations – NR Band n71 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n71	20	QPSK	A	08039	1:1	0.05	680.50	136100	DFT-s-OFDM	0.0	24.00	1	104	Back	0	0.589	28.4	28.4
Phablet	NR Band n71	20	QPSK	A	08039	1:1	-0.01	680.50	136100	DFT-s-OFDM	0.0	24.00	1	104	Front	0	0.205	33.0	
Phablet	NR Band n71	20	QPSK	A	08039	1:1	0.01	680.50	136100	DFT-s-OFDM	0.0	24.00	1	104	Bottom	0	0.439	29.7	
Phablet	NR Band n71	20	QPSK	A	08039	1:1	0.01	680.50	136100	DFT-s-OFDM	0.0	24.00	1	104	Right	0	0.288	31.5	
Phablet	NR Band n71	20	QPSK	A	08039	1:1	0.02	680.50	136100	DFT-s-OFDM	0.0	24.00	1	104	Left	0	0.078	37.2	

Table K-15
ECI = 4 P_{Limit} Calculations – NR Band n5 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n5	20	QPSK	A	08039	1:1	0.06	836.50	167300	DFT-s-OFDM	0.0	23.38	1	53	Back	0	0.607	28.6	28.0
Phablet	NR Band n5	20	QPSK	A	08039	1:1	0.03	836.50	167300	DFT-s-OFDM	0.0	23.38	1	53	Front	0	0.344	31.0	
Phablet	NR Band n5	20	QPSK	A	08039	1:1	-0.06	836.50	167300	DFT-s-OFDM	0.0	23.38	1	53	Bottom	0	0.698	28.0	
Phablet	NR Band n5	20	QPSK	A	08039	1:1	0.00	836.50	167300	DFT-s-OFDM	0.0	23.38	1	53	Right	0	0.388	30.5	
Phablet	NR Band n5	20	QPSK	A	08039	1:1	0.07	836.50	167300	DFT-s-OFDM	0.0	23.38	1	53	Left	0	0.083	37.2	

Table K-16
ECI = 4 P_{Limit} Calculations – NR Band n70 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n70	15	QPSK	B	07122	1:1	-0.09	1702.50	340500	DFT-s-OFDM	0.0	22.45	36	0	Back	0	1.190	24.7	24.7
Phablet	NR Band n70	15	QPSK	B	07122	1:1	-0.06	1702.50	340500	DFT-s-OFDM	0.0	22.45	36	0	Front	0	0.824	26.3	
Phablet	NR Band n70	15	QPSK	B	07122	1:1	-0.03	1702.50	340500	DFT-s-OFDM	0.0	22.45	36	0	Bottom	0	0.884	26.0	
Phablet	NR Band n70	15	QPSK	B	07122	1:1	-0.03	1702.50	340500	DFT-s-OFDM	0.0	22.45	36	0	Left	0	0.550	28.1	

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 4 of 7

Table K-17
ECI = 4 P_{Limit} Calculations – NR Band n66 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n66	40	QPSK	B	07122	1:1	0.00	1745.00	349000	CP-OFDM	0.0	19.28	1	1	Back	0	0.640	24.2	24.2
Phablet	NR Band n66	40	QPSK	B	07122	1:1	0.02	1745.00	349000	CP-OFDM	0.0	19.28	1	1	Front	0	0.449	25.8	
Phablet	NR Band n66	40	QPSK	B	07122	1:1	0.02	1745.00	349000	CP-OFDM	0.0	19.28	1	1	Bottom	0	0.436	25.9	
Phablet	NR Band n66	40	QPSK	B	07122	1:1	0.00	1745.00	349000	CP-OFDM	0.0	19.28	1	1	Left	0	0.244	28.4	
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n66	40	QPSK	C	08005	1:1	-0.02	1745.00	349000	DFT-s-OFDM	0.0	20.49	1	108	Back	0	0.183	30.9	30.9
Phablet	NR Band n66	40	QPSK	C	08005	1:1	-0.01	1745.00	349000	DFT-s-OFDM	0.0	20.49	1	108	Front	0	0.012	42.7	
Phablet	NR Band n66	40	QPSK	C	08005	1:1	0.07	1745.00	349000	DFT-s-OFDM	0.0	20.49	1	108	Top	0	0.000	63.5	
Phablet	NR Band n66	40	QPSK	C	08005	1:1	0.03	1745.00	349000	DFT-s-OFDM	0.0	20.49	1	108	Left	0	0.057	35.9	

Table K-18
ECI = 4 P_{Limit} Calculations – NR Band n25 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n25	40	QPSK	B	08039	1:1	0.00	1882.50	376500	DFT-s-OFDM	0.0	20.37	108	54	Back	0	1.190	21.8	21.8
Phablet	NR Band n25	40	QPSK	B	08039	1:1	0.01	1882.50	376500	DFT-s-OFDM	0.0	20.37	108	54	Front	0	0.429	26.2	
Phablet	NR Band n25	40	QPSK	B	08039	1:1	0.01	1882.50	376500	DFT-s-OFDM	0.0	20.37	108	54	Bottom	0	0.492	25.6	
Phablet	NR Band n25	40	QPSK	B	08039	1:1	0.05	1882.50	376500	DFT-s-OFDM	0.0	20.37	108	54	Left	0	0.374	26.7	

Table K-19
ECI = 4 P_{Limit} Calculations – NR Band n2 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n2	40	QPSK	C	07056	1:1	0.04	1880.00	376000	DFT-s-OFDM	0.0	20.53	108	54	Back	0	1.370	21.3	21.3
Phablet	NR Band n2	40	QPSK	C	07056	1:1	0.01	1880.00	376000	DFT-s-OFDM	0.0	20.53	108	54	Front	0	0.251	28.6	
Phablet	NR Band n2	40	QPSK	C	07056	1:1	-0.08	1880.00	376000	DFT-s-OFDM	0.0	20.53	108	54	Top	0	0.089	33.1	
Phablet	NR Band n2	40	QPSK	C	07056	1:1	-0.04	1880.00	376000	DFT-s-OFDM	0.0	20.53	108	54	Left	0	0.938	22.9	

Table K-20
ECI = 4 P_{Limit} Calculations – NR Band n41 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n41	100	QPSK	B	07056	1:1	0.03	2592.99	518598	DFT-s-OFDM	0.0	16.97	1	137	Back	0	0.772	20.2	19.8
Phablet	NR Band n41	100	QPSK	B	07296	1:1	-0.01	2592.99	518598	DFT-s-OFDM	0.0	16.91	135	69	Back	0	0.830	19.8	
Phablet	NR Band n41	100	QPSK	B	07296	1:1	0.00	2592.99	518598	CP-OFDM	0.0	16.51	1	1	Back	0	0.743	19.9	
Phablet	NR Band n41	100	QPSK	B	07056	1:1	0.00	2592.99	518598	DFT-s-OFDM	0.0	16.97	1	137	Front	0	0.516	22.0	
Phablet	NR Band n41	100	QPSK	B	07296	1:1	-0.02	2592.99	518598	DFT-s-OFDM	0.0	16.91	135	69	Front	0	0.547	21.6	
Phablet	NR Band n41	100	QPSK	B	07056	1:1	0.01	2592.99	518598	DFT-s-OFDM	0.0	16.97	1	137	Bottom	0	0.512	22.0	
Phablet	NR Band n41	100	QPSK	B	07296	1:1	0.00	2592.99	518598	DFT-s-OFDM	0.0	16.91	135	69	Bottom	0	0.520	21.9	
Phablet	NR Band n41	100	QPSK	B	07056	1:1	0.02	2592.99	518598	DFT-s-OFDM	0.0	16.97	1	137	Left	0	0.393	23.1	

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 5 of 7

Table K-21
ECI = 4 P_{Limit} Calculations – NR Band n48 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n48	40	QPSK	F	07973	1:1	0.06	3624.99	641666	CP-OFDM	0.0	17.92	1	1	Back	0	1.450	18.4	18.4
Phablet	NR Band n48	40	QPSK	F	07973	1:1	-0.04	3624.99	641666	CP-OFDM	0.0	17.92	1	1	Front	0	0.257	25.9	
Phablet	NR Band n48	40	QPSK	F	07973	1:1	0.01	3624.99	641666	CP-OFDM	0.0	17.92	1	1	Top	0	0.219	26.6	
Phablet	NR Band n48	40	QPSK	F	07973	1:1	0.02	3624.99	641666	CP-OFDM	0.0	17.92	1	1	Left	0	0.546	22.7	
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]				
Phablet	NR Band n48	40	E	07973	1:1	-0.05	3570.00	638000	CW/SRS	14.90	Back	0	0.375	22.2	22.2				
Phablet	NR Band n48	40	E	07973	1:1	0.01	3570.00	638000	CW/SRS	14.90	Front	0	0.142	26.4					
Phablet	NR Band n48	40	E	07973	1:1	-0.02	3570.00	638000	CW/SRS	14.90	Top	0	0.187	25.2					
Phablet	NR Band n48	40	E	07973	1:1	0.00	3570.00	638000	CW/SRS	14.90	Left	0	0.050	30.9					
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]				
Phablet	NR Band n48	40	H	0722M	1:1	-0.01	3570.00	638000	CW/SRS	12.08	Back	0	0.066	26.0	25.7				
Phablet	NR Band n48	40	H	0722M	1:1	-0.04	3570.00	638000	CW/SRS	12.08	Front	0	0.018	31.6					
Phablet	NR Band n48	40	H	0722M	1:1	-0.06	3570.00	638000	CW/SRS	12.08	Top	0	0.071	25.7					
Phablet	NR Band n48	40	H	0722M	1:1	0.03	3570.00	638000	CW/SRS	12.08	Left	0	0.003	39.4					
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]				
Phablet	NR Band n48	40	G	0722M	1:1	-0.02	3570.00	638000	CW/SRS	12.51	Back	0	0.218	21.2	21.2				
Phablet	NR Band n48	40	G	0722M	1:1	0.21	3570.00	638000	CW/SRS	12.51	Front	0	0.021	31.4					
Phablet	NR Band n48	40	G	0722M	1:1	0.08	3570.00	638000	CW/SRS	12.51	Top	0	0.004	38.6					
Phablet	NR Band n48	40	G	0722M	1:1	-0.02	3570.00	638000	CW/SRS	12.51	Right	0	0.106	24.4					

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 6 of 7

Table K-22
ECI = 4 P_{Limit} Calculations – NR Band n77 Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	MPR [dB]	Conducted Power [dBm]	RB Size	RB Offset	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]
Phablet	NR Band n77 DoD	100	QPSK	F	07973	1:1	0.01	3500.01	633334	CP-OFDM	0.0	15.00	1	1	Back	0	0.730	19.4	19.4
Phablet	NR Band n77	100	QPSK	F	07973	1:1	0.00	3930.00	662000	CP-OFDM	0.0	15.77	1	1	Back	0	0.616	20.9	
Phablet	NR Band n77	100	QPSK	F	07973	1:1	0.00	3930.00	662000	CP-OFDM	0.0	15.77	1	1	Front	0	0.183	26.2	
Phablet	NR Band n77	100	QPSK	F	07973	1:1	-0.03	3930.00	662000	CP-OFDM	0.0	15.77	1	1	Top	0	0.154	26.9	
Phablet	NR Band n77	100	QPSK	F	07973	1:1	0.04	3930.00	662000	CP-OFDM	0.0	15.77	1	1	Left	0	0.399	22.8	
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]				
Phablet	NR Band n77 DoD	100	E	07999	1:1	-0.01	3500.01	633334	CW/SRS	12.11	Back	0	0.318	20.1	19.6				
Phablet	NR Band n77	100	E	07973	1:1	-0.08	3930.00	662000	CW/SRS	13.54	Back	0	0.498	19.6					
Phablet	NR Band n77	100	E	07973	1:1	-0.02	3930.00	662000	CW/SRS	13.54	Front	0	0.226	23.0					
Phablet	NR Band n77	100	E	07973	1:1	0.00	3930.00	662000	CW/SRS	13.54	Top	0	0.304	21.7					
Phablet	NR Band n77	100	E	07973	1:1	-0.06	3930.00	662000	CW/SRS	13.54	Left	0	0.083	27.4					
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]				
Phablet	NR Band n77 DoD	100	G	0709M	1:1	-0.01	3500.01	633334	CW/SRS	9.81	Back	0	0.156	20.9	20.9				
Phablet	NR Band n77	100	G	07973	1:1	-0.07	3930.00	662000	CW/SRS	11.42	Back	0	0.137	23.1					
Phablet	NR Band n77	100	G	07973	1:1	0.00	3930.00	662000	CW/SRS	11.42	Front	0	0.015	32.7					
Phablet	NR Band n77	100	G	07973	1:1	0.07	3930.00	662000	CW/SRS	11.42	Top	0	0.003	39.7					
Phablet	NR Band n77	100	G	07973	1:1	-0.06	3930.00	662000	CW/SRS	11.42	Right	0	0.072	25.9					
Exposure	Band / Mode	Bandwidth [MHz]	Ant.	Serial Number	Duty Cycle	Power Drift [dB]	Frequency [MHz]	Channel #	Waveform	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Plimit [dBm]	Overall Plimit [dBm]				
Phablet	NR Band n77 DoD	100	H	0709M	1:1	0.00	3500.01	633334	CW/SRS	9.94	Back	0	0.073	24.3	24.3				
Phablet	NR Band n77	100	H	07973	1:1	-0.04	3930.00	662000	CW/SRS	9.81	Back	0	0.053	25.6					
Phablet	NR Band n77	100	H	07973	1:1	0.06	3930.00	662000	CW/SRS	9.81	Front	0	0.023	29.2					
Phablet	NR Band n77	100	H	07973	1:1	-0.13	3930.00	662000	CW/SRS	9.81	Top	0	0.056	25.3					
Phablet	NR Band n77	100	H	07973	1:1	0.05	3930.00	662000	CW/SRS	9.81	Right	0	0.005	35.8					

Table K-23
ECI = 4 P_{Limit} Calculations – DTS Phablet SAR

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 10g SAR [W/kg]	Duty Cycle Scaling Factor	Plimit [dBm]	Overall Plimit [dBm]
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	E	02347	99.57	0.02	2437.00	6	1	20.87	Back	0	1.300	1.004	20.3	20.3
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	E	02347	99.57	-0.03	2437.00	6	1	20.87	Front	0	0.590	1.004	23.7	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	E	02347	99.57	0.10	2437.00	6	1	20.87	Top	0	0.684	1.004	23.1	
Phablet	2.4 GHz WiFi/ IEEE 802.11b	20	DSSS	E	02347	99.57	-0.02	2437.00	6	1	20.87	Left	0	0.171	1.004	29.1	

FCC ID: A3LSMA156U	SAR CHARACTERIZATION	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX K: Page 7 of 7