



MDE_MAGNET_1607

Telefication
Edisonstr. 12a
6902 PK Zevenaar
The Netherlands

Abdellah Ahakki
14.11.2016
Phone +49 (0) 2102 749 285
Fax +49 (0) 2102 749 350

FCC-ID : RX2EE0001

Maximum Permissible Exposure calculation

Dear Madams or Sirs,

please find here our Maximum Permissible Exposure calculations for the Bluetooth/WLAN Module EE0001.

Best Regards

A handwritten signature in blue ink, appearing to be 'A. Ahakki', with a large, stylized loop at the beginning.

i.A.

Abdellah Ahakki

7layers GmbH
Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350
www.7layers.com

Geschäftsführer /
Managing Directors:
Frank Spiller
Bernhard Retka
Alexandre Norré-Oudard

Registergericht registered in:
Düsseldorf, HRB 75554
USt-IdNr VAT No.:
DE203159652
TAX No. 147/5869/0385
A Bureau Veritas Group Company



Maximum Permissible Exposure

(as specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure)

<i>Frequency range (MHz)</i>	<i>Power density (mW/cm²)</i>
300 – 1,500	f/1500
1,500 – 100,000	1.0

Calculations 2400-2483.5 MHz band

Maximum peak output power at antenna input terminal for Bluetooth/WLAN module:

0.00234 W

Prediction distance **R**: 20 cm

Prediction frequency: 2.4 GHz

Prediction Antenna Gain **G**: -2.0 dBi (WiFi Antenna)

MPE limit **S**: 1 mW/cm²

Equation OET bulletin 65, page 18, edition 97-01: $S = P \cdot G / (4\pi R^2)$

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum permissible power density: **0.0003 mW/cm²**

=> Delta to MPE Limit: **0.9997 mW/cm²**