

FCC Part 15C Measurement and Test Report


For

Sky Phone LLC

1348 Washington Av.Suite 350 Miami Beach, FL 33139

FCC ID: 2ABOSSKYPLA55

FCC Rule(s):	<u>FCC Part 15C</u>
Product Description:	<u>3G Smart Phone</u>
Tested Model:	<u>Platinum 5.5</u>
Report No.:	<u>STR15098339I-4</u>
Tested Date:	<u>2015-09-29 to 2015-10-15</u>
Issued Date:	<u>2015-10-16</u>
Tested By:	<u>Vigoss Liang / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	



Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. POWER SPECTRAL DENSITY.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 ENVIRONMENTAL CONDITIONS.....	10
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	11
6. 6DB BANDWIDTH.....	18
6.1 STANDARD APPLICABLE.....	18
6.2 TEST PROCEDURE.....	18
6.3 ENVIRONMENTAL CONDITIONS.....	18
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	18
7. RF OUTPUT POWER.....	25
7.1 STANDARD APPLICABLE.....	25
7.2 TEST PROCEDURE.....	25
7.3 ENVIRONMENTAL CONDITIONS.....	25
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	26
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	33
8.1 MEASUREMENT UNCERTAINTY.....	33
8.2 STANDARD APPLICABLE.....	33
8.3 TEST PROCEDURE.....	33
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	35
8.5 ENVIRONMENTAL CONDITIONS.....	35
8.6 SUMMARY OF TEST RESULTS/PLOTS.....	35
9. OUT OF BAND EMISSIONS.....	64
9.1 STANDARD APPLICABLE.....	64
9.2 TEST PROCEDURE.....	64
9.3 ENVIRONMENTAL CONDITIONS.....	65
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	65
10. CONDUCTED EMISSIONS.....	84
10.1 MEASUREMENT UNCERTAINTY.....	84
10.2 TEST PROCEDURE.....	84
10.3 BASIC TEST SETUP BLOCK DIAGRAM.....	84
10.4 ENVIRONMENTAL CONDITIONS.....	85
10.5 TEST RECEIVER SETUP.....	85
10.6 SUMMARY OF TEST RESULTS/PLOTS.....	85
10.7 CONDUCTED EMISSIONS TEST DATA.....	85

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Sky Phone LLC
Address of applicant: 1348 Washington Av.Suite 350 Miami Beach, FL 33139

Manufacturer: Shenzhen Tablet Electronics Limited
Address of manufacturer: 2F, B5b Building, Yingzhan Industrial Zone, Longtian Community, Kengzi Street, Longgang, Shenzhen, China

General Description of EUT	
Product Name:	3G Smart Phone
Brand Name:	/
Model No.:	Platinum 5.5
Adding Model(s):	PQ55, PQ551, PQ552, SKY 5.5WPlus
Adapter Model:	WTA0501000USA1
	INPUT:100-240V,50/60Hz,0.3A; OUTPUT:5V,1A
Hardware version:	AL_Q220_MB_V20
Software version:	Sky5.5WPLUS.v1.0.0_20150916
Rated Voltage:	DC 3.8V Li-ion Battery
Battery Capacity:	2200mAh
Device Category:	Portable Device
<i>The EUT Main board support GSM850/900/DCS1800/PCS1900, WCDMA Band 2/5, It is intended for speech, Multimedia Message Service (MMS) transmission and Platinum 5.5. It is equipped with GPRS class 12 for GSM850/900/DCS1800/PCS1900, GPS, FM, Bluetooth and Wi-Fi functions. For more information see the following datasheet</i>	
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model Platinum 5.5, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
RF Output Power:	14.90dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11/7
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	2dBi
Lowest Internal frequency of EUT:	32.768kHz

1.2 Test Standards

The following report is prepared on behalf of the Sky Phone LLC in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 V03r03 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.05	Unshielded	Without Ferrite
Earphone	1.10	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	N9020A	US47140102	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16
Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 V03r03, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/100kHz	Limit dBm/3kHz
802.11b	2412	6.147	8
	2437	6.421	8
	2462	6.299	8
802.11g	2412	0.790	8
	2437	0.186	8
	2462	0.001	8
802.11n HT20	2412	-0.260	8
	2437	-0.181	8
	2462	0.164	8
802.11n HT40	2422	-5.132	8
	2437	-5.232	8
	2452	-5.166	8

Please refer to the following test plots:

802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel



802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit kHz
802.11b	2412	8.891	12.446	≥ 500
	2437	8.883	12.508	≥ 500
	2462	8.886	12.610	≥ 500
802.11g	2412	16.46	16.392	≥ 500
	2437	16.45	16.402	≥ 500
	2462	16.46	16.397	≥ 500
802.11n-HT20	2412	17.65	17.574	≥ 500
	2437	17.59	17.562	≥ 500
	2462	17.59	17.571	≥ 500
802.11n-HT40	2422	36.29	35.866	≥ 500
	2437	36.30	35.889	≥ 500
	2452	36.04	35.847	≥ 500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to section 15.247(b)-power output of the KDB-558074 D01 V03r03, 9.2.2.2 (channel integration method) When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98 \%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	14.90	30.90	1000
	2437	14.77	29.99	1000
	2462	14.73	29.72	1000
802.11g_54Mbps	2412	11.58	14.39	1000
	2437	11.58	14.39	1000
	2462	11.64	14.59	1000
802.11n HT20_MCS7	2412	11.38	13.74	1000
	2437	11.78	15.07	1000
	2462	11.85	15.31	1000
802.11n HT40_MCS7	2422	10.28	10.67	1000
	2437	10.24	10.57	1000
	2452	10.13	10.30	1000

Please refer to the following test plots:


802.11b-11Mbps-Low Channel




802.11b -11Mbps-Middle Channel




802.11b -11Mbps-High Channel




802.11g-54Mbps-Low Channel




802.11g-54Mbps-Middle Channel




802.11g-54Mbps-High Channel




802.11n-HT20-MCS7-Low Channel




802.11n-HT20-MCS7-Middle Channel




802.11n-HT20-MCS7-High Channel




802.11n-HT40-MCS7-Low Channel



802.11n-HT40-MCS7-Middle Channel



802.11n-HT40-MCS7-High Channel



8. Field Strength of Spurious Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

8.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.6 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note: this EUT was tested in 3 orthogonal positions, the **antenna vertically** is worst case position and the data was reported.*

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: 3G Smart Phone
 Tested Model: Platinum 5.5
 Operating Condition: 802.11b Transmitting Low Channel-2412MHz
 Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.6586	23.20	-7.46	15.74	40.00	-24.26	148	100	QP
2	98.4866	22.11	-9.75	12.36	43.50	-31.14	152	100	QP
3	955.4381	21.45	6.01	27.46	46.00	-18.54	136	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	41.1320	25.84	-8.21	17.63	40.00	-22.37	148	100	QP
2	490.7447	24.76	-1.33	23.43	46.00	-22.57	250	100	QP
3	900.1474	24.56	5.38	29.94	46.00	-16.06	165	100	QP

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.9940	23.63	-7.46	16.17	40.00	-23.83	148	100	QP
2	483.9094	24.85	-1.49	23.36	46.00	-22.64	154	100	QP
3	945.4399	24.33	5.88	30.21	46.00	-15.79	168	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	45.3755	24.37	-7.46	16.91	40.00	-23.09	125	100	QP
2	107.8877	24.55	-9.59	14.96	43.50	-28.54	102	100	QP
3	938.8326	24.35	5.81	30.16	46.00	-15.84	185	100	QP

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.4918	22.38	-7.45	14.93	40.00	-25.07	162	100	QP
2	108.2667	21.86	-9.59	12.27	43.50	-31.23	200	100	QP
3	906.4824	22.37	5.45	27.82	46.00	-18.18	359	200	QP

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	(.)	(cm)	
1	46.9948	23.90	-7.45	16.45	40.00	-23.55	168	100	QP
2	100.2286	24.30	-9.56	14.74	43.50	-28.76	152	100	QP
3	955.4381	24.85	6.01	30.86	46.00	-15.14	178	100	QP

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: 3G Smart Phone
 Tested Model: Platinum 5.5
 Operating Condition: 802.11g Transmitting Low Channel-2412MHz
 Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.6719	22.73	-7.45	15.28	40.00	-24.72	102	100	QP
2	508.2582	22.70	-1.17	21.53	46.00	-24.47	140	100	QP
3	955.4381	21.63	6.01	27.64	46.00	-18.36	255	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.8119	24.38	-7.71	16.67	40.00	-23.33	240	100	QP
2	449.5558	25.41	-2.17	23.24	46.00	-22.76	187	100	QP
3	942.1305	24.54	5.84	30.38	46.00	-15.62	220	100	QP

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	48.6719	22.73	-7.45	15.28	40.00	-24.72	270	100	QP
2	647.3856	23.06	-1.18	21.88	46.00	-24.12	160	100	QP
3	906.4824	22.26	5.45	27.71	46.00	-18.29	228	200	QP

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	48.3318	24.38	-7.45	16.93	40.00	-23.07	360	100	QP
2	502.9395	24.35	-1.05	23.30	46.00	-22.70	120	100	QP
3	863.0562	25.03	4.65	29.68	46.00	-16.32	270	100	QP

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.8260	23.49	-7.46	16.03	40.00	-23.97	270	100	QP
2	207.1226	22.98	-9.01	13.97	43.50	-29.53	150	100	QP
3	955.4381	22.10	6.01	28.11	46.00	-17.89	360	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	44.2752	25.36	-7.61	17.75	40.00	-22.25	360	100	QP
2	96.7749	24.98	-9.95	15.03	43.50	-28.47	180	100	QP
3	925.7563	25.24	5.66	30.90	46.00	-15.10	120	100	QP

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: 3G Smart Phone
 Tested Model: Platinum 5.5
 Operating Condition: 802.11n-HT20 Transmitting Low Channel-2412MHz
 Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.9658	23.55	-7.68	15.87	40.00	-24.13	260	100	QP
2	99.1797	23.95	-9.66	14.29	43.50	-29.21	120	200	QP
3	948.7610	22.21	5.92	28.13	46.00	-17.87	289	200	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	48.5016	24.70	-7.45	17.25	40.00	-22.75	130	100	QP
2	556.7744	23.61	0.27	23.88	46.00	-22.12	120	100	QP
3	922.5157	24.30	5.63	29.93	46.00	-16.07	360	100	QP

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	46.8303	23.34	-7.45	15.89	40.00	-24.11	274	100	QP
2	199.9856	23.06	-9.06	14.00	43.50	-29.50	130	100	QP
3	906.4824	22.37	5.45	27.82	46.00	-18.18	120	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	42.0066	24.55	-8.05	16.50	40.00	-23.50	360	100	QP
2	545.1826	23.10	0.02	23.12	46.00	-22.88	110	100	QP
3	945.4399	24.13	5.88	30.01	46.00	-15.99	120	100	QP

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.1866	23.48	-7.45	16.03	40.00	-23.97	360	100	QP
2	519.0649	23.02	-1.22	21.80	46.00	-24.20	138	100	QP
3	958.7943	22.08	6.06	28.14	46.00	-17.86	180	200	QP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.6586	25.22	-7.46	17.76	40.00	-22.24	270	100	QP
2	97.4560	25.62	-9.87	15.75	43.50	-27.75	120	100	QP
3	912.8620	25.65	5.53	31.18	46.00	-14.82	360	100	QP

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: 3G Smart Phone

Tested Model: Platinum 5.5

Operating Condition: 802.11n-HT40 Transmitting Low Channel-2422MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.3594	22.05	-7.45	14.60	40.00	-25.40	155	100	QP
2	519.0649	22.99	-1.22	21.77	46.00	-24.23	197	100	QP
3	968.9338	21.83	6.21	28.04	54.00	-25.96	310	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	49.0145	24.42	-7.44	16.98	40.00	-23.02	274	100	QP
2	631.6884	22.27	1.59	23.86	46.00	-22.14	116	100	QP
3	938.8326	24.96	5.81	30.77	46.00	-15.23	82	100	QP

Operating Condition: 802.11n-HT40 Transmitting Middle Channel-2437MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.4918	23.48	-7.45	16.03	40.00	-23.97	274	100	QP
2	506.4791	23.03	-1.16	21.87	46.00	-24.13	130	100	QP
3	965.5421	22.32	6.16	28.48	54.00	-25.52	120	100	QP

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.6585	25.89	-7.73	18.16	40.00	-21.84	360	100	QP
2	517.2480	24.85	-0.68	24.17	46.00	-21.83	110	100	QP
3	955.4381	25.13	6.01	31.14	46.00	-14.86	120	100	QP

Operating Condition: 802.11n-HT40 Transmitting High Channel-2452MHz


Comment: Battery: DC 3.8V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	54.8348	23.04	-7.93	15.11	40.00	-24.89	264	100	QP
2	494.1984	22.02	-1.26	20.76	46.00	-25.24	110	100	QP
3	952.0937	21.23	5.96	27.19	46.00	-18.81	136	100	QP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	47.6586	23.20	-7.46	15.74	40.00	-24.26	360	100	QP
2	492.4685	23.09	-1.29	21.80	46.00	-24.20	112	100	QP
3	909.6667	22.45	5.49	27.94	46.00	-18.06	180	200	QP

Spurious Emissions Above 1GHz

Test Mode: 802.11b

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	46.28	12.37	58.65	74	-15.35	H	PK
4824.000	31.98	12.37	44.35	54	-9.65	H	AV
7236.000	39.14	15.49	54.63	74	-19.37	H	PK
7236.000	26.80	15.49	42.29	54	-11.71	H	AV
4824.000	37.88	12.37	50.25	74	-23.75	V	PK
4824.000	49.65	12.37	62.02	54	8.02	V	AV
7236.000	37.66	15.49	53.15	74	-20.85	V	PK
7236.000	26.90	15.49	42.39	54	-11.61	V	AV
Middle Channel-2437MHz							
4874.000	45.41	12.46	57.87	74	-16.13	H	PK
4874.000	35.11	12.46	47.57	54	-6.43	H	AV
7311.000	38.27	15.56	53.83	74	-20.17	H	PK
7311.000	25.93	15.56	41.49	54	-12.51	H	AV
4874.000	37.01	12.46	49.47	74	-24.53	V	PK
4874.000	48.78	12.46	61.24	54	7.24	V	AV
7311.000	36.79	15.56	52.35	74	-21.65	V	PK
7311.000	26.03	15.56	41.59	54	-12.41	V	AV
High Channel-2462MHz							
4924.000	46.59	12.55	59.14	74	-14.86	H	PK
4924.000	33.38	12.55	45.93	54	-8.07	H	AV
7386.000	36.96	15.64	52.6	74	-21.4	H	PK
7386.000	26.1	15.64	41.74	54	-12.26	H	AV
4924.000	48.63	12.55	61.18	74	-12.82	V	PK
4924.000	34.65	12.55	47.2	54	-6.8	V	AV
7386.000	37.13	15.64	52.77	74	-21.23	V	PK
7386.000	26.23	15.64	41.87	54	-12.13	V	AV

Test Mode: 802.11g

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	43.10	12.37	55.47	74	-18.53	H	PK
4824.000	31.62	12.37	43.99	54	-10.01	H	AV
7236.000	37.09	15.49	52.58	74	-21.42	H	PK
7236.000	25.68	15.49	41.17	54	-12.83	H	AV
4824.000	43.50	12.37	55.87	74	-18.13	V	PK
4824.000	31.73	12.37	44.10	54	-9.90	V	AV
7236.000	37.23	15.49	52.72	74	-21.28	V	PK
7236.000	25.73	15.49	41.22	54	-12.78	V	AV
Middle Channel-2437MHz							
4874.000	43.08	12.46	55.54	74	-18.46	H	PK
4874.000	31.6	12.46	44.06	54	-9.94	H	AV
7311.000	37.07	15.56	52.63	74	-21.37	H	PK
7311.000	25.66	15.56	41.22	54	-12.78	H	AV
4874.000	43.48	12.46	55.94	74	-18.06	V	PK
4874.000	31.71	12.46	44.17	54	-9.83	V	AV
7311.000	37.21	15.56	52.77	74	-21.23	V	PK
7311.000	25.71	15.56	41.27	54	-12.73	V	AV
High Channel-2462MHz							
4924.000	42.52	12.55	55.07	74	-18.93	H	PK
4924.000	31.02	12.55	43.57	54	-10.43	H	AV
7386.000	37.81	15.64	53.45	74	-20.55	H	PK
7386.000	25.77	15.64	41.41	54	-12.59	H	AV
4924.000	42.4	12.55	54.95	74	-19.05	V	PK
4924.000	31.09	12.55	43.64	54	-10.36	V	AV
7386.000	37	15.64	52.64	74	-21.36	V	PK
7386.000	25.82	15.64	41.46	54	-12.54	V	AV

Test Mode: 802.11n-HT20

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	42.14	12.55	54.69	74	-19.31	H	PK
4824.000	31.32	12.55	43.87	54	-10.13	H	AV
7236.000	37.57	15.64	53.21	74	-20.79	H	PK
7236.000	26.05	15.64	41.69	54	-12.31	H	AV
4824.000	42.43	12.55	54.98	74	-19.02	V	PK
4824.000	31.53	12.55	44.08	54	-9.92	V	AV
7236.000	37.06	15.64	52.7	74	-21.3	V	PK
7236.000	26.01	15.64	41.65	54	-12.35	V	AV
Middle Channel-2437MHz							
4874.000	42.91	12.46	55.37	74	-18.63	H	PK
4874.000	32.61	12.46	45.07	54	-8.93	H	AV
7311.000	35.77	15.56	51.33	74	-22.67	H	PK
7311.000	23.43	15.56	38.99	54	-15.01	H	AV
4874.000	34.51	12.46	46.97	74	-27.03	V	PK
4874.000	46.28	12.46	58.74	54	4.74	V	AV
7311.000	34.29	15.56	49.85	74	-24.15	V	PK
7311.000	23.53	15.56	39.09	54	-14.91	V	AV
High Channel-2462MHz							
4924.000	40.9	12.55	53.45	74	-20.55	H	PK
4924.000	30.08	12.55	42.63	54	-11.37	H	AV
7386.000	36.33	15.64	51.97	74	-22.03	H	PK
7386.000	24.81	15.64	40.45	54	-13.55	H	AV
4924.000	41.19	12.55	53.74	74	-20.26	V	PK
4924.000	30.29	12.55	42.84	54	-11.16	V	AV
7386.000	35.82	15.64	51.46	74	-22.54	V	PK
7386.000	24.77	15.64	40.41	54	-13.59	V	AV

Test Mode: 802.11n-HT40

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2422MHz							
4844.000	43.60	12.4	56.00	74	-18.00	H	PK
4824.000	32.74	12.4	45.14	54	-8.86	H	AV
7266.000	35.06	15.52	50.58	74	-23.42	H	PK
7266.000	26.22	15.52	41.74	54	-12.26	H	AV
4844.000	45.70	12.4	58.10	74	-15.90	V	PK
4824.000	31.93	12.4	44.33	54	-9.67	V	AV
7266.000	35.67	15.52	51.19	74	-22.81	V	PK
7266.000	25.61	15.52	41.13	54	-12.87	V	AV
Middle Channel-2437MHz							
4874.000	42.66	12.37	55.03	74	-18.97	H	PK
4874.000	30.88	12.37	43.25	54	-10.75	H	AV
7311.000	36.99	15.49	52.48	74	-21.52	H	PK
7311.000	25.88	15.49	41.37	54	-12.63	H	AV
4874.000	42.5	12.37	54.87	74	-19.13	V	PK
4874.000	30.88	12.37	43.25	54	-10.75	V	AV
7311.000	36.9	15.49	52.39	74	-21.61	V	PK
7311.000	25.43	15.49	40.92	54	-13.08	V	AV
High Channel-2452MHz							
4904.000	43.77	12.52	56.29	74	-17.71	H	PK
4904.000	31.73	12.52	44.25	54	-9.75	H	AV
7356.000	36.64	15.61	52.25	74	-21.75	H	PK
7356.000	26.34	15.61	41.95	54	-12.05	H	AV
4904.000	43.13	12.52	55.65	74	-18.35	V	PK
4904.000	31.64	12.52	44.16	54	-9.84	V	AV
7356.000	36.95	15.61	52.56	74	-21.44	V	PK
7356.000	26.56	15.61	42.17	54	-11.83	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v03r02, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 V03r03, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

Please refer to the test plots as below.


802.11b-Lowest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	37.11	-4.42	32.69	54.00	-21.31	Average Detector
	2310.000	48.35	-4.42	43.93	74.00	-30.07	Peak Detector
2	2390.000	40.46	-3.72	36.74	54.00	-17.26	Average Detector
	2390.000	51.22	-3.72	47.50	74.00	-26.50	Peak Detector
3	2398.920	59.45	-3.65	55.80	Delta =40.33dBc		Average Detector
4	2400.000	58.94	-3.64	55.30			Average Detector
5	2412.720	99.17	-3.54	95.63			Average Detector

802.11b-Highest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.500	98.88	-3.17	95.71	/	/	Average Detector
	2463.300	106.95	-3.16	103.79	/	/	Peak Detector
2	2483.500	38.93	-3.01	35.92	54.00	-18.08	Average Detector
	2483.500	49.92	-3.01	46.91	74.00	-27.09	Peak Detector
3	2500.000	37.14	-2.88	34.26	54.00	-19.74	Average Detector
	2500.000	48.76	-2.88	45.88	74.00	-28.12	Peak Detector

802.11g-Lowest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	37.18	-4.42	32.76	54.00	-21.24	Average Detector
	2310.000	48.48	-4.42	44.06	74.00	-29.94	Peak Detector
2	2390.000	49.89	-3.72	46.17	54.00	-7.83	Average Detector
	2390.000	67.68	-3.72	63.96	74.00	-10.04	Peak Detector
3	2400.000	57.41	-3.64	53.77	Delta =37.34dBc		Average Detector
4	2411.040	94.67	-3.56	91.11			Average Detector

802.11g-Highest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.000	94.15	-3.18	90.97	/	/	Average Detector
	2463.650	105.46	-3.16	102.30	/	/	Peak Detector
2	2483.500	49.25	-3.01	46.24	54.00	-7.76	Average Detector
	2483.500	66.18	-3.01	63.17	74.00	-10.83	Peak Detector
3	2500.000	39.68	-2.88	36.80	54.00	-17.20	Average Detector
	2500.000	53.89	-2.88	51.01	74.00	-22.99	Peak Detector

802.11n-HT20-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	37.22	-4.42	32.80	54.00	-21.20	Average Detector
	2310.000	49.92	-4.42	45.50	74.00	-28.50	Peak Detector
2	2390.000	49.92	-3.72	46.20	54.00	-7.80	Average Detector
	2390.000	69.13	-3.72	65.41	74.00	-8.59	Peak Detector
3	2400.000	56.85	-3.64	53.21	Delta =37.26dBc		Average Detector
4	2410.920	94.03	-3.56	90.47			Average Detector


802.11n-HT20-Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.850	93.66	-3.18	90.48	/	/	Average Detector
	2461.450	105.03	-3.17	101.86	/	/	Peak Detector
2	2483.500	49.65	-3.01	46.64	54.00	-7.36	Average Detector
	2483.500	67.88	-3.01	64.87	74.00	-9.13	Peak Detector
3	2500.000	39.78	-2.88	36.90	54.00	-17.10	Average Detector
	2500.000	55.48	-2.88	52.60	74.00	-21.40	Peak Detector


802.11n-HT40-Lowest Bandedge

Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	37.06	-4.42	32.64	54.00	-21.36	Average Detector
	2310.000	47.96	-4.42	43.54	74.00	-30.46	Peak Detector
2	2390.000	50.17	-3.72	46.45	54.00	-7.55	Average Detector
	2390.000	68.25	-3.72	64.53	74.00	-9.47	Peak Detector
3	2400.000	53.06	-3.64	49.42	Delta =37.44dBc		Average Detector
4	2423.880	90.32	-3.46	86.86			Average Detector



802.11n-HT40-Highest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2457.860	88.98	-3.20	85.78	/	/	Average Detector
	2459.190	100.06	-3.19	96.87	/	/	Peak Detector
2	2483.500	48.75	-3.01	45.74	54.00	-8.26	Average Detector
	2483.500	63.22	-3.01	60.21	74.00	-13.79	Peak Detector
3	2500.000	43.97	-2.88	41.09	54.00	-12.91	Average Detector
	2500.000	59.04	-2.88	56.16	74.00	-17.84	Peak Detector

Conducted Emissions in non-restricted Frequency Bands:


11b-Low




11b-Middle




11b-High






11g-Low








11g-Middle




11g-High




11n-HT20-Low




11n-HT20-Middle





11n-HT20-High






11n-HT40-Low







11n-HT40-Middle



11n-HT40-High



10. Conducted Emissions

10.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.


10.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

10.3 Basic Test Setup Block Diagram



10.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

10.6 Summary of Test Results/Plots

According to the data in section 10.7, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-0.88 dB at 0.4700MHz in the **Line, AVG** detector, 0.15-30MHz

10.7 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: 3G Smart Phone
 Tested Model: Platinum 5.5
 Operating Condition: (WIFI)Transmitting
 Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4140	37.77	12.50	50.27	57.57	-7.30	QP
2	0.4260	29.02	12.50	41.52	47.33	-5.81	AVG
3	0.4660	39.13	12.50	51.63	56.58	-4.95	QP
4*	0.4700	29.46	12.50	41.96	46.51	-4.55	AVG
5	0.4940	38.02	12.50	50.52	56.10	-5.58	QP
6	0.5060	25.93	12.51	38.44	46.00	-7.56	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4140	43.31	12.50	55.81	57.57	-1.76	QP
2	0.4220	33.14	12.50	45.64	47.41	-1.77	AVG
3*	0.4700	33.13	12.50	45.63	46.51	-0.88	AVG
4	0.4740	42.02	12.50	54.52	56.44	-1.92	QP
5	0.5140	41.73	12.51	54.24	56.00	-1.76	QP
6	0.5140	32.26	12.51	44.77	46.00	-1.23	AVG

***** END OF REPORT *****